



pteh4

Report generated by Tenable Nessus™

Wed, 15 Jul 2026 08:43:59 EDT

TABLE OF CONTENTS

Vulnerabilities by Host

- 10.0.2.6.....4

Vulnerabilities by Host

10.0.2.6



Scan Information

Start time: Wed Jul 15 08:36:55 2026

End time: Wed Jul 15 08:43:59 2026

Host Information

IP: 10.0.2.6

MAC Address: 08:00:27:86:73:FC

OS: Linux Kernel 2.6

Vulnerabilities

172186 - Apache 2.4.x < 2.4.56 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.56. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.56 advisory.

- HTTP request splitting with mod_rewrite and mod_proxy: Some mod_proxy configurations on Apache HTTP Server versions 2.4.0 through 2.4.55 allow a HTTP Request Smuggling attack. Configurations are affected when mod_proxy is enabled along with some form of RewriteRule or ProxyPassMatch in which a non-specific pattern matches some portion of the user-supplied request-target (URL) data and is then re-inserted into the proxied request-target using variable substitution. For example, something like: RewriteEngine on RewriteRule ^/here/(.*) http://example.com:8080/elsewhere?\$1 http://example.com:8080/elsewhere ; [P] ProxyPassReverse /here/ http://example.com:8080/ http://example.com:8080/ Request splitting/smuggling could result in bypass of access controls in the proxy server, proxying unintended URLs to existing origin servers, and cache poisoning. Acknowledgements: finder: Lars Krapf of Adobe (CVE-2023-25690)

- Apache HTTP Server: mod_proxy_uwsgi HTTP response splitting: HTTP Response Smuggling vulnerability in Apache HTTP Server via mod_proxy_uwsgi. This issue affects Apache HTTP Server: from 2.4.30 through 2.4.55.

Special characters in the origin response header can truncate/split the response forwarded to the client.

Acknowledgements: finder: Dimas Fariski Setyawan Putra (nyxsorcerer) (CVE-2023-27522)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

Solution

Upgrade to Apache version 2.4.56 or later.

Risk Factor

Critical

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.8 (CVSS:3.0/E:P/RL:O/RC:C)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

7.8 (CVSS2#E:POC/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2023-25690
CVE	CVE-2023-27522
XREF	IAVA:2023-A-0124-S

Plugin Information

Published: 2023/03/07, Modified: 2023/10/21

Plugin Output

tcp/80/www

URL	: http://10.0.2.6/
Installed version	: 2.4.46
Fixed version	: 2.4.56

Potential Vulnerability : Backported

201198 - Apache 2.4.x < 2.4.60 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.60. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.60 advisory.

- Serving WebSocket protocol upgrades over a HTTP/2 connection could result in a Null Pointer dereference, leading to a crash of the server process, degrading performance. (CVE-2024-36387)
- SSRF in Apache HTTP Server on Windows allows to potentially leak NTLM hashes to a malicious server via SSRF and malicious requests or content Users are recommended to upgrade to version 2.4.60 which fixes this issue. Note: Existing configurations that access UNC paths will have to configure new directive UNCLIST to allow access during request processing. (CVE-2024-38472)
- Encoding problem in mod_proxy in Apache HTTP Server 2.4.59 and earlier allows request URLs with incorrect encoding to be sent to backend services, potentially bypassing authentication via crafted requests. Users are recommended to upgrade to version 2.4.60, which fixes this issue. (CVE-2024-38473)
- Substitution encoding issue in mod_rewrite in Apache HTTP Server 2.4.59 and earlier allows attacker to execute scripts in directories permitted by the configuration but not directly reachable by any URL or source disclosure of scripts meant to only to be executed as CGI. Users are recommended to upgrade to version 2.4.60, which fixes this issue. Some RewriteRules that capture and substitute unsafely will now fail unless rewrite flag UnsafeAllow3F is specified. (CVE-2024-38474)
- Improper escaping of output in mod_rewrite in Apache HTTP Server 2.4.59 and earlier allows an attacker to map URLs to filesystem locations that are permitted to be served by the server but are not intentionally/ directly reachable by any URL, resulting in code execution or source code disclosure. Substitutions in server context that use a backreferences or variables as the first segment of the substitution are affected. Some unsafe RewriteRules will be broken by this change and the rewrite flag UnsafePrefixStat can be used to opt back in once ensuring the substitution is appropriately constrained. (CVE-2024-38475)
- Vulnerability in core of Apache HTTP Server 2.4.59 and earlier are vulnerably to information disclosure, SSRF or local script execution via backend applications whose response headers are malicious or exploitable. Users are recommended to upgrade to version 2.4.60, which fixes this issue. (CVE-2024-38476)
- null pointer dereference in mod_proxy in Apache HTTP Server 2.4.59 and earlier allows an attacker to crash the server via a malicious request. Users are recommended to upgrade to version 2.4.60, which fixes this issue. (CVE-2024-38477)
- Potential SSRF in mod_rewrite in Apache HTTP Server 2.4.59 and earlier allows an attacker to cause unsafe RewriteRules to unexpectedly setup URL's to be handled by mod_proxy. Users are recommended to upgrade to version 2.4.60, which fixes this issue. (CVE-2024-39573)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

Solution

Upgrade to Apache version 2.4.60 or later.

Risk Factor

Critical

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

9.1 (CVSS:3.0/E:F/RL:O/RC:C)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2024-36387
CVE	CVE-2024-38472
CVE	CVE-2024-38473
CVE	CVE-2024-38474
CVE	CVE-2024-38475
CVE	CVE-2024-38476
CVE	CVE-2024-38477
CVE	CVE-2024-39573
XREF	IAVA:2024-A-0378-S
XREF	CISA-KNOWN-EXPLOITED:2025/05/22

Plugin Information

Published: 2024/07/01, Modified: 2025/05/02

Plugin Output

tcp/80/www

```
URL : http://10.0.2.6/  
Installed version : 2.4.46  
Fixed version : 2.4.60  
Potential Vulnerability : Backported
```

311940 - Apache 2.4.x < 2.4.67 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.67. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.67 advisory.

- Heap-based Buffer Overflow vulnerability in mod_proxy_ajp of Apache HTTP Server. If mod_proxy_ajp connects to a malicious AJP server this AJP server can send a malicious AJP message back to mod_proxy_ajp and cause it to write 4 attacker controlled bytes after the end of a heap based buffer. This issue affects Apache HTTP Server: through 2.4.66. Users are recommended to upgrade to version 2.4.67, which fixes the issue.

(CVE-2026-28780)

- Double Free and possible RCE vulnerability in Apache HTTP Server with the HTTP/2 protocol. This issue affects Apache HTTP Server: 2.4.66. Users are recommended to upgrade to version 2.4.67, which fixes the issue. (CVE-2026-23918)

- An escalation of privilege bug in various modules in Apache HTTP 2.4.66 and earlier allows local .htaccess authors to read files with the privileges of the httpd user. Users are recommended to upgrade to version 2.4.67, which fixes this issue. (CVE-2026-24072)

- Allocation of Resources Without Limits or Throttling vulnerability in Apache HTTP Server's mod_md via OCSP response data. This issue affects Apache HTTP Server: from 2.4.30 through 2.4.66. Users are recommended to upgrade to version 2.4.67, which fixes the issue. (CVE-2026-29168)

- A NULL pointer dereference in mod_dav_lock in Apache HTTP Server 2.4.66 and earlier may allow an attacker to crash the server with a malicious request.mod_dav_lock is not used internally by mod_dav or mod_dav_fs.

The only known use-case for mod_dav_lock was mod_dav_svn from Apache Subversion earlier than version 1.2.0. Users are recommended to upgrade to version 2.4.66, which fixes this issue, or remove mod_dav_lock.

(CVE-2026-29169)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

Solution

Upgrade to Apache version 2.4.67 or later.

Risk Factor

Critical

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.8 (CVSS:3.0/E:P/RL:O/RC:C)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

7.8 (CVSS2#E:POC/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2026-23918
CVE	CVE-2026-24072
CVE	CVE-2026-28780
CVE	CVE-2026-29168
CVE	CVE-2026-29169
CVE	CVE-2026-33006
CVE	CVE-2026-33007
CVE	CVE-2026-33523
CVE	CVE-2026-33857
CVE	CVE-2026-34032
CVE	CVE-2026-34059
XREF	IAVA:2026-A-0423

Plugin Information

Published: 2026/05/04, Modified: 2026/05/08

Plugin Output

tcp/80/www

```
URL : http://10.0.2.6/
Installed version : 2.4.46
Fixed version : 2.4.67
Potential Vulnerability : Backported
```

150280 - Apache 2.4.x < 2.4.47 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.47. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.47 changelog:

- Unexpected <Location> section matching with 'MergeSlashes OFF' (CVE-2021-30641)
- mod_auth_digest: possible stack overflow by one nul byte while validating the Digest nonce. (CVE-2020-35452)
- mod_session: Fix possible crash due to NULL pointer dereference, which could be used to cause a Denial of Service with a malicious backend server and SessionHeader. (CVE-2021-26691)
- mod_session: Fix possible crash due to NULL pointer dereference, which could be used to cause a Denial of Service. (CVE-2021-26690)
- mod_proxy_http: Fix possible crash due to NULL pointer dereference, which could be used to cause a Denial of Service. (CVE-2020-13950)
- Windows: Prevent local users from stopping the httpd process (CVE-2020-13938)
- mod_proxy_wstunnel, mod_proxy_http: Handle Upgradable protocols end-to-end negotiation. (CVE-2019-17567)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

https://downloads.apache.org/httpd/CHANGES_2.4

Solution

Upgrade to Apache version 2.4.47 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.5 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2019-17567
CVE	CVE-2020-13938
CVE	CVE-2020-13950
CVE	CVE-2020-35452
CVE	CVE-2021-26690
CVE	CVE-2021-26691
CVE	CVE-2021-30641
XREF	IAVA:2021-A-0259-S

Plugin Information

Published: 2021/06/04, Modified: 2022/04/11

Plugin Output

tcp/80/www

```
URL : http://10.0.2.6/
Installed version : 2.4.46
Fixed version : 2.4.47
Potential Vulnerability : Backported
```

161454 - Apache 2.4.x < 2.4.52 mod_lua Buffer Overflow

Synopsis

The remote web server is affected by a buffer overflow vulnerability.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.52. It is, therefore, affected by a flaw related to mod_lua when handling multipart content. A carefully crafted request body can cause a buffer overflow in the mod_lua multipart parser (r:parsebody() called from Lua scripts). The Apache httpd team is not aware of an exploit for the vulnerability though it might be possible to craft one.

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

Solution

Upgrade to Apache version 2.4.52 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

9.1 (CVSS:3.0/E:F/RL:O/RC:C)

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

6.2 (CVSS2#E:F/RL:O/RC:C)

STIG Severity

I

References

CVE	CVE-2021-44790
XREF	IAVA:2021-A-0604-S

Plugin Information

Published: 2022/05/24, Modified: 2023/10/26

Plugin Output

tcp/80/www

```
URL           : http://10.0.2.6/  
Installed version : 2.4.46  
Fixed version  : 2.4.52  
Potential Vulnerability : Backported
```

158900 - Apache 2.4.x < 2.4.53 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.53. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.53 advisory.

- mod_lua Use of uninitialized value of in r:parsebody: A carefully crafted request body can cause a read to a random memory area which could cause the process to crash. This issue affects Apache HTTP Server 2.4.52 and earlier. Acknowledgements: Chamal De Silva (CVE-2022-22719)
- HTTP request smuggling: Apache HTTP Server 2.4.52 and earlier fails to close inbound connection when errors are encountered discarding the request body, exposing the server to HTTP Request Smuggling Acknowledgements: James Kettle <james.kettle portswigger.net> (CVE-2022-22720)
- Possible buffer overflow with very large or unlimited LimitXMLRequestBody in core: If LimitXMLRequestBody is set to allow request bodies larger than 350MB (defaults to 1M) on 32 bit systems an integer overflow happens which later causes out of bounds writes. This issue affects Apache HTTP Server 2.4.52 and earlier. Acknowledgements: Anonymous working with Trend Micro Zero Day Initiative (CVE-2022-22721)
- Read/write beyond bounds in mod_sed: Out-of-bounds Write vulnerability in mod_sed of Apache HTTP Server allows an attacker to overwrite heap memory with possibly attacker provided data. This issue affects Apache HTTP Server 2.4 version 2.4.52 and prior versions. Acknowledgements: Ronald Crane (Zippenhop LLC) (CVE-2022-23943)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<http://www.apache.org/dist/httpd/Announcement2.4.html>

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.53 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

9.1 (CVSS:3.0/E:F/RL:O/RC:C)

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

6.2 (CVSS2#E:F/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2022-22719
CVE	CVE-2022-22720
CVE	CVE-2022-22721
CVE	CVE-2022-23943
XREF	IAVA:2022-A-0124-S

Plugin Information

Published: 2022/03/14, Modified: 2023/11/06

Plugin Output

tcp/80/www

```
URL : http://10.0.2.6/
Installed version : 2.4.46
Fixed version : 2.4.53
Potential Vulnerability : Backported
```

193421 - Apache 2.4.x < 2.4.54 Authentication Bypass

Synopsis

The remote web server is affected by an authentication bypass vulnerability.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.54. It is, therefore, affected by an authentication bypass vulnerability as referenced in the 2.4.54 advisory.

- X-Forwarded-For dropped by hop-by-hop mechanism in mod_proxy: Apache HTTP Server 2.4.53 and earlier may not send the X-Forwarded-* headers to the origin server based on client side Connection header hop-by-hop mechanism. This may be used to bypass IP based authentication on the origin server/application.

Acknowledgements: The Apache HTTP Server project would like to thank Gaetan Ferry (Synacktiv) for reporting this issue

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.54 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.5 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE CVE-2022-31813
XREF IAVA:2022-A-0230-S

Plugin Information

Published: 2024/04/17, Modified: 2024/04/18

Plugin Output

tcp/80/www

```
URL : http://10.0.2.6/
Installed version : 2.4.46
Fixed version : 2.4.54
Potential Vulnerability : Backported
```

170113 - Apache 2.4.x < 2.4.55 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.55. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.55 advisory.

- A carefully crafted If: request header can cause a memory read, or write of a single zero byte, in a pool (heap) memory location beyond the header value sent. This could cause the process to crash. This issue affects Apache HTTP Server 2.4.54 and earlier. (CVE-2006-20001)

- Inconsistent Interpretation of HTTP Requests ('HTTP Request Smuggling') vulnerability in mod_proxy_ajp of Apache HTTP Server allows an attacker to smuggle requests to the AJP server it forwards requests to. This issue affects Apache HTTP Server Apache HTTP Server 2.4 version 2.4.54 and prior versions. (CVE-2022-36760)

- Prior to Apache HTTP Server 2.4.55, a malicious backend can cause the response headers to be truncated early, resulting in some headers being incorporated into the response body. If the later headers have any security purpose, they will not be interpreted by the client. (CVE-2022-37436)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

Solution

Upgrade to Apache version 2.4.55 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.0 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

7.8 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

7.6 (CVSS2#AV:N/AC:H/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

5.6 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2006-20001
CVE	CVE-2022-36760
CVE	CVE-2022-37436
XREF	IAVA:2023-A-0047-S

Plugin Information

Published: 2023/01/18, Modified: 2023/03/10

Plugin Output

tcp/80/www

```
URL : http://10.0.2.6/
Installed version : 2.4.46
Fixed version : 2.4.55
Potential Vulnerability : Backported
```

183391 - Apache 2.4.x < 2.4.58 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.58. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.58 advisory.

- Apache HTTP Server: DoS in HTTP/2 with initial windows size 0: An attacker, opening a HTTP/2 connection with an initial window size of 0, was able to block handling of that connection indefinitely in Apache HTTP Server. This could be used to exhaust worker resources in the server, similar to the well known slow loris attack pattern. This has been fixed in version 2.4.58, so that such connection are terminated properly after the configured connection timeout. This issue affects Apache HTTP Server: from 2.4.55 through 2.4.57. Users are recommended to upgrade to version 2.4.58, which fixes the issue.

Acknowledgements: (CVE-2023-43622)

- Apache HTTP Server: HTTP/2 stream memory not reclaimed right away on RST: When a HTTP/2 stream was reset (RST frame) by a client, there was a time window where the request's memory resources were not reclaimed immediately. Instead, de-allocation was deferred to connection close. A client could send new requests and resets, keeping the connection busy and open and causing the memory footprint to keep on growing. On connection close, all resources were reclaimed, but the process might run out of memory before that. This was found by the reporter during testing of CVE-2023-44487 (HTTP/2 Rapid Reset Exploit) with their own test client. During normal HTTP/2 use, the probability to hit this bug is very low. The kept memory would not become noticeable before the connection closes or times out. Users are recommended to upgrade to version 2.4.58, which fixes the issue. Acknowledgements: (CVE-2023-45802)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

Solution

Upgrade to Apache version 2.4.58 or later.

Risk Factor

High

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

5.8 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2023-43622
CVE	CVE-2023-45802
XREF	IAVA:2023-A-0572-S

Plugin Information

Published: 2023/10/19, Modified: 2024/04/29

Plugin Output

tcp/80/www

```
URL : http://10.0.2.6/
Installed version : 2.4.46
Fixed version : 2.4.58
Potential Vulnerability : Backported
```

193419 - Apache 2.4.x < 2.4.58 Out-of-Bounds Read (CVE-2023-31122)

Synopsis

The remote web server is affected by an out-of-bounds read vulnerability.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.58. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.58 advisory.

- mod_macro buffer over-read: Out-of-bounds Read vulnerability in mod_macro of Apache HTTP Server. This issue affects Apache HTTP Server: through 2.4.57.

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

Solution

Upgrade to Apache version 2.4.58 or later.

Risk Factor

High

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

5.8 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2023-31122
XREF	IAVA:2023-A-0572-S

Plugin Information

Published: 2024/04/17, Modified: 2024/04/29

Plugin Output

tcp/80/www

```
URL           : http://10.0.2.6/  
Installed version : 2.4.46  
Fixed version  : 2.4.58  
Potential Vulnerability : Backported
```

192923 - Apache 2.4.x < 2.4.59 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.59. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.59 advisory.

- Apache HTTP Server: HTTP Response Splitting in multiple modules: HTTP Response splitting in multiple modules in Apache HTTP Server allows an attacker that can inject malicious response headers into backend applications to cause an HTTP desynchronization attack. Users are recommended to upgrade to version 2.4.59, which fixes this issue. Acknowledgements: (CVE-2024-24795)

- Apache HTTP Server: HTTP/2 DoS by memory exhaustion on endless continuation frames: HTTP/2 incoming headers exceeding the limit are temporarily buffered in nghttp2 in order to generate an informative HTTP 413 response. If a client does not stop sending headers, this leads to memory exhaustion.

Acknowledgements: finder: Bartek Nowotarski (<https://nowotarski.info/>) (CVE-2024-27316)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

Solution

Upgrade to Apache version 2.4.59 or later.

Risk Factor

High

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

5.8 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2023-38709
CVE	CVE-2024-24795
CVE	CVE-2024-27316
XREF	IAVA:2024-A-0202-S

Plugin Information

Published: 2024/04/04, Modified: 2024/07/12

Plugin Output

tcp/80/www

```
URL           : http://10.0.2.6/
Installed version : 2.4.46
Fixed version  : 2.4.59
Potential Vulnerability : Backported
```

319665 - Apache 2.4.x < 2.4.68 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.68. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.68 advisory.

- CVE-2026-49975, also known as HTTP/2 Bomb, is a remote denial-of-service exploit against most major web servers, including: nginx, Apache httpd, Microsoft IIS, Envoy, Cloudflare Pingor. The vulnerable behavior exists in each server's default HTTP/2 configuration (CVE-2026-49975)

- mod_xml2enc heap overflow: Heap-based Buffer Overflow vulnerability in Apache HTTP Server with mod_xml2enc, xml2StartParse, and untrusted content This issue affects Apache HTTP Server: from 2.4.0 through 2.4.67. Users are recommended to upgrade to version 2.4.68, which fixes the issue.

Acknowledgements: finder: Zhenpeng (Leo) Lin at depthfirst (CVE-2026-42536)

- OOB Read in `merge\_response\_headers` can cause crash: Out-of-bounds Read vulnerability in Apache HTTP Server with mod_headers and mod_mime and multiple response languages. This issue affects Apache HTTP Server: from 2.4.0 through 2.4.67. Acknowledgements: finder: Zhenpeng (Leo) Lin at depthfirst (CVE-2026-43951)

- escalation of privilege through expressions in .htaccess in multiple modules: Improper Privilege Management vulnerability in Apache HTTP Server 2.4.67 and earlier allows local .htaccess authors to read files with the privileges of the httpd user. This issue affects Apache HTTP Server: from through 2.4.67.

Users are recommended to upgrade to version 2.4.68, which fixes the issue. Acknowledgements: (CVE-2026-44119)

- Stack Buffer Over-Read in mod_ssl OCSP `send\_request`: Buffer Over-read vulnerability in Apache HTTP Server via outbound OCSP requests to an attacker controlled OCSP server This issue affects Apache HTTP Server: from 2.4.0 through 2.4.67. Users are recommended to upgrade to version 2.4.68, which fixes the issue. Acknowledgements: finder: Zhenpeng (Leo) Lin at depthfirst (CVE-2026-44185)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

Solution

Upgrade to Apache version 2.4.68 or later.

Risk Factor

High

CVSS v4.0 Base Score

8.7 (CVSS:4.0/AV:N/AC:L/AT:N/PR:N/UI:N/VC:N/VI:N/VA:H/SC:N/SI:N/SA:N)

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.8 (CVSS:3.0/E:P/RL:O/RC:C)

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

6.1 (CVSS2#E:POC/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2026-29167
CVE	CVE-2026-29170
CVE	CVE-2026-34355
CVE	CVE-2026-34356
CVE	CVE-2026-42535
CVE	CVE-2026-42536
CVE	CVE-2026-43951
CVE	CVE-2026-44119
CVE	CVE-2026-44185
CVE	CVE-2026-44186
CVE	CVE-2026-44631
CVE	CVE-2026-48913
CVE	CVE-2026-49975
XREF	IAVA:2026-A-0558

Plugin Information

Published: 2026/06/08, Modified: 2026/06/12

Plugin Output

tcp/80/www

URL	: http://10.0.2.6/
Installed version	: 2.4.46

Fixed version : 2.4.68
Potential Vulnerability : Backported

156255 - Apache 2.4.x >= 2.4.7 / < 2.4.52 Forward Proxy DoS / SSRF

Synopsis

The remote web server is affected by a denial of service or server-side request forgery vulnerability.

Description

The version of Apache httpd installed on the remote host is equal to or greater than 2.4.7 and prior to 2.4.52.

It is, therefore, affected by a flaw related to acting as a forward proxy.

A crafted URI sent to httpd configured as a forward proxy (ProxyRequests on) can cause a crash (NULL pointer dereference) or, for configurations mixing forward and reverse proxy declarations, can allow for requests to be directed to a declared Unix Domain Socket endpoint (Server Side Request Forgery).

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

Solution

Upgrade to Apache version 2.4.52 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

9.1 (CVSS:3.0/E:F/RL:O/RC:C)

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

6.2 (CVSS2#E:F/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2021-44224
CVE	CVE-2021-44790
XREF	IAVA:2021-A-0604-S

Plugin Information

Published: 2021/12/23, Modified: 2023/11/22

Plugin Output

tcp/80/www

```
URL                : http://10.0.2.6/  
Installed version  : 2.4.46  
Fixed version      : 2.4.52  
Potential Vulnerability : Backported
```

153584 - Apache < 2.4.49 Multiple Vulnerabilities

Synopsis

The remote web server is affected by a vulnerability.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.49. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.49 changelog.

- ap_escape_quotes() may write beyond the end of a buffer when given malicious input. No included modules pass untrusted data to these functions, but third-party / external modules may. (CVE-2021-39275)
- Malformed requests may cause the server to dereference a NULL pointer. (CVE-2021-34798)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

https://downloads.apache.org/httpd/CHANGES_2.4

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.49 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.5 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2021-34798
CVE	CVE-2021-39275
XREF	IAVA:2021-A-0440-S

Plugin Information

Published: 2021/09/23, Modified: 2022/04/11

Plugin Output

tcp/80/www

```
URL                : http://10.0.2.6/
Installed version   : 2.4.46
Fixed version       : 2.4.49
Potential Vulnerability : Backported
```

193422 - Apache 2.4.x < 2.4.54 HTTP Request Smuggling Vulnerability

Synopsis

The remote web server is affected by a HTTP request smuggling vulnerability.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.54. It is, therefore, affected by a http request smuggling vulnerability as referenced in the 2.4.54 advisory.

- Possible request smuggling in mod_proxy_ajp: Inconsistent Interpretation of HTTP Requests ('HTTP Request Smuggling') vulnerability in mod_proxy_ajp of Apache HTTP Server allows an attacker to smuggle requests to the AJP server it forwards requests to. This issue affects Apache HTTP Server Apache HTTP Server 2.4 version 2.4.53 and prior versions. Acknowledgements: Richter Z @ 360 Noah Lab

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.54 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:H/A:N)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE CVE-2022-26377
XREF IAVA:2022-A-0230-S

Plugin Information

Published: 2024/04/17, Modified: 2024/04/18

Plugin Output

tcp/80/www

```
URL : http://10.0.2.6/  
Installed version : 2.4.46  
Fixed version : 2.4.54  
Potential Vulnerability : Backported
```

161948 - Apache 2.4.x < 2.4.54 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.54. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.54 advisory.

- Read beyond bounds via ap_rwrite(): The ap_rwrite() function in Apache HTTP Server 2.4.53 and earlier may read unintended memory if an attacker can cause the server to reflect very large input using ap_rwrite() or ap_rputs(), such as with mod_lua's r:puts() function. Acknowledgements: The Apache HTTP Server project would like to thank Ronald Crane (Zippenhop LLC) for reporting this issue (CVE-2022-28614)

- Read beyond bounds in ap_strcmp_match(): Apache HTTP Server 2.4.53 and earlier may crash or disclose information due to a read beyond bounds in ap_strcmp_match() when provided with an extremely large input buffer. While no code distributed with the server can be coerced into such a call, third-party modules or lua scripts that use ap_strcmp_match() may hypothetically be affected. Acknowledgements: The Apache HTTP Server project would like to thank Ronald Crane (Zippenhop LLC) for reporting this issue (CVE-2022-28615)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.54 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

9.1 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:H)

CVSS v3.0 Temporal Score

7.9 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:P)

CVSS v2.0 Temporal Score

4.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2022-28614
CVE	CVE-2022-28615
XREF	IAVA:2022-A-0230-S

Plugin Information

Published: 2022/06/08, Modified: 2024/04/18

Plugin Output

tcp/80/www

```
URL : http://10.0.2.6/
Installed version : 2.4.46
Fixed version : 2.4.54
Potential Vulnerability : Backported
```

193423 - Apache 2.4.x < 2.4.54 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.54. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.54 advisory.

- Denial of Service mod_sed: If Apache HTTP Server 2.4.53 is configured to do transformations with mod_sed in contexts where the input to mod_sed may be very large, mod_sed may make excessively large memory allocations and trigger an abort. Acknowledgements: This issue was found by Brian Moussalli from the JFrog Security Research team

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.54 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE CVE-2022-30522
XREF IAVA:2022-A-0230-S

Plugin Information

Published: 2024/04/17, Modified: 2024/04/18

Plugin Output

tcp/80/www

```
URL : http://10.0.2.6/  
Installed version : 2.4.46  
Fixed version : 2.4.54  
Potential Vulnerability : Backported
```

193424 - Apache 2.4.x < 2.4.54 Multiple Vulnerabilities (mod_lua)

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.54. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.54 advisory.

- Denial of service in mod_lua r:parsebody: In Apache HTTP Server 2.4.53 and earlier, a malicious request to a lua script that calls r:parsebody(0) may cause a denial of service due to no default limit on possible input size. Acknowledgements: The Apache HTTP Server project would like to thank Ronald Crane (Zippenhop LLC) for reporting this issue (CVE-2022-29404)

- Information Disclosure in mod_lua with websockets: Apache HTTP Server 2.4.53 and earlier may return lengths to applications calling r:wsread() that point past the end of the storage allocated for the buffer.

Acknowledgements: The Apache HTTP Server project would like to thank Ronald Crane (Zippenhop LLC) for reporting this issue (CVE-2022-30556)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.54 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2022-29404
CVE	CVE-2022-30556
XREF	IAVA:2022-A-0230-S

Plugin Information

Published: 2024/04/17, Modified: 2024/04/18

Plugin Output

tcp/80/www

```
URL : http://10.0.2.6/
Installed version : 2.4.46
Fixed version : 2.4.54
Potential Vulnerability : Backported
```

193420 - Apache 2.4.x < 2.4.54 Out-Of-Bounds Read (CVE-2022-28330)

Synopsis

The remote web server is affected by an out-of-bound read vulnerability

Description

The version of Apache httpd installed on the remote host is prior to 2.4.54. It is, therefore, affected by an out-of-bounds read vulnerability as referenced in the 2.4.54 advisory.

- Read beyond bounds in mod_isapi: Apache HTTP Server 2.4.53 and earlier on Windows may read beyond bounds when configured to process requests with the mod_isapi module. Acknowledgements: The Apache HTTP Server project would like to thank Ronald Crane (Zippenhop LLC) for reporting this issue

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.54 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2022-28330
XREF	IAVA:2022-A-0230-S

Plugin Information

Published: 2024/04/17, Modified: 2024/04/18

Plugin Output

tcp/80/www

```
URL           : http://10.0.2.6/
Installed version : 2.4.46
Fixed version  : 2.4.54
Potential Vulnerability : Backported
```

241984 - Apache 2.4.x < 2.4.64 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.64. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.64 advisory.

- In certain proxy configurations, a denial of service attack against Apache HTTP Server versions 2.4.26 through to 2.4.63 can be triggered by untrusted clients causing an assertion in mod_proxy_http2.

Configurations affected are a reverse proxy is configured for an HTTP/2 backend, with ProxyPreserveHost set to on. (CVE-2025-49630)

- HTTP response splitting in the core of Apache HTTP Server allows an attacker who can manipulate the Content-Type response headers of applications hosted or proxied by the server can split the HTTP response.

This vulnerability was described as CVE-2023-38709 but the patch included in Apache HTTP Server 2.4.59 did not address the issue. Users are recommended to upgrade to version 2.4.64, which fixes this issue.

(CVE-2024-42516)

- SSRF in Apache HTTP Server with mod_proxy loaded allows an attacker to send outbound proxy requests to a URL controlled by the attacker. Requires an unlikely configuration where mod_headers is configured to modify the Content-Type request or response header with a value provided in the HTTP request. Users are recommended to upgrade to version 2.4.64 which fixes this issue. (CVE-2024-43204)

- Server-Side Request Forgery (SSRF) in Apache HTTP Server on Windows allows to potentially leak NTLM hashes to a malicious server via mod_rewrite or apache expressions that pass unvalidated request input. This issue affects Apache HTTP Server: from 2.4.0 through 2.4.63. Note: The Apache HTTP Server Project will be setting a higher bar for accepting vulnerability reports regarding SSRF via UNC paths. The server offers limited protection against administrators directing the server to open UNC paths. Windows servers should limit the hosts they will connect over via SMB based on the nature of NTLM authentication.

(CVE-2024-43394)

- Insufficient escaping of user-supplied data in mod_ssl in Apache HTTP Server 2.4.63 and earlier allows an untrusted SSL/TLS client to insert escape characters into log files in some configurations. In a logging configuration where CustomLog is used with %{varname}x or %{varname}c to log variables provided by mod_ssl such as SSL_TLS_SNI, no escaping is performed by either mod_log_config or mod_ssl and unsanitized data provided by the client may appear in log files. (CVE-2024-47252)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

Solution

Upgrade to Apache version 2.4.64 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.2 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2024-42516
CVE	CVE-2024-43204
CVE	CVE-2024-43394
CVE	CVE-2024-47252
CVE	CVE-2025-23048
CVE	CVE-2025-49630
CVE	CVE-2025-49812
CVE	CVE-2025-53020
XREF	IAVA:2025-A-0508-S

Plugin Information

Published: 2025/07/11, Modified: 2025/08/12

Plugin Output

tcp/80/www

```
URL : http://10.0.2.6/
Installed version : 2.4.46
Fixed version : 2.4.64
Potential Vulnerability : Backported
```

153583 - Apache < 2.4.49 Multiple Vulnerabilities

Synopsis

The remote web server is affected by a vulnerability.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.49. It is, therefore, affected by a vulnerability as referenced in the 2.4.49 changelog.

- A crafted request uri-path can cause mod_proxy to forward the request to an origin server chosen by the remote user. (CVE-2021-40438)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

https://downloads.apache.org/httpd/CHANGES_2.4

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.49 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

9.0 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.3 (CVSS:3.0/E:F/RL:O/RC:C)

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.6 (CVSS2#E:F/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2021-40438
XREF	IAVA:2021-A-0440-S
XREF	CISA-KNOWN-EXPLOITED:2021/12/15

Plugin Information

Published: 2021/09/23, Modified: 2023/04/25

Plugin Output

tcp/80/www

```
URL           : http://10.0.2.6/
Installed version : 2.4.46
Fixed version   : 2.4.49
Potential Vulnerability : Backported
```

Synopsis

The remote web server is affected by a vulnerability.

Description

The version of Apache httpd installed on the remote host is greater than 2.4.17 and prior to 2.4.49. It is, therefore, affected by a vulnerability as referenced in the 2.4.49 changelog. A crafted method sent through HTTP/2 will bypass validation and be forwarded by mod_proxy, which can lead to request splitting or cache poisoning.

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

https://downloads.apache.org/httpd/CHANGES_2.4

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.49 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:H/A:N)

CVSS v3.0 Temporal Score

6.7 (CVSS:3.0/E:P/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.9 (CVSS2#E:POC/RL:OF/RC:C)

STIG Severity

I

References

CVE CVE-2021-33193
XREF IAVA:2021-A-0440-S

Plugin Information

Published: 2021/09/23, Modified: 2023/11/29

Plugin Output

tcp/80/www

```
URL : http://10.0.2.6/  
Installed version : 2.4.46  
Fixed version : 2.4.49  
Potential Vulnerability : Backported
```

153586 - Apache >= 2.4.30 < 2.4.49 mod_proxy_uwsgi

Synopsis

The remote web server is affected by a vulnerability.

Description

The version of Apache httpd installed on the remote host greater than 2.4.30 and is prior to 2.4.49. It is, therefore, affected by a vulnerability as referenced in the 2.4.49 changelog. A carefully crafted request uri-path can cause mod_proxy_uwsgi to read above the allocated memory and crash (DoS).

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

https://downloads.apache.org/httpd/CHANGES_2.4

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.49 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE CVE-2021-36160
XREF IAVA:2021-A-0440-S

Plugin Information

Published: 2021/09/23, Modified: 2022/04/11

Plugin Output

tcp/80/www

```
URL           : http://10.0.2.6/  
Installed version : 2.4.46  
Fixed version   : 2.4.49  
Potential Vulnerability : Backported
```

106230 - Apache Default Index Page

Synopsis

The remote web server uses the default Apache index page

Description

The remote web server uses the default Apache index page. This page may contain some sensitive data like the server root and installation paths.

See Also

https://www.owasp.org/index.php/SCG_WS_Apache

Solution

Remove the default index page.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2018/01/22, Modified: 2024/09/03

Plugin Output

tcp/80/www

```
The Apache server listening on port 80 uses a
default install page as the index:
```

```
http://10.0.2.6/
```

106232 - Apache ServerTokens Information Disclosure

Synopsis

The remote web server discloses information via HTTP headers.

Description

The HTTP headers sent by the remote web server disclose information that can aid an attacker, such as the server version, operating system, and module versions.

See Also

https://www.owasp.org/index.php/SCG_WS_Apache

Solution

Change the Apache ServerTokens configuration value to 'Prod'

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2018/01/22, Modified: 2020/04/22

Plugin Output

tcp/80/www

```
The Apache server listening on port 80 contains  
sensitive information in the HTTP Server field.
```

```
Server: Apache/2.4.46 (Ubuntu)
```

88490 - Web Server Error Page Information Disclosure

Synopsis

The remote web server discloses information via a default error page.

Description

The default error page sent by the remote web server discloses information that can aid an attacker, such as the server version and languages used by the web server.

Solution

Modify the web server to not disclose detailed information about the underlying web server, or use a custom error page instead.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2016/01/29, Modified: 2022/04/11

Plugin Output

tcp/80/www

```
Server Type      : Apache
Server Version   : Apache/2.4.46
Source           : http://10.0.2.6/Jwe8mYWT
```

88099 - Web Server HTTP Header Information Disclosure

Synopsis

The remote web server discloses information via HTTP headers.

Description

The HTTP headers sent by the remote web server disclose information that can aid an attacker, such as the server version and languages used by the web server.

Solution

Modify the HTTP headers of the web server to not disclose detailed information about the underlying web server.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2016/01/22, Modified: 2019/04/30

Plugin Output

tcp/80/www

```
Server type      : Apache
Server version  : 2.4.46
Source          : 2.4.46
```

111465 - Apache HTTP Server Error Page Detection

Synopsis

The remote web server version can be obtained via a default error page.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from an error page.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/07/31, Modified: 2026/03/23

Plugin Output

tcp/80/www

```
Version : 2.4.46
Source  : Apache/2.4.46 (Ubuntu)
URL     : http://10.0.2.6/.htaccess
```

48204 - Apache HTTP Server Version

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0030
XREF	IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2026/01/22

Plugin Output

tcp/80/www

```
URL      : http://10.0.2.6/
Version  : 2.4.46
Source   : Server: Apache/2.4.46 (Ubuntu)
backported : 1
os       : Ubuntu
```

49704 - External URLs

Synopsis

Links to external sites were gathered.

Description

Nessus gathered HREF links to external sites by crawling the remote web server.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/10/04, Modified: 2011/08/19

Plugin Output

tcp/80/www

```
2 external URLs were gathered on this web server :  
URL... - Seen on...  
  
http://httpd.apache.org/docs/2.4/mod/mod_userdir.html - /  
https://bugs.launchpad.net/ubuntu/+source/apache2 - /
```

11919 - HMAP Web Server Fingerprinting

Synopsis

HMAP fingerprints the remote HTTP server.

Description

Nessus was able to identify the remote web server type by sending several valid and invalid HTTP requests. In some cases, its version can also be approximated, as well as some options.

See Also

<http://www.nessus.org/u?05d4ce87>

<http://seclab.cs.ucdavis.edu/papers/hmap-thesis.pdf>

<http://projects.webappsec.org/w/page/13246925/Fingerprinting>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/11/11, Modified: 2022/08/15

Plugin Output

tcp/80/www

```
This web server was fingerprinted as : Apache 2.2 or Apache 2.4
```

43111 - HTTP Methods Allowed (per directory)

Synopsis

This plugin determines which HTTP methods are allowed on various CGI directories.

Description

By calling the OPTIONS method, it is possible to determine which HTTP methods are allowed on each directory.

The following HTTP methods are considered insecure:

PUT, DELETE, CONNECT, TRACE, HEAD

Many frameworks and languages treat 'HEAD' as a 'GET' request, albeit one without any body in the response. If a security constraint was set on 'GET' requests such that only 'authenticatedUsers' could access GET requests for a particular servlet or resource, it would be bypassed for the 'HEAD' version. This allowed unauthorized blind submission of any privileged GET request.

As this list may be incomplete, the plugin also tests - if 'Thorough tests' are enabled or 'Enable web applications tests' is set to 'yes'

in the scan policy - various known HTTP methods on each directory and considers them as unsupported if it receives a response code of 400, 403, 405, or 501.

Note that the plugin output is only informational and does not necessarily indicate the presence of any security vulnerabilities.

See Also

<http://www.nessus.org/u?d9c03a9a>

<http://www.nessus.org/u?b019cbdb>

[https://www.owasp.org/index.php/Test_HTTP_Methods_\(OTG-CONFIG-006\)](https://www.owasp.org/index.php/Test_HTTP_Methods_(OTG-CONFIG-006))

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/12/10, Modified: 2022/04/11

Plugin Output

tcp/80/www

Based on the response to an OPTIONS request :

- HTTP methods GET HEAD OPTIONS POST are allowed on :

/

/icons

Based on tests of each method :

- HTTP methods GET HEAD OPTIONS POST are allowed on :

/

/icons

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/80/www

```
The remote web server type is :  
Apache/2.4.46 (Ubuntu)
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/80/www

Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : no

Keep-Alive : yes

Options allowed : (Not implemented)

Headers :

Date: Wed, 15 Jul 2026 12:37:34 GMT

Server: Apache/2.4.46 (Ubuntu)

Last-Modified: Thu, 29 Jul 2021 23:13:28 GMT

ETag: "2aa6-5c84b4033ab77"

Accept-Ranges: bytes

Content-Length: 10918

Vary: Accept-Encoding

Keep-Alive: timeout=5, max=98

Connection: Keep-Alive

Content-Type: text/html

Response Body :

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
```

```

<!--
  Modified from the Debian original for Ubuntu
  Last updated: 2016-11-16
  See: https://launchpad.net/bugs/1288690
-->
<head>
  <meta http-equiv="Content-Type" content="text/html; charset=UTF-8" />
  <title>Apache2 Ubuntu Default Page: It works</title>
  <style type="text/css" media="screen">
* {
  margin: 0px 0px 0px 0px;
  padding: 0px 0px 0px 0px;
}

body, html {
  padding: 3px 3px 3px 3px;

  background-color: #D8DBE2;

  font-family: Verdana, sans-serif;
  font-size: 11pt;
  text-align: center;
}

div.main_page {
  position: relative;
  display: table;

  width: 800px;

  margin-bottom: 3px;
  margin-left: auto;
  margin-right: auto;
  padding: 0px 0px 0px 0px;

  border-width: 2px;
  border-color: #212738;
  border-style: solid;

  background-color: #FFFFFF;

  text-align: center;
}

div.page_header {
  height: 99px;
  width: 100%;

  background-color: #F5F6F7;
}

div.page_header span {
  margin: 15px 0px 0px 50px;

  font-size: 180%;
  font-weight: bold;
}

div.page_header img {
  margin: 3px 0px 0px 40px;

  border: 0px 0px 0px;
}

div.table_of_contents {
  clear: left;

  min-width: 200px;

  margin: 3px 3px 3px 3px;

```

```
background-color: #FFFFFF;  
text-align: left;  
}  
  
div.table_of_contents_item {  
clear: left;  
  
width: [...]
```

50344 - Missing or Permissive Content-Security-Policy frame-ancestors HTTP Response Header

Synopsis

The remote web server does not take steps to mitigate a class of web application vulnerabilities.

Description

The remote web server in some responses sets a permissive Content-Security-Policy (CSP) frame-ancestors response header or does not set one at all.

The CSP frame-ancestors header has been proposed by the W3C Web Application Security Working Group as a way to mitigate cross-site scripting and clickjacking attacks.

See Also

<http://www.nessus.org/u?55aa8f57>

<http://www.nessus.org/u?07cc2a06>

<https://content-security-policy.com/>

<https://www.w3.org/TR/CSP2/>

Solution

Set a non-permissive Content-Security-Policy frame-ancestors header for all requested resources.

Risk Factor

None

Plugin Information

Published: 2010/10/26, Modified: 2021/01/19

Plugin Output

tcp/80/www

The following pages do not set a Content-Security-Policy frame-ancestors response header or set a permissive policy:

- <http://10.0.2.6/>

50345 - Missing or Permissive X-Frame-Options HTTP Response Header

Synopsis

The remote web server does not take steps to mitigate a class of web application vulnerabilities.

Description

The remote web server in some responses sets a permissive X-Frame-Options response header or does not set one at all.

The X-Frame-Options header has been proposed by Microsoft as a way to mitigate clickjacking attacks and is currently supported by all major browser vendors

See Also

<https://en.wikipedia.org/wiki/Clickjacking>

<http://www.nessus.org/u?399b1f56>

Solution

Set a properly configured X-Frame-Options header for all requested resources.

Risk Factor

None

Plugin Information

Published: 2010/10/26, Modified: 2021/01/19

Plugin Output

tcp/80/www

The following pages do not set a X-Frame-Options response header or set a permissive policy:

- <http://10.0.2.6/>

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/22/ssh

```
Port 22/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/80/www

```
Port 80/tcp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/07/10

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.12.1
Nessus build : 20018
Plugin feed version : 202607150258
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : pteh4
```

```
Scan policy used : Web Application Tests
Scanner IP : 10.0.2.5
Port scanner(s) : nessus_syn_scanner
Port range : 1-65535
Ping RTT : 75.375 ms
Thorough tests : yes
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 2
Assess component installs : yes
Report verbosity : 1
Safe checks : no
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : enabled
Web application tests : enabled
Web app tests - Test mode : single
Web app tests - Try all HTTP methods : yes
Web app tests - Maximum run time : 5 minutes.
Web app tests - Stop at first flaw : CGI
Max hosts : 30
Max checks : 5
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/7/15 8:37 EDT (UTC -04:00)
Scan duration : 418 sec
Scan for malware : no
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no
```

Synopsis

The remote host is missing several patches.

Description

The remote host is missing one or more security patches. This plugin lists the newest version of each patch to install to make sure the remote host is up-to-date.

Note: Because the 'Show missing patches that have been superseded' setting in your scan policy depends on this plugin, it will always run and cannot be disabled.

Solution

Install the patches listed below.

Risk Factor

None

Plugin Information

Published: 2013/07/08, Modified: 2026/07/14

Plugin Output

tcp/0

```
. You need to take the following action :  
[ Apache 2.4.x < 2.4.68 Multiple Vulnerabilities (319665) ]  
+ Action to take : Upgrade to Apache version 2.4.68 or later.  
+Impact : Taking this action will resolve 64 different vulnerabilities (CVEs).
```

Synopsis

The remote web server hosts linkable content that can be crawled by Nessus.

Description

The remote web server contains linkable content that can be used to gather information about a target.

See Also

<http://www.nessus.org/u?5496c8d9>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2016/06/24, Modified: 2016/06/24

Plugin Output

tcp/80/www

The following sitemap was created from crawling linkable content on the target host :

- <http://10.0.2.6/>

Attached is a copy of the sitemap file.

11032 - Web Server Directory Enumeration

Synopsis

It is possible to enumerate directories on the web server.

Description

This plugin attempts to determine the presence of various common directories on the remote web server. By sending a request for a directory, the web server response code indicates if it is a valid directory or not.

See Also

<http://projects.webappsec.org/w/page/13246953/Predictable%20Resource%20Location>

Solution

n/a

Risk Factor

None

References

XREF OWASP:OWASP-CM-006

Plugin Information

Published: 2002/06/26, Modified: 2024/06/07

Plugin Output

tcp/80/www

```
The following directories were discovered:  
/icons
```

```
While this is not, in and of itself, a bug, you should manually inspect  
these directories to ensure that they are in compliance with company  
security standards
```