

Haskell Workshop

FINN.no

FINN.no

Haskell

- Purely functional
- Statically Typed
- Lazy
- GHC: Glasgow Haskell Compiler

REPL

```
$ stack repl ./src/Part1.hs
(...)
*Part1>
```

Unloading and Loading

```
*Loaded Modules> :l
Ok, no modules loaded.
Prelude>
```

```
Prelude> :l Part1
Ok, one module loaded.
*Part1>
```

Evaluating values and types

```
>1 + 1
2
```

```
>:t 1
1 :: Num a => a
```

create a function

```
isPrime :: Int -> Bool
isPrime 0 = False
isPrime 1 = False
isPrime 2 = True
isPrime 3 = True
isPrime 4 = False
isPrime 5 = True
isPrime 6 = False
isPrime 7 = True
```

Curried signatures

```
myFunction :: Int -> Int -> Int
              ^arg0 ^arg1 ^res

myFunction :: Int -> (Int -> Int)
              ^arg0 ^res

>:t myFunction 1
myFunction 1 :: Int -> Int
```

create a function 2

```
myFunction :: Int -> Int -> Int
myFunction a b = (a + 1) * b ^ 2
```

Applying the function

```
> myFunction 1 2
8
```

Everything is an expression

```
isNine :: Int -> Bool
isNine i = if i == 9
           then True
           else False
```

You must have an else

lists

```
listOfInts :: [Int]
listOfInts = [1,2,3]

concat :: [a] -> [a] -> [a]
concat as bs = as ++ bs
```

Tips

- Indentation matters
- Slack : #finn-haskell-workshop
- Examples-folder
- README.md
- presentation/CheatSheet.pdf
- presentation/index.html

Exercise time :

```
./runtests 1
```

Higher order functions

Functions are values and can be passed as arguments to, and be returned from, other functions.

```
applyTwice :: (a -> a) -> a -> a
applyTwice f x = f (f x)
```

Recursion on lists

There are no for/while loops in haskell.

```
loopThrough :: [a] -> [a]
loopThrough [] = []
loopThrough (a : as) = a : loopThrough as
```

Recursively looping through a list and changing nothing.

Infix functions 1

You can turn an infix function into a prefix function by wrapping it in parantheses.

This is required to pass it as an argument.

```
(+) 1 2 == 1 + 2
```

Infix functions 2

You can include one operand inside the parantheses to create a partially applied function.

```
(/ 2) 1 == 1 / 2
```

```
(2 /) 1 == 2 / 1
```

let .. in expressions

```
cylinderVolume :: Float -> Float -> Float
cylinderVolume diameter height =
    let radius = diameter / 2
        area = pi * radius ^ 2
    in area * height
```

Variables can not be reassigned.

Exercise time :

```
./runtests 2
```

Exercise time :

```
./runtests 3
```

Anonymous functions (lambda)

```
\a b c -> 2 * a + c
filter (\x -> x ^ 2 > 5) [1,2,3,4]
```

Sometimes more convenient than creating a named function, or partially applying an existing function.

Unused variables

Use an underscore to tell the compiler (and yourself) that an argument is intentionally not used.

```
\a _ c -> 2 * a + c
```

Exercise time :

```
./runtests 4
```

Exercise time :

```
./runtests 5
```

Creating a type

```
data TrafficLight = Red | Yellow | Green
```

```
safe :: TrafficLight -> Bool
```

```
safe Red    = False
```

```
safe Yellow = False
```

```
safe Green  = True
```

Part 6

- Tests are green
- Keep them green after bumping to Lib.CCLib2
- Expand the datatype Bit as instructed