Haskell Workshop

FINN.no

FINN.no

Haskell

- Haskell / GHC
- Purely functional
- Statically Typed
- Lazy

Part 1

create a function

```
isPrime :: Int -> Bool
isPrime 0 = False
isPrime 1 = False
isPrime 2 = True
isPrime 3 = True
isPrime 4 = False
isPrime 5 = True
isPrime 6 = False
isPrime 7 = True
```

create a function 2

```
myFunction :: Int -> Int
myFunction a b = (a + 1) * b ^ 2
Applying arguments
> myFunction 1 2
```

Curried signatures

```
myFunction :: Int -> Int -> Int
myFunction :: Int -> (Int -> Int)
>:t myFunction 1
myFunction 1 :: Int -> Int
```

Everything is an expression

```
isNine :: Integer -> Bool
isNine i = if i == 9
   then True
   else False
```

You must have an else

let .. in expressions

```
cylVolume :: Float -> Float -> Float
cylVolume diam h =
  let rad = diam / 2
     area = pi * rad^2
  in area * h
```

lists

```
listOfInts :: [Integer]
listOfInts = [1,2,3]

concat :: [a] -> [a] -> [a]
concat as bs = as ++ bs
```

REPL

```
$ stack repl ./src/Part1.hs
(...)
*Part1>
```

Unloading and Loading

```
*Loaded Modules> :1 Ok, no modules loaded.
```

Prelude>

```
Prelude> :1 Part1
Ok, one module loaded.
*Part1>
```

Evaluating values and types

```
>1 + 1
2
>:t 1
1 + 1 :: Num a => a
```

Part 2 - 5

Recursion on lists

```
uppercase :: [Char] -> [Char]
uppercase [] = []
uppercase (x:xs) = toUpper x :: uppercase xs
x is a Char but xs is a [Char]
```

Functions over lists

```
inc :: [Integer] -> [Integer]
inc numbers = map (+1) numbers

inc2 :: [Integer] -> [Integer]
inc2 numbers = map (\x -> x + 1) numbes
```

Functions over lists 2

```
firstFive :: [a] -> [a]
firstFive as = take 5 as
onlyEven :: [Integer] -> [Integer]
onlyEven xs = filter even xs
```

Part 6

Creating a type

```
data TrafficLight = Red | Yellow | Green

safe :: TrafficLight -> Bool
safe Red = False
safe Yellow = False
safe Green = True
```

What to do

git clone $\mbox{https://github.com/mariatsji/haskell-workshop}$ open README.md