

LBPA Sardina Sur Austral Aysen 2021

Length Based Pseudo-Cohort Analysis LBPA

Mardones, M., Zúñiga, MJ.

19-06-2021

Contents

Introduction	2
Basic functionality	2
Bug Reports	2
Step 1	2
Set working directory	2
Step 2	3
Run model	3
Step 3	4
Read Report	4
Step 4	7
Plotting variables used in LBPA method	7
Estimate Length current, objective and expected	10
Table of estimated parameters of LBPA model;	10
Step 5	11
SPR and YPR analisys.	11

Introduction

This guide contains functions to compile and run the Length-based PseudoCohort Analysis (LBPA) fisheries stock assessment method in data limited conditions [Canales2021]

This model is an estimation model by fitting to length composition data to estimate annual fishing mortality, annual recruitment and spawning potential ratio (SPR). LBPA was published in Fisheries Research 234C (2021) <https://doi.org/10.1016/j.fishres.2020.105810>.

LBPA was developed for data-limited fisheries, where few data are available other than a representative sample of the size structure of the vulnerable portion of the population (i.e., length composition data from the catch) and an understanding of the life history of the species [Hordyk2014]; [Carruthers2014], [Carruthers2016c], [Amorim2020].

Basic functionality

The LBPA model is built based on a C++ language programmed in ADMB, and below we provide the steps to compile and build from a simple code implemented in R that had next step. This guide is an example from other length based method ([Chong2019a], [Rudd2018])

To do this, you must have installed the ADMB version (12 or newer). Can download in this site: <http://www.admb-project.org/>

The LBPA model and data example can be obtained from <https://github.com/criscan/LBPA>

Bug Reports

Alert to any bugs or issues by using GitHub. Suggestions and comments for additional features are welcome and we can discuss via email at

Step 1

Set working directory

In this folder you need put two files, .tpl and .dat to run LBPA estimation model

Once you have defined your working directory, you can take a look and check the contains files.

```
dir()
```

Step 2

Run model

Now we compile it in ADMB set. If you have read it, don't need run again:

```
system('~ /admb-12.2/admb LBPA')
```

Now you need run the model with console. The *system* function could run *.tpl* code from R.

Step 3

Read Report

To read report (.rep) is necessary to get a function to can read report. This function is hold in the same folder than .tpl and .dat.

```
source('~/.read.admb.R')
```

Once run our LBPA model, we can read report with *read.rep()* function.

```
data <-read.rep('LBPA.rep')
```

In data example we have a set data from fishery monitoring. You can set you own data relative to your stock in the .dat hosted in the github repository

Now, can read data all variables in your **.rep* file.

```
## [1] "Length_bins"
## [2] "Observed_frequencies"
## [3] "Predicted_frequency"
## [4] "Catch_length_frequency"
## [5] "Probability_of_length"
## [6] "Age_Length_s.e_N_Catch_Selectivity_F_Weight_Maturity"
## [7] "Length_frequency_of_exploitable_population_current_target_unfished"
## [8] "Selectivity_and_maturity_at_length"
## [9] "F_L50_slope_a0_cv_Lr_Ftar"
## [10] "F/Ftar_SPR_SPRtar"
## [11] "Proportions"
## [12] "Lr"
## [13] "a0"
## [14] "cv"
## [15] "L50"
## [16] "slope"
## [17] "F"
## [18] "Total"
## [19] "F_Y/R_SSB/R"
```

Setting of different variables names to produce complementary plots;

```
age      <- seq(1,6) #this age depend of your specie
BinLen   <- data$Length_bins
NObsFre  <- length(data$Observed_frequencies[,1]) #this numbers of observations depend of the oun data
ObsFre   <- data$Observed_frequencies
PredFre  <- data$Predicted_frequency
CatchLFre<- data$Catch_length_frequency
ProbleLen <- data$Probability_of_length
Nage     <- length(data$Probability_of_length[,1])
```

Lets plot length structure from data and get a plot from all length set data available;




Figure 1: Set of Length data with model fit

```
plot(BinLen, PredFre,type="l", ylab="Frecuencia",
     xlab="Tallas (cm)", lwd=2.3, ylim=c(0, max(ObsFre)))
for (i in 1:NobsFre) {
  lines(BinLen, ObsFre[i,], type="l", col=2)
}
```

Catch at length

```
par(mfrow=c(3,4),mar=c(3,4,1,1)+1)
for(i in 1:6){
  plot(BinLen ,CatchLFre[i,],ylab="",
       xlab="Length",type="h",lwd=2, col="gray",
       xlim = c(0,25))
}
```




Figure 2: Length frequencies of catches (red lines) and predicted values by LBPA model (black line)

Step 4

Plotting variables used in LBPA method

Now we plot different variables, as lengths, adjust models, fishing mortality, selectivity, maturity ogive and SPR.

```
l <- ggplot(data=NULL, aes(x=age))+
  geom_line(aes(y = Length))+
  scale_x_continuous(breaks = seq(from = 0, to = 6, by = 1))+
  xlab("Relative Age")+
  theme_bw()
se <- ggplot(data=NULL, aes(x=age))+
  geom_line(aes(y = SE))+
  scale_x_continuous(breaks = seq(from = 0, to = 6, by = 1))+
  xlab("Relative Age")+
  theme_bw()
fm <- ggplot(data=NULL, aes(x=age))+
  geom_line(aes(y = Fm))+
  scale_x_continuous(breaks = seq(from = 0, to = 6, by = 1))+
  xlab("Relative Age")+
  theme_bw()
pop <- ggplot(data=NULL, aes(x=age))+
  geom_line(aes(y = Population))+
  scale_x_continuous(breaks = seq(from = 0, to = 6, by = 1))+
  xlab("Relative Age")+
  theme_bw()
ct <- ggplot(data=NULL, aes(x=age))+
  geom_line(aes(y = Catch))+
  scale_x_continuous(breaks = seq(from = 0, to = 6, by = 1))+
  xlab("Relative Age")+
  theme_bw()
sel <- ggplot(data=NULL, aes(x=age))+
  geom_line(aes(y = Selec))+
  scale_x_continuous(breaks = seq(from = 0, to = 6, by = 1))+
  xlab("Relative Age")+
  theme_bw()
we <- ggplot(data=NULL, aes(x=age))+
  geom_line(aes(y = Weight))+
  scale_x_continuous(breaks = seq(from = 0, to = 6, by = 1))+
  theme_bw()
mat <- ggplot(data=NULL, aes(x=age))+
  geom_line(aes(y = Mat))+
  scale_x_continuous(breaks = seq(from = 0, to = 6, by = 1))+
  theme_bw()

l/se/fm/pop|ct/sel/we/mat
```




Figure 3: Variables used in LBPA estimation model

Some plot about proportion in Maturity and Selectivity at lentgh.

```
SeMaLe <- ggplot(data=NULL, aes(x=BinLen))+
  geom_line(aes(y = SeLength, colour = 'Selectivity'), size = 1)+
  geom_line(aes(y = MaLength, colour = 'Maturity'), linetype = 2, size = 1)+
  scale_color_manual(name = '',
                     values = c('red1', 'black'),
                     limits = c('Selectivity', 'Maturity'),
                     breaks = c('Selectivity', 'Maturity')) +
  theme(legend.position = 'bottom') + ylab('Proporción') + xlab('Tallas (cm)') +
  scale_x_continuous(breaks = seq(from = 0, to = 24, by = 2))+
  scale_y_continuous(breaks = seq(from = 0, to = 1, by = 0.1))+
  theme_bw()
```

SeMaLe

```
SeMaLe <- ggplot(data=NULL, aes(x=age))+
  geom_line(aes(y = Selec, colour = 'Selectivity'), size = 1)+
  geom_line(aes(y = Mat, colour = 'Maturity'), linetype = 2, size = 1)+
  scale_color_manual(name = '',
                     values = c('red1', 'black'),
                     limits = c('Selectivity', 'Maturity'),
                     breaks = c('Selectivity', 'Maturity')) +
  theme(legend.position = 'bottom') + ylab('Proporción') + xlab('Edadesjiuhnkl') +
  scale_x_continuous(breaks = seq(from = 0, to = 6, by = 1))+
  scale_y_continuous(breaks = seq(from = 0, to = 1, by = 0.1))+
  theme_bw()
```





Figure 4: Maturity and Selectivity at Length

SeMaLe




Figure 5: Maturity and Selectivity at Length

Estimate Length current, objective and expected

This plot represent length structure estimated by LBPA in each conditions: length current, target and unfished

```
L1 <- (data$Length_frequency_of_exploitable_population_current_target_unfished[1,])
L2 <- (data$Length_frequency_of_exploitable_population_current_target_unfished[2,])
L3 <- (data$Length_frequency_of_exploitable_population_current_target_unfished[3,])
```




Figure 6: Outputs of different relative Length estimated in LBPA

Table of estimated parameters of LBPA model;

```
tabla <- matrix(ncol=1, round(data$F_L50_slope_a0_cv_Lr_Ftar, 2))
rownames(tabla) <- c("F Current", "L50", "Slope", "a0", "cv", "Lr", "F Target")
kable(tabla)
```

F Current	1.61
L50	10.15
Slope	1.32
a0	1.00
cv	0.03
Lr	9.47
F Target	0.24

Step 5

SPR and YPR analisys.

Assign value of PBR to add plot, in this case; F/Ftar, SPR and SPR Target

```
F_FTar <- (data$`F/Ftar_SPR_SPRtar`[1])
SPR <- data$`F/Ftar_SPR_SPRtar`[2]
SPR_Tar <- data$`F/Ftar_SPR_SPRtar`[3]
```

YPR Plot with PBR estimated in LBPA model

```
ypr <- ggplot(data=YPR1, aes(x=YPR[,1]))+
  geom_line(aes(y = YPR1$RSSB, colour = 'YPR'))+
  geom_line(aes(y = YPR1$R, colour = 'SPR'))+
  geom_hline(aes(yintercept = SPR_Tar, linetype = "SPR Objetivo "), colour= 'black') +
  geom_vline(aes(xintercept = tabla[7,1], linetype = "SPR Objetivo "), colour= 'black') +
  geom_hline(aes(yintercept = SPR, linetype = "SPR"), colour= 'black') +
  geom_point(aes(y=SPR, x=tabla[1,1], type = "F Current"), colour= 'red') +
  geom_point(aes(y=SPR_Tar ,x= tabla[7,1], type = "F Objetivo"), colour= 'green') +
  scale_color_manual(name = '',
                     values = c('red1', 'gold1'),
                     limits = c('YPR', 'SPR'),
                     breaks = c('YPR', 'SPR')) +
  scale_linetype_manual(name = "PBR", values = c(3, 2),
                       guide = guide_legend(override.aes = list(color = c('black', 'black')))) +
  scale_x_continuous(breaks = seq(from = 0, to = 15, by = 1))+
  scale_y_continuous(breaks = seq(from = 0, to = 1, by = 0.1))+
  ylab('SPR, YPR') + xlab('Mortalidad por pesca') +
  theme_light()
ypr
```

The green point on YPR graph represents F Target, and red point represents F Current at the SPR current. In this analysis, F Current is higher than F Target. This mean, to drive population to sustainable condition, we need to reduce fishing mortality. This approach keep some assumptions about work from [Goodyear1993].




Figure 7: Yield and Spawning Biomass-per-recruit as a function of fishing mortality

```
ypr <- ggplot() +
  geom_point(aes(x=0.12794, y = 0.64593), type = "Fobj",size=3)+
  geom_hline(aes(yintercept = 1,linetype = "Fobj,SPRobj"), colour= 'black') +
  geom_vline(aes(xintercept = 1,linetype = "Fobj,SPRobj"), colour= 'black') +
  geom_vline(aes(xintercept = 0.5), colour= 'red') +
  scale_x_continuous(limits = c(0, 2),breaks = seq(from = 0, to = 2, by = 0.5))+
  scale_y_continuous(limits = c(0, 1),breaks = seq(from = 0, to = 1, by = 0.1))+
  ylab('YPR/Fobj') + xlab('SPR/SPRobj')+
  theme_light()

ypr
```




Figure 8: Estatus




Figure 9: **Figura x**. Diagrama de fase