```
import { useState } from "react";

const COLORS = {
  bg: "#05050f",
  pink: "#ff6eb4",
  skyblue: "#7ee8fa",
  cyan: "#00ffcc",
  purple: "#bf5fff",
  card: "rgba(255,255,255,0.04)",
  border: "rgba(255,110,180,0.2)",
};

const Particle = ({ left, top, char, color, delay, size }) => (
  <span style={{
    position: "fixed", left: `${left}%`, top: `${top}%`,
    fontSize: size, color, pointerEvents: "none", zIndex: 0,
    animation: `floatP ${3 + delay}s ease-in-out ${delay}s infinite`,
    opacity: 0.25,
  }}>{char}</span>
);

const particles = Array.from({ length: 20 }, (_, i) => ({
  id: i,
  left: (i * 17 + 5) % 95,
  top: (i * 23 + 8) % 88,
  char: ["✦", "✧", "◈", "·", "★"][i % 5],
  color: ["#ff6eb4", "#7ee8fa", "#00ffcc", "#bf5fff"][i % 4],
  delay: (i * 0.3) % 4,
  size: 7 + (i % 3) * 4,
}));

function InputField({ label, type, value, onChange, placeholder, icon }) {
  const [focused, setFocused] = useState(false);
  return (
    <div style={{ marginBottom: 14 }}>
      <div style={{
        fontSize: 10, fontWeight: 700, letterSpacing: 2,
        color: focused ? COLORS.skyblue : "#555",
        marginBottom: 6, transition: "color 0.2s",
      }}>{label}</div>
      <div style={{
        display: "flex", alignItems: "center",
        background: focused ? "rgba(126,232,250,0.06)" : COLORS.card,
        border: `1px solid ${focused ? COLORS.skyblue : COLORS.border}`,
```

```
        borderRadius: 14, padding: "0 14px",
        transition: "all 0.2s",
        boxShadow: focused ? `0 0 16px ${COLORS.skyblue}33` : "none",
      }}>
        <span style={{ fontSize: 16, marginRight: 10, opacity: 0.6 }}>{icon}</spa
        <input
          type={type}
          value={value}
          onChange={onChange}
          onFocus={() => setFocused(true)}
          onBlur={() => setFocused(false)}
          placeholder={placeholder}
          style={{
            flex: 1, background: "none", border: "none", outline: "none",
            color: "#eee", fontSize: 13, padding: "14px 0",
            fontFamily: "inherit",
          }}
        />
      </div>
    </div>
  );
}

function LoginScreen({ onSwitch }) {
  const [email, setEmail] = useState("");
  const [password, setPassword] = useState("");
  const [loading, setLoading] = useState(false);

  const handleLogin = () => {
    setLoading(true);
    setTimeout(() => setLoading(false), 1500);
  };

  return (
    <div style={{ animation: "fadeUp 0.5s ease both" }}>
      {/* Header */}
      <div style={{ textAlign: "center", marginBottom: 36 }}>
        {/* Icon */}
        <div style={{
          width: 72, height: 72, borderRadius: 22, margin: "0 auto 16px",
          background: "linear-gradient(135deg, #ff6eb4, #bf5fff, #7ee8fa, #00ffcc
          display: "flex", alignItems: "center", justifyContent: "center",
          fontSize: 32, boxShadow: "0 0 30px #ff6eb455, 0 0 60px #7ee8fa22",
          animation: "glowPulse 3s ease infinite",
        }}>✦</div>
        <div style={{
          fontSize: 32, fontWeight: 900, letterSpacing: 4,
```

```
    background: "linear-gradient(90deg, #ff6eb4, #bf5fff, #7ee8fa, #00ffcc,
    backgroundSize: "300% auto",
    WebkitBackgroundClip: "text", WebkitTextFillColor: "transparent",
    animation: "shimmer 4s linear infinite",
    marginBottom: 6,
  }}>GLOWZ✦</div>
  <div style={{ fontSize: 11, color: "#444", letterSpacing: 2, fontWeight:
    your vibe. your glow.
  </div>
</div>

{/* Card */}
<div style={{
  background: "rgba(255,255,255,0.03)",
  border: "1px solid rgba(255,110,180,0.15)",
  borderRadius: 24, padding: "28px 24px",
  backdropFilter: "blur(20px)",
}}>
  <div style={{
    fontSize: 18, fontWeight: 900, letterSpacing: 1,
    color: "#eee", marginBottom: 6,
  }}>おかえり ✦</div>
  <div style={{ fontSize: 11, color: "#444", marginBottom: 24, letterSpacin
    ログインしてグロウしよう
  </div>

  <InputField label="メールアドレス" type="email" value={email}
    onChange={e => setEmail(e.target.value)}
    placeholder="glowz@example.com" icon="✉️" />
  <InputField label="パスワード" type="password" value={password}
    onChange={e => setPassword(e.target.value)}
    placeholder="••••••••" icon="🔒" />

  {/* Forgot */}
  <div style={{ textAlign: "right", marginBottom: 20, marginTop: -6 }}>
    <span style={{
      fontSize: 11, color: COLORS.skyblue, cursor: "pointer", fontWeight: 6
    }}>パスワードを忘れた？</span>
  </div>

  {/* Login button */}
  <button onClick={handleLogin} style={{
    width: "100%",
    background: loading
      ? "rgba(255,110,180,0.3)"
      : "linear-gradient(135deg, #ff6eb4, #bf5fff, #7ee8fa, #00ffcc)",
    border: "none", borderRadius: 16, padding: "16px",
```

```
    color: "#fff", fontWeight: 900, fontSize: 15,
    cursor: loading ? "not-allowed" : "pointer",
    letterSpacing: 2,
    boxShadow: loading ? "none" : "0 6px 30px #ff6eb455",
    transition: "all 0.3s",
    marginBottom: 16,
  }}>
    {loading ? "✦ ログイン中..." : "✦ ログイン"}
  </button>

  {/* Divider */}
  <div style={{
    display: "flex", alignItems: "center", gap: 12, marginBottom: 16,
  }}>
    <div style={{ flex: 1, height: 1, background: "rgba(255,255,255,0.06)"
    <span style={{ fontSize: 10, color: "#333", letterSpacing: 1 }}>または</
    <div style={{ flex: 1, height: 1, background: "rgba(255,255,255,0.06)"
  </div>

  {/* Social login */}
  {[
    { icon: "🍎", label: "Appleでログイン", bg: "rgba(255,255,255,0.06)" },
    { icon: "G", label: "Googleでログイン", bg: "rgba(255,255,255,0.06)", isG
  ].map((s, i) => (
    <button key={i} style={{
      width: "100%", background: s.bg,
      border: "1px solid rgba(255,255,255,0.08)",
      borderRadius: 14, padding: "13px",
      color: "#bbb", fontWeight: 600, fontSize: 13,
      cursor: "pointer", marginBottom: 10,
      display: "flex", alignItems: "center", justifyContent: "center", gap:
    }}>
      <span style={{
        fontSize: s.isG ? 13 : 16,
        fontWeight: s.isG ? 900 : "normal",
        color: s.isG ? "#7ee8fa" : "inherit",
      }}>{s.icon}</span>
      {s.label}
    </button>
  ))}
</div>

{/* Switch to signup */}
<div style={{ textAlign: "center", marginTop: 24 }}>
  <span style={{ fontSize: 12, color: "#444" }}>アカウントがない？ </span>
  <span onClick={onSwitch} style={{
    fontSize: 12, fontWeight: 800,
```

```
          background: "linear-gradient(90deg, #ff6eb4, #7ee8fa)",
          WebkitBackgroundClip: "text", WebkitTextFillColor: "transparent",
          cursor: "pointer",
        }}>新規登録 ✦</span>
      </div>
    </div>
  );
}

function SignupScreen({ onSwitch }) {
  const [step, setStep] = useState(1); // 1: basic info, 2: profile setup
  const [name, setName] = useState("");
  const [username, setUsername] = useState("");
  const [email, setEmail] = useState("");
  const [password, setPassword] = useState("");
  const [loading, setLoading] = useState(false);
  const [selectedVibe, setSelectedVibe] = useState(null);

  const vibes = [
    { label: "サイバーガール", emoji: "⚡" },
    { label: "ピンクポップ", emoji: "🌸" },
    { label: "ストリート", emoji: "🖤" },
    { label: "フェミニン", emoji: "🎀" },
    { label: "Y2K", emoji: "⭐" },
    { label: "ナチュラル", emoji: "🌿" },
  ];

  const handleNext = () => {
    if (step === 1) setStep(2);
    else {
      setLoading(true);
      setTimeout(() => setLoading(false), 1500);
    }
  };

  return (
    <div style={{ animation: "fadeUp 0.5s ease both" }}>
      {/* Header */}
      <div style={{ textAlign: "center", marginBottom: 28 }}>
        <div style={{
          width: 72, height: 72, borderRadius: 22, margin: "0 auto 16px",
          background: "linear-gradient(135deg, #ff6eb4, #bf5fff, #7ee8fa, #00ffcc
          display: "flex", alignItems: "center", justifyContent: "center",
          fontSize: 32, boxShadow: "0 0 30px #ff6eb455, 0 0 60px #7ee8fa22",
          animation: "glowPulse 3s ease infinite",
        }}>✦</div>
        <div style={{
```

```
    fontSize: 28, fontWeight: 900, letterSpacing: 4,
    background: "linear-gradient(90deg, #ff6eb4, #bf5fff, #7ee8fa, #00ffcc,
    backgroundSize: "300% auto",
    WebkitBackgroundClip: "text", WebkitTextFillColor: "transparent",
    animation: "shimmer 4s linear infinite",
    marginBottom: 6,
  }}>GLOWZ✦</div>

  {/* Step indicator */}
  <div style={{ display: "flex", justifyContent: "center", gap: 8, marginTo
    {[1, 2].map(s => (
      <div key={s} style={{
        height: 4, borderRadius: 10,
        width: step === s ? 28 : 14,
        background: step >= s
          ? "linear-gradient(90deg, #ff6eb4, #7ee8fa)"
          : "rgba(255,255,255,0.1)",
        transition: "all 0.3s ease",
      }} />
    ))}
  </div>
</div>

{/* Card */}
<div style={{
  background: "rgba(255,255,255,0.03)",
  border: "1px solid rgba(255,110,180,0.15)",
  borderRadius: 24, padding: "28px 24px",
  backdropFilter: "blur(20px)",
}}>
  {step === 1 ? (
    <>
      <div style={{ fontSize: 18, fontWeight: 900, color: "#eee", marginBot
        はじめまして ✦
      </div>
      <div style={{ fontSize: 11, color: "#444", marginBottom: 24, letterSp
        アカウントを作ってグロウしよう
      </div>

      <InputField label="ニックネーム" type="text" value={name}
        onChange={e => setName(e.target.value)}
        placeholder="例) marie" icon="✦" />
      <InputField label="ユーザーID" type="text" value={username}
        onChange={e => setUsername(e.target.value)}
        placeholder="例) marie_glowz" icon="◈" />
      <InputField label="メールアドレス" type="email" value={email}
        onChange={e => setEmail(e.target.value)}
```

```
        placeholder="glowz@example.com" icon="✉️" />
      <InputField label="パスワード" type="password" value={password}
        onChange={e => setPassword(e.target.value)}
        placeholder="8文字以上" icon="🔒" />
    </>
  ) : (
    <>
      <div style={{ fontSize: 18, fontWeight: 900, color: "#eee", marginBot
        あなたのVibeは？ ✦
      </div>
      <div style={{ fontSize: 11, color: "#444", marginBottom: 20, letterSp
        好きなスタイルを選んでね（複数OK）
      </div>

      <div style={{ display: "grid", gridTemplateColumns: "1fr 1fr", gap: 1
        {vibes.map((v, i) => (
          <div key={i} onClick={() => setSelectedVibe(selectedVibe === i ?
            background: selectedVibe === i
              ? "rgba(126,232,250,0.1)"
              : "rgba(255,255,255,0.03)",
            border: `1px solid ${selectedVibe === i ? COLORS.skyblue : "rgb
            borderRadius: 14, padding: "14px 12px",
            display: "flex", alignItems: "center", gap: 8,
            cursor: "pointer", transition: "all 0.2s",
            boxShadow: selectedVibe === i ? `0 0 14px ${COLORS.skyblue}33`
          }}>
            <span style={{ fontSize: 20 }}>{v.emoji}</span>
            <span style={{
              fontSize: 11, fontWeight: 700,
              color: selectedVibe === i ? COLORS.skyblue : "#666",
            }}>{v.label}</span>
          </div>
        ))}
      </div>

      {/* Avatar picker */}
      <div style={{
        marginTop: 16, marginBottom: 4,
        fontSize: 10, fontWeight: 700, letterSpacing: 2, color: "#555",
      }}>アイコンカラー</div>
      <div style={{ display: "flex", gap: 10, marginTop: 8 }}>
        {["#ff6eb4", "#7ee8fa", "#00ffcc", "#bf5fff", "#ffb347"].map((c, i)
          <div key={i} style={{
            width: 32, height: 32, borderRadius: "50%",
            background: `linear-gradient(135deg, ${c}, ${c}99)`,
            cursor: "pointer",
            boxShadow: `0 0 10px ${c}66`,
```

```
          border: "2px solid rgba(255,255,255,0.15)",
          display: "flex", alignItems: "center", justifyContent: "center"
          fontSize: 14,
        }}>✦</div>
      ))}
    </div>
  </>
)}

{/* Next / Submit */}
<button onClick={handleNext} style={{
  width: "100%", marginTop: 24,
  background: loading
    ? "rgba(255,110,180,0.3)"
    : "linear-gradient(135deg, #ff6eb4, #bf5fff, #7ee8fa, #00ffcc)",
  border: "none", borderRadius: 16, padding: "16px",
  color: "#fff", fontWeight: 900, fontSize: 15,
  cursor: loading ? "not-allowed" : "pointer",
  letterSpacing: 2,
  boxShadow: loading ? "none" : "0 6px 30px #ff6eb455",
  transition: "all 0.3s",
}}>
  {loading ? "✦ 作成中..." : step === 1 ? "次へ ✦" : "✦ GLOWZ を始める"}
</button>

{step === 1 && (
  <>
    <div style={{
      display: "flex", alignItems: "center", gap: 12, margin: "16px 0",
    }}>
      <div style={{ flex: 1, height: 1, background: "rgba(255,255,255,0.0
      <span style={{ fontSize: 10, color: "#333", letterSpacing: 1 }}>また
      <div style={{ flex: 1, height: 1, background: "rgba(255,255,255,0.0
    </div>
    {[
      { icon: "🍎", label: "Appleで登録" },
      { icon: "G", label: "Googleで登録", isG: true },
    ].map((s, i) => (
      <button key={i} style={{
        width: "100%",
        background: "rgba(255,255,255,0.04)",
        border: "1px solid rgba(255,255,255,0.08)",
        borderRadius: 14, padding: "13px",
        color: "#bbb", fontWeight: 600, fontSize: 13,
        cursor: "pointer", marginBottom: 10,
        display: "flex", alignItems: "center", justifyContent: "center",
      }}>
```

```
                <span style={{
                  fontSize: s.isG ? 13 : 16, fontWeight: s.isG ? 900 : "normal",
                  color: s.isG ? COLORS.skyblue : "inherit",
                }}>{s.icon}</span>
                {s.label}
              </button>
            ))}
          </>
        )}

        {step === 2 && (
          <button onClick={() => setStep(1)} style={{
            width: "100%", marginTop: 10,
            background: "none", border: "1px solid rgba(255,110,180,0.15)",
            borderRadius: 14, padding: "12px",
            color: "#555", fontWeight: 600, fontSize: 12,
            cursor: "pointer", letterSpacing: 1,
          }}>← 戻る</button>
        )}
      </div>

      {/* Switch to login */}
      <div style={{ textAlign: "center", marginTop: 24 }}>
        <span style={{ fontSize: 12, color: "#444" }}>すでにアカウントがある？ </span
        <span onClick={onSwitch} style={{
          fontSize: 12, fontWeight: 800,
          background: "linear-gradient(90deg, #ff6eb4, #7ee8fa)",
          WebkitBackgroundClip: "text", WebkitTextFillColor: "transparent",
          cursor: "pointer",
        }}>ログイン ✦</span>
      </div>
    </div>
  );
}

export default function App() {
  const [mode, setMode] = useState("login"); // login | signup

  return (
    <div style={{
      fontFamily: "'Hiragino Sans', 'Noto Sans JP', sans-serif",
      background: COLORS.bg,
      minHeight: "100vh",
      maxWidth: 390,
      margin: "0 auto",
      position: "relative",
      overflowX: "hidden",
```

```
    }}>
      <style>{`
        @keyframes floatP {
          0%,100%{transform:translateY(0) rotate(0deg);opacity:0.2;}
          50%{transform:translateY(-14px) rotate(18deg);opacity:0.6;}
        }
        @keyframes shimmer {
          0%{background-position:-400% center;}
          100%{background-position:400% center;}
        }
        @keyframes glowPulse {
          0%,100%{box-shadow:0 0 30px #ff6eb455,0 0 60px #7ee8fa22;}
          50%{box-shadow:0 0 50px #ff6eb488,0 0 80px #7ee8fa44;}
        }
        @keyframes fadeUp {
          from{opacity:0;transform:translateY(20px);}
          to{opacity:1;transform:translateY(0);}
        }
        input::placeholder{color:#333;}
        input{caret-color:#7ee8fa;}
      `}</style>

      {/* bg particles */}
      {particles.map(p => <Particle key={p.id} {...p} />)}

      {/* bg mesh */}
      <div style={{
        position: "fixed", inset: 0, pointerEvents: "none", zIndex: 0,
        background: `
          radial-gradient(ellipse at 20% 20%, rgba(255,110,180,0.06) 0%, transpar
          radial-gradient(ellipse at 80% 80%, rgba(126,232,250,0.06) 0%, transpar
          radial-gradient(ellipse at 50% 50%, rgba(191,95,255,0.04) 0%, transpare
        `,
      }} />

      {/* Content */}
      <div style={{ position: "relative", zIndex: 1, padding: "50px 20px 40px" }}
        {mode === "login"
          ? <LoginScreen onSwitch={() => setMode("signup")} />
          : <SignupScreen onSwitch={() => setMode("login")} />
        }
      </div>
    </div>
  );
}
```