

Akademija tehničko-umetničkih strukovnih studija Beograd  
Odsek Visoka Škola za informacione i komunikacione  
tehnologije

# Dokumentacija

FURNITURE.minimalistic

Predmet: Web Programiranje PHP2  
Student: Marija Vučićević 18/19 Mart 2022

# Sadržaj

1. Uvod .....	3
1.1 Korišćeni jezici i okruženje.....	3
1.2 Opis funkcionalnosti.....	3
1.3 Template .....	4
2. Organizaciona šema .....	5
2.1 Mapa sajta-sitemap .....	4
2.2 RSS .....	4
3. Sema baze.....	6
4. Organizacija sajta.....	7
4.1.1 Meni.....	7
4.1.2 Pretraga+ paginacija.....	7
4.1.3 Prikaz proizvoda.....	8
4.1.4 Prikaz izabranih proizvoda u korpi.....	8
4.1.5 Contact strana.....	9
4.1.6 Register strana.....	9
4.1.7 Login.....	10
4.1.8 Footer.....	10
4.1.9 Admin Panel.....	11
5. Kodovi.....	16
5.1 JS Kodovi .....	20
5.2 PHP-laravel Kodovi.....	108

# 1. Uvod

## 1.1 Korišćeni jezici i okruženje

- HTML/HTML5
- CSS/CSS3
- JavaScript
- jQuery
- Laravel,PHP, MySql
- AJAX
- PHP Storm za kreiranje projekta-okruženje

## 1.2 Opis funkcionalnosti

-Na svakoj strani je dinamički ispisan meni, koji u zavisnosti da li je ulogovan admin ili korisnik, prikazuje različite stranice i delove na sajtu(npr. contact samo može videti ulogovan korisnik, admin panelu samo admin...)

-Ruti /contact se ne može pristupiti ako korisnik nije ulogovan. Takođe, „add to cart“ dugme je disabled ako korisnik nije ulogovan. Nakon logovanja dugme gubi disabled funkciju

-Klikom na „add to cart“(svaki klik trigeruje broj proizvoda pored cart ikonice) proizvod odlazi u /cart gde korisnik može da briše proizvod po proizvod, sve odjednom, ili da završi kupovinu gde se podaci čuvaju u bazi (Koji user, koji proizvod, quantity..) Da se ne bi bespotrebno opterećivala baza, kod je radjen sa Local Storage-om dok ne dodje do klika na dugme „Finish“ kada podaci odlaze u bazu)

- Registracija ,logovanje i kontakt(slanje poruke administratoru koji se izlistavaju u Admin Panelu i salju administrator na mejlu - radjeno preko MailTrap-a)-provera radjena preko laravelove validacije (sa requestovima) sa try i catch blokovima pri radu sa bazom. Ukoliko udje u catch prikaze se stranica „Error“ koja prikazuje error sa quid(unique id)

-U Admin Panelu su zabeležene ključne aktivnosti kao što su - pored filtriranja po datumu registrovanih usera (nalazi se u delu gde su i CRUD operacije vezane za usera) postoji i posebna stranica „Users Activity“ gde se može, takođe filtrirati po datumu, ali sada filtriranje usera po datumu logina i logout-a. Pored tih aktivnosti, prikazane su i aktivnosti kreiranja ordera na strani „Cart Activity“(koji order, koji user, koji proizvodi, quantity i ukupna cena) – mogućnost filtriranja po datumu izvršenog ordera.

-Za pravljenje tabela u bazi su iskorišćene migracije, a za unos podataka seederi(ne za svaku tabelu, takođe je došlo do raznih promena)

- Takođe, glavni administratorski profil i skoro svaku tabelu za razne operacije(za svaku tabelu za koju je bilo potrebno postavljen je delete, update i insert). Za update i insert proizvoda je postavljen „Choose File“ , kao i za update glavnih proizvoda na ruti /

-Klik na bilo koji proizvod prikazuje taj proizvod sa dodatnim opisom koji nije vidljiv u galeriji-shop-u

-Klijentska pretraga (filter odradjen u Admin Panelu) spojena sa paginacijom koja prikazuje cetiri proizvoda po strani

-Određenim stranicama i određenim korisnicima je zabranjen pristup preko url adrese odradjeno preko middleware-a (odradjena redirekcija na home stranu(ruta /))

-Dokumentacija i Autor se nalaze u footert(kao Author je postavljen link ka portfolio sajtu radjen na Praktikum iz Web Dizajna)

### 1.3 Template

-Za izradu ovog sajta je korišćen gotov css template

<https://www.free-css.com/free-css-templates/page235/treviso> uz modifikacije, kako bi sajt sto vise odgovarao mojim potrebama i potrebi teme koja je izabrana

-Deo za admin panel je takodje template

## 2. Organizaciona šema


### 2.1 Mapa sajta-sitemap

```
<?xml version="1.0" encoding="UTF-8"?>
<urlset xmlns="http://www.sitemaps.org/schemas/sitemap/0.9">
  <url>
    <loc>http://127.0.0.1:8000/</loc>
    <lastmod>2022-03-05</lastmod>
    <changefreq>monthly</changefreq>
    <priority>0.8</priority>
  </url>
  <url>
    <loc>http://127.0.0.1:8000/products</loc>
    <lastmod>2022-03-10</lastmod>
    <changefreq>weekly</changefreq>
    <priority>0.9</priority>
  </url>
  <url>
    <loc>http://127.0.0.1:8000/cart</loc>
    <lastmod>2022-02-24</lastmod>
    <changefreq>weekly</changefreq>
    <priority>0.8</priority>
  </url>
</urlset>
```

### 2.2 RSS

```
<?xml version="1.0" encoding="utf-8"?>
<rss version="2.0">
  <channel>
    <title>New furniture out now</title>
    <link>http://127.0.0.1:8000/products</link>
    <description> We just got new furniture, come check them out! </description>
  >
  <item>
    <title>New location?</title>
    <link>http://127.0.0.1:8000/contactForm</link>
    <description> We might open in a new town sooner then you think -
keep in touch. </description>
  </item>
</channel>
</rss>
```

### 3. Sema baze



## 4. Organizacija sajta

Slike stranica i kratki opisi funkcionalnosti


<http://127.0.0.1:8000/>



### 4.1.1 Meni


-Meni(dinamicki ispisan iz baze), koji se razlikuje u zavisnosti da li korisnik uopste nije ulogovan(prikaz gore), nakon logovanja(admin ili obican korisnik) prikaz se menja

<http://127.0.0.1:8000/products>




### 4.1.2 Pretraga + paginacija

-Pretraga proizvoda urađena preko ajaxa, gde pri klikom na dugme „search” izlistavaju proizvodi spojeni sa paginacijom(8 proizvoda – 2 strane)



#### 4.1.3 Prikaz proizvoda

-Izlistani proizvodi koji ispod imaju paginaciju u kojoj se prikazuje po cetiri proizvoda (stanje se menja pri uploadu dodatnih proizvoda). Kada korisnik nije ulogovan dugme „Add to cart” je disabled dok se neko ne uloguje( pored toga, nema pristup cart strain )  
 Nakon logovanja pristup odobren i korpa funkcionalna




#### 4.1.4 Prikaz izabranih proizvoda u korpi

Za svaki proizvod su izlistane date informacije

- Button „Remove“ uklanja samo taj proizvod u kom se redu kliknulo
- Button „Back“ vraća korisnika na shop stranu, drugi button „Clear “ uklanja sve odabraneproizvode iz korpe nakon cega se prikazuje poruka da je korpa prazna
- Treci button „Finish“ pri kliku prikazuje alert i cuva podatke u bazu(koji korisnik, koji proizvod..)



<http://127.0.0.1:8000/contactForm>



CONTACT US

If you have some Questions for administrator, Please Contact Us through this field bellow  
We are here to listen!


Your Message:

Send Message

#### 4.1.5 Contact strana

-Ovoj stranici moze pristupiti samo ulogovan korisnik koji kasnije moze i poslati poruku administratoru na njegov mejl (korišćen MailTrap).Ta poruka se takođe automatski upisuju u bazu i izlistavaju u Admin Panel-u

<http://127.0.0.1:8000/registerForm>



REGISTER

If you like our page and want to do some shopping  
Just register!

Your Name:

Your Lastname:

Your Email:


Your Password:

Register

#### 4.1.6 Register strana

-Forma za registraciju(uradna validacija sa requestovima)

<http://127.0.0.1:8000/loginForm>



LOGIN

We are glad you are back  
Login down bellow!

Your Email:

Your Password:

Login

#### 4.1. 7 Login.php

-Forma za logovanje(uradna validacija sa requestovima)

Nakon uspesnog login-a u meniju ce se umesto register-a i login-a pojaviti logout na ciji se klik sesija unistava i korisnik dobija prvobitan prikaz menija

[DOCUMENTATION](#)


MARIJA VUČIĆEVIĆ 18/19 © VISOKA ICT SKOLA

[AUTHOR](#)

#### 4.1.8 Footer

- U footeru se nalazi link do portfolia od admina, kao i link do dokumentacije

http://127.0.0.1:8000/adminPanel



#### 4.1.9-Lista menija u admin panelu

-Adminov profil -  
(Nalazi se na pocetnoj Admin stranici)

The screenshot shows the 'Admins Profile' page. It features a large placeholder for a profile picture. Below it, there are four input fields containing the following information: 'Marija', 'Vucicevic', 'marija.vucicevic.78.19@ict.edu.rs', and '2022-03-06 20:53:42'. At the bottom left, there is a button labeled 'UPDATE PROFILE'.

-Aktivnost usera pri login-u i logout-u-  
(Mogucnost filtera po datumu)

The screenshot shows the 'Users Activity Table' page. It has a title 'Users Activity' and two filter inputs: 'Filter by log in date' and 'Filter by log out date', both with date pickers. A 'Remove filter' button is located between them. Below the filters is a table with the following data:

ID	FIRST NAME	LAST NAME	EMAIL	ROLE
21	Kiki	Kikić	kiki@gmail.com	user
23	Marija	Vucicevic	marija.vucicevic.78.19@ict.edu.rs	admin
24	Bojan	Stefanovski	youtube.bojans@gmail.com	user

-Prikaz ordera usera-  
(Mogucnost filtera po datumu)

Cart Activity Table

Cart Activity - Users Orders

Filter orders by date: mm/dd/yyyy

Remove filter

ID	USER	PRODUCTS IN USERS ORDER	TOTAL PRICE
8	Maria Vukovic	Maria's products	\$423
9	Maria Vukovic	Maria's products	\$250
11	Maria Vukovic	Maria's products	\$132
15	Kim Kim	Kim's products	\$238
17	Kim Kim	Kim's products	\$110

-Message table-

Message Table

Messages from users to you

ID	MESSAGE	DELETE
21	Hej, kao kako si mo	DELETE
22	Cacoooooooooooo	DELETE

-Menu table-

Menu Table

Menu

Priority disclaimer! 2 is for users/3 for admin

ID	NAME	ROUTE	ORDER	PRIORITY	UPDATE	DELETE
1	Home	home	1	1	UPDATE	DELETE
2	Shop	products	2	1	UPDATE	DELETE
3	Contact	contactForm	3	2	UPDATE	DELETE
4	Admin Panel	adminPanel	4	3	UPDATE	DELETE

### -Category Table-

Category Table

Category

ID	NAME	UPDATE	DELETE
1	<input type="text" value="user"/>	<input type="button" value="UPDATE"/>	<input type="button" value="DELETE"/>
2	<input type="text" value="teacher"/>	<input type="button" value="UPDATE"/>	<input type="button" value="DELETE"/>
3	<input type="text" value="workshop"/>	<input type="button" value="UPDATE"/>	<input type="button" value="DELETE"/>
4	<input type="text" value="forum"/>	<input type="button" value="UPDATE"/>	<input type="button" value="DELETE"/>
5	<input type="text" value="gallery"/>	<input type="button" value="UPDATE"/>	<input type="button" value="DELETE"/>
6	<input type="text" value="music"/>	<input type="button" value="UPDATE"/>	<input type="button" value="DELETE"/>

Insert category

### -Users Table- (Mogucnost filtera kada se ko registrovao po datumu)

Users Table

Users

Filter by date of registration

ID	FIRST NAME	LAST NAME	EMAIL	ROLE	UPDATE ROLE	DELETE USER
21	Kiki	Kiki	kiki@gmail.com	<input type="text" value="user"/>	<input type="button" value="UPDATE ROLE"/>	<input type="button" value="DELETE"/>
23	Mirja	Vucelovic	mirjavucelovic3819@et.edu.rs	<input type="text" value="admin"/>	<input type="button" value="UPDATE ROLE"/>	<input type="button" value="DELETE"/>
24	Bojan	Stefanovskii	youtubecbojano@gmail.com	<input type="text" value="user"/>	<input type="button" value="UPDATE ROLE"/>	<input type="button" value="DELETE"/>

## -Role table-

Role Table

Role







ID	ROLE		
1	<input type="text" value="admin"/>	<input type="button" value="UPDATE"/>	<input type="button" value="DELETE"/>
2	<input type="text" value="user"/>	<input type="button" value="UPDATE"/>	<input type="button" value="DELETE"/>

Insert role

## -Product Table-

Products Table

Products

ID	NAME	PRICE	IMAGE	CHANGE SRC	NAME CAT	DESCRIPTION	UPDATE	DELETE
1	Grey Velvet	228		<input type="button" value="Choose File"/> No file chosen	couch	This wingback ch	<input type="button" value="UPDATE"/>	<input type="button" value="DELETE"/>
2	Dark Black	413		<input type="button" value="Choose File"/> No file chosen	want	This armchair has 1	<input type="button" value="UPDATE"/>	<input type="button" value="DELETE"/>
3	Simple Wood	488		<input type="button" value="Choose File"/> No file chosen	chair	Add elegance to y	<input type="button" value="UPDATE"/>	<input type="button" value="DELETE"/>
4	Mustard	822		<input type="button" value="Choose File"/> No file chosen	couch	Form meets funci	<input type="button" value="UPDATE"/>	<input type="button" value="DELETE"/>
5	Simple Wood	224		<input type="button" value="Choose File"/> No file chosen	mim	This fascinating	<input type="button" value="UPDATE"/>	<input type="button" value="DELETE"/>
6	White Wood	337		<input type="button" value="Choose File"/> No file chosen			<input type="button" value="UPDATE"/>	<input type="button" value="DELETE"/>

Insert product

No file chosen

## -Main Product Table-

ID	NAME	IMAGE	CHANGE SRC	NAME CAT	DESCRIPTION	UPDATE
31	main1	pic1.jpg	<input type="button" value="Choose File"/> No file chosen	pouches	Want one? Come ch...	<input type="button" value="UPDATE"/>
32	main2	pic2.jpg	<input type="button" value="Choose File"/> No file chosen	shoe	I know you need it, k	<input type="button" value="UPDATE"/>
33	main3	pic3.jpg	<input type="button" value="Choose File"/> No file chosen	wardrobe	Your clothes is in nee	<input type="button" value="UPDATE"/>
34	main4	pic4.jpg	<input type="button" value="Choose File"/> No file chosen	table	Check it now we kno	<input type="button" value="UPDATE"/>
35	main5	pic5.jpg	<input type="button" value="Choose File"/> No file chosen	mirror	Take a look at our m	<input type="button" value="UPDATE"/>
36	main6	pic6.jpg	<input type="button" value="Choose File"/> No file chosen	shelves	You need a storage s	<input type="button" value="UPDATE"/>

# 5. Kodovi

## 5.1 JS kodovi

```
$(document).ready(function () {
    cartLength();
    //token
    const token = $('meta[name="csrf-token"]').attr('content');
    //search
    $("#search").click(search);
    //cart
    $(".addToCart").click(addToCart);
    //updateAdmin
    $("#updateAdmin").click(updateAdmin);
    //filter by date-registration
    $("#date").change(filterByRdate);
    //filter by date-log in
    $("#dateLogIn").change(filterByLogInDate);
    //filter by date-logged out
    $("#dateLogOut").change(filterByLoggedOutDate);
    //filter by date-cart
    $("#dateCart").change(filterByCartDate);

    //funkcija za ajax
    function ajaxCallBack(url, method, data, result) {
        $.ajax({
            headers: {'X-CSRF-TOKEN': token},
            url: url,
            method: method,
            dataType: "json",
            data: data,
            success: result,
            error: function (xhr) {
                writeErrors(xhr.responseJSON.errors);
            }
        });
    }

    //ispis errors-a
    function writeErrors(errors) {
        $.each(errors, function (key, value) {
            $("#msg").html(value);
        });
    }

    //skladistenje u Local Storage
    function setItemToLocalStorage(name, value) {
        localStorage.setItem(name, JSON.stringify(value));
    }

    //vracanje iz Local Storage
    function getItemFromLocalStorage(name) {
        return JSON.parse(localStorage.getItem(name));
    }

    //funkcija za search
    function search(e) {
        e.preventDefault();
        var keyword = $("#keyword").val();

        valueToSend = {
```



```

        keyword: keyword
    }

    ajaxCallBAck('/search/' + keyword, "GET", valueToSend, function
(result) {
        writeProducts(result, keyword);
    });
}

//funkcija za ispis proizvoda iz ajaxa
function writeProducts(arrayProducts, keyword) {
    var html = "";
    var lastPage = arrayProducts.last_page;
    console.log(lastPage)
    var url = window.location.origin;
    var arrayProducts = arrayProducts.data;
    if (arrayProducts.length != 0) {
        for (var obj of arrayProducts) {
            html += `<div class="col-md-6 MB">
                <div class="team-item ">
                    <div class="team-image">
                        <a href="/show/${obj.id}">
                            
                        </a>
                    </div>
                    <div class="team-text">
                        <h3>${obj.name} - ${obj.category.name}</h3>`
                        for (var obj2 of obj.price) {
                            html += `<div className="team-
position">${obj2.price}</div>`
                        }
                        html += `</br>
                                </div>
                                <input type="button" class="btn
btn-secondary MB addToCart ${disabled()}" value="Add to cart" data-
id="${obj.id}"/>
                                </div>
                            </div>`
                    }
                } else {
                    html += `<h1 class="text-center">There are no products!</h1>`
                }
            $("#products").html(html);
            $(".addToCart").click(addToCart);
            writePag();

            function writePag() {
                var html2 = "";
                if (lastPage != 1) {
                    html2 += `<li class="page-item disabled"><a class="page-
link"></a></li>`
                    for (var i = 1; i <= lastPage; i++) {
                        if(i==1){
                            html2 += `
                                <li class="page-item active"><a class="page-link"
href="http://127.0.0.1:8000/products/${keyword}?page=${i}">${i}</a></li>`
                        }
                        else{
                            html2 += `

```

```

        <li class="page-item"><a class="page-link"
href="http://127.0.0.1:8000/products/${keyword}?page=${i}">${i}</a></li>`
    }

    }
    html2 += `<li class="page-item"><a class="page-link"
href="http://127.0.0.1:8000/products/${keyword}?page=${lastPage+1}">></a></li>
>`
    }

    $("#pagination").html(html2);
}

}

//funkcija za disable-vanje dugmeta kada nema sesije
function disabled() {
    var html3 = "";
    var session = $('#session').val();

    if (session) {
        html3 += "";
    } else {
        html3 += "disabled";
    }
    return html3;
}

//dohvatanje svih proizvoda
ajaxCallBAck("/products/get", "GET", "", function (result) {
    setItemToLocalStorage("products", result);
});

//funkcija za izracunavanje quantity-ja
function cartLength() {
    var cartItems = getItemFromLocalStorage("cartItems");
    if (cartItems != null) {
        var nmbOfProd = cartItems.length;
        $("#countCart").html(nmbOfProd);
    }
}

//funkcija za korpu
function addToCart() {
    var products = getItemFromLocalStorage("products");
    var idCart = $(this).attr("data-id");
    var currentLS = catchAll();
    var objectProduct = products.filter(p => p.id == idCart);
    if (!currentLS) {
        notInCurrentLS(objectProduct);
    } else {
        var isInCart = currentLS.some(s => s.id == idCart);
        if (!isInCart) {
            notInCart(objectProduct, currentLS);
        } else {
            alreadyExists(currentLS, idCart);
        }
        setItemToLocalStorage("cartItems", currentLS);
        cartLength();
    }
    alertAddToCart();
}

```

```

}

function alertAddToCart() {
    alert("Album has been added to the cart.");
}

//dohvatanje svakog proizvoda iz korpe
function catchAll() {
    return getItemFromLocalStorage("cartItems");
}

function notInCurrentLS(objectProduct) {
    objectProduct[0].quantity = 1;
    setItemToLocalStorage("cartItems", objectProduct);
    cartLength();
}

function notInCart(objectProduct, currentLS) {
    objectProduct = objectProduct[0];
    objectProduct.quantity = 1;
    currentLS.push(objectProduct);
    cartLength();
}

function alreadyExists(currentLS, idCart) {
    currentLS = currentLS.map(m => {
        if (m.id == idCart) {
            m.quantity += 1;
        }
        return m;
    });
}

//funkcija za ispis na strani cart
var cartItems = getItemFromLocalStorage("cartItems");
if (cartItems == null) {
    $("#cartEmpty").html("Your cart is empty - go back to shopping.");
} else {
    checkCart();
}

function checkCart() {
    var cartItems = getItemFromLocalStorage("cartItems");
    html3 = "";
    html3 += `<table id="cart" class="table table-hover table-condensed">
    <thead>
    <tr>
        <th class="col-5 ">Products</th>
        <th class="col-2">Price</th>
        <th class="col-1">Quantity</th>
        <th class="col-3 text-center">Total</th>
        <th class="col-2">Remove</th>
    </tr>
    </thead>`
    for (var obj3 of cartItems) {
        html3 += `<tbody>
        <tr>
            <td data-th="Product">
                <div class="col-sm-2 hidden-xs mr-5" >
                    

```

```

        </div>
        <div class="col-sm-5">
            <h5>${obj3.name}</h5>
        </div>
    </td>`
    for (var obj4 of obj3.price) {
        html3 += `<td data-th="Price">${obj4.price}</td>
            <td data-th="Quantity">
                <p>${obj3.quantity}</p>
            </td>
            <td data-th="Total" class="text-
center">${(obj4.price * obj3.quantity)}</td>`
    }
    html3 += `<td class="actions">
        <a href="#" class="btn btn-warning remove" data-
id="${obj3.id}" >Remove</a>
    </td>
    </tr>
</tbody>`
}
html3 += `<tfoot class="MB">
    <tr>
        <td><a href="/products" class="btn btn-warning"
id="fontColor"><i class="fa fa-angle-left"></i>Back</a></td>
        <td colspan="1" class="hidden-xs"></td>
        <td><a href="#" class="btn btn-warning"
id="clear">Clear</a></td>
        <td class="text-center"><strong id="totalPrice">Total
${totalCost()}</strong></td>
        <td><input type="submit" value="Finish" class="btn btn-
warning" id="finish"/></td>
    </tr>
</tfoot>
</table>`
$("#cartWrite").html(html3);
}

$("#finish").click(alertFinish);
$("#clear").click(clearCartAll);
$(".remove").click(removeCartItem);

function alertFinish(e) {
    e.preventDefault();
    if (cartItems.length != 0) {
        var idUser = $("#cartUser").val();
        var dataToSend = {
            data: idUser
        };
        let cart;
        for (let i = 0; i < cartItems.length; i++) {
            cart = "cart" + i;
            dataToSend[cart] = cartItems[i];
        }

        ajaxCallBack('/cart/store', "POST", dataToSend, function (result)
{
            alert(result);
            localStorage.removeItem("cartItems");
            location.reload();
        }));
    }
}

```

```

}

function clearCartAll(e) {
    e.preventDefault();
    localStorage.removeItem("cartItems");
    location.reload();
}

function removeCartItem(e) {
    e.preventDefault();
    var cartItems = getItemFromLocalStorage("cartItems");

    if (cartItems.length == 1) {
        clearCartAll(e);
    } else {
        var idR = $(this).attr("data-id");
        var removeFilter = cartItems.filter(c => c.id != idR);

        setItemToLocalStorage("cartItems", removeFilter);
        location.reload();
    }
}

function totalCost() {
    var cartItems = getItemFromLocalStorage("cartItems");
    for (var obj6 of cartItems) {
        if (cartCost != null) {
            for (var obj7 of obj6.price) {
                setItemToLocalStorage("totalCost",
getItemFromLocalStorage("totalCost") + obj7.price * obj6.quantity);
            }
        } else {
            for (var obj8 of obj6.price) {
                setItemToLocalStorage("totalCost", obj8.price *
obj6.quantity);
            }
        }
        var cartCost = getItemFromLocalStorage("totalCost");
    }
    if (cartCost != null) {
        return cartCost;
    } else {
        return 0;
    }
}

//funkcija za update adminovog profila
function updateAdmin() {
    var firstName = $("#nameInputAdmin").val();
    var lastName = $("#lastNameInputAdmin").val();
    var email = $("#emailInputAdmin").val();

    var dataToSend = {
        firstName: firstName,
        lastName: lastName,
        email: email
    }

    ajaxCallBAck("admin/put", "POST", dataToSend, function (result) {
        $("#msg").html(result)
    });
}

```

```

}

//funkcija za filter by date-registration
function filterbyRdate() {
    var valueDate = $(this).val();

    var valueToSend = {
        valueDate: valueDate
    }

    ajaxCallBack("/adminPanel/activity/registrationFilter", "POST",
valueToSend, function (result) {
        writeRegistrationUsers(result.dateUsers);
    });
}

//funkcija za ispis iz prethodne funkcije
function writeRegistrationUsers(arrayUsers) {
    var html4 = "";
    var html5 = "";
    html4 += `<thead>
        <tr>
            <th scope="col">id</th>
            <th scope="col">first name</th>
            <th scope="col">last name</th>
            <th scope="col">email</th>
            <th scope="col">role</th>
        </tr>
    </thead>
    <tbody>`
    if (arrayUsers.length != 0) {
        for (var obj9 of arrayUsers) {
            html4 += `<tr>
                <th scope="row">${obj9.id}</th>
                <td name="nameUser">${obj9.firstName}</td>
                <td name="lastNameUser">${obj9.lastName}</td>
                <td name="emailUser">${obj9.email}</td>
                <td name="roleUser">${obj9.role.role}</td>
            </tr>
        </tbody>`
        }
    } else {
        html5 += `<div class="alert alert-dark">There are no registered
users on this date!</div>`
    }
    $("#users").html(html4);
    $("#text").html(html5);
}

//funkcija za filter by date-log in
function filterByLogInDate() {
    var valueDate = $(this).val();

    var valueToSend = {
        valueDate: valueDate
    }

    ajaxCallBack("/adminPanel/activity/loginFilter", "POST", valueToSend,
function (result) {
        writeUsers(result.users, result.roles);
    });
}

```

```

}

//funkcija za ispis iz prethodne funkcije
function writeUsers(arrayUsers, arrayRoles) {
    var html6 = "";
    var html7 = "";
    if (arrayUsers.length != 0) {
        for (var obj10 of arrayUsers) {
            html6 += `<tr>
                <th scope="row">${obj10.user.id}</th>
                <td name="nameUser">${obj10.user.firstName}</td>
                <td name="lastNameUser">${obj10.user.lastName}</td>
                <td name="emailUser">${obj10.user.email}</td>`
            for (var obj11 of arrayRoles) {
                if (obj11.id == obj10.user.roles_id) {
                    html6 += `<td name="roleUser">${obj11.role}</td>`
                }
            }
            html6 += `</tr>`
        }
    } else {
        html7 += `<div class="alert alert-dark">There are no logged in
users on this date!</div>`
    }
    $("#usersLoggedIn").html(html6);
    $("#text").html(html7);
}

//funkcija za filter by date-logged out
function filterByLoggedOutDate() {
    var valueDate = $(this).val();

    var valueToSend = {
        valueDate: valueDate
    }

    ajaxCallBack("/adminPanel/activity/loggedOutFilter", "POST",
valueToSend, function (result) {
        writeUsers(result.users, result.roles);
    });
}

//funkcija za filter by date-cart orders
function filterByCartDate() {
    var valueDate = $(this).val();

    var valueToSend = {
        valueDate: valueDate
    }

    ajaxCallBack("/adminPanel/cart/cartFilter", "POST", valueToSend,
function (result) {
        writeCartByDate(result.carts, result.orders, result.prices);
    });
}

//funkcija za ispis iz prethodne funkcije
function writeCartByDate(arrayCarts, arrayOrders, arrayPrices) {
    var html8 = "";
    var html9 = "";
    var allP = 0;

```

```

        if (arrayCarts.length != 0) {
            for (var obj12 of arrayCarts) {
                html8 += `<tr>
                    <th scope="row">${obj12.id}</th>
                    <td name="nameUser">${obj12.user.firstName}
${obj12.user.lastName}</td>
                    <td>
                        <select name="productsCart" class="form-control">
                            <option selected
value="0">${obj12.user.firstName}'s products</option>`
                            for (var obj13 of arrayOrders) {
                                if (obj13.cart_id == obj12.id) {
                                    html8 += `<option
value="${obj13.product.id}">${obj13.product.name}
(${obj13.quantity})</option>`
                                }
                            }
                        </select>
                    </td>`
                for (var obj14 of arrayOrders) {
                    if (obj14.cart_id == obj12.id) {
                        for (var obj15 of arrayPrices) {
                            if (obj15.products_id == obj14.products_id) {
                                allP += obj15.price * obj14.quantity
                            }
                        }
                    }
                }
                html8 += `<td>${allP}</td>
            </tr>`
        }
    } else {
        html9 += `<div class="alert alert-dark">There are no orders made
on this date by any user!</div>`
    }

    $("#cartDate").html(html8);
    $("#text").html(html9);
}
})

```

kraj JS kodova

## 5.2 PHP-laravel kodovi

### Controllers/admin/AdminController.php

```
<?php
```

```

namespace App\Http\Controllers\admin;

use App\Http\Controllers\admin\MainController;
use App\Http\Requests\updateAdminRequest;
use App\Models\Products;
use App\Models\Users;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Log;

```



```

class AdminController extends MainController
{
    public function index(){

        $this->data['admin']=Users::with(['role'])
            ->where("roles_id","=", "1")
            ->first();

        return view("pages.admin.admin", $this->data);
    }

    public function put(UpdateAdminRequest $request){

        $user = Users::where("roles_id","=", "1")->first();
        $firstName = $request->input("firstName");
        $lastName = $request->input("lastName");
        $email = $request->input("email");

        try {
            DB::beginTransaction();
            $user->firstName = $firstName;
            $user->lastName = $lastName;
            $user->email = $email;
            $user->save();

            DB::commit();

            if ($user->save()) {
                session()->put("user", $user);
                return json_encode("Your account has been updated!");
            }
        } catch (\Exception $e){
            DB::rollBack();
            $guid = uniqid();
            Log::error( $guid . " " . $e->getMessage());
            return view("error", ["errorId" => $guid]);
        }
    }
}

```

## Controllers/admin/CartAdminController.php

```

<?php

namespace App\Http\Controllers\admin;

use App\Http\Controllers\admin\MainController;
use App\Models\Cart;
use App\Models\Order;
use App\Models\Prices;
use App\Models\Products;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Log;

```

```

class CartAdminController extends MainController
{
    public function index() {

        $this->data["carts"]=Cart::with(["user", "order"])
            ->get();

        $this->data["orders"]=Order::with(["product"])
            ->get();

        $this->data["prices"]=Prices::with(['product'])
            ->get();

        return view("pages.admin.cart", $this->data);
    }

    public function cartFilter(Request $request) {
        $valueDate=$request->valueDate;

        try{
            DB::beginTransaction();
            $carts=Cart::with(['user', 'order'])
                ->where("created_at","LIKE", "$valueDate%")
                ->get();

            $orders=Order::with(['product'])
                ->get();

            $prices=Prices::with(['product'])
                ->get();

            DB::commit();

            if($carts){
                return json_encode([
                    "carts"=>$carts,
                    "orders"=>$orders,
                    "prices"=>$prices
                ]);
            }
        }
        catch (\Exception $e) {
            DB::rollBack();
            $guid = uniqid();
            Log::error($guid . " " . $e->getMessage());
            return view("pages.main.error", ["errorId" => $guid]);
        }
    }
}

```

## Controllers/admin/CategoryController.php

```

<?php

namespace App\Http\Controllers\admin;

use App\Http\Controllers\admin\MainController;
use App\Http\Requests\AdminCategoryRequest;

```

```

use App\Http\Requests\AdminMenuRequest;
use App\Models\Categories;
use App\Models\Menus;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Log;

class CategoryController extends MainController
{
    public function index() {

        $this->data["categories"]=Categories::all();

        return view("pages.admin.category", $this->data);
    }

    public function put(AdminCategoryRequest $request) {
        $id=$request->hiddenId;
        $category=Categories::where("id","=", $id)->first();

        try {
            DB::beginTransaction();
            $category->name = $request->nameCategory;
            $category->save();

            DB::commit();

            if ($category->save()) {
                return redirect()->back()->with([
                    "msg" => ucfirst($request->nameCategory)." row has been
updated!"
                ]);
            }
        } catch (\Exception $e) {
            DB::rollBack();
            $guid = uniqid();
            Log::error( $guid . " " . $e->getMessage());
            return view("error", ["errorId" => $guid]);
        }
    }

    public function delete(Request $request) {
        $id=$request->hiddenId;

        try {
            DB::beginTransaction();
            $category=Categories::find($id);
            $category->delete();

            DB::commit();

            if($category->delete()) {
                return redirect()->back()->with([
                    "msg" => "Deleting was successful!"
                ]);
            }
        } catch (\Exception $e) {

```

```

        DB::rollback();
        $guid = uniqid();
        Log::error( $guid . " " . $e->getMessage());
        return view("error", ["errorId" => $guid]);
    }

}

public function store(AdminCategoryRequest $request){

    try{
        DB::beginTransaction();
        $insertCategory=CATEGORIES::create([
            "name"=>$request->nameCategory
        ]);

        DB::commit();

        if($insertCategory){
            return redirect()->back()->with([
                "msg" => "Inserting ".$request->nameCategory." category
was successful!"
            ]);
        }
    }
    catch(\Exception $exception){
        DB::rollback();
        $guid = uniqid();
        Log::error( $guid . " " . $exception->getMessage());
        dd($exception->getMessage());
        return view("pages.main.error", ["errorId" => $guid]);
    }
}
}

```

## Controllers/admin/MainController.php

```

<?php

namespace App\Http\Controllers\admin;

use App\Http\Controllers\Controller;

class MainController extends Controller
{
    public $data;

    public function __construct(){
        $this->data["menuAdmin"]=[ [
            "link"=>"/adminPanel",
            "icon"=>"nc-circle-10",
            "name"=>"Admins profile"
        ],
        [
            "link"=>"/adminPanel/activity",
            "icon"=>"nc-tap-01",
            "name"=>"Users activity"
        ],
        [

```

```

        "link"=>"/adminPanel/cart",
        "icon"=>"nc-cart-simple",
        "name"=>"Cart activity"
    ],
    [
        "link"=>"/adminPanel/message",
        "icon"=>"nc-email-85",
        "name"=>"Messages Table"
    ],
    [
        "link"=>"/adminPanel/menu",
        "icon"=>"nc-bullet-list-67",
        "name"=>"Menus Table"
    ],
    [
        "link"=>"/adminPanel/category",
        "icon"=>"nc-bullet-list-67",
        "name"=>"Categories Table"
    ],
    [
        "link"=>"/adminPanel/user",
        "icon"=>"nc-bullet-list-67",
        "name"=>"Users Table"
    ],
    [
        "link"=>"/adminPanel/role",
        "icon"=>"nc-bullet-list-67",
        "name"=>"Roles Table"
    ],
    [
        "link"=>"/adminPanel/product",
        "icon"=>"nc-bullet-list-67",
        "name"=>"Products Table"
    ],
    [
        "link"=>"/adminPanel/mainProduct",
        "icon"=>"nc-bullet-list-67",
        "name"=>"Main products Table"
    ],
    [
        "link"=>"/",
        "icon"=>"nc-spaceship",
        "name"=>"Go back to site"
    ]
];
}
}

```

## Controllers/admin/MainProductController.php

```

<?php

namespace App\Http\Controllers\admin;

use App\Http\Controllers\admin\MainController;
use App\Http\Requests\AdminMainProductRequest;
use App\Models\Products;
use Illuminate\Support\Facades\DB;

```

```

use Illuminate\Support\Facades\Log;

class MainProductController extends MainController
{
    public function index(){
        $this->data['mainProducts'] = Products::with(['category', 'price'])
            ->where("main", "=", "1")
            ->get();

        return view("pages.admin.mainProduct", $this->data);
    }

    public function put(AdminMainProductRequest $request){
        $id=$request->hiddenId;
        $product=Products::where("id", "=", $id)->first();

        if($request->fileProducts != null){
            $name=$request->fileProducts->getClientOriginalName();
            $nameArray=explode(".", $name);
            $src=$nameArray[0].time().".$nameArray[1];
        }
        else{
            $src=$product->image;
        }

        try {
            DB::beginTransaction();
            $product->image = $src;
            $product->description = $request->descriptionProducts;
            $product->save();

            if($request->fileProducts != null){
                $request->fileProducts-
>move(public_path("asset/images/main"), $src);
            }

            DB::commit();

            if ($product->save()) {
                return redirect()->back()->with([
                    "msg" => "This row has been updated!"
                ]);
            }
        }
        catch (\Exception $e){
            DB::rollBack();
            $guid = uniqid();
            Log::error( $guid . " " . $e->getMessage());
            return view("pages.main.error", ["errorId" => $e->getMessage()]);
        }
    }
}

```

Controllers/admin/MenuController.php

```

<?php

namespace App\Http\Controllers\admin;

use App\Http\Controllers\admin\MainController;
use App\Http\Requests\AdminMenuRequest;
use App\Models\Menus;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Log;

class MenuController extends MainController
{
    public function index(){

        $this->data["menu"]=Menus::all();

        return view("pages.admin.menu", $this->data);
    }

    public function put(AdminMenuRequest $request){
        $id=$request->hiddenId;
        $menu=Menus::where("id","=", $id)->first();

        try {
            DB::beginTransaction();
            $menu->name = $request->nameMenu;
            $menu->route = $request->routeMenu;
            $menu->order = $request->orderMenu;
            $menu->priority = $request->priorityMenu;
            $menu->save();

            DB::commit();

            if ($menu->save()) {
                return redirect()->back()->with([
                    "msg" => $request->nameMenu." row has been updated!"
                ]);
            }
        } catch (\Exception $e){
            DB::rollBack();
            $guid = uniqid();
            Log::error( $guid . " " . $e->getMessage());
            return view("error", ["errorId" => $guid]);
        }
    }

    public function delete(Request $request){
        $id=$request->hiddenId;

        try {
            DB::beginTransaction();
            $menu=Menus::find($id);
            $menu->delete();

            DB::commit();

            if ($menu->delete()) {

```

```

        return redirect()->back()->with([
            "msg" => "Deleting was successful!"
        ]);
    }
}
}
catch (\Exception $e){
    DB::rollback();
    $guid = uniqid();
    Log::error( $guid . " " . $e->getMessage());
    return view("error", ["errorId" => $guid]);
}
}
}
}

```

## Controllers/admin/MessageController.php

```

<?php

namespace App\Http\Controllers\admin;

use App\Http\Controllers\admin\MainController;
use App\Models\Message;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Log;

class MessageController extends MainController
{
    public function index() {

        $this->data['messages']=Message::with(['user'])->get();

        return view("pages.admin.message", $this->data);

    }

    public function delete(Request $request)
    {
        $id = $request->hiddenId;

        try {
            DB::beginTransaction();
            $message = Message::find($id);
            $message->delete();

            DB::commit();

            if ($message->delete()) {
                return redirect()->back()->with([
                    "msg" => "Deleting was successful!"
                ]);
            }
        } catch (\Exception $e) {
            DB::rollback();
            $guid = uniqid();
            Log::error($guid . " " . $e->getMessage());
            return view("pages.main.error", ["errorId" => $guid]);
        }
    }
}

```



## Controllers/admin/ProductController.php

```
<?php

namespace App\Http\Controllers\admin;

use App\Http\Controllers\admin\MainController;
use App\Http\Requests\AdminProductRequest;
use App\Models\CATEGORIES;
use App\Models\Prices;
use App\Models\Products;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Log;
use Illuminate\Support\Facades\File;

class ProductController extends MainController
{
    public function index()
    {
        $this->data['products'] = Products::with(['category', 'price'])
            ->where("main", "=", "0")
            ->get();
        $this->data["categories"] = Categories::all();

        return view("pages.admin.product", $this->data);
    }

    public function put(AdminProductRequest $request){
        $id=$request->hiddenId;
        $product=Products::where("id","=", $id)->first();
        $price=Prices::where("products_id","=", $id)->first();

        if($request->fileProducts != null){
            $name=$request->fileProducts->getClientOriginalName();
            $nameArray=explode(".", $name);
            $src=$nameArray[0].time().".$nameArray[1];
        }
        else{
            $src=$product->image;
        }

        try {
            DB::beginTransaction();
            $product->name = $request->nameProducts;
            $product->image = $src;
            $product->description = $request->descriptionProducts;
            $product->categories_id = $request->catProducts;
            $product->save();

            if ($product->save()) {
                $price->price=$request->priceProducts;
                $price->save();
            }
        }
    }
}
```

```

        if($request->fileProducts != null){
            $request->fileProducts->
>move(public_path("asset/images/gallery"), $src);
        }

        DB::commit();

        if ($product->save() && $price->save()) {
            return redirect()->back()->with([
                "msg" => ucfirst($request->nameProducts)." row has been
updated!"
            ]);
        }

    }
    catch (\Exception $e){
        DB::rollback();
        $guid = uniqid();
        Log::error( $guid . " " . $e->getMessage());
        return view("pages.main.error", ["errorId" => $e->getMessage()]);
    }
}

public function delete(Request $request){
    $id=$request->hiddenId;

    try {
        DB::beginTransaction();
        $product=Products::find($id);
        $productImg=Products::find($id)->image;
        $price=Prices::where("products_id","=", $id)->first();
        $product->delete();
        File::delete("asset/images/gallery/".$productImg);

        if($product->delete()){
            $price->delete();
        }

        DB::commit();

        if($product->delete() && $price->delete()){
            return redirect()->back()->with([
                "msg" => "Deleting was successful!"
            ]);
        }
    }
    catch (\Exception $e){
        DB::rollback();
        $guid = uniqid();
        Log::error( $guid . " " . $e->getMessage());
        return view("pages.main.error", ["errorId" => $guid]);
    }
}

public function store(AdminProductRequest $request){

    if($request->fileProducts !=null){
        $name=$request->fileProducts->getClientOriginalName();
    }
}

```

```

        $nameArray=explode(".", $name);
        $src=$nameArray[0].time().".$nameArray[1];
    }
    else{
        return redirect()->back()->with([
            "msgerror" => "The file products field is required."
        ]);
    }

    if($request->catProducts == 0){
        return redirect()->back()->with([
            "msgerror" => "Category must be chosen."
        ]);
    }

    try{
        DB::beginTransaction();
        $insertProduct=Products::create([
            "name"=>$request->nameProducts,
            "image"=>$src,
            "description"=>$request->descriptionProducts,
            "main"=>"0",
            "categories_id"=>$request->catProducts,
        ]->id;

        if($insertProduct){
            $insertPrice=Prices::create([
                "price"=>$request->priceProducts,
                "products_id"=>$insertProduct
            ]);
        }

        $request->fileProducts->move(public_path("asset/images/gallery"),
$src);

        DB::commit();

        if($insertProduct && $insertPrice){
            return redirect()->back()->with([
                "msg" => "Inserting ".$request->nameProducts." product
was successful!"
            ]);
        }
    }
    catch(\Exception $exception){
        DB::rollBack();
        $guid = uniqid();
        Log::error( $guid . " " . $exception->getMessage());
        dd($exception->getMessage());
        return view("pages.main.error", ["errorId" => $guid]);
    }
}
}

```

Controllers/admin/RoleController.php

```

<?php

namespace App\Http\Controllers\admin;

use App\Http\Controllers\admin\MainController;
use App\Http\Requests\AdminRoleRequest;
use App\Models\Roles;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Log;

class RoleController extends MainController
{
    public function index()
    {
        $this->data['roles']=Roles::all();

        return view("pages.admin.role", $this->data);
    }

    public function put(AdminRoleRequest $request){
        $id=$request->hiddenId;
        $role=Roles::where("id","=", $id)->first();

        try {
            DB::beginTransaction();
            $role->role = $request->nameRole;
            $role->save();

            DB::commit();

            if ($role->save()) {
                return redirect()->back()->with([
                    "msg" => ucfirst($request->nameRole)." row has been
updated!"
                ]);
            }
        } catch (\Exception $e){
            DB::rollBack();
            $guid = uniqid();
            Log::error( $guid . " " . $e->getMessage());
            return view("pages.main.error", ["errorId" => $guid]);
        }
    }

    public function delete(Request $request){
        $id=$request->hiddenId;

        try {
            DB::beginTransaction();
            $role=Roles::find($id);
            $role->delete();

            DB::commit();

            if($role->delete()){
                return redirect()->back()->with([
                    "msg" => "Deleting was successful!"
                ]);
            }
        }
    }
}

```

```

        });
    }
}
catch (\Exception $e){
    DB::rollback();
    $guid = uniqid();
    Log::error( $guid . " " . $e->getMessage());
    return view("pages.main.error", ["errorId" => $guid]);
}
}

public function store(AdminRoleRequest $request){

    try{
        DB::beginTransaction();
        $insertRole=Roles::create([
            "role"=>$request->nameRole
        ]);

        DB::commit();

        if($insertRole){
            return redirect()->back()->with([
                "msg" => "Inserting ".$request->nameRole." category was
successful!"
            ]);
        }
    }
    catch (\Exception $exception){
        DB::rollback();
        $guid = uniqid();
        Log::error( $guid . " " . $exception->getMessage());
        dd($exception->getMessage());
        return view("pages.main.error", ["errorId" => $guid]);
    }
}
}
}

```

## Controllers/admin/UserController.php

```

<?php

namespace App\Http\Controllers\admin;

use App\Http\Controllers\admin\MainController;
use App\Models\Roles;
use App\Models\Users;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Log;

class UserController extends MainController
{
    public function index()
    {
        $this->data['users'] = Users::all();
    }
}

```

```

        $this->data['roles'] = Roles::all();

        return view("pages.admin.user", $this->data);
    }

    public function put(Request $request)
    {
        $id = $request->hiddenId;
        $role = $request->roleUser;
        $user = Users::where("id", "=", $id)->first();

        try {
            DB::beginTransaction();
            $user->roles_id = $role;
            $user->save();

            DB::commit();

            if ($user->save()) {
                return redirect()->back()->with([
                    "msg" => "Role has been updated for " . $user->firstName
                    . " " . $user->lastName
                ]);
            }
        } catch (\Exception $e) {
            DB::rollBack();
            $guid = uniqid();
            Log::error($guid . " " . $e->getMessage());
            return view("pages.main.error", ["errorId" => $guid]);
        }
    }

    public function delete(Request $request)
    {
        $id = $request->hiddenId;

        try {
            DB::beginTransaction();
            $user = Users::find($id);
            $user->delete();

            DB::commit();

            if ($user->delete()) {
                return redirect()->back()->with([
                    "msg" => "Deleting was successful!"
                ]);
            }
        } catch (\Exception $e) {
            DB::rollBack();
            $guid = uniqid();
            Log::error($guid . " " . $e->getMessage());
            return view("pages.main.error", ["errorId" => $guid]);
        }
    }
}

```

```

<?php

namespace App\Http\Controllers\admin;

use App\Http\Controllers\admin\MainController;
use App\Models\Roles;
use App\Models\Users;
use App\Models\UsersActivity;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Log;
use Psy\Util\Json;

class UsersActivityController extends MainController
{
    public function index()
    {
        $this->data['users'] = Users::with(["role"])->get();

        return view("pages.admin.usersActivity", $this->data);
    }

    public function registrationFilter(Request $request){
        $valueDate=$request->valueDate;

        try{
            DB::beginTransaction();
            $dateUsers=Users::with(["role"])
                ->where("created_at","LIKE", "$valueDate%")
                ->get();

            DB::commit();

            if($dateUsers){
                return json_encode([
                    "dateUsers"=>$dateUsers
                ]);
            }
        } catch (\Exception $e) {
            DB::rollBack();
            $guid = uniqid();
            Log::error($guid . " " . $e->getMessage());
            return view("pages.main.error", ["errorId" => $guid]);
        }
    }

    public function loginFilter(Request $request){
        $valueDate=$request->valueDate;

        try{
            DB::beginTransaction();
            $users=UsersActivity::with(['user'])
                ->where("dateLogin","=", $valueDate)
                ->get();

            $roles=Roles::all();

            DB::commit();

```

```

        if($users){
            return json_encode([
                "users"=>$users,
                "roles"=>$roles
            ]);
        }
    }
    catch (\Exception $e) {
        DB::rollBack();
        $guid = uniqid();
        Log::error($guid . " " . $e->getMessage());
        return view("pages.main.error", ["errorId" => $guid]);
    }
}

public function loggedOutFilter(Request $request){
    $valueDate=$request->valueDate;

    try{
        DB::beginTransaction();
        $users=UsersActivity::with(['user'])
            ->where("dateLoggingOut","=", $valueDate)
            ->get();

        $roles=Roles::all();

        DB::commit();

        if($users){
            return json_encode([
                "users"=>$users,
                "roles"=>$roles
            ]);
        }
    }
    catch (\Exception $e) {
        DB::rollBack();
        $guid = uniqid();
        Log::error($guid . " " . $e->getMessage());
        return view("pages.main.error", ["errorId" => $guid]);
    }
}
}

```

## Controllers/CartController.php

```

<?php

namespace App\Http\Controllers;

use App\Models\Cart;
use App\Models\Order;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Log;

class CartController extends MainController
{

```



```

public function index() {
    return view("pages.products.cart", $this->data);
}

public function store(Request $request) {
    $idUser = $request->input("data");

    try {
        DB::beginTransaction();
        $insertUser = Cart::create([
            "user_id" => $idUser
        ])->id;

        if($insertUser) {
            for($i=0; $i<count($_POST)-1; $i++) {
                $quantity = $_POST['cart'][$i]['quantity'];
                $idProducts = $_POST['cart'][$i]['id'];

                $insertProduct = Order::create([
                    "quantity" => $quantity,
                    "products_id" => $idProducts,
                    "cart_id" => $insertUser
                ]);
                DB::commit();
            }
        }
        if($insertProduct) {
            return json_encode("Thank you for supporting us.");
        }
    } catch(\Exception $e) {
        DB::rollBack();
        $guid = uniqid();
        Log::error($guid . " " . $e->getMessage());
        return view("error", ["errorId" => $guid]);
    }
}
}

```

## Controllers/ContactController.php

```

<?php

namespace App\Http\Controllers;

use App\Http\Requests\ContactRequest;
use App\Models\Message;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Log;
use Illuminate\Support\Facades\Mail;
use App\Mail\MyMail;

class ContactController extends MainController
{
    public function index() {
        $this->data["messages"] = Message::with(['user'])
            ->get();
        return view("pages.main.contact", $this->data);
    }
}

```

```

public function store(ContactRequest $request) {
    $message=$request->message;
    $id=$request->idUser;

    try{
        DB::beginTransaction();
        $messageInsert=Message::create([
            "message"=>$message,
            "users_id"=>$id
        ]);

        $user=DB::table("users")
            ->where("id", "=", $id)
            ->first();

        DB::commit();

        if($messageInsert){
            $details = [
                'message' => $message,
                'user' => $user->email
            ];

            Mail::to('marija.vucicevic.18.19@ict.edu.rs')->send(new
MyMail($details));

            return redirect()->back()->with([
                "msg" => "Your message has been sent to our
administrators email. Thank you!"
            ]);
        }
        else{
            return redirect("/contactForm");
        }
    }
    catch (\Exception $e){
        DB::rollBack();
        $guid = uniqid();
        Log::error( $guid . " " . $e->getMessage());
        return view("error", ["errorId" => $guid]);
    }
}
}

```

## Controllers/Controller.php

```

<?php

namespace App\Http\Controllers;

use Illuminate\Foundation\Auth\Access\AuthorizesRequests;
use Illuminate\Foundation\Bus\DispatchesJobs;
use Illuminate\Foundation\Validation\ValidatesRequests;
use Illuminate\Routing\Controller as BaseController;

class Controller extends BaseController
{
    use AuthorizesRequests, DispatchesJobs, ValidatesRequests;
}

```

## Controllers/HomeController.php

```
<?php

namespace App\Http\Controllers;

use App\Models\Products;
use App\Models\Users;

class HomeController extends MainController
{
    public function index() {

        $this->data["productsMain"]=Products::with(['category'])
            ->where("main","=", "1")
            ->get();

        return view("pages.main.index", $this->data);
    }
}
```

## Controllers/LoginController.php

```
<?php

namespace App\Http\Controllers;

use App\Http\Requests\LoginRequest;
use App\Models\UsersActivity;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Log;

class LoginController extends MainController
{
    public function index() {
        return view("pages.auth.login", $this->data);
    }

    public function login(LoginRequest $request) {
        $email=$request->email;
        $password=$request->password;

        try{
            DB::beginTransaction();

            $user=DB::table("users")
                ->where("email","=", $email)
                ->where("password", "=", md5($password))
                ->first();

            $userId=DB::table("users")
                ->where("email","=", $email)
                ->where("password", "=", md5($password))
                ->first()->id;

            DB::commit();
        }
```

```

        if($user){
            session()->put("user", $user);
            $currentDate= date("Y-m-d");

            $activity=UsersActivity::create([
                "users_id"=>$userId,
                "dateLogin"=>$currentDate
            ]);

            return redirect("/products");
        }
        else{
            return redirect()->back()->with([
                "msg" => "Check your email or password!"
            ]);
        }
    }
    catch(\Exception $exception){
        DB::rollBack();
        $guid = uniqid();
        Log::error( $guid . " " . $exception->getMessage());
        return view("error", ["errorId" => $guid]);
    }
}

public function logout() {
    $userId=session()->get("user")->id;
    $currentDate= date("Y-m-d");

    try{
        DB::beginTransaction();
        $activity=UsersActivity::create([
            "users_id"=>$userId,
            "dateLoggingOut"=>$currentDate
        ]);

        DB::commit();

        session()->forget("user");
        return redirect("/");
    }
    catch(\Exception $exception){
        DB::rollBack();
        $guid = uniqid();
        Log::error( $guid . " " . $exception->getMessage());
        return view("pages.main.error", ["errorId" => $guid]);
    }
}
}
}

```

## Controllers/MainController.php

```

<?php

namespace App\Http\Controllers;

use App\Models\Users;
use Illuminate\Http\Request;
use App\Models\Menus;

```

```

use Illuminate\Support\Facades\DB;

class MainController extends Controller
{
    public $data;

    public function __construct() {

        $this->data['menusA']=DB::table("menuses")
            ->where("priority", '=', '1')
            ->orWhere("priority", '=', '2')
            ->orWhere("priority", '=', '3')
            ->orderBy("order")
            ->get();

        $this->data['menuU']=DB::table("menuses")
            ->where("priority", "=", "1")
            ->orWhere("priority", "=", "2")
            ->orderBy("order")->get();

        $this->data['menuO']=DB::table("menuses")
            ->where("priority", "=", "1")
            ->orWhere("priority", "=", "0")
            ->orderBy("order")->get();

    }
}

```

## Controllers/ProductsController.php

```

<?php

namespace App\Http\Controllers;
use App\Models\Categories;
use App\Models\Products;
use Illuminate\Http\Request;

class ProductsController extends MainController
{
    public function index($keyword=null) {

        if($keyword!=null){
            $this->data['products']=Products::with(['category', 'price'])
                ->where("name", "LIKE", "%$keyword%")
                ->where("main", "=", "0")
                ->paginate(4);
        }
        else{
            $this->data['products']=Products::where("main", "=", "0")
                ->paginate(4);
        }
        return view("pages.products.index", $this->data);
    }

    public function show($id) {
        $this->data["oneProduct"]=Products::with(['category', 'price'])
            ->where("main", "=", "0")
            ->where("id", "=", $id)
            ->first();
    }
}

```

```

        return view("pages.products.showOne", $this->data,
['description'=>true]);
    }

    public function search($keyword){

        $this->data['products']=Products::with(['category', 'price'])
        ->where("name", "LIKE", "%$keyword%")
        ->paginate(4);

        return json_encode($this->data['products']);

    }

    public function get(){
        $this->data['products']=Products::with(['category', 'price'])
        ->where("main", "=", "0")
        ->get();
        return json_encode($this->data['products']);
    }
}

```

## Controllers/RegisterController.php

```

<?php

namespace App\Http\Controllers;

use App\Http\Requests\RegisterRequest;
use App\Models\User;
use App\Models\Users;
use App\Models\UsersActivity;
use Illuminate\Support\Facades\Date;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Log;

class RegisterController extends MainController
{
    public function index(){
        return view("pages.auth.register", $this->data);
    }

    public function register(RegisterRequest $request){

        try{
            DB::beginTransaction();
            $registered=Users::create([
                "firstName"=>ucfirst($request->firstName),
                "lastName"=>ucfirst($request->lastName),
                "email"=>$request->email,
                "roles_id"=>2,
                "password"=>md5($request->password)
            ]->id;

            DB::commit();

            if($registered){
                return redirect()->back()->with([

```

```

        "msg" => "You have been registered!"
    });
}

else{
    return redirect("/registerForm");
}

}

catch(\Exception $exception){
    DB::rollBack();
    $guid = uniqid();
    Log::error( $guid . " " . $exception->getMessage());
    return view("pages.main.error", ["errorId" => $exception-
>getMessage()]);
}

}

}

```

## Middleware/LoggedInMiddleware

```

<?php

namespace App\Http\Middleware;

use Closure;
use Illuminate\Http\Request;

class LoggedInMiddleware
{
    /**
     * Handle an incoming request.
     *
     * @param  \Illuminate\Http\Request  $request
     * @param  \Closure(\Illuminate\Http\Request):
(\Illuminate\Http\Response|\Illuminate\Http\RedirectResponse)  $next
     * @return \Illuminate\Http\Response|\Illuminate\Http\RedirectResponse
     */
    public function handle(Request $request, Closure $next)
    {
        if(!$request->session()->has("user")){
            return redirect()->route("home");
        }
        return $next($request);
    }
}

```

## Requests/AdminCategoryRequest.php

```

<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class AdminCategoryRequest extends FormRequest
{

```

```

/**
 * Determine if the user is authorized to make this request.
 *
 * @return bool
 */
public function authorize()
{
    return true;
}

/**
 * Get the validation rules that apply to the request.
 *
 * @return array
 */
public function rules()
{
    return [
        "nameCategory"=>"required|string|max:255",
    ];
}
}

```

## Requests/AdminMainProductRequest.php

```

<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class AdminMainProductRequest extends FormRequest
{
    /**
     * Determine if the user is authorized to make this request.
     *
     * @return bool
     */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array
     */
    public function rules()
    {
        return [
            "fileProducts"=>"file|image",
            "descriptionProducts"=>"required|string|max:255"
        ];
    }
}

```



## Requests/AdminMenuRequest.php

```
<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class AdminMenuRequest extends FormRequest
{
    /**
     * Determine if the user is authorized to make this request.
     *
     * @return bool
     */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array
     */
    public function rules()
    {
        return [
            "nameMenu"=>"required|string|max:255",
            "routeMenu"=>"required|string|max:255",
            "orderMenu"=>"required|numeric|min:1",
            "priorityMenu"=>"required|numeric|min:0|max:3"
        ];
    }
}
```

## Requests/AdminProductRequest.php

```
<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class AdminProductRequest extends FormRequest
{
    /**
     * Determine if the user is authorized to make this request.
     *
     * @return bool
     */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     */
}
```

```

        *
        * @return array
        */
public function rules()
{
    return [
        "nameProducts"=>"required|string|max:100",
        "priceProducts"=>"required|numeric",
        "fileProducts"=>"file|image",
        "descriptionProducts"=>"required|string|max:255"
    ];
}
}

```

## Requests/AdminRoleRequest.php

```

<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class AdminRoleRequest extends FormRequest
{
    /**
     * Determine if the user is authorized to make this request.
     *
     * @return bool
     */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array
     */
    public function rules()
    {
        return [
            "nameRole"=>"required|string|max:255"
        ];
    }
}

```

## Requests/ContactRequest.php

```

<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class ContactRequest extends FormRequest
{
    /**

```

```

        * Determine if the user is authorized to make this request.
        *
        * @return bool
        */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array
     */
    public function rules()
    {
        return [
            "message"=>"required|string|max:255"
        ];
    }
}

```

## Requests/LoginRequest.php

```

<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class LoginRequest extends FormRequest
{
    /**
     * Determine if the user is authorized to make this request.
     *
     * @return bool
     */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array
     */
    public function rules()
    {
        return [
            "email"=>"required|email",
            "password"=>"required"
        ];
    }
}

```

## Requests/RegisterRequest.php

```

<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class RegisterRequest extends FormRequest
{
    /**
     * Determine if the user is authorized to make this request.
     *
     * @return bool
     */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array
     */
    public function rules()
    {
        return [
            "firstName" => "required|string|min:3|regex:/^[A-Z] [a-z]{2,15}+$/",
            "lastName" => "required|string|max:15|regex:/^[A-Z] [a-z]{2,15}+$/",
            "email" => "required|unique:users|email|max:255|",
            "password" => "required|regex:/^.{5,}$/",
        ];
    }
}

```

## Requests/UpdateAdminRequest.php

```

<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class updateAdminRequest extends FormRequest
{
    /**
     * Determine if the user is authorized to make this request.
     *
     * @return bool
     */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array
     */
    public function rules()
    {

```

```

    {
        return [
            "firstName"=>"required|string|min:3|regex:/^[A-Z] [a-z]{2,15}+$/",
            "lastName"=>"required|string|max:15|regex:/^[A-Z] [a-z]{2,15}+$/",
            "email"=>"required|email|max:255|"
        ];
    }
}

```

## Mail/MyMail.php

```

<?php

namespace App\Mail;

use Illuminate\Bus\Queueable;
use Illuminate\Contracts\Queue\ShouldQueue;
use Illuminate\Mail\Mailable;
use Illuminate\Queue\SerializesModels;

class MyMail extends Mailable
{
    use Queueable, SerializesModels;

    public $details;

    /**
     * Create a new message instance.
     *
     * @return void
     */
    public function __construct($details)
    {
        $this->details = $details;
    }

    /**
     * Build the message.
     *
     * @return $this
     */
    public function build()
    {
        return $this->subject('Mail from FURNITURE.minimalistic.com')
            ->view('mails.mail');
    }
}

```

## Models/Cart.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;

```

```

use Illuminate\Database\Eloquent\Model;
use Illuminate\Database\Eloquent\SoftDeletes;

class Cart extends Model
{
    use HasFactory, SoftDeletes;
    protected $table="carts";
    protected $fillable=["user_id", "created_at", "updated_at",
"deleted_at"];

    public function user(){
        return $this->belongsTo(Users::class, "user_id", "id");
    }

    public function order(){
        return $this->hasMany(Order::class);
    }
}

```

## Models/Categories.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Database\Eloquent\SoftDeletes;

class Categories extends Model
{
    use HasFactory, SoftDeletes;

    protected $table="categories";
    protected $fillable=["name", "created_at", "updated_at", "deleted_at"];

}

```

## Models/Menus.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Database\Eloquent\SoftDeletes;

class Menus extends Model
{
    use HasFactory, SoftDeletes;
    protected $table="menuses";
    protected $fillable=["name", "route","order", "priority", "created_at",
"updated_at", "deleted_at"];
}

```

## Models/Message.php

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Database\Eloquent\SoftDeletes;

class Message extends Model
{
    use HasFactory, SoftDeletes;
    protected $table="messages";
    protected $fillable=["message", "users_id", "created_at", "updated_at",
"deleted_at"];

    public function user() {
        return $this->belongsTo(Users::class, "users_id", "id");
    }
}
```

## Models/Order.php

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Database\Eloquent\SoftDeletes;

class Order extends Model
{
    use HasFactory, SoftDeletes;

    protected $table="orders";
    protected $fillable=["quantity", "products_id", "cart_id", "created_at",
"updated_at", "deleted_at"];

    public function product() {
        return $this->belongsTo(Products::class, "products_id", "id");
    }

    public function cart() {
        return $this->belongsTo(Cart::class, "cart_id", "id");
    }
}
```

## Models/Prices.php

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
```

```

use Illuminate\Database\Eloquent\Model;
use Illuminate\Database\Eloquent\SoftDeletes;

class Prices extends Model
{
    use HasFactory, SoftDeletes;
    protected $table="prices";
    protected $fillable=["price", "products_id","created_at", "updated_at",
"deleted_at"];

    public function product(){
        return $this->belongsTo(Products::class, "products_id", "id");
    }
}

```

## Models/Products.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Database\Eloquent\SoftDeletes;

class Products extends Model
{
    use HasFactory, SoftDeletes;
    protected $table="products";
    protected $fillable=["name", "image", "description", "main",
"categories_id", "created_at", "updated_at", "deleted_at"];

    public function category(){
        return $this->belongsTo(Categories::class, "categories_id", "id");
    }

    public function price(){
        return $this->hasMany(Prices::class);
    }

    public function order(){
        return $this->hasMany(Order::class);
    }
}

```

## Models/Roles.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Database\Eloquent\SoftDeletes;

class Roles extends Model
{

```



```

        use HasFactory, SoftDeletes;
        protected $table="roles";
        protected $fillable=["role", "created_at", "updated_at", "deleted_at"];

        public function user(){
            return $this->hasMany(Users::class);
        }
    }
}

```

## Models/User.php

```

<?php

namespace App\Models;

use Illuminate\Contracts\Auth\MustVerifyEmail;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\SoftDeletes;
use Illuminate\Foundation\Auth\User as Authenticatable;
use Illuminate\Notifications\Notifiable;
use Laravel\Sanctum\HasApiTokens;

class User extends Authenticatable
{
    use HasApiTokens, HasFactory, Notifiable, SoftDeletes;

    /**
     * The attributes that are mass assignable.
     *
     * @var array<int, string>
     */
    protected $fillable = ["firstName", "lastName", "email", "password",
"email_verified_at", "roles_id", "password", "remember_token", "created_at",
"updated_at", "deleted_at"];

    /**
     * The attributes that should be hidden for serialization.
     *
     * @var array<int, string>
     */
    protected $hidden = [
        'password',
        'remember_token',
    ];

    /**
     * The attributes that should be cast.
     *
     * @var array<string, string>
     */
    protected $casts = [
        'email_verified_at' => 'datetime',
    ];
}

```

## Models/Users.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Database\Eloquent\SoftDeletes;

class Users extends Model
{
    use HasFactory, SoftDeletes;

    protected $table="users";
    protected $fillable=["firstName", "lastName", "email",
"email_verified_at", "roles_id", "password", "remember_token", "created_at",
"updated_at", "deleted_at"];

    public function message() {
        return $this->hasMany(Messages::class);
    }

    public function cart() {
        return $this->hasMany(Cart::class);
    }

    public function role() {
        return $this->belongsTo(Roles::class, "roles_id", "id");
    }

    public function activity() {
        return $this->hasMany(UsersActivity::class);
    }
}

```

## Models/UsersActivity.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class UsersActivity extends Model
{
    use HasFactory;

    protected $table="users_activities";
    protected $fillable=["users_id", "dateLogin",
"dateLoggingOut", "created_at", "updated_at"];

    public function user() {
        return $this->belongsTo(Users::class, "users_id", "id");
    }
}

```

views/fixed/admin/head.blade.php

```

<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="utf-8" />
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width, initial-scale=1">
    <meta name="description" content=@yield("description")>
    <meta name="keywords" content=@yield("keywords")>
    <meta name="author" content="Marija Vučićević">
    <link rel="icon" href="{{asset('asset/images/favicon.png')}}">
    <title>@yield("title")</title>
    <meta content='width=device-width, initial-scale=1.0, maximum-scale=1.0,
user-scalable=0, shrink-to-fit=no' name='viewport' />
    <link
href="https://fonts.googleapis.com/css?family=Montserrat:400,700,200"
rel="stylesheet" />
    <link href="https://maxcdn.bootstrapcdn.com/font-awesome/latest/css/font-
awesome.min.css" rel="stylesheet">
    <link href="{{asset('asset/css/bootstrapM.min.css')}}" rel="stylesheet"
/>
    <link href="{{asset('asset/css/paper-dashboard.css?v=2.0.1')}}"
rel="stylesheet" />
    <link href="{{asset('asset/css/demo.css')}}" rel="stylesheet" />
</head>

```

## views/fixed/admin/nav.blade.php

```

<div class="sidebar" data-color="white" data-active-color="danger">
    <div class="logo">
        <a href="/" class="simple-text logo-normal">
            FURNITURE.    minimalistic
        </a>
    </div>
    <div class="sidebar-wrapper">
        <ul class="nav">
            @foreach($menuAdmin as $m)
                <li>
                    <a href="{{${m['link']}}}">
                        <i class="nc-icon {{${m['icon']}}}"></i>
                        <p>{{${m['name']}}</p>
                    </a>
                </li>
            @endforeach
        </ul>
    </div>
</div>

```

## views/fixed/admin/scripts.blade.php

```

<script src="{{asset('asset/js/jquery.min.js')}}"></script>
<script src="{{asset('asset/js/popper.min.js')}}"></script>
<script src="{{asset('asset/js/bootstrapM.min.js')}}"></script>
<script src="https://maps.googleapis.com/maps/api/js"></script>
<script src="{{asset('asset/js/chartjs.min.js')}}"></script>
<script src="{{asset('asset/js/bootstrap-notify.js')}}"></script>
<script src="{{asset('asset/js/paper-dashboard.min.js?v=2.0.1')}}">1"

```

```
type="text/javascript"></script>
<script src="{{asset('asset/js/main.js')}}" type="text/javascript"></script>
```

## views/fixed/main/footer.blade.php

```
<footer>
    <div class="container">
        <div class="row d-flex justify-content-center">
            <div class="col-sm-12 col-md-4 text-center">
                <a href=""><p>Documentation</p></a>
            </div>
            <div class="col-sm-12 col-md-4 text-center" id="liLI2">
                <p>Marija Vučićević 18/19 &copy; <a
href="https://www.ict.edu.rs/">Visoka ICT Skola</a></p>
            </div>
            <div class="col-sm-12 col-md-4 text-center">
                <a href="https://mvportfolio.netlify.app/"
target="_blank"><p>Author</p></a>
            </div>
        </div>
    </div>
</footer>
```

## views/fixed/main/head.blade.php

```
<head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width, initial-scale=1">
    <meta name="description" content=@yield("description")>
    <meta name="keywords" content=@yield("keywords")>
    <meta name="author" content="Marija Vučićević">
    <link rel="icon" href="{{asset('asset/images/favicon.png')}}">
    <title>@yield("title")</title>
    <link href="{{asset('asset/css/bootstrap.min.css')}}" rel="stylesheet">
    <!--<link rel="stylesheet" href="https://maxcdn.bootstrapcdn.com/font-
awesome/4.4.0/css/font-awesome.min.css">-->
    <script src="https://kit.fontawesome.com/07d868ae10.js"
crossorigin="anonymous"></script>
    <link href="{{asset('asset/css/style.css')}}" rel="stylesheet"
type="text/css">
    <script
src="https://ajax.googleapis.com/ajax/libs/jquery/3.5.1/jquery.min.js"></scri
pt>
    <script src="https://code.jquery.com/jquery-3.2.1.min.js"
integrity="sha384-
xBuQ/xzmlsLoJpyjoggmTEz8OWUFM0/RC5BsqqBDX2v5cMvDHcMakNTNrHIW2I5f"
crossorigin="anonymous"></script>
</head>
```

## views/fixed/main/nav.blade.php

```
<nav class="navbar navbar-default" id="fixed">
    <div class="container">
        <p> {{ session()->has("user") ? "Hi ".session("user") -
```

```

>firstName." ". session("user")->lastName : "" }}</p>
    <div class="navbar-header page-scroll" id="pScroll">
        <button type="button" class="navbar-toggle" data-
toggle="collapse" data-target="#bs-example-navbar-collapse-1">
            <span class="sr-only">Toggle navigation</span>
            <span class="icon-bar"></span>
            <span class="icon-bar"></span>
            <span class="icon-bar"></span>
        </button>
    </div>
    <div class="collapse navbar-collapse" id="bs-example-navbar-collapse-
1">
        <ul class="MB">
            <a class="navbar-brand page-scroll"
href="{{route("home')}}"><h1><mark>FURNITURE.</mark>minimalistic</h1></a>
        </ul>
        <ul class="nav navbar-nav navbar-right">
            @if(session()->has("user"))
                @if(session()->get("user")->roles_id == 1)
                    @foreach($menusA as $ma)
                        <li>
                            <a class="page-scroll"
href="{{route("$ma->route')}}">{{ $ma->name}}
                                @if($ma->name=="Cart") <i class="fa-
solid fa-cart-shopping"><span id="countCart">0</span></i> @endif</a>
                            </li>
                        @endforeach
                    @else
                        @foreach($menusU as $mu)
                            <li>
                                <a class="page-scroll"
href="{{route("$mu->route')}}">{{ $mu->name}}
                                    @if($mu->name=="Cart") <i class="fa-
solid fa-cart-shopping"><span id="countCart">0</span></i> @endif</a>
                                </li>
                            @endforeach
                        @endif
                    @else
                        @foreach($menusO as $mo)
                            <li>
                                <a class="page-scroll" href="{{route("$mo-
>route')}}">{{ $mo->name}}</a>
                            </li>
                        @endforeach
                    @endif
                </ul>
            </div>
        </div>
</nav>

```

## views/fixed/main/scripts.blade.php

```

<!-- Bootstrap core JavaScript
===== -->
<!-- Placed at the end of the document so the pages load faster -->
<script src="{{asset("asset/js/main.js")}}"></script>
<script src="{{asset("asset/js/bootstrap.min.js")}}"></script>
<script src="{{asset("asset/js/SmoothScroll.js")}}"></script>
<script src="{{asset("asset/js/theme-scripts.js")}}"></script>

```

## views/layouts/layout.blade.php

```
<!DOCTYPE html>
<html lang="">
    @include("fixed.main.head")
    <body id="top">
        @include("fixed.main.nav")

        @yield("content")

        @include("fixed.main.footer")

        @include("fixed.main.scripts")
    </body>
</html>
<!DOCTYPE html>
<html lang="">
    @include("fixed.main.head")
    <body id="top">
        @include("fixed.main.nav")

        @yield("content")

        @include("fixed.main.footer")

        @include("fixed.main.scripts")
    </body>
</html>
```

## views/layouts/layoutAdmin.blade.php

```
<!DOCTYPE html>
<html lang="">
    @include("fixed.admin.head")
    <body>
        @include("fixed.admin.nav")

        @yield("content")

        @include("fixed.admin.scripts")
    </body>
</html>
```

## views/emails/mail.blade.php

```
<!DOCTYPE html>
<html>
<head>
    <title>Email for administrator!</title>
</head>
<body>
<h1>From: {{ $details['user'] }}</h1>
<p>Message: {{ $details['message'] }}</p>

<p>Thank you</p>
```

```
</body>
</html>
```

```
views/pages/admin/admin.blade.php
```

[illegible]





[illegible]

```

>product->id}}">{{{$o->product->name}} ({{{$o->quantity}}})</option>
                                @endif
                                @endforeach
                                </select>
                                </td>
                                @foreach($orders as $o)
                                @if($o->cart_id == $c->id)
                                @foreach($prices as $p)
                                @if($p->products_id ==
$o->products_id)
                                {{$allP+=$p->price * $o-
>quantity}}
                                @endif
                                @endforeach
                                @endif
                                @endforeach
                                @endforeach
                                <td>${{$allP}}</td>
                                </tr>
                                @endforeach
                                </tbody>
                                </table>
                                </div>
                                </div>
                                </div>
                                </div>
                                </div>
                                </div>
                                @endsection

```

## views/pages/admin/category.blade.php

```

@extends("layouts.layoutAdmin")

@section("title") Menu Table @endsection
@section("description") Category Admin Panel @endsection
@section("keywords") category, admin, panel @endsection

@section("content")
    <div class="main-panel" style="height: 100vh;">
        <!-- Navbar -->
        <nav class="navbar navbar-expand-lg navbar-absolute fixed-top navbar-
transparent">
            <div class="container-fluid">
                <div class="navbar-wrapper">
                    <div class="navbar-toggle">
                        <button type="button" class="navbar-toggler">
                            <span class="navbar-toggler-bar bar1"></span>
                            <span class="navbar-toggler-bar bar2"></span>
                            <span class="navbar-toggler-bar bar3"></span>
                        </button>
                    </div>
                    <p class="navbar-brand">Category Table</p>
                </div>
                <button class="navbar-toggler" type="button" data-
toggle="collapse" data-target="#navigation" aria-controls="navigation-index"
aria-expanded="false" aria-label="Toggle navigation">
                    <span class="navbar-toggler-bar navbar-kebab"></span>
                    <span class="navbar-toggler-bar navbar-kebab"></span>
                    <span class="navbar-toggler-bar navbar-kebab"></span>
                </button>
            </div>
        </nav>
    </div>

```

```

        </div>
    </nav>
    <!-- End Navbar -->
    <div class="content">
        <div class="container">
            <div class="row">
                <!-- update i delete -->
                <div class="col-md-12">
                    <h3>Category</h3>
                    <div id="category">
                        <table class="table">
                            <thead>
                                <tr>
                                    <th scope="col">id</th>
                                    <th scope="col">name</th>
                                    <th scope="col">update</th>
                                    <th scope="col">delete</th>
                                </tr>
                            </thead>
                            <tbody>
                                @foreach($categories as $c)
                                <tr>
                                    <form action="/adminPanel/category/put"
method="POST">
                                        <input type="hidden" name="hiddenId"
value="{{ $c->id }}" />
                                        <th scope="row">{{ $c->id }}</th>
                                        <td><input type="text"
name="nameCategory" class="form-control" value="{{ $c->name }}"></td>
                                        <td><input type="submit"
value="Update" class="updateCategory btn btn-dark"/></td>
                                        @csrf
                                    </form>
                                    <form action="/adminPanel/category/delete"
method="POST">
                                        <input type="hidden" name="hiddenId"
value="{{ $c->id }}" />
                                        <td><input type="submit"
value="Delete" class="deleteCategory btn btn-danger"/></td>
                                        @csrf
                                    </form>
                                </tr>
                                @endforeach
                                @if($errors->any())
                                    <div class="alert alert-danger">
                                        @foreach ($errors->all() as $error)
                                            <p>{{ $error }}</p>
                                        @endforeach
                                    </div>
                                @endif
                                @if(session('msg'))
                                    <div class="alert alert-dark">
                                        {{ session('msg') }}</div>
                                @endif
                            </tbody>
                        </table>
                    </div>
                </div>
            </div>
        </div>
    <!-- kraj update i delete -->

```

```

        <!-- insert -->
        <div class="row">
            <div class="col-md-12 mt-5">
                <table class="table">
                    <h3>Insert category</h3>
                    <tbody>
                        <tr>
                            <td><input type="text"
method="POST">
name="nameCategory" class="form-control" placeholder="Enter name"></td>
                            <td><input type="submit" value="Insert"
class="insertCategory btn btn-dark"/></td>
                        </tr>
                    </tbody>
                </table>
            </div>
        </div>
        <!-- kraj inserta -->
    </div>
</div>
@endsection

```

## views/pages/admin/mainProduct.blade.php

```

@extends("layouts.layoutAdmin")

@section("title") Main Product Table @endsection
@section("description") Main Product Admin Panel @endsection
@section("keywords") product, main, admin, panel @endsection

@section("content")
    <div class="main-panel" style="height: 100vh;">
        <!-- Navbar -->
        <nav class="navbar navbar-expand-lg navbar-absolute fixed-top navbar-transparent">
            <div class="container-fluid">
                <div class="navbar-wrapper">
                    <div class="navbar-toggle">
                        <button type="button" class="navbar-toggler">
                            <span class="navbar-toggler-bar bar1"></span>
                            <span class="navbar-toggler-bar bar2"></span>
                            <span class="navbar-toggler-bar bar3"></span>
                        </button>
                    </div>
                    <p class="navbar-brand">Main products Table</p>
                </div>
                <button class="navbar-toggler" type="button" data-
toggle="collapse" data-target="#navigation" aria-controls="navigation-index"
aria-expanded="false" aria-label="Toggle navigation">
                    <span class="navbar-toggler-bar navbar-kebab"></span>
                    <span class="navbar-toggler-bar navbar-kebab"></span>
                    <span class="navbar-toggler-bar navbar-kebab"></span>
                </button>
            </div>
        </nav>
        <!-- End Navbar -->
        <div class="content">

```

```

<div class="container">
  <div class="row">
    <!-- update i delete -->
    <div class="col-md-12">
      <h3>Main Products</h3>
      <div id="menu">
        <table class="table">
          <thead>
            <tr>
              <th scope="col">id</th>
              <th scope="col">name</th>
              <th scope="col">image</th>
              <th scope="col">change src</th>
              <th scope="col">name cat</th>
              <th scope="col">description</th>
              <th scope="col">update</th>
            </tr>
          </thead>
          <tbody>
            @foreach($mainProducts as $mp)
              <tr>
                <td>
                  <form
action="/adminPanel/mainProduct/put" method="POST" enctype="multipart/form-
data">
                    <th scope="row">{{ $mp->id }}</th>
                    <input type="hidden"
name="hiddenId" value="{{ $mp->id }}" />
                    <td><input type="text"
name="nameProducts" class="form-control" value="{{ $mp->name }}" disabled></td>
                    <td><input type="text"
name="srcProducts" class="form-control" value="{{ $mp->image }}" disabled></td>
                    <td><input type="file"
name="fileProducts" class="form-control-file"></td>
                    <td><input type="text"
name="catProducts" class="form-control" value="{{ $mp->category->name }}"
disabled></td>
                    <td><input type="text"
name="descriptionProducts" class="form-control" value="{{ $mp-
>description }}"></td>
                    <td><input type="submit"
value="Update" class="updateProduct btn btn-dark"/></td>
                    @csrf
                  </form>
                </td>
              </tr>
            @endforeach
            @if($errors->any())
              <div class="alert alert-danger">
                @foreach ($errors->all() as $error)
                  <p>{{ $error }}</p>
                @endforeach
              </div>
            @endif
            @if(session('msg'))
              <div class="alert alert-dark">
                {{ session('msg') }}</div>
            @endif
          </tbody>
        </table>
      </div>
    </div>
  </div>
</div>

```

```

        </div>
        <!-- kraj update i delete -->
    </div>
</div>
@endsection

```

## views/pages/admin/menu.blade.php

```

@extends("layouts.layoutAdmin")

@section("title") Menu Table @endsection
@section("description") Menu Admin Panel @endsection
@section("keywords") menu, admin, panel @endsection

@section("content")
    <div class="main-panel" style="height: 100vh;">
        <!-- Navbar -->
        <nav class="navbar navbar-expand-lg navbar-absolute fixed-top navbar-transparent">
            <div class="container-fluid">
                <div class="navbar-wrapper">
                    <div class="navbar-toggler">
                        <button type="button" class="navbar-toggler">
                            <span class="navbar-toggler-bar bar1"></span>
                            <span class="navbar-toggler-bar bar2"></span>
                            <span class="navbar-toggler-bar bar3"></span>
                        </button>
                    </div>
                    <p class="navbar-brand">Menu Table</p>
                </div>
                <button class="navbar-toggler" type="button" data-
toggle="collapse" data-target="#navigation" aria-controls="navigation-index"
aria-expanded="false" aria-label="Toggle navigation">
                    <span class="navbar-toggler-bar navbar-kebab"></span>
                    <span class="navbar-toggler-bar navbar-kebab"></span>
                    <span class="navbar-toggler-bar navbar-kebab"></span>
                </button>
            </div>
        </nav>
        <!-- End Navbar -->
        <div class="content">
            <div class="container">
                <div class="row">
                    <!-- update i delete -->
                    <div class="col-md-12">
                        <h3>Menu</h3>
                        <h4>Priority disclaimer! 2 is for users/3 for
admin</h4></br>

                        <div id="menu">
                            <table class="table">
                                <thead>
                                    <tr>
                                        <th scope="col">id</th>
                                        <th scope="col">name</th>
                                        <th scope="col">route</th>
                                        <th scope="col">order</th>
                                        <th scope="col">priority</th>
                                        <th scope="col">update</th>

```

```

                <th scope="col">delete</th>
            </tr>
        </thead>
        <tbody>
            @foreach($menu as $m)
            <tr>
                <form action="/adminPanel/menu/put"
method="POST">
                    <th scope="row">{{ $m->id }}</th>
                    <input type="hidden" name="hiddenId"
value="{{ $m->id }}" />
                    <td><input type="text" name="nameMenu"
class="form-control" value="{{ $m->name }}"></td>
                    <td><input type="text" name="routeMenu"
class="form-control" value="{{ $m->route }}"></td>
                    <td><input type="text" name="orderMenu"
class="form-control" value="{{ $m->order }}"></td>
                    <td><input type="text"
name="priorityMenu" class="form-control" value="{{ $m->priority }}"></td>
                    <td><input type="submit"
value="Update" class="updateMenu btn btn-outline-dark"/></td>
                    @csrf
                </form>
                <form action="/adminPanel/menu/delete"
method="POST">
                    <input type="hidden" name="hiddenId"
value="{{ $m->id }}" />
                    <td><input type="submit"
value="Delete" class="deleteMenu btn btn-danger"/></td>
                    @csrf
                </form>
            </tr>
            @endforeach
            @if($errors->any())
                <div class="alert alert-danger">
                    @foreach ($errors->all() as $error)
                        <p>{{ $error }}</p>
                    @endforeach
                </div>
            @endif
            @if(session('msg'))
                <div class="alert alert-dark">
                    {{ session('msg') }}</div>
            @endif
        </tbody>
    </table>
</div>
</div>
</div>
<!-- kraj update i delete -->
</div>
</div>
@endsection

```

views/pages/admin/message.blade.php

```

@extends("layouts.layoutAdmin")

@section("title") Message Table @endsection

```

```

@section("description") Message Admin Panel @endsection
@section("keywords") message, admin, panel @endsection

@section("content")
<div class="main-panel" style="height: 100vh;">
  <!-- Navbar -->
  <nav class="navbar navbar-expand-lg navbar-absolute fixed-top navbar-transparent">
    <div class="container-fluid">
      <div class="navbar-wrapper">
        <div class="navbar-toggler">
          <button type="button" class="navbar-toggler">
            <span class="navbar-toggler-bar bar1"></span>
            <span class="navbar-toggler-bar bar2"></span>
            <span class="navbar-toggler-bar bar3"></span>
          </button>
        </div>
        <p class="navbar-brand">Message Table</p>
      </div>
      <button class="navbar-toggler" type="button" data-
toggle="collapse" data-target="#navigation" aria-controls="navigation-index"
aria-expanded="false" aria-label="Toggle navigation">
        <span class="navbar-toggler-bar navbar-kebab"></span>
        <span class="navbar-toggler-bar navbar-kebab"></span>
        <span class="navbar-toggler-bar navbar-kebab"></span>
      </button>
    </div>
  </nav>
  <!-- End Navbar -->
  <div class="content">
    <div class="container">
      <div class="row">
        <!-- delete -->
        <div class="col-md-12">
          <h3>Messages from users to you</h3>
          <div id="message">
            <table class="table">
              <thead>
                <tr>
                  <th scope="col">id</th>
                  <th scope="col">message</th>
                </tr>
              </thead>
              <tbody>
                @foreach($messages as $m)
                  <tr>
                    <td>
                      <form
action="/adminPanel/message/delete" method="POST">
                        <input type="hidden"
name="hiddenId" value="{{ $m->id }}" />
                        <th scope="row">{{ $m->id }}</th>
                        <td name="messageUser">{{ $m-
>message }}</td>
                        <td><input type="submit"
value="Delete" class="deleteMessage btn btn-danger" /></td>
                        @csrf
                      </form>
                    </td>
                  </tr>
                @endforeach
                @if($errors->any())
                  <div class="alert alert-danger">

```





```

        <div id="productss">
            <table class="table">
                <thead>
                    <tr>
                        <th scope="col">id</th>
                        <th scope="col">name</th>
                        <th scope="col">price</th>
                        <th scope="col">image</th>
                        <th scope="col">change src</th>
                        <th scope="col">name cat</th>
                        <th scope="col">description</th>
                        <th scope="col">update</th>
                        <th scope="col">delete</th>
                    </tr>
                </thead>
                <tbody>
                    @foreach($products as $p)
                    <tr>
                        <form action="/adminPanel/product/put"
method="POST" enctype="multipart/form-data">
                            <th scope="row">{{ $p->id }}</th>
                            <input type="hidden" name="hiddenId"
value="{{ $p->id }}" />
                            <td><input type="text"
name="nameProducts" class="form-control" value="{{ $p->name }}"></td>
                            @foreach($p->price as $price)
                            <td><input type="text"
name="priceProducts" class="form-control" value="{{ $price->price }}"></td>
                            @endforeach
                            <td><input type="text"
name="srcProducts" class="form-control" value="{{ $p->image }}" disabled></td>
                            <td><input type="file"
name="fileProducts" class="form-control-file"></td>
                            <td>
                                <select name="catProducts"
class="form-control">
                                    @foreach($categories as $c)
                                    @if($p->categories_id == $c-
>id)
                                        <option selected
value="{{ $c->id }}">{{ $c->name }}</option>
                                    @else
                                        <option value="{{ $c-
>id }}">{{ $c->name }}</option>
                                    @endif
                                @endforeach
                                </select>
                            </td>
                            <td><input type="text"
name="descriptionProducts" class="form-control" value="{{ $p-
>description }}"></td>
                            <td><input type="submit"
value="Update" class="updateProduct btn btn-sm btn-dark"/></td>
                            @csrf
                        </form>
                        <form action="/adminPanel/product/delete"
method="POST">
                            <input type="hidden" name="hiddenId"
value="{{ $p->id }}" />
                            <td><input type="submit"
value="Delete" class="deleteProduct btn btn-sm btn-danger"/></td>

```

```

        @csrf
    </form>
</tr>
@endforeach
@if($errors->any())
    <div class="alert alert-danger">
        @foreach ($errors->all() as $error)
            <p>{{ $error }}</p>
        @endforeach
    </div>
@endif
@if(session('msg'))
    <div class="alert alert-dark">
        {{ session('msg') }}</br>
    </div>
@endif
@if(session('msgerror'))
    <div class="alert alert-danger">
        {{ session('msgerror') }}</br>
    </div>
@endif
</tbody>
</table>
</div>
</div>
</div>
<!-- kraj update i delete -->
<!-- insert -->
<div class="row">
    <div class="col-md-12 mt-5">
        <table class="table">
            <h3>Insert product</h3>
            <tbody>
                <tr>
                    <form action="/adminPanel/product/store"
method="POST" enctype="multipart/form-data">
                        <td><input type="text"
name="nameProducts" class="form-control" placeholder="Enter name"></td>
                        <td><input type="text"
name="priceProducts" class="form-control" placeholder="Enter price"></td>
                        <td><input type="file"
name="fileProducts" class="form-control-file"></td>
                        <td>
                            <select name="catProducts"
class="form-control">
                                <option value="0">Choose</option>
                                @foreach($categories as $c)
                                    <option value="{{ $c-
>id }}">{{ $c->name }}</option>
                                @endforeach
                            </select>
                        </td>
                        <td><input type="text"
name="descriptionProducts" class="form-control" placeholder="Enter
description"></td>
                        <td><input type="submit" value="Insert"
id="insertCategory" class="btn btn-sm btn-dark"/></td>
                    @csrf
                </form>
            </tr>
        </tbody>

```

```

        </table>
    </div>
</div>
<!-- kraj inserta -->
</div>
</div>
@endsection

```

## views/pages/admin/role.blade.php

```

@extends("layouts.layoutAdmin")

@section("title") Role Table @endsection
@section("description") Role Admin Panel @endsection
@section("keywords") admin, role, panel @endsection

@section("content")
    <div class="main-panel" style="height: 100vh;">
        <!-- Navbar -->
        <nav class="navbar navbar-expand-lg navbar-absolute fixed-top navbar-transparent">
            <div class="container-fluid">
                <div class="navbar-wrapper">
                    <div class="navbar-toggler">
                        <button type="button" class="navbar-toggler">
                            <span class="navbar-toggler-bar bar1"></span>
                            <span class="navbar-toggler-bar bar2"></span>
                            <span class="navbar-toggler-bar bar3"></span>
                        </button>
                    </div>
                    <p class="navbar-brand">Role Table</p>
                </div>
                <button class="navbar-toggler" type="button" data-
toggle="collapse" data-target="#navigation" aria-controls="navigation-index"
aria-expanded="false" aria-label="Toggle navigation">
                    <span class="navbar-toggler-bar navbar-kebab"></span>
                    <span class="navbar-toggler-bar navbar-kebab"></span>
                    <span class="navbar-toggler-bar navbar-kebab"></span>
                </button>
            </div>
        </nav>
        <!-- End Navbar -->
        <div class="content">
            <div class="container">
                <div class="row">
                    <!-- update i delete -->
                    <div class="col-md-12">
                        <h3>Role</h3>
                        <div id="role">
                            <table class="table">
                                <thead>
                                    <tr>
                                        <th scope="col">id</th>
                                        <th scope="col">role</th>
                                    </tr>
                                </thead>
                                <tbody>
                                    @foreach($roles as $r)
                                        <tr>
                                            <form action="/adminPanel/role/put"

```

```

method="POST">
                                <input type="hidden"
name="hiddenId" value="{{ $r->id }}" />
                                <th scope="row">{{ $r->id }}</th>
                                <td><input type="text"
name="nameRole" class="form-control" value="{{ $r->role }}"></td>
                                <td><input type="submit"
value="Update" class="updateRole btn btn-dark" /></td>
                                @csrf
                                </form>
                                <form
action="/adminPanel/role/delete" method="POST">
                                <input type="hidden"
name="hiddenId" value="{{ $r->id }}" />
                                <td><input type="submit"
value="Delete" class="deleteRole btn btn-danger" /></td>
                                @csrf
                                </form>
                                </tr>
                                @endforeach
                                @if($errors->any())
                                <div class="alert alert-danger">
                                @foreach ($errors->all() as $error)
                                <p>{{ $error }}</p>
                                @endforeach
                                </div>
                                @endif
                                @if(session('msg'))
                                <div class="alert alert-dark">
                                {{ session('msg') }}</div>
                                @endif
                                </tbody>
                                </table>
                                </div>
                                </div>
                                </div>
                                <!-- kraj update i delete -->
                                <!-- insert -->
                                <div class="row">
                                <div class="col-md-12 mt-5">
                                <table class="table">
                                <h3>Insert role</h3>
                                <tbody>
                                <tr>
                                <form action="/adminPanel/role/store"
method="POST">
                                <td><input type="text" name="nameRole"
class="form-control" placeholder="Enter name"></td>
                                <td><input type="submit" value="Insert"
class="insertRole btn btn-dark" /></td>
                                @csrf
                                </form>
                                </tr>
                                </tbody>
                                </table>
                                </div>
                                </div>
                                <!-- kraj inserta -->
                                </div>

```

[illegible]

```

value="Remove filter" class="form-control" >
    </form>
</div>
</div>
</div>
<table class="table" id="users">
    <h3 id="text" class="alert"></h3>
    <thead>
    <tr>
        <th scope="col">id</th>
        <th scope="col">first name</th>
        <th scope="col">last name</th>
        <th scope="col">email</th>
        <th scope="col">role</th>
        <th scope="col">update role</th>
        <th scope="col">delete user</th>
    </tr>
    </thead>
    <tbody>
    @foreach($users as $u)
    <tr>
        <form action="/adminPanel/user/put"
method="POST">
            <input type="hidden" name="hiddenId"
value="{{ $u->id }}" />
            <th scope="row">{{ $u->id }}</th>
            <td name="nameUser">{{ $u->
>firstName }}</td>
            <td name="lastNameUser">{{ $u->
>lastName }}</td>
            <td name="emailUser">{{ $u->
>email }}</td>
            <td>
                <select name="roleUser"
                    @foreach($roles as $r)
                        @if($u->roles_id == $r->id)
                            <option selected
value="{{ $r->id }}">{{ $r->role }}</option>
                        @else
                            <option value="{{ $r->id }}">{{ $r->role }}</option>
                        @endif
                    @endforeach
                </select>
            </td>
            <td><input type="submit"
value="Update role" class="updateRole btn btn-dark"/></td>
            @csrf
        </form>
        <form action="/adminPanel/user/delete"
method="POST">
            <input type="hidden" name="hiddenId"
value="{{ $u->id }}" />
            <td><input type="submit"
value="Delete" class="deleteUser btn btn-danger"/></td>
            @csrf
        </form>
    </tr>
    @endforeach

```

```

                @if($errors->any())
                <div class="alert alert-danger">
                    @foreach ($errors->all() as $error)
                    <p>{{ $error }}</p>
                    @endforeach
                </div>
                @endif
                @if(session('msg'))
                <div class="alert alert-dark">
                    {{ session('msg') }}</div>
                @endif
            </tbody>
        </table>
    </div>
</div>
<!-- kraj update i update-->
</div>
</div>
@endsection

```

## views/pages/admin/usersActivity.blade.php

```

@extends("layouts.layoutAdmin")

@section("title") Activity Table @endsection
@section("description") Activity User Admin Panel @endsection
@section("keywords") activity, admin, panel, user @endsection

@section("content")
    <div class="main-panel" style="height: 100vh;">
        <!-- Navbar -->
        <nav class="navbar navbar-expand-lg navbar-absolute fixed-top navbar-transparent">
            <div class="container-fluid">
                <div class="navbar-wrapper">
                    <div class="navbar-toggler">
                        <button type="button" class="navbar-toggler">
                            <span class="navbar-toggler-bar bar1"></span>
                            <span class="navbar-toggler-bar bar2"></span>
                            <span class="navbar-toggler-bar bar3"></span>
                        </button>
                    </div>
                    <p class="navbar-brand">Users Activity Table</p>
                </div>
                <button class="navbar-toggler" type="button" data-
toggle="collapse" data-target="#navigation" aria-controls="navigation-index"
aria-expanded="false" aria-label="Toggle navigation">
                    <span class="navbar-toggler-bar navbar-kebab"></span>
                    <span class="navbar-toggler-bar navbar-kebab"></span>
                    <span class="navbar-toggler-bar navbar-kebab"></span>
                </button>
            </div>
        </nav>
        <!-- End Navbar -->
        <div class="content">
            <div class="container">
                <div class="row">
                    <div class="col-md-12">

```



```

        <h3>Users Activity</h3>
        <div>
            <div class="container">
                <div class="row">
                    <div class="col-md-4">
                        <form action="" method="POST">
                            <th class="font-weight-
bold">Filter by log in date</th>
                            <meta name="csrf-token"
content="{{csrf_token()}}">
                            <td><input type="date"
id="dateLogIn" class="form-control"/></td>
                        </form>
                    </div>
                    <div class="col-md-4">
                        <th>&nbsp;</th>
                        <form action="/adminPanel/activity">
                            <input type="submit"
value="Remove filter" class="form-control" >
                        </form>
                    </div>
                    <div class="col-md-4">
                        <form action="" method="POST">
                            <th class="font-weight-
bold">Filter by log out date</th>
                            <meta name="csrf-token"
content="{{csrf_token()}}">
                            <td><input type="date"
id="dateLogOut" class="form-control"/></td>
                        </form>
                    </div>
                </div>
            </div>
            <table class="table" id="users">
                <h3 id="text" class="alert"></h3>
                <thead>
                    <tr>
                        <th scope="col">id</th>
                        <th scope="col">first name</th>
                        <th scope="col">last name</th>
                        <th scope="col">email</th>
                        <th scope="col">role</th>
                    </tr>
                </thead>
                <tbody id="usersLoggedIn">
                    @foreach($users as $u)
                        <tr>
                            <th scope="row">{{ $u->id }}</th>
                            <td name="nameUser">{{ $u->firstName }}</td>
                            <td name="lastNameUser">{{ $u->lastName }}</td>
                            <td name="emailUser">{{ $u->email }}</td>
                            <td name="roleUser">{{ $u->role }}</td>
                        </tr>
                    @endforeach
                </tbody>
            </table>
        </div>

```

```

        </div>
    </div>
</div>
</div>
@endsection

```

## views/pages/auth/login.blade.php

```

@extends("layouts.layout")

@section("title") Login @endsection
@section("description") Login Page. Come log in @endsection
@section("keywords") login, page @endsection

@section("content")
    <section id="contact">
        <div class="container">
            <div class="row">
                <div class="col-lg-12 text-center">
                    <div class="section-title">
                        <h2>Login</h2>
                        <p>We are glad you are back<br>Login down bellow!</p>
                    </div>
                </div>
            </div>
            <div class="row">
                <div class="col-lg-12 text-center">
                    <form action="/login" method="POST">
                        <div class="row">
                            <div class="col-md-12">
                                <div class="form-group">
                                    <input type="email" class="form-control"
placeholder="Your Email: " id="email" name="email" />
                                    <span class="help-block"
id="errorEmail"></span>
                                </div>
                            </div>
                            <div class="col-md-12">
                                <div class="form-group">
                                    <input type="password" class="form-
control" placeholder="Your Password: " id="password" name="password" />
                                    <span class="help-block"
id="errorPassword"></span>
                                </div>
                            </div>
                        </div>
                    </div>
                    <div class="row">
                        <div class="clearfix"></div>
                    </div>
                    <div class="row">
                        <div class="col-lg-12 text-center">
                            <div id="success"></div>
                            <input type="submit" class="btn" id="btn"
value="Login" />
                        </div>
                    </div>
                </div>
            </div>
        </div>
        @csrf
    </form>
    @if($errors->any())
        <div class="alert alert-danger">

```

```

                @foreach ($errors->all() as $error)
                    <p>{{ $error }}</p>
                @endforeach
            </div>
        @endif
        @if(session('msg'))
            <div class="alert alert-danger">
                {{ session('msg') }}</div>
        @endif
    </div>
</div>
</div>
</section>
@endsection

```

## views/pages/auth/register.blade.php

```

@extends("layouts.layout")

@section("title") Register @endsection
@section("description") Register on our site. Come register, quick!@endsection
@section("keywords") register, quick, come @endsection

@section("content")
    <section id="contact">
        <div class="container">
            <div class="row">
                <div class="col-lg-12 text-center">
                    <div class="section-title">
                        <h2>Register</h2>
                        <p>If you like our page and want to do some shopping<br>Just register!</p>
                    </div>
                </div>
            </div>
            <div class="row">
                <div class="col-lg-12 text-center">
                    <form action="/register" method="POST">
                        <div class="row">
                            <div class="col-md-6">
                                <div class="form-group">
                                    <input type="text" class="form-control"
placeholder="Your Name: " id="name" name="firstName"/>
                                    <span class="help-block"
id="errorName"></span>
                                </div>
                            </div>
                            <div class="col-md-6">
                                <div class="form-group">
                                    <input type="text" class="form-control"
placeholder="Your Lastname: " id="lastname" name="lastName" />
                                    <span class="help-block"
id="errorLastName"></span>
                                </div>
                            </div>
                        </div>
                    </form>
                </div>
            </div>
        </div>
    </section>

```

```

        <input type="text" class="form-control"
placeholder="Your Email: " id="email" name="email"/>
        <span class="help-block"
id="errorEmail"></span>
    </div>
</div>
<div class="col-md-6">
    <div class="form-group">
        <input type="password" class="form-
control" placeholder="Your Password: " id="password" name="password"/>
        <span class="help-block"
id="errorPassword"></span>
    </div>
</div>
</div>
<div class="row">
    <div class="clearfix"></div>
</div>
<div class="row">
    <div class="col-lg-12 text-center">
        <div id="success"></div>
        <input type="submit" class="btn" id="btn"
value="Register"/>
    </div>
</div>
@csrf
</form>
@if($errors->any())
    <div class="alert alert-danger">
        @foreach ($errors->all() as $error)
            <p>{{ $error }}</p>
        @endforeach
    </div>
@endif
@if(session('msg'))
    <div class="alert alert-success">
        {{ session('msg') }}</br>
        <a href="{{route('loginForm')}}"
id="fontColor">Want to login now? Click me</a>
    </div>
@endif
</div>
</div>
</div>
</section>
@endsection

```

## views/pages/main/contact.blade.php

```

@extends("layouts.layout")

@section("title") Contact @endsection
@section("description") Contact page. Come see our location and send a
message. @endsection
@section("keywords") contact, map, message @endsection

@section("content")
    <section id="contact">
        <div class="container">

```

```

        <div class="row">
            <div class="col-lg-12 text-center">
                <div class="section-title">
                    <h2>Contact Us</h2>
                    <p>If you have some Questions for administrator,
Please Contact Us through this field bellow<br>We are here to listen!</p>
                </div>
            </div>
        </div>
    </div>
    <div class="row">
        <div class="col-lg-12 text-center">
            <form action="/contact" method="POST">
                <input type="hidden" name="idUser"
value="{{session()->get("user")->id}}"/>
                <div class="row">
                    <div class="col-md-12">
                        <div class="form-group">
                            <textarea class="form-control"
placeholder="Your Message: " id="message" name="message"></textarea>
                        </div>
                    </div>
                    <div class="clearfix"></div>
                </div>
                <div class="row">
                    <div class="col-lg-12 text-center">
                        <div id="success"></div>
                        <input type="submit" class="btn" id="btn"
value="Send Message"/>
                    </div>
                </div>
            </form>
            @csrf
        </div>
    </div>
    <div class="row">
        <div class="col-lg-12">
            <div class="row">
                <div class="col-md-12">
                    <div class="alert alert-danger">
                        @foreach ($errors->all() as $error)
                            <p>{{ $error }}</p>
                        @endforeach
                    </div>
                </div>
            </div>
            @endif
            <div class="row">
                <div class="col-md-12">
                    <div class="alert alert-success">
                        {{ session('msg') }}</div>
                    </div>
                </div>
            </div>
            @endif
        </div>
    </div>
</div>
</section>
<section id="team">
    <div class="container">
        <div class="row">
            <div class="col-lg-12 text-center">
                <div class="section-title">
                    <h2>Our Location</h2>
                </div>
            </div>
        </div>
        <div class="row text-center" id="loc">
            <iframe
src="https://www.google.com/maps/embed?pb=!1m18!1m12!1m3!1d90593.29045061053!
2d20.473446298187802!3d44.800366791900124!2m3!1f0!2f0!3f0!3m2!1i1024!2i768!4f

```

```

13.1!3m3!1m2!1s0x475a7007ae411f8d%3A0xfc2b6c76f90bb500!2sMap!5e0!3m2!1sen!2sr
s!4v1646221250978!5m2!1sen!2srs" width="600" height="450" style="border:0;"
allowfullscreen="" loading="lazy"></iframe>
    </div>
</div>
</section>
@endsection

```

## views/pages/main/error.blade.php

```

@extends("layouts.layout")

@section("title") Contact @endsection
@section("description") Error page. @endsection
@section("keywords") error, message, page @endsection

@section("content")
<h1>An error has ocured.</h1>
<h2>Please reach our support with this ID {{ $errorId }}</h2>
@endsection

```

## views/pages/main/index.blade.php

```

@extends("layouts.layout")
@section("title") FURNITURE.minimalistic | Gallery @endsection
@section("description") Visit our online gallery with best minimalistic
furniture you can find while browsing-click on us and let's shop! @endsection
@section("keywords") FURNITURE.minimalistic gallery, come and look.
@endsection

@section("content")
    <section id="portfolio">
        <div class="container">
            <div class="row">
                <div class="col-lg-12 text-center" id="fixedMargin">
                    <div class="section-title">
                        <h2>-Welcome to our online shop-</h2>
                        <p>This is a safe place for minimalistic(and other)
people to come and walk around via internet through our gallery.
                        We have everything and nothing in the same time-
minimalistic right?</p>
                    </div>
                </div>
            </div>
            <div class="row row-0-gutter" id='items'>
                @foreach($productsMain as $key => $value)
                    @include("partials.mainProduct")
                @endforeach
            </div>
        </div><!-- container -->
    </section>
    <section id="about" class="mz-module">
        <div class="container light-bg">
            <div class="row">
                <div class="col-lg-12 text-center">
                    <div class="section-title">
                        <h2>ABOUT US</h2>
                    </div>

```

```

        </div>
    </div>
    <div class="row MB">
        <div class="col-md-6 text-center">
            <div class="mz-about-container">
                <p> As we are based only at one place in this world -
we would say we are minimalistic for that to. Jokes aside, we
                love our little company that we established 2016.-
year, where all bloomed and started. With our creator, Sarah, we
                can do anything - she's like the glue - always
keeping us together, which is the most important thing for a bussines.</p>
            </div>
        </div>
        <div class="col-md-6 MB">
            <!-- skill bar item -->
            <div class="skillPic mt-5">
                
            </div>
        </div>
    </div>
    <div class="row row-0-gutter" id="blackIcons">
        <div class="col-md-3 col-0-gutter mz-about-default text-
center">
            <div class="mz-module-about"><i class="fa-solid fa-chair
ot-circle"></i>
                <h3>Unique-minimalistic</h3>
            </div>
        </div>
        <div class="col-md-3 col-0-gutter mz-about-default text-
center">
            <div class="mz-module-about"><i class="fa-solid fa-shop
ot-circle"></i>
                <h3>Small bussines shop!</h3>
            </div>
        </div>
        <div class="col-md-3 col-0-gutter mz-about-default text-
center">
            <div class="mz-module-about">
                <i class="fa-solid fa-couch ot-circle"></i>
                <h3>Comfortable seating</h3>
            </div>
        </div>
        <div class="col-md-3 col-0-gutter mz-about-default text-
center">
            <div class="mz-module-about"><i class="fa-solid fa-tag
ot-circle">
                </i><h3>Best prices!</h3>
            </div>
        </div>
    </div>
</div>
</section>
<section id="about" class="mz-module">
    <div class="container light-bg">
        <div class="row">
            <div class="col-lg-12 text-center">
                <div class="section-title">
                    <h2>ABOUT OUR MERCHANDISE</h2>
                </div>
            </div>
        </div>
    </div>
</section>

```

```

        </div>
    </div>
    <div class="row MB">
        <div class="col-md-6 MB">
            <!-- skill bar item -->
            <div class="skillPic mt-5">
                
            </div>
        </div>
        <div class="col-md-6 text-center">
            <div class="mz-about-container">
                <p>Our merchandise is top notch, unique and
minimalistic too. Simple look - simple color.
                If we caught your attention here is a link so you
can chech it out right now.</p><br>
                <div class="modal-works text-center"> <a
href="{{route('products')}}" target="_blank"><span>Click here for some
shopping</span></a></div>
            </div>
        </div>
    </div>
</section>
<p id="back-top">
    <a href="#top"><i class="fa fa-angle-up"></i></a>
</p>
<!-- Modal for portfolio items -->
@foreach($productsMain as $key => $value)
    <div class="modal fade" id="Modal-{{$key+1}}" tabindex="-1" role="dialog"
aria-labelledby="Modal-label-{{$key+1}}">
        <div class="modal-dialog" role="document">
            <div class="modal-content">
                <div class="modal-header">
                    <button type="button" class="close" data-dismiss="modal"
aria-label="Close"><span aria-hidden="true">&times;</span></button>
                    <h4 class="modal-title text-center" id="Modal-label-
1">{{$value->category->name}}</h4>
                </div>
                <div class="modal-body">
                    name}}}" class="img-responsive" />
                    <div class="modal-works text-center" ><a
href="{{route('products')}}" target="_blank"><span>Click here if you're
interested</span></a></div>
                    <p class="text-center">{{$value->description}} </p>
                </div>
                <div class="modal-footer">
                    <button type="button" class="btn btn-default" data-
dismiss="modal">Close</button>
                </div>
            </div>
        </div>
    </div>
@endforeach
</div>
@endsection

```



```

@extends("layouts.layout")

@section("title") Cart @endsection
@section("description") Check our online gallery for some fresh ideas! Come
shop @endsection
@section("keywords") FURNITURE.minimalistic gallery, come and shop.
@endsection

@section("content")
    <input type="hidden" id="cartUser" value="{{session()->get("user")-
>id}}">
<div class="container table-responsive-sm" id="contact">
    <div class="col-12">
        <h2 class="my-5 tm-section-title text-center">-Here are the items you
choose-</h2>
        <h4 id="cartEmpty" class="alert text-center mt-5"></h4>
    </div>
    <!-- ispis tabele -->
    <div>
        <form action="" method="POST">
            @csrf
            <meta name="csrf-token" content="{{csrf_token()}}">
            <div id="cartWrite">
            </div>
        </form>
        <!-- ispis tabele kraj -->
    </div>
</div>
@endsection

```

## views/pages/products/index.blade.php

```

@extends("layouts.layout")

@section("title") Gallery @endsection
@section("description") Check our online gallery for some fresh ideas! Come
shop! @endsection
@section("keywords") FURNITURE.minimalistic gallery, come and shop.
@endsection

@section("content")
    <!-- COUCHES -->
    <section id="team1">
        <div class="container">
            <div class="row" id="fixedMargin">
                <div class="col-lg-12 text-center">
                    <div class="section-title" id="first">
                        <h2>Gallery shop</h2>
                    </div>
                </div>
            </div>
            <div class="row">
                <div class="col-lg-12 text-center">
                    <nav class="navbar navbar-light bg-light">
                        <form class="form-inline" action="" method="GET">
                            <meta name="csrf-token"
content="{{csrf_token()}}">
                            <input class="form-control mr-sm-3" type="search"
id="keyword" placeholder="Search by name" aria-label="Search" name="keyword">
                            <button class="btn btn-outline-success my-2 my-

```

```

sm-0" type="submit" id="search">Search</button>
        </form>
    </nav>
</div>
</div>
<div class="row" id="products">
    @if(count($products) > 0)
    @foreach($products as $p)
        @include("partials.product", ["description"=>false])
    @endforeach
    @else
        <h1 class="text-center">There are no products!</h1>
    @endif
</div>

    <div class="row">
        <div class="col-lg-12 text-center">
            <nav aria-label="Page navigation example">
                <ul class="pagination" id="pagination">
                    @if(count($products) > 0)
                        {{ $products->links() }}
                    @endif
                </ul>
            </nav>
        </div>
    </div>
</div>
</section>
<p id="back-top">
    <a href="#top"><i class="fa fa-angle-up"></i></a>
</p>
@endsection

```

## views/pages/products/showOne.blade.php

```

@extends("layouts.layout")

@section("title") Gallery @endsection
@section("description") Check our onlne gallery for some fresh ideas!
@endsection
@section("keywords") FURNITURE.minimalistic gallery, come and look.
@endsection

@section("content")
    <div class="container" id="fixedMargin">
        <div class="row">
            <div class="col-md-12 MB">
                <div class="team-item ">
                    <div class="team-image">
                        name}}">
                    </div>
                    <div class="team-text">
                        <h3>{{ $oneProduct->name}} - {{ $oneProduct->category-
>name}}</h3>
                        @foreach($oneProduct->price as $price)
                            <div class="team-position">${{ $price-
>price}}</div>
                        @endforeach
                    </div>
                </div>
            </div>
        </div>
    </div>

```

```

                @if($description)
                    <p>{{ $oneProduct->description }}</p>
                @endif
            </br>
        </div>
        <button type="button" class="btn btn-secondary MB
addToCart">Add to cart</button>
        <a href="/products" class="btn btn-secondary MB"
id="goBack">Go back</a>
    </div>
</div>
</div>
</div>
@endsection

```

## views/pages/partials/mainProduct.blade.php

```

<!-- start portfolio item-->
<div class="col-md-6 col-0-gutter" >
    <div class="ot-portfolio-item">
        <figure class="effect-bubba">
            name }}" class="img-responsive" />
            <figcaption>
                <h2>{{ $value->category->name }}</h2>
                <p>{{ $value->description }}</p>
                <a href="#" data-toggle="modal" data-target="#Modal-
{{ $key+1 }}">View more</a>
            </figcaption>
        </figure>
    </div>
</div>
<!-- end portfolio item -->

```

## views/pages/partials/product.blade.php

```

<div class="col-md-6 MB">
    <div class="team-item">
        <div class="team-image">
            <a href="/show/{{ $p->id }}">
                name }}">
            </a>
        </div>
        <div class="team-text">
            <h3>{{ $p->name }} - {{ $p->category->name }}</h3>
            @foreach($p->price as $price)
                <div class="team-position">${{ $price->price }}</div>
            @endforeach
            @if($description)
                <p>{{ $p->description }}</p>
            @endif
        </br>
    </div>
    @if(session()->has("user"))
        <input type="hidden" id="session" value="{{session()-
>has("user") }}">
        <input type="button" class="btn btn-secondary MB addToCart"
value="Add to cart" data-id="{{ $p->id }}" />
    @endif
</div>

```

```

        @else
            <input type="button" class="btn btn-secondary MB disabled"
value="Add to cart"/>
        @endif
    </div>
</div>

```

## routes/web.php

```

<?php

use Illuminate\Support\Facades\Route;
use App\Http\Controllers\HomeController;
use App\Http\Controllers\ProductsController;
use App\Http\Controllers>ContactController;
use App\Http\Controllers>LoginController;
use App\Http\Controllers\RegisterController;
use App\Http\Controllers\CartController;
use App\Http\Controllers\admin\AdminController;
use App\Http\Controllers\admin\MenuController;
use App\Http\Controllers\admin\CategoryController;
use App\Http\Controllers\admin\UserController;
use App\Http\Controllers\admin\RoleController;
use App\Http\Controllers\admin\MessageController;
use App\Http\Controllers\admin\ProductController;
use App\Http\Controllers\admin>MainProductController;
use App\Http\Controllers\admin\UsersActivityController;
use App\Http\Controllers\admin\CartAdminController;
use App\Mail\MailtrapExample;
use App\Mail\MyMail;

/*
|-----
| Web Routes
|-----
|
| Here is where you can register web routes for your application. These
| routes are loaded by the RouteServiceProvider within a group which
| contains the "web" middleware group. Now create something great!
|
*/

Route::get('/', [HomeController::class, "index"])->name("home");

Route::get('/products/get', [ProductsController::class, "get"])-
>name("productsGet");

Route::get('/products/{keyword?}', [ProductsController::class, "index"])-
>name("products");

Route::get('/show/{id}', [ProductsController::class, "show"])-
>name("showProduct");

Route::get('/search/{keyword}', [ProductsController::class, "search"])-
>name("search");

Route::get('/loginForm', [LoginController::class, "index"])-
>name("loginForm");

Route::post('/login', [LoginController::class, "login"])->name("login");

```

```
Route::get('/logout', [LoginController::class, "logout"]->name("logout"));

Route::get('/registerForm', [RegisterController::class, "index"]->name("registerForm"));

Route::post('/register', [RegisterController::class, "register"]->name("register"));

Route::middleware(['loggedIn'])->group(function () {

    Route::get('/contactForm', [ContactController::class, "index"]->name("contactForm"));

    Route::post('/contact', [ContactController::class, "store"]->name("contact"));

    Route::get('/adminPanel', [AdminController::class, "index"]->name("adminPanel"));

    Route::post('/admin/put', [AdminController::class, "put"]->name("adminPut"));

    Route::get('/adminPanel/menu', [MenuController::class, "index"]->name("menuPanel"));

    Route::post('/adminPanel/menu/put', [MenuController::class, "put"]->name("menuPut"));

    Route::post('/adminPanel/menu/delete', [MenuController::class, "delete"]->name("menuDelete"));

    Route::get('/adminPanel/category', [CategoryController::class, "index"]->name("categoryPanel"));

    Route::post('/adminPanel/category/put', [CategoryController::class, "put"]->name("categoryPut"));

    Route::post('/adminPanel/category/delete', [CategoryController::class, "delete"]->name("categoryDelete"));

    Route::post('/adminPanel/category/store', [CategoryController::class, "store"]->name("categoryStore"));

    Route::get('/adminPanel/user', [UserController::class, "index"]->name("userPanel"));

    Route::post('/adminPanel/user/put', [UserController::class, "put"]->name("userPut"));

    Route::post('/adminPanel/user/delete', [UserController::class, "delete"]->name("userDelete"));

    Route::get('/adminPanel/role', [RoleController::class, "index"]->name("rolePanel"));

    Route::post('/adminPanel/role/put', [RoleController::class, "put"]->name("rolePut"));

    Route::post('/adminPanel/role/delete', [RoleController::class, "delete"]->name("roleDelete"));

});
```

```

Route::post('/adminPanel/role/store', [RoleController::class, "store"])->name("roleStore");

Route::get('/adminPanel/message', [MessageController::class, "index"])->name("messagePanel");

Route::post('/adminPanel/message/delete', [MessageController::class, "delete"])->name("messageDelete");

Route::get('/adminPanel/product', [ProductController::class, "index"])->name("productPanel");

Route::post('/adminPanel/product/put', [ProductController::class, "put"])->name("productPut");

Route::post('/adminPanel/product/delete', [ProductController::class, "delete"])->name("productDelete");

Route::post('/adminPanel/product/store', [ProductController::class, "store"])->name("productStore");

Route::get('/adminPanel/mainProduct', [MainProuductController::class, "index"])->name("mainProductPanel");

Route::post('/adminPanel/mainProduct/put', [MainProuductController::class, "put"])->name("mainProductPut");

Route::get('/adminPanel/activity', [UsersActivityController::class, "index"])->name("activityPanel");

Route::post('/adminPanel/activity/registrationFilter', [UsersActivityController::class, "registrationFilter"])->name("registrationFilter");

Route::post('/adminPanel/activity/loginFilter', [UsersActivityController::class, "loginFilter"])->name("loginFilter");

Route::post('/adminPanel/activity/loggedOutFilter', [UsersActivityController::class, "loggedOutFilter"])->name("loggedOutFilter");

Route::get('/adminPanel/cart', [CartAdminController::class, "index"])->name("cartPanel");

Route::post('/adminPanel/cart/cartFilter', [CartAdminController::class, "cartFilter"])->name("cartFilter");

Route::get('/cart', [CartController::class, "index"])->name("cart");

Route::post('/cart/store', [CartController::class, "store"])->name("cartInsert");
});

```

## .env

```

APP_NAME=Laravel
APP_ENV=local
APP_KEY=base64:oJCzw80nAFDXGuuVlCH55LYKqhIZBP8NphdQApkNXeo=
APP_DEBUG=true

```

```
APP_URL=http://localhost

LOG_CHANNEL=stack
LOG_DEPRECATED_CHANNELS_CHANNEL=null
LOG_LEVEL=debug

DB_CONNECTION=mysql
DB_HOST=127.0.0.1
DB_PORT=3306
DB_DATABASE=furnituredatabase
DB_USERNAME=root
DB_PASSWORD=

BROADCAST_DRIVER=log
CACHE_DRIVER=file
FILESYSTEM_DRIVER=local
QUEUE_CONNECTION=sync
SESSION_DRIVER=file
SESSION_LIFETIME=120

MEMCACHED_HOST=127.0.0.1

REDIS_HOST=127.0.0.1
REDIS_PASSWORD=null
REDIS_PORT=6379

MAIL_MAILER=smtp
MAIL_HOST=smtp.mailtrap.io
MAIL_PORT=587
MAIL_USERNAME=d3fa11b37c5804
MAIL_PASSWORD=440dae7ddfbe91
MAIL_ENCRYPTION=tls
MAIL_FROM_ADDRESS=marija.vucicevic.18.19@ict.edu.rs
MAIL_FROM_NAME="${APP_NAME}"

AWS_ACCESS_KEY_ID=
AWS_SECRET_ACCESS_KEY=
AWS_DEFAULT_REGION=us-east-1
AWS_BUCKET=
AWS_USE_PATH_STYLE_ENDPOINT=false

PUSHER_APP_ID=
PUSHER_APP_KEY=
PUSHER_APP_SECRET=
PUSHER_APP_CLUSTER=mt1

MIX_PUSHER_APP_KEY="${PUSHER_APP_KEY}"
MIX_PUSHER_APP_CLUSTER="${PUSHER_APP_CLUSTER}"
```