

```

SQL> SET SERVEROUTPUT ON;
SQL> BEGIN
        DBMS_OUTPUT.PUT_LINE('HELLO');
        DBMS_OUTPUT.PUT_LINE('DE CLASS');
END;
/
  2      3      4      5  HELLO
DE CLASS

PL/SQL procedure successfully completed.

```

```

CREATE TABLE temp (
    id NUMBER,
    description VARCHAR2(20) NOT NULL
);

```

```

DECLARE
    x NUMBER(3) := 10;

PROCEDURE abc
IS
BEGIN
    INSERT INTO temp VALUES (1, 'In abc');
END abc;
BEGIN
    INSERT INTO temp VALUES (1, 'In main');
    abc;
END;
/

```

```

SQL> SELECT * FROM temp;

  ID DESCRIPTION
-----
  1 In main
  1 In abc

```

DECLARE

PROCEDURE pqr(msg IN VARCHAR2) IS -- or VARCHAR2(50)

BEGIN

INSERT INTO temp VALUES (2, msg);

END pqr;

BEGIN

INSERT INTO temp VALUES (1, 'In main');

pqr('This');

END;

/

```
SQL> SELECT * FROM temp;
```

ID	DESCRIPTION
1	In main
1	In abc
1	In main
2	This

```
SQL> DECLARE
```

```
  x NUMBER(3) := 10;
```

```
PROCEDURE xyz(val2 IN OUT NUMBER) IS -- or VARCHAR2(50)
```

```
BEGIN
```

```
  DBMS_OUTPUT.PUT_LINE('val 2 is ' || val2);
```

```
  val2:=300;
```

```
END xyz;
```

```
BEGIN
```

```
  xyz(x);
```

```
  DBMS_OUTPUT.PUT_LINE('x is ' || x);
```

```
END;
```

```
/
```

```
  2      3      4      5      6      7      8      9      10     11     12     13     14     15
val 2 is 10
x is 300
```

```
PL/SQL procedure successfully completed.
```

```

SQL> DECLARE
  x NUMBER(3) := 10;

  PROCEDURE abc
  IS
  BEGIN
    INSERT INTO temp VALUES (1, 'In abc');
  END abc;

  PROCEDURE pqr(msg IN VARCHAR2) IS  -- or VARCHAR2(50)
  BEGIN
    INSERT INTO temp VALUES (2, msg);
  END pqr;

  PROCEDURE xyz(val2 IN OUT NUMBER) IS  -- or VARCHAR2(50)
  BEGIN
    DBMS_OUTPUT.PUT_LINE('val 2 is ' || val2);
    val2:=300;
  END xyz;

BEGIN

  xyz(x);
  DBMS_OUTPUT.PUT_LINE('x is ' || x);
END;
/
  2      3      4      5      6      7      8      9     10     11     12     13     1
4     15     16     17     18     19     20     21     22     23     24     25     26
  val 2 is 10
  x is 300

```

```

SQL> DECLARE
  x NUMBER(3) := 10;

  FUNCTION xyz(val2 IN NUMBER)
    RETURN NUMBER
  IS
  BEGIN
    DBMS_OUTPUT.PUT_LINE('val 2 is ' || val2);
    RETURN 300;
  END xyz;

BEGIN
  x := xyz(x);
  DBMS_OUTPUT.PUT_LINE('x is ' || x);
END;
/
   2    3    4    5    6    7    8    9   10   11   12   13   14   15   16
val 2 is 10
x is 300

PL/SQL procedure successfully completed.

```

```

DECLARE
x NUMBER(4):=10;
PROCEDURE abc (y IN NUMBER)
IS
BEGIN
INSERT INTO temp VALUES(y, 'abc');
END;

```

```

PROCEDURE def (y OUT NUMBER)
IS
BEGIN
y:=100;
END;

```

```

PROCEDURE pqr (y IN OUT NUMBER)
IS
BEGIN
y:=y*2;
END;

```

```
BEGIN  
abc(10);  
def(x);  
pqr(x);  
END;  
/
```

```
SQL> SELECT * FROM temp;
```

ID	DESCRIPTION
----	-------------

1	In main
1	In abc
1	In main
2	This
10	abc