- Home
- <u>Developers</u>
- How To
- Git
- Bug fixes

Fix bugs in devel and release

Goal: Maintainers will have to fix bugs from time to time, and make sure the patch is available both in the master branch (svn devel) and the current release branch.

Steps:

1. Sync existing repositories.

```
git fetch --all
git checkout master
git merge upstream/master
git merge origin/master
git checkout <RELEASE_X_Y>
git merge upstream/<RELEASE_X_Y>
git merge origin/<RELEASE_X_Y>
```

2. On your local machine, be sure that you are on the master branch.

```
git checkout master
```

Make the changes you need to fix your bug. Add the modified files to the commit. Remember to edit the DESCRIPTION file to update the version number, and ensure that **only bug-fix changes** are introduced in the commit.

```
git add <files changed>
## after version bump
git add DESCRIPTION
```

Commit the modified files. It is helpful to tag the commit as bug fix.

```
git commit -m "bug fix: my bug fix"
```

3. (Alternative) If the changes are non-trivial, create a new branch where you can easily abandon any false starts. Merge the final version onto master

```
git checkout master
git checkout -b bugfix-my-bug
## add and commit to this branch. When the bug fix is complete...
git checkout master
git merge bugfix-my-bug
```

4. Switch to the release branch and cherry-pick the commits from master corresponding to the bug fix, e.g., reference the most recent commit on the master branch with master; see examples in git cherry-pick --help. Remember to edit the DESCRIPTION file to update the release version according to *Bioconductor*'s version numbering scheme.

```
git checkout <RELEASE_X_Y>
git cherry-pick master
## Fix version bump by editing 'Version:' field of DESCRIPTION, then
git add DESCRIPTION
git commit -m "update RELEASE version number"
```

NOTE: If you are patching your release for the first time, you have to make a local copy of the RELEASE_X_Y branch, by

```
git checkout -b <RELEASE_X_Y> upstream/<RELEASE_X_Y>
```

Following this one time local checkout, you may switch between RELEASE_X_Y and master with git checkout <RELEASE_X_Y>. If you do not use the command to get a local copy of the release branch, you will get the message,

```
(HEAD detached from origin/RELEASE_X_Y)
```

5. Push your changes to both the GitHub and Bioconductor master and <RELEASE_X_Y> branches. Make sure you are on the correct branch on your local machine.

For the master branch,

```
git checkout master
git push upstream master
git push origin master

For the release branch,

git checkout <RELEASE_X_Y>
git push upstream <RELEASE_X_Y>
git push origin <RELEASE_X_Y>
```

Bioconductor

Contact us: support.bioconductor.org

Copyright © 2003 - 2018, Bioconductor

- Home
- <u>Install</u>
 - <u>Install R</u>
 - o Find Bioconductor Packages

- Install Bioconductor Packages
- o <u>Update Bioconductor Packages</u>
- Help
 - Workflows
 - Package Vignettes
 - FAQ
 - Support
 - <u>Using R</u>
 - Courses
 - Publications
 - Cloud AMI

 - Cloud AMI
 Community Resources
 Developers
 Package Guidelines
 Package Submission
 Release Schedule
 Source Control
 About

- About

 - Advisory Board
 Annual Reports

 - Core Team
 Mirrors
 Related Projects



- <u>Home</u> <u>Install</u>
- HelpDevelopers
- About