MOCK - Reading a Small Data Table
SYNTHETIC LOCAL DEMO - NOT INSTITUTIONAL CONTENT OR APPROVAL

Objective: Identify a primary key and count rows that satisfy a stated equality condition in a small table.

MOCK ORIGINAL LESSON. A table organizes records as rows and attributes as columns. A primary key distinguishes each row and must be unique and present. Filtering selects matching rows; it does not rewrite the original table.

WORKED EXAMPLE
Consider rows (id=1, subject=computing), (id=2, subject=math), (id=3, subject=computing), (id=4, subject=art). The condition subject = computing selects rows 1 and 3, so COUNT(*) for that filtered set is 2. The table still has four stored rows.

CHECK AND CORRECTION
Which property is required of the id column when it is the primary key?
Uniqueness and presence are essential for primary-key identity; the values need not be consecutive.

Read a condition one row at a time. Mark matching rows, then count those marks. COUNT(*) counts matching rows in this example, whereas reading a column value reports data from a row. A SELECT filter does not delete nonmatching rows.

INDEPENDENT APPLICATION
Rows have subjects computing, math, computing and art. How many satisfy subject = computing?
The first and third rows match. Two matching rows are returned; the stored table is unchanged.

GLOSSARY
Row: One record in a table.
Column: A named attribute represented across the rows of a table.
Primary key: A unique, present column or column set that identifies a row.
Filter: A condition used to choose matching rows for a query result.

Separate storage from a query result. A key identifies rows, a condition selects them, and a count reports how many matched. The original rows remain unchanged by this read-only selection.

Original mock fixture. No real learner data, school policy, signatures or redistribution review.
Version 1. Accessible lesson text and authored checks are included separately in this package.