Condition Inspection Record

Section 1 General Information

USMC Serial Number	Type/Capacity	Purpose of Inspection

Section 2 Inspection
S = Satisfactory NA = Not Applicable U = Unsatisfactory

Inspection Task Number	Inspection Details	Inspection	Inspection Task Number	Inspection Details	Inspection
1	Bent, cracked, or corroded structural members.		18	Verify that correct certified capacity charts or hook load rating data is in view of operator and or rigging personnel.	
2	Cracked or corroded welds.		19	Inspect operator's cab for cleanliness, proper safety guards, warning signs, and storage of tools andequipment.	
3	Loose, broken, missing, or deteriorated rivets or bolts.		20	Check machinery house for cleanliness, proper safety guards, warning signs, and storage of tools and equipment.	
4	Inspect all wire rope for wear, broken wires, corrosion, kinks, damaged strands, crushed or flattened sections, condition of sockets, and dead end connections. Check for proper lubrication and evidence of proper inspection of idler sheaves and saddles.		21	Check operation of all indicators, warning devices, and lights.	
5	Inspect hooks for cracks, sharp edges, and distortion. Verify disassembly, inspection and NDT, asapplicable.		22	Check for proper type and condition of all fire protection equipment.	
6	Inspect all brakes and clutches for proper operation. Spot check components for proper adjustmentand acceptable wear.		23	Check condition and function of outriggers, pads boxes, wedges, and cylinder mountings. Check level indicators.	
7	Check all controls for proper condition and operation.		24	Check center pin nut and sediment by observing operational behavior during load test.	
8	Check all control components for proper condition and operation.		25	Check travel, steering, braking, locking devices for condition and proper operation.	
9	Inspect all limit switches for condition and proper operation.		26	Check radius indicator for accuracy by measuring actual radius in at least two boom positions.	
10	Ensure each drum has minimum of two complete wraps of wire rope at lowest working level.		27	Check pawls, ratchets, and spuds for proper engagement and operation of interlocks.	
11	Check load indicators for condition and working accuracy.		28	Inspect tanks, lines, valves, drains, filters, and other components of air systems for leakage and proper operation.	
12	Inspect all mechanical equipment which is reasonably accessible for wear, cracks, and alignment.		29	Inspect reservoirs, pumps, motors, valves, lines, cylinders, and other components of hydraulic systems for leakage and proper operation.	
13	Inspect, where practical, for worm, defective or misaligned bearings, bushings, shafts, pins, and gears.		30	Check engines and engine generator sets for proper performance, safety, and system leakage.	
14	Check components for excessive heat, vibration, noise, and oil leaks.		31	Inspect for bent, cracked, corroded, or dented boom members.	
15	Inspect sheaves for wear, roughness, free turning, and alignment. Gauge sheave groove,where possible.		32	Check condition of counterweights, ballast, and securing fasteners.	
16	Inspect for excessive wear of wheels, tires, rollers. and roller paths or rails.		33	Check all compartments (voids) for water tightness.	
17	Inspect for excessive wear of chains and sprockets. Measure chain stretch of load chains.		34	Check accuracy of list and trim indicators against design data or previous test data.	

Section 3 Remarks

Section 4 Certification

Load Test Inspector:	Date:
Test Director:	Date:
Certifying Official:	Date: