PARACHUTIST ALTIMETER HISTORY RECORD

			c. Indicated altitude of the Altimeter being tested when the Master Altimeter indicates the following altitudes:						d. Altimeter tested by:	
	a. TEST DATE	b. MASTER ALT @ 29.92" +/- ___ FT.	(1) 30,000' (+/- 500')	(2) 20,000' (+/- 400')	(3) 15,000' (+/- 400')	(4) 10,000' (+/- 400')	(5) 5,000' (+/- 350')	(6) 2,500' (+/- 300')	(1) TESTER PRINTED NAME:	(2) SIGNATURE
1.										
2.										
3.										
4.										
5.										
6.										
7.										
8.										
9.										
10.										
11.										
12.										
13.										
14.										
15.										
16.										
17.										
18.										
19.										
20.										

NOTE: 1. Altimaster IIs and Altimaster IIIs have a maximum operational altitude of 18,000 ft msl. Modify the maximum testing altitude of these altimeters to not exceed 18,000 ft.
2. Reduce altitude at a rate of 180 to 200 feet per second and observe both master and tested altimeters. If the tested altimeter exceeds acceptable tolerances, it is unserviceable and shall be removed from service and replaced.
3. If the tested altimeter passes, mark it with date tested and next test due date.

21. REMARKS:

22. PART NUMBER:	23. CONTRACT NUMBER:	
24. ALTIMETER TYPE:	25. SERNO:	26. FIELD NUMBER: