**VLA MAINTENANCE ACTION**

DATE: _____ JSN _____

**FRESNEL LENS, MK 6 MOD 3 ALIGNMENT, STABILIZATION AND POLE CHECK DATA**

NOTE: REFER TO THE APPLICABLE MAINTENANCE REQUIREMENT CARD AND ENTER ONLY THE DATA REQUIRED FOR THE PERIODICITY INDICATED.

**POWER SUPPLY DATA**

| | | |
|---|---|---|
| +10V FOR +/-0.50 (UP TO 0.75 IS ACCEPTABLE) | 15V FOR +/-0.30 | +28V FOR +/-5.0 |
| -10V FOR +/-0.50 (UP TO 0.75 IS ACCEPTABLE) | 15V FOR +/-0.30 | -28V FOR +/-5.0 |

**BASIC ANGLE DATA**

NOTE: PITCH AND ROLL SYNCHROS SET 0.000+/-0.005 VDC

DAILY

| POLE LOC | B/A SET | POLE HEIGHT (+/- 1.0 IN) | | | RESP METER READING COMPUTER #1 | | | (+/-3.0 MIN) COMPUTER #2 | |
|---|---|---|---|---|---|---|---|---|---|
| FT | DEG | IDEAL | ACTUAL | ERROR | IDEAL | ACTUAL | ERROR | ACTUAL | ERROR |
| 79 | 3.5 | | | | 3 30' | | | | |
| 79 | 3.75 | | | | 3 45' | | | | |
| 69 | 4.00 | | | | 4 00' | | | | |

WEEKLY

| POLE LOC | B/A SET | POLE HEIGHT (+/- 1.0 IN) | | | RESP METER READING COMPUTER #1 | | | (+/-3.0 MIN) COMPUTER #2 | |
|---|---|---|---|---|---|---|---|---|---|
| FT | DEG | IDEAL | ACTUAL | ERROR | IDEAL | ACTUAL | ERROR | ACTUAL | ERROR |
| 79 | 3.5 | | | | 3 30' | | | | |
| 79 | 3.75 | | | | 3 45' | | | | |
| 69 | 4.00 | | | | 4 00' | | | | |

MAINT. MAN _____ BRANCH LPO/CHIEF _____

QA INSPECTOR _____ MAINT. CHIEF/OFFICER _____