INSTRUCTIONS FOR PREPARATION OF ENGINEERING TRIAL REPORTS

1. OPNAV 9091/1B Engineering Trial Report, applies to steam-driven surface ships. OPNAV 9094/1C Engineering Trial Report, Sheets 1 and 2 apply to diesel-driven surface ships and submarines. OPNAV 9094/1D Engineering Trial Report, Sheets 1 and 2 apply to gas turbine-driven ships. Only data applicable to the ship in question should be entered.

2. The forms are designed to provide data for the analysis of all the machinery associated with each main propulsion unit. It is, therefore, necessary to use a separate set of sheets for each main propulsion unit installed or operating.

3. Where hourly readings are required in the Engineering Trial Reports, readings should be taken at frequent intervals (e.g., every 15 minutes) during the hour and the average entered in the hourly column. To indicate the degree of accuracy of the recorded data it is necessary that the interval that readings are taken be entered in the space provided on each sheet.

4. Space is provided on the back of each data sheet to report additional information which may be required by Type Commanders or would aid in determining the cause for an unsatisfactory trial.

5. Fuel consumption shall be determined by the *MOST* accurate means available.

6. This report shall be submitted to the Type Commanders via the Trial Ship chain of command.

a. In all cases whether SATISFACTORY or UNSATISFACTORY, this report shall be submitted to the Type Commander, with an advance copy to NAVSEA. The Type Commander and Naval Sea Systems Command Headquarters will, in their endorsements, explain, if possible, the cause of Unsatisfactory Trials.

b. In all cases of new construction or major conversion a copy of this report (complete) shall be sent to NAVSEA for all trials.