



PRODUCT SPECIFICATION

Model No	T128HC-C12-05
Product Name	1.28 TFT LCD Module
Version	V1.0
Date	2022-05-05

☐ Preliminary
Specification ☒ Final
Specification

PREPARED BY	CHECKED BY	APPROVED BY

Factory Contact Information 工厂联系信息

Linda GENA格钠

Hangzhou Gena Electronics Co., Ltd.

海外营业部 Linda Wechat: ADM1253282093 MP/WhatsApp:

+86 13675823107 E-mail: gena_lcd@163.com Add: 5th. Fl.,

Block 27, No. 536, Shunfeng Road,Donghu Street, Linping

District, Hangzhou City, Zhejiang Province,China



Revision History

Version	Date	Page	Revise record	Remarks
V1.0	2022.05.05	-	First issued	-



TABLE OF CONTENT

NO.Contents	Page
1. General Parameter	4
2. Physical drawing	4
3. Mechanical Dimension	5
4. Absolute Maximum Ratings	6
5. DC Characteristics	6
6. Backlight Characteristic	6
7. Pins Definitions.	7
8. Schematic Diagram	7
9. Timing Characteristics	8
10. Optical Characteristics	9
11. Reliability	12
12. Precautions	13

1. General Parameter


NO.	Features	Details	Unit
1	Display Size(Diagonal)	1.28"	Inch
2	LCD type	IPS TFT	-
3	Display Mode	Normally black	-
4	Resolution	240 RGB(H) x 240(V)	Pixels
5	Viewing Direction	ALL	-
6	Module size	35.6(W) x 37.74(H) x 1.66(T)	mm
7	Active Area	32.4(W) x 32.4(H)	mm
8	Pixel Size	0.135(W) x 0.135(H)	mm
9	Color arrangement	RGB Vertical stripe	-
10	Interface	4 Wire SPI	-
11	Display Colors	262K	-
12	Driver IC	GC9A01	-
13	With or Without Touch Panel	Without	-
14	Operating Temperature	-20℃~70℃	℃
15	Storage Temperature	-30℃~80℃	℃
16	Weight	3.36	g

Note 1: Please refer to the mechanical drawing.

2. Physical drawing



3. Mechanical Dimension



4. Absolute Maximum Ratings

Item	Symbol	Min.	Max.	Unit
Analog Supply Voltage	VCC	-0.3	4.6	V
Operating temperature	Top	-20	70	°C
Storage temperature	Tst	-30	80	°C

Note 1: If Ambient temperature below 50°C, the maximal humidity is 90%RH, if Ambient temperature over 50°C, absolute humidity should be less than 60%RH.

Note 2: The response time will be extremely slow when the operating temperature is around -10°C, and the back ground will become darker at high temperature operating.

Note 3: If one of the above items is exceeded its maximum limitation momentarily, the quality of the product may be degraded. Absolute maximum limitation, therefore, specify the values exceeding which the product may be physically damaged. Be sure to use the product within the recommend range.

5. DC Characteristics

Item	Symbol	Min.	Typ.	Max.	Unit
Analog Supply Voltage	VCC	2.5	2.8	3.3	V
Input high voltage	V _{IN}	0.7*IOVCC	-	IOVCC	V
Input low voltage	V _{IL}	VSS	-	0.3*IOVCC	V
Output high voltage	V _{OH}	0.8*IOVCC	-	IOVCC	V
Output low voltage	V _{OL}	VSS	-	0.2*IOVCC	V
Input Current	I _{IN}	-	20	-	mA

6. Backlight Characteristic

Item	Symbol	Min.	Typ.	Max.	Unit	Condition
Forward Voltage	V _F	2.9	3.0	3.1	V	-
Forward Current	I _F	-	40	-	mA	-
Power dissipation	P _d	-	120	-	mW	-
LED Life Time(25 °C)	-	-	10000	-	Hrs	-

Note: LED life time defined as follows: The final brightness is at 50% of original brightness. Typical operating life time is estimated data.




7. Pins Definitions


Pin.No	Symbol	Description
1	GND	Ground.
2	LED-K	Backlight cathode
3	LED-A	Backlight anode
4	VDD	Power supply for Analog.
5	GND	Ground.
6	GND	Ground.
7	D/CX	Display data/command selection pin
8	CSX	-Chip selection pin Low enable. High disable.
9	SCL	Serial interface clock.
10	SDA	SPI interface input/output pin.
11	RESX	This signal will reset the device and it must be applied to properly initialize the chip. -Signal is active low
12	GND	Ground.

Note: The backlight LED is recommended to be powered independently by constant current drive.

8. Schematic Diagram



9. Timing Characteristics



4-line serial Interface Timing Characteristics

VCC=2.5 to 3.3V, AGND=DGND=0V, Ta=25°C

Signal	Symbol	Parameter	MIN	MAX	Unit	Description
CSX	T _{CSS}	Chip select setup time (write)	20	-	ns	
	T _{CSH}	Chip select hold time (write)	40		ns	
SCL	T _{SCYCW}	Serial clock cycle (Write)	10		ns	
	T _{SHW}	SCL "H" pulse width (Write)	5		ns	
	T _{SLW}	SCL "L" pulse width (Write)	5		ns	
	T _{SCYCR}	Serial clock cycle (Read)	150		ns	
	T _{SHR}	SCL "H" pulse width (Read)	60		ns	
	T _{SLR}	SCL "L" pulse width (Read)	60		ns	
D/CX	T _{DCS}	D/CX setup time	10		ns	
	T _{DCH}	D/CX hold time	10		ns	
SDA (DIN)	T _{SDS}	Data setup time	5		ns	
	T _{SDH}	Data hold time	5		ns	
DOUT	T _{ACC}	Access time	10		ns	

10. Optical Characteristics

Item		Symbol	Condition	Min.	Typ.	Max.	Unit	Note
Transmittance (without Polarizer)		T (%)	Θ=0 Normal viewing angle	(4.4)	(4.9)	-	%	Measuring with Polarizer, Reference Only
Transmittance (with Polarizer)		T (%)		(13.5)	(15.0)	-	%	
Contrast Ratio		CR		900	1100	-	—	(1)(2)
Response Time		T _R + T _F		—	30	35	msec	(1)(3)
Color Gamut	(%)			55	60	—	%	C-light
Color Chromaticity (CIE1931)	White	W _x		-0.02	(0.324)	+0.02	—	(1)(4) CF glass C-light
		W _y			(0.347)			
	Red	R _x			(0.644)		—	
		R _y			(0.333)		—	
	Green	G _x			(0.325)		—	
		G _y	(0.566)					
	Blue	B _x	(0.134)		—			
		B _y	(0.124)					
Viewing angle	Hor.	Θ _L	CR>10	80	85	—	—	(1)(4) Measuring with Polarizer · Reference Only
		Θ _R		80	85	—		
	Ver.	Θ _U		80	85	—		
		Θ _D		80	85	—		
Optima View Direction		Free						(5)

1. Measuring Condition

Measuring surrounding : dark room


Ambient temperature : $25 \pm 2^\circ\text{C}$

15min. warm-up time.

2. Measuring Equipment

FPM520 of Westar Display technologies, INC., which utilized SR-3 for Chromaticity and BM-5A for other optical characteristics.


Note (1) Definition of Viewing Angle:



Note (2) Contrast ratio is calculated by the following formula:


$$\text{Contrast ratio (CR)} = \frac{\text{Brightness on the "white" state}}{\text{Brightness on the "black" state}}$$

Note (3) Definition of Response Time: Sum of TR and TF




Note (4) Definition of optical

measurement setup



Note (5) Rubbing Direction (The different Rubbing Direction will cause the different optima view direction.)



11. Reliability

11.1. MTBF

The LCD module shall be designed to meet a minimum MTBF value of 50000 hours with normal.

11.2. Test Condition

No	Item	Condition	Criteria
1	High Temperature Operating	70℃*24Hrs	1. No Defect Of Operational Function In Room Temperature Are Allowable. 2. IDD of LCM in Pre-and Post-Test Should Follow Specification.
2	Low Temperature Operating	-20℃*24Hrs	
3	High Humidity Storage	50℃*90%RH*24Hrs	
4	High Temperature Storage	80℃*24Hrs	
5	Low Temperature Storage	-30℃*24Hrs	
6	Thermal Cycling Test Storage	-	
7	Packing vibration	-	
8	Electrical Static Discharge	-	
		-	
9	Drop Test (Packaged)	-	

Note1. The test samples should be applied to only one test item.

Note2. Sample size for each test item is 2pcs.

Note3. No defection function allowable.

12. Precautions

12.1. Storage Conditions

- 12.1.1. Store the panel or module in a dark place where the temperature is $23\pm5^{\circ}\text{C}$ and the humidity is below $45\pm 20\%\text{RH}$.
- 12.1.2. Store in anti-static electricity container.
- 12.1.3. Store in clean environment, free from dust, active gas, and solvent.
- 12.1.4. Do not place the module near organics solvents or corrosive gases.
- 12.1.5. Do not crush, shake, or jolt the module.
- 12.1.6. Strong light exposure causes degradation of polarizer and color filter.

12.2. Handling Precautions

- 12.2.1. Avoid static electricity, which can damage the CMOS LSI.
- 12.2.2. The polarizing plate of the display is very fragile, please handle it very carefully.
- 12.2.3. Do not give external shock.
- 12.2.4. Do not apply excessive force on the surface.
- 12.2.5. Do not wipe the polarizer with dry cloth, as it might cause scratch. If the surface of the LCD needs to be cleaned, wipe it swiftly with cotton or other soft cloth soaked with petroleum IPA, do not use other chemicals.
- 12.2.6. Reverse and use within ratings in order to keep performance and prevent damage
- 12.2.7. Do not remove the panel or frame from the module.
- 12.2.8. Except for soldering the interface, do not make any alterations or modifications with a soldering iron; Ensure welding temperature at 320°C to 350°C , the welding time control within the 10 s, welding note don't stay too long in the same place to avoid scald FPC.

12.3. Limited Warranty

- 12.3.1. Our warranty liability is limited to repair and/or replacement. We will not be responsible for any consequential loss. (我们的保证责任仅限于修理和/或更换。我们将不负任何相应的损失。)
- 12.3.2. If possible, we suggest customer to use up all modules in six months. If the module storage time over twelve months, we suggest that recheck it before the module be used. (如果可能，我们建议客户在 6 个月内用完所有模块。如果模块存放时间超过 12 个月，我们建议在使用模块前重新检查。)
- 12.3.3. The warranty period is twelve months from the date of delivery. Buyer shall complete the assembly of all processes within twelve months of validity. During the warranty period, if the product quality problems, our company will be responsible for repair and replacement. All products must be stored and handled in accordance with regulations. Under warranty. When the goods do not comply with the above terms, we do not provide warranty services. (保修期为交货之日起十二个月。买方应在 12 个月内完成所有流程的组装。在保修期内，如果产品出现质量问题，我公司将负责维修和更换。所有产品必须按照规定储存和处理。在保修期内。当货物不符合上述条款时，我们不提供保修服务。)