

Mass properties of Base_Assembly
Configuration: Default
Coordinate system: Base_Coordinates

Mass = 999.02 grams

Volume = 484030.20 cubic millimeters

Surface area = 166100.45 square millimeters

Center of mass: (millimeters)

X = -36.09

Y = 0.1

Z = 41.05

Principal axes of inertia and principal moments of inertia: (grams * square millimeters)

taken at the center of mass.

Ix = (0.99, 0.00, -0.13) Px = 1024124.32

Iy = (-0.13, 0.00, -0.99) Py = 2453441.82

Iz = (0.00, 1.00, 0.00) Pz = 2734227.60

Moments of inertia: (grams * square millimeters)

taken at the center of mass and aligned with the output coordinate system. (Using positive tensor notation.)

Lxx = 1046850.94 Lxy = -5081.33 Lxz = -178732.64

lyx = -5081.33 lyy = 2734212.13 lyz = 761.80

Lzx = -178732.64 Lzy = 761.80 Lzz = 2430730.67

Moments of inertia: (grams * square millimeters)

taken at the output coordinate system. (Using positive tensor notation.)

lxx = 2730644.14 lxy = -9098.05 lxz = -1658910.47

lyx = -9098.05 lyy = 5719187.48 lyz = 5331.03

lzx = -1658910.47 lzy = 5331.03 lzz = 3731937.63

One or more components have overridden mass properties:

M5_ISO (4762)_70<91290A201>

M5_ISO (4762)_70<91290A201>

M5_ISO (4762)_70<91290A201>

M5_ISO (4762)_70<91290A201>

M5_ISO (4762)_70<91290A201>

M3_ISO (4762)_10<92000A120>

M3_ISO (4762)_10<92000A120>

M3_ISO (4762)_10<92000A120>

M3_ISO (4762)_10<92000A120>

M5_ISO (4032)_Nut<90591A260>

M5_ISO (4032)_Nut<90591A260>

M5_ISO (4032)_Nut<90591A260>

M5_ISO (4032)_Nut<90591A260>

M5_ISO (4032)_Nut<90591A260>

M5_ISO (4032)_Nut<90591A260>

M5_ISO (4032)_Nut<90591A260>

M5_ISO (4032)_Nut<90591A260>

M5_ISO (4032)_Nut<90591A260>

M5_ISO (4032)_Nut<90591A260>

M5_ISO (4032)_Nut<90591A260>

Angular Contact Bearing (7002) 15x32x9<2385K42>

Thrust ball bearing (5104) 20x35x10<7806K716>

Thrust ball bearing (5104) 20x35x10<7806K716>

Angular Contact Bearing (7002) 15x32x9<2385K42>