

Mass properties of Joint03_Assembly
Configuration: Default
Coordinate system: Joint03_Coordinates

Mass = 437.93 grams

Volume = 195653.96 cubic millimeters

Surface area = 67538.41 square millimeters

Center of mass: (millimeters)

X = -18.68

Y = 5.37

Z = -10.61

Principal axes of inertia and principal moments of inertia: (grams * square millimeters)

taken at the center of mass.

Ix = (-0.64, -0.24, -0.73) Px = 241372.52

Iy = (-0.70, 0.56, 0.44) Py = 399414.91

Iz = (0.31, 0.79, -0.53) Pz = 424982.29

Moments of inertia: (grams * square millimeters)

taken at the center of mass and aligned with the output coordinate system. (Using positive tensor notation.)

Lxx = 336996.04 Lxy = 17757.31 Lxz = 78065.99

lyx = 17757.31 lyy = 406643.04 lyz = 38017.26

Lzx = 78065.99 Lzy = 38017.26 Lzz = 322130.64

Moments of inertia: (grams * square millimeters)

taken at the output coordinate system. (Using positive tensor notation.)

Ixx = 398983.23 Ixy = -26203.92 Ixz = 164895.37

Iyx = -26203.92 Iyy = 608787.42 Iyz = 13036.83

Izx = 164895.37 Izy = 13036.83 Izz = 487582.75

One or more components have overridden mass properties:

Nema_14_stepper<1><Default>

M8_ISO (4762)_80_Part<96144A239>

M4_ISO (4762)_15<91290A306>

M4_ISO (4762)_15<91290A306>

M4_ISO (4762)_15<91290A306>

M4_ISO (4762)_15<91290A306>

M3_ISO (4762)_8_Part<91290A13>

M3_ISO (4762)_8_Part<91290A13>

M3_ISO (4762)_8_Part<91290A13>

M3_ISO (4762)_8_Part<91290A13>

Angular Contact Bearing (7002)_Up_ 15x32x9<2385K42>

Angular Contact Bearing (7002)_Up_ 15x32x9<2385K42>