

# Weather sensor fault detection in Meteorological masts

Franco Piergallini Guida, Filippo Visco-Comandini

**Abstract**—Wind power has become the world’s fastest growing renewable technology. The world-wide wind power installed capacity has exceeded 518 GW, and the new installations during the last three years was an average of 50 GW per year. A major issue with wind power system and with meteorological masts is the relatively high cost of operation and maintenance (OM). Wind turbines and sensor towers are hard-to-access structures, and they are often located in remote areas. That’s why continuous monitoring of wind turbine health using automated failure detection algorithms can improve turbine reliability and reduce maintenance costs by detecting failures before they reach a catastrophic stage and by eliminating unnecessary scheduled maintenance. Most of the wind turbines and meteorological masts have supervisory control and data acquisition (SCADA) system and it rapidly became the standard. SCADA has been used in other industries for accurate and timely detection, diagnostics and prognostics of failures and performance problems. In the present work, mathematical methods are proposed for sensor fault detection for meteorological masts through the analysis of the SCADA data. The idea is to compare and analyze measurements coming from the various sensors located in the same tower and different heights. We used a number of measurements to develop anomaly detection algorithms and investigated classification techniques using manual check and model parameter tuning. These methods are tested on wind masts situated in Argentina.

## I. INTRODUCTION

Renewable energy source is playing an important role in the global energy mix, as a mean of reducing the impact of energy production on climate change and wind power has become the fastest growing renewable technology. Wind energy is fundamentally used to produce electric energy. Wind turbines (WTs) are unmanned, remote power plants. Unlike conventional power stations, WTs are exposed to highly variable and harsh weather conditions, including calm to severe winds, tropical heat, lightning, arctic cold, hail, and snow. Due to these external variations, WTs undergo constantly changing loads, which result in highly variable operational conditions that lead to intense mechanical stress [1].

Supervisory control and data acquisition (SCADA) is an application that collects data from a system and sends them to a central computer for monitoring and controlling. Current controlling monitor (CM) systems essentially provide the necessary sensor and capability of data capture required for monitoring.

The research for fault detections and diagnostic techniques has been widely studying using various methods [2], [3]. Clustering algorithms and principal components analysis [4], AI based framework [5], performance evaluation and wake analysis [6], various machine learning algorithms used in fault prediction for SCADA data [8].

Meteorological masts but the literature about the fault diagnostic technique is quite limited [7] .

This paper proposes a methodology for fault diagnosis in sensor tower using a data-driven approach. The fault- related data is analyzed with two different algorithms

This paper is organized as following. In Section II we describe the sensor tower components and the scada data, in Section III we show what kind of failures we might encounter in the sensor towers, fault detection algorithms are presented in Section IV. Results and discussion are in section V. We conclude the paper in Section VI

## A. Notas bibliografica

- [9]
- [10]
- [11]
- [12]

## II. SENSOR TOWER

### A. Components

### B. scada data

## III. FAILURE IN THE SENSOR TOWERS

In contrast to control engineering applications, the weather sensor fault detection has a few special features. Namely, the phenomenon itself, weather, can be non-linear and time-varying. The local fault detection model for the weather measurement can change drastically and disturbances can be very large.

In this section, we are going to describe different existing types of failures in sensor towers. We can classify them in three group

### A. Mechanical faults

Mechanicals faults are identify by a mechanical failure in the sensor. For example in the XXX *veleta*, in the anemometers .there is a large variety of mechanical faults

### B. Connection faults

Intermittant faults

### C. Calibration faults

Faults that changes the measurement all along the scales

#### IV. ALGORITHMS

##### A. Ratio

We group the same type of sensors and calculates the ratio between them, if it is greater than a threshold it is classified as anomalous.

$$R_i^{j,k} = \frac{m_i^j}{m_i^k}, k \neq j$$

##### B. Pearson correlations

For each sensor's measurements, a moving Pearson correlation is calculated with a parameterized window valor, if a specific value is greater than a threshold it counts as an anomaly, a normal behavior dictates that all sensors must follow a same trend. This metric is mainly used for detects anomalies on anemometers types sensors.

$$C_i^{j,k} = \rho\left(\frac{V_{i-w}^j}{V_{i-w}^k}\right)$$

##### C. Logic combinations

If a specific sensor value have multiples discrepancies both in correlation or ratio with other sensors of the same type, then we classify that value as an anomalous measurement.

##### D. Parameter tuning

With this process, we obtained the bests thresholds for the Pearson correlation and the ratio. We performed the algorithm for several ranges of values of the parameters and contrast it with the real faults on data sets, to obtain the best combination that has the best sensibility for detect real faults. The parameters that we can adjust are the quotient on the ratio, correlation result and correlation window, this windows are the number of previous measurements that we will take to do this operation.

#### V. RESULTS AND DISCUSSION

XXXXX

#### VI. CONCLUSION

A methodology to predict faults using information provided by SCADA systems and fault files was presented.

#### REFERENCES

- [1] J. Ribrant, "Reliability performance and maintenance? a survey of failures in wind power systems," Ph.D. dissertation, School of Electrical Engineering, KTH Royal Institute of Technology, 2006.
- [2] P. Tchakoua, R. Wamkeue, M. Ouhrouche, F. Slaoui-Hasnaoui, T. Tameghe, and G. Ekemb, "Wind turbine condition monitoring: State-of-the-art review, new trends, and future challenges," *Energies*, vol. 7, no. 4, pp. 2595–2630, 2014.
- [3] M. L. Wymore, J. E. Van Dam, H. Ceylan, and D. Qiao, "A survey of health monitoring systems for wind turbines," *Renewable and Sustainable Energy Reviews*, vol. 52, pp. 976–990, 2015.
- [4] K. Kim, G. Parthasarathy, O. Uluyol, W. Foslien, S. Sheng, and P. Fleming, "Use of scada data for failure detection in wind turbines," National Renewable Energy Lab.(NREL), Golden, CO (United States), Tech. Rep., 2011.
- [5] K.-S. Wang, V. S. Sharma, and Z.-Y. Zhang, "Scada data based condition monitoring of wind turbines," *Advances in Manufacturing*, vol. 2, no. 1, pp. 61–69, 2014.

- [6] D. Astolfi, F. Castellani, and L. Terzi, "Mathematical methods for scada data mining of onshore wind farms: Performance evaluation and wake analysis," *Wind Engineering*, vol. 40, no. 1, pp. 69–85, 2016.
- [7] V. Hasu, H. Koivo, and J. Poutiainen, "Weather sensor fault detection with time-dependent recursive thresholds," in *First International Conference on Innovative Computing, Information and Control-Volume 1 (ICICIC'06)*, vol. 3. IEEE, 2006, pp. 140–144.
- [8] A. Kusiak and W. Li, "The prediction and diagnosis of wind turbine faults," *Renewable Energy*, vol. 36, no. 1, pp. 16–23, 2011.
- [9] B. Lu, Y. Li, X. Wu, and Z. Yang, "A review of recent advances in wind turbine condition monitoring and fault diagnosis," in *2009 IEEE Power Electronics and Machines in Wind Applications*. IEEE, 2009, pp. 1–7.
- [10] M. Schlechtingen and I. Santos, "Condition monitoring with ordinary wind turbine scada data—a neuro-fuzzy approach," in *Offshore 2011*, 2012.
- [11] M. Schlechtingen and I. F. Santos, "Comparative analysis of neural network and regression based condition monitoring approaches for wind turbine fault detection," *Mechanical systems and signal processing*, vol. 25, no. 5, pp. 1849–1875, 2011.
- [12] W. Yang, P. J. Tavner, C. J. Crabtree, Y. Feng, and Y. Qiu, "Wind turbine condition monitoring: technical and commercial challenges," *Wind Energy*, vol. 17, no. 5, pp. 673–693, 2014.