

Weather sensor fault detection in meteorological masts

Franco Piergallini Guida, Filippo Visco-Comandini, Máximo Iaconis

Abstract—Wind power has become the world’s fastest growing renewable technology. The world-wide wind power installed capacity has exceeded 518 GW, and the new installations during the last three years was an average of 50 GW per year. A major issue with wind power system and with meteorological masts is the relatively high cost of operation and maintenance (OM). Wind turbines and sensor towers are hard-to-access structures, and they are often located in remote areas. That’s why continuous monitoring of wind turbine health using automated failure detection algorithms can improve turbine reliability and reduce maintenance costs by detecting failures before they reach a catastrophic stage and by eliminating unnecessary scheduled maintenance. Most of the wind turbines and meteorological masts have supervisory control and data acquisition (SCADA) system and it rapidly became the standard. SCADA has been used in other industries for accurate and timely detection, diagnostics and prognostics of failures and performance problems. In the present work, mathematical methods are proposed for sensor fault detection for meteorological masts through the analysis of the SCADA data. The idea is to compare and analyze measurements coming from the various sensors located in the same tower and different heights. We used a number of measurements to develop anomaly detection algorithms and investigated classification techniques using manual check and model parameter tuning. These methods are tested on wind masts situated in Argentina.

I. INTRODUCTION

Renewable energy source is playing an important role in the global energy mix, as a mean of reducing the impact of energy production on climate change and wind power has become the fastest growing renewable technology. Wind energy is fundamentally used to produce electric energy. Wind turbines (WTs) are unmanned, remote power plants. Efforts have been made to develop efficient and cost-effective condition monitoring techniques for wind turbines [1]. Unlike conventional power stations, WTs are exposed to highly variable and harsh weather conditions, including calm to severe winds, tropical heat, lightning, arctic cold, hail, and snow. Due to these external variations, WTs undergo constantly changing loads, which result in highly variable operational conditions that lead to intense mechanical stress [2].

Supervisory control and data acquisition (SCADA) is an application that collects data from a system and sends them to a central computer for monitoring and controlling. Current controlling monitor (CM) systems essentially provide the necessary sensor and capability of data capture required for monitoring.

In contrast to control engineering applications, the weather sensor fault detection has a few special features. Namely, the phenomenon itself, weather, can be non-linear and time-varying. The local fault detection model for the weather

measurement can change drastically and disturbances can be very large. Fault diagnosis systems aims at detecting and locating degradation in the operation of sensors as early as possible. This way, maintenance operations can be performed in due time, and during time periods with low wind speed. Therefore, maintenance costs are reduced as the number of costly corrective maintenance actions decreases. Besides, the loss of production due to maintenance operations is minimized [18].

The research for fault detection and diagnostic techniques for wind turbines has been widely studying [3], [4], [5]. Some of the techniques involves clustering algorithms and principal components analysis [6], artificial intelligence based framework [7], performance evaluation and wake analysis [8], machine learning algorithm [9], [10] and neuro fuzzy approach [11].

Our research focus the fault diagnosis on meteorological masts, but the literature about these techniques is quite limited [12].

This paper proposes a methodology for fault diagnosis in sensor tower using a data-driven approach through the analysis of the SCADA data of two components. The anemometers and wind vanes measurements are analyzed with two different algorithms in order to develop anomaly detection techniques using manual check and model parameter tuning.

This paper is organized as following. In section II, we describe the SCADA data coming from the two sensor tower components used in the algorithms, in section III we show the different kind of failures that can happen in the sensor towers. In section IV, fault detection algorithms are presented. Results and discussion are in section V and the conclusion can be found in section VI.

II. METEOROLOGICAL MAST COMPONENTS

Meteorological masts are towers made of steel where measuring components are installed. In this section we explain two components of sensor towers called anemometers and wind vanes and we describe how these components records their data thru the SCADA system. The sensor towers, are lattice constructions consisting in three main beams shored up by smaller beams. The mast is a long slender construction, which gives an almost two-dimensional flow round a cross-section at certain height above the ground.

A. Components

Meteorological masts usually have several measuring components, such as barometers, temperature sensors, but we focus in two of them.

1) *Anemometers*: An anemometer is a device for measuring wind speed. It consists in three horizontal arms where at each end an hemispherical cup is mounted. The air flow pushes the cups in any horizontal direction. Anemometers configuration involves offset, scale, boom orientation, units, and sensor height. Usually a sensor tower has on average six anemometers placed on different heights, and anemometers are paired at each heights to have redundant measures [13].

2) *Wind vane*: A wind vane is an instrument used for measure the winds direction. When mounted on an elevated shaft or spire, the vane rotates under the influence of the wind and the vane points into the wind. Wind direction is measured in degrees from true north [14].

B. SCADA data

SCADA systems are widely used for monitoring and control of Industrial Control System (ICS), including the emerging energy system, transportation systems, gas and water systems, and so on. The primary objective of a SCADA system is to control real-life physical equipment and devices, e.g., an energy system SCADA may be used for monitoring and controlling of the electrical plants [15]. SCADA collects data from one or more distant facilities dispersed across a large geographic area. SCADA makes it unnecessary for an operator to be assigned to stay at or frequently visit remote locations when those are operating normally [16].

A functionality of SCADA system in a sensor tower is archiving the data coming from the data logger, the central computer instrument that records measurements from several sensors. Typically data are stored on a cyclic basis: sometimes files are created based on file size, number of points of time period rate [17]. In our case, the data logger archives time series measurements with a specific sampling rate set to be 10 minutes.

Through the paper, we will consider time series measurements $\{m_t^i\}$ for both wind directions and wind speed at time t and on i -th positions of the sensor on the meteorological mast. For each time t , the data logger stores the minimum value, the maximum value, the standard deviation and the average of the measurements occurred during the t -th 10 minutes interval.

III. FAILURE IN THE SENSOR COMPONENTS

In this section, we are going to describe different existing types of failures for sensor components in the meteorological mast. We classify these failures in three categories, each one with its own characteristics.

Porque lo citamos??[20].

A. Mechanical faults

In the wind vane, mechanical failures correspond to a break in the head or tail of the instrument: usually these types of failures are produced by a lightning strike or hailstorms. They are reflected in the wind measurements only when the wind is going above or below a certain thresholds. Also, a mechanical faults could provoke a blockage of the wind vane and the results is a unrealistic fixed wind direction over a long period

of time ???. In the anemometers, there is a large variety of mechanical faults and they are detectable in SCADA data. Lightning strikes or hailstorms could provoke a break on the anemometer's spoons, the wind speed measured by a broken anemometer could be both greater or lesser than the real value, depending on the breakage. Also, a blockage could occurs, preventing the rotation of the cups. They appear in certain specific wind conditions, for example when the wind speed is very slow.

B. Connection faults

Connection faults are due to a faulty connector between sensors, wires and the data logger. These faulty connectors make the measurements unstable in the sense that they are blocking the connections between sensors and the data logger. The effect of the connection faults can interfere with the SCADA data in two possible way: either the faulty connections happens over a long period and hence they are reflected as intermittent values or it can happen between the sampling rate, making the standard deviation bigger than usual.

C. Calibration faults

Calibration faults are due to bad configuration of the data logger, it could be when it is initialized or when a sensor is replaced with another that has a totally different configuration and this is not updated on the data logger. Those faults are easily recognizable in the SCADA data, since their values have a constant offset compared to healthy sensors. In practice those type of faults change the measurement all along the scales. (Figure 3)

IV. ALGORITHMS

In this section, we describe the algorithms used to detect anomalies. Anomalies are patterns in data that do not conform to a well defined notion of normal behavior. This section is divided in three parts; first in IV-A we define some computed variable for our algorithms. In IV-B, we explain how to flag possible faults in the time series measurements, and in subsection IV-C, we show the logic to determine whether the flags are faults or not.

A. Computed variables

We have two types of measurements. In the data logger, wind vanes measures are expressed in degree and the anemometers units are in m/s. The vanes' measurements are converted first to radians and then to sin and we use this sin result for compute the variables.

1) *Ratio*: The ratio is only computed for the anemometers type sensors. m_t^i represents the measurement at time t on the i -th sensor. For each sensor type, we compute the ratio among all measurements in the sensors as

$$R_t^{j,i} = \frac{m_t^j}{m_t^i}, \quad i \neq j \quad (1)$$

2) *Pearson correlations*: We compute the Pearson correlations only for anemometers. For the i -th sensor and for each time t , we define the measurement vector with a time window w as

$$M_{t,w}^i = [m_{t-w}^i, m_{t-w+1}^i, \dots, m_t^i] \quad (2)$$

We compute the moving Pearson correlation depending on the time window w between the i -th and the j -th sensors

$$C_{t,w}^{i,j} = \rho \left(\frac{M_{t,w}^i}{M_{t,w}^j} \right) \quad (3)$$

3) *Difference*: A difference between vanes sin values is computed as follow

$$D_t^{j,i} = m_t^j - m_t^i, \quad i \neq j \quad (4)$$

B. Flagging

There are several thresholds that serve to flag a measurement as a possible anomaly. Any time that a measurement crosses a specific threshold for one of its computed variables, this measurement is marked with a flag as a possible anomaly. Each computed variable has its own threshold. Physical boundaries are set for the different sensors types. If a signal measurement value is greater than the boundary is flagged as anomalous. Considering the average of wind speed, a value greater than 70 m/s would imply that over a 10 minutes period, the wind speed registered was in some occasion much greater than this value. This condition could be a key used for detecting anomalous behaviors on an anemometer.

C. Fault detection

We consider that a sensor is faulty when it is flagged by our algorithm.

1) *Anemometer*: The i -th anemometer is flagged and detected as an anomaly if the following conditions are verified:

- At least two measurements between $R_t^{j,i}$ and $C_t^{j,i}$ are flagged for $i \neq j$.
- At least one of the previous flag belongs to a redundant sensor.

An anemometer is also considered faulty when the measurement values are greater than 70 m/s.

2) *Wind vane*: A wind vane is detected as an anomaly only when

- At least one of $D_t^{i,j}$ is flagged.

V. RESULTS AND DISCUSSION

Parameter tuning. With this process, we obtained the bests thresholds for the Pearson correlation and the ratio. We performed the algorithm for several ranges of values of the parameters and contrast it with the real faults on data sets, to obtain the combination that has the best sensibility for detect real faults. The parameters that we can adjust are the quotient on the ratio, correlation result and correlation window, this windows are the number of previous measurements that we will take to do this operation.

VI. CONCLUSION

A methodology to predict faults using data provided by SCADA systems and fault files was presented.

REFERENCES

- [1] W. Yang, P. J. Tavner, C. J. Crabtree, Y. Feng, and Y. Qiu, "Wind turbine condition monitoring: technical and commercial challenges," *Wind Energy*, vol. 17, no. 5, pp. 673–693, 2014.
- [2] J. Ribrant, *Reliability Performance and Maintenance? A Survey of Failures in Wind Power Systems*. PhD thesis, School of Electrical Engineering, KTH Royal Institute of Technology, 2006.
- [3] P. Tchakoua, R. Wamkeue, M. Ouhrouche, F. Slaoui-Hasnaoui, T. Tameghe, and G. Ekemb, "Wind turbine condition monitoring: State-of-the-art review, new trends, and future challenges," *Energies*, vol. 7, no. 4, pp. 2595–2630, 2014.
- [4] M. L. Wymore, J. E. Van Dam, H. Ceylan, and D. Qiao, "A survey of health monitoring systems for wind turbines," *Renewable and Sustainable Energy Reviews*, vol. 52, pp. 976–990, 2015.
- [5] B. Lu, Y. Li, X. Wu, and Z. Yang, "A review of recent advances in wind turbine condition monitoring and fault diagnosis," in *2009 IEEE Power Electronics and Machines in Wind Applications*, pp. 1–7, IEEE, 2009.
- [6] K. Kim, G. Parthasarathy, O. Uluoyol, W. Foslien, S. Sheng, and P. Fleming, "Use of scada data for failure detection in wind turbines," tech. rep., National Renewable Energy Lab.(NREL), Golden, CO (United States), 2011.
- [7] K.-S. Wang, V. S. Sharma, and Z.-Y. Zhang, "Scada data based condition monitoring of wind turbines," *Advances in Manufacturing*, vol. 2, no. 1, pp. 61–69, 2014.
- [8] D. Astolfi, F. Castellani, and L. Terzi, "Mathematical methods for scada data mining of onshore wind farms: Performance evaluation and wake analysis," *Wind Engineering*, vol. 40, no. 1, pp. 69–85, 2016.
- [9] A. Kusiak and W. Li, "The prediction and diagnosis of wind turbine faults," *Renewable Energy*, vol. 36, no. 1, pp. 16–23, 2011.
- [10] M. Schlechtingen and I. F. Santos, "Comparative analysis of neural network and regression based condition monitoring approaches for wind turbine fault detection," *Mechanical systems and signal processing*, vol. 25, no. 5, pp. 1849–1875, 2011.
- [11] M. Schlechtingen and I. Santos, "Condition monitoring with ordinary wind turbine scada data—a neuro-fuzzy approach," in *Offshore 2011*, 2012.
- [12] V. Hasu, H. Koivo, and J. Poutiainen, "Weather sensor fault detection with time-dependent recursive thresholds," in *First International Conference on Innovative Computing, Information and Control-Volume I (ICICIC'06)*, vol. 3, pp. 140–144, IEEE, 2006.
- [13] A. Clifton, "135-m meteorological masts at the national wind technology center: Instrumentation, data acquisition, and processing.?", *Report*, July, 2014.
- [14] A. Sayigh, *Comprehensive renewable energy*. Elsevier Science & Technology, 2012.
- [15] M. Ahmed, A. Anwar, A. N. Mahmood, Z. Shah, and M. J. Maher, "An investigation of performance analysis of anomaly detection techniques for big data in scada systems.," *EAI Endorsed Trans. Indust. Netw. & Intellig. Syst.*, vol. 2, no. 3, p. e5, 2015.
- [16] S. A. Boyer, *SCADA: supervisory control and data acquisition*. International Society of Automation, 2009.
- [17] A. Daneels and W. Salter, "What is scada?," 1999.
- [18] N. Luo, Y. Vidal, and L. Acho, *Wind turbine control and monitoring*, vol. 821. Springer, 2014.
- [19] V. Morris, J. Barnard, L. Wendell, and S. Tomich, "Comparison of anemometers for turbulence characterization," tech. rep., Pacific Northwest Lab., Richland, WA (United States), 1992.
- [20] V. Chandola, A. Banerjee, and V. Kumar, "Anomaly detection: A survey," *ACM computing surveys (CSUR)*, vol. 41, no. 3, p. 15, 2009.