eosc-basic-compliance

Test suite, workflow and configuration overview

Clean clone, 26 September 2026 — rebuilt 10 November 2026 — EOSC Node Latvia and Scholarly Commons added (eighteen nodes configured; published run web-35, sixteen nodes; re-issued checklist v3.2), 464 test cases

Repository: github.com/marioreale/eosc-basic-compliance

What the test suite covers, how the tool is configured, and what the published figures actually say. Every figure was measured on 25 September 2026 against a clean clone of the repository state this document is committed with (from commit ada1b4a). The test count was re-checked on 26 September 2026 against a clean clone of commit 678b75e (checklist v3.1, run web-8 published): **426 test cases, all passing in CI**. It was re-checked again on 29 September 2026 for checklist v3.2: **453 test cases**, all passing (**462** since the per-node time limit of 20 October 2026, below; **464** since the two cases for the EOSC Federation logo on the results page, in test_report.py, of 5 November 2026 (commit 6b24380). Adding EOSC Node Latvia and Scholarly Commons on 10 November 2026 added no case: the node guards check every entry inside one case). No node website was contacted to prepare this edition.

👉 **Installation, configuration and run guide** — how to install and run the tool. Section 7 of that guide is the short version of this document.

👉 **Analysis workflow** — what the tool does once running: the collection sequence, the evidence model, and the exact branch conditions behind each of the ten checklist points.

> **In one line.** A Python tool that checks EOSC Node Landing Pages against *Node Landing Page Verification Checklist v3.2*, with a pytest suite of 453 hermetic test cases that never touch a node's website, and at most two bounded hops of link following.
>
> **On "the previous edition".** This document has been revised several times while the tool was being built. Earlier editions circulated as Word and PDF files outside the repository; this is the first to be committed. Where the text below says a previous edition was wrong, that correction is kept rather than silently dropped, because a figure that was quoted in a meeting is worth being able to trace.
>
> **What changed since the 21 September edition.** The suite grew from 111 to **426 cases** (450 since checklist v3.2, below, and 453 since the broken-link fix of 1 October 2026) and gained four files: tests/test_names.py (64 cases, the approved-name matcher), tests/test_nodes.py (14 cases, guarding the node configuration) and tests/test_privacy.py (51 cases, personal-data masking) and tests/test_update_row.py (22 cases, updating one node's row). Four things the previous edition described as true are no longer true, and each is corrected in place below rather than quietly dropped:

Previous edition said	Now
--only rewrites the shared report — a known defect, unfixed	**Fixed**, and pinned by four tests (section 5)
Two latent defects in report.py, known and unfixed	**Fixed** at commit 014682c (section 7)
uv.lock is not committed, so runs are not reproducible	**Committed**; CI installs with --locked (section 9)
The web form cannot reach depth 2	It can — the depth input now offers 2 (section 6)

Since 26 September 2026: a new published run. results/ held run web-4, collected by the GitHub workflow from all thirteen nodes, Italy included at its new address: 45 PASS, 8 FAIL, 77 MANUAL_REVIEW. It replaced the reviewed run of 24 September by decision of the maintainer and has **not** been reviewed by hand; section 10 has the figures. Four tests pinned to the old run were updated to the new one (section 10), and the count stayed 425.

Since 26 September 2026: checklist v3.1. The reference document is now *Node Landing Page Verification Checklist v3.1* (24 September 2026), transcribed to checklist/v3.1.yaml and made the default; v3.0.yaml is kept so older runs can be rebuilt. The rules did not change: v3.1 rewords points 1, 2, 4, 6 and 7, narrows 1R and 5a–5c to *Node Exchange* resources, and defines EOSC AAI login by requirement [P.2] of the Production 1.0 Checklist v1.4, so only titles, quoted text and review messages were updated. The evidence of run web-4 was first re-scored against v3.1 without contacting any node, and every one of the 130 verdicts was unchanged; runs web-5, web-6, web-8 and web-9, collected under v3.1 by the workflow, then replaced it with the same verdicts; web-9 is the published one. The suite now has 426 cases: the per-revision provenance test also runs on v3.1, and the stored-results update test no longer assumes version 3.0.

Since 29 September 2026: checklist v3.2. The reference document is now *Node Landing Page Verification Checklist v3.2* (28 September 2026), transcribed to checklist/v3.2.yaml and made the default; v3.1.yaml and v3.0.yaml are kept. Unlike v3.1, this revision **changes a rule**. Item 5 now requires the purpose description, the AUP and the UAP of every Node Exchange resource to be available both on the NLP (directly, or, since the re-issue, via pages it links to) and in the resource's EOSC Catalogue metadata, where v3.1 accepted either. So a landing page that links to neither policy (nor to a licence, nor to the other policy, which the new notes allow) now gets FAIL on 5b or 5c instead of MANUAL_REVIEW. The rule is chosen by the checklist file (item5_on_nlp: true in v3.2.yaml only), so older runs still rebuild exactly under -c checklist/v3.1.yaml; this was verified on run web-11. The published evidence of web-11 was re-scored against v3.2 without contacting any node and published as web-11-v3.2: six cells moved from review to FAIL (section 10). Run web-12, the first collected under v3.2, then replaced it with the same 130 verdicts, and web-13, at depth 2, confirmed them. The suite grew from 426 to 438 cases: eight in test_checks.py for the two item 5 rules, two in test_checklist.py (each revision selects its own rule; the default is v3.2 or later and applies it) with one more provenance case for v3.2, and one in test_report.py for the column legend.

Since 29 September 2026: v3.2 re-issued. The v3.2 document was circulated again with a different item 5: the policies must be on the NLP "directly on the NLP itself or via intermediate web pages linked by the NLP", not only directly. The first copy is discarded: checklist/v3.2.yaml and the committed PDF were replaced, with the new hash. A pointer on a linked page the tool read now settles the NLP half, the crawler follows policies, legal, services and resources links for it (purposes 5p and 5s, after all others), and an unread page of that kind turns a missing policy into review instead of FAIL. The published evidence of web-13 was re-scored without contacting any node as web-13-rescored: 50 PASS, 8 FAIL, 72 review, with no 5b/5c FAIL left (section 10). The suite grew to 449 cases: eight in test_checks.py for pointers on linked pages, and three in test_crawl.py for the new purposes. Run web-14, the first collection under the re-issued v3.2, showed that privacy and cookie policies spelled with a hyphen in the address were still followed, and that looking for services pages at the second hop too used the whole fetch budget. Both were fixed, with no verdict changed, and one more crawl test brings the suite to **450 cases**.

Since the 24 September edition. Personal data is now masked in the evidence and in every report (section 5), and the published run was masked at commit ada1b4a with every verdict unchanged (section 10). BBMRI-ERIC's configured URL changed to a dev3. address on 25 September, and the published run was collected from the old one, so rebuilding it needs the old node list (section 5). The suite grew from 326 to 329 cases for these changes, to 333 with four tests that keep the

command-line help complete, and to 339 with the tests for the URL-mismatch warning and for switching the default checklist revision (section 11). It is 357 with eighteen cases for `--node`, 369 with twelve for the configuration listings, 379 with ten for `--list-nodes-ids` and `--show-node`, and 390 with eleven for `--update-nlp` (section 5).

The node list also grew from nine to **thirteen** (CERN and EOSC Node Czechia on 21 September, Italy and Slovakia on 24 September), and the reviewed report of 24 September covered twelve of them. Italy was skipped because its domain did not resolve that day; section 10 has the details. The suite's runtime rose from ~0.2 s to ~5.9 s for a reason worth knowing (section 2). Every figure below was re-measured rather than carried over, and section 7 records a further defect found while preparing this edition, since fixed.

---

1. Language and framework

Python, requiring 3.12 or newer, developed on 3.14. Packaged with hatchling and managed with `uv`. Roughly **4,498 lines across seven modules** (`checks.py` 1142, `report.py` 1019, `cli.py` 819, `fetch.py` 712, `privacy.py` 383, `names.py` 247, `patterns.py` 176), plus **3,460 lines of tests**. Tests are now about three quarters the size of the code they exercise.

The suite is **pytest** — the PyUnit lineage rather than JUnit, but it does not use `unittest.TestCase` classes at all. Tests are plain functions with bare `assert` statements. There is no `setUp`/`tearDown`; shared setup is a few small helper functions that build page evidence.

JUnit appears only as an output format. Continuous integration runs `pytest -q --junitxml=results/junit.xml`, and the `mikepenz/action-junit-report` action turns that XML into the GitHub Checks summary. So you get JUnit-style reporting in the Actions tab without JUnit being the test framework. `ruff` runs as a lint gate before pytest, and the XML is also kept as a build artifact.

Component	Choice
Language	Python ≥ 3.12, developed on 3.14 (declared in `pyproject.toml`)
Test framework	pytest 8 (plain functions, no TestCase classes)
Report format	JUnit XML, published to GitHub Checks
Lint gate	ruff (E, F, I, B, SIM, UP), line length 100
Page rendering	Playwright + Chromium (headless)
HTML parsing	selectolax
Language detection	lingua-language-detector
CLI	typer
Config format	YAML (pyyaml)

2. What is actually tested

374 test functions, expanding to 464 executed cases (twenty-three tests are parametrized). **None of them touch the network, and none of them open a browser.** This is the central design decision: most tests construct `PageEvidence` objects directly in memory — a synthetic page carrying the links, HTTP status and

text a scenario needs. Nothing in the suite requests a real website, so the suite costs nothing and cannot fail because a node is down or because someone edited a page.

The absence of a browser requirement is verified rather than assumed: running the suite with PLAYWRIGHT_BROWSERS_PATH pointed at an empty directory still yields 425 passed, while collect fails with Playwright's "Executable doesn't exist" error. That is why the CI job installs no browser.

File	Cases	Covers
test_names.py	64	The approved-name matcher: separator tolerance, scoping to a node, anchoring, the committed default list and its provenance
test_checks.py	94	The checklist rules per point — 1, 3, 4, 5b, 5c, 6, 7 — with both item 5 rules (v3.1 and v3.2) and policy pointers on linked pages, plus cross-point invariants, that a point 3 summary never contradicts its own evidence, and the point 6 and 5b/5c cases found by the 24 September review
test_report.py	39	Matrix rendering, the column legend under each item 5 rule, the dual-depth tables, Markdown escaping, table-breaking input
test_crawl.py	39	Link selection, the item 5 intermediate pages, host containment, whether following a link changes a verdict, the depth-2 budget, the depth-1 view
test_cli.py	113	Argument handling, node-id derivation, output isolation, report scope, --skip, command wiring, and that every option has help text, shared options are described alike, and --help lists the node ids; that evidence from a URL other than the configured one is flagged in every report; --node with an alternative --url; the configuration listings (--list-nodes/--list-nodes-ids, --list-nlps, --list-approved-names, --print-config, --show-node) and --update-nlp
test_checklist.py	19	Provenance of the checklist: source document hash for every committed revision, point-to-rule

File	Cases	Covers
		mapping, version/filename convention, that the default revision is one line that --help follows, and that each revision selects its own item 5 rule
test_nodes.py	14	The node configuration itself: required fields, unique ids, well-formed URLs, no two nodes sharing an eosc.eu entry, every node's name covered by the scoped list, and the default copy for --restore-default-config identical to the committed nodes.yaml
test_privacy.py	51	Personal-data masking: what is masked, what is kept, that evidence files and every report format are written masked, and that the committed evidence stays masked
test_node_timeout.py	9	The per-node time limit, with a fake browser: a node that finishes is untouched; a node hung in navigation or in reading the page is abandoned at the limit, keeps what it had gathered and reads ERROR on all ten points; a clean-up that hangs too does not become the hang; 0 disables the limit; in a three-node run the node after a hung one is still collected and the browser is restarted
test_update_row.py	22	--update-results-for-node: only the named row of the stored results changes, the reports gain one banner, one node is collected, a failed fetch changes nothing, a skipped node is inserted in order, and the refusals
Total	**464**	

test_names.py is the largest file in the suite, and deliberately so: point 3 is the only check that compares page text against an externally supplied list of official names, which makes it the check most able to produce a confident wrong answer. test_nodes.py is new since the node list grew — adding a node is now a configuration edit that the suite validates rather than a change nothing checks.

Why the suite takes ~5–6 seconds rather than ~0.2

The previous edition reported ~0.2 s. It is now **5–6 s** (5.2–5.9 s across four consecutive runs on 25 September 2026; 5.64–5.96 s across three on 24 September), and the cause is not a slow test but a change in what some tests do. A dozen or so tests in test_names.py and test_cli.py copy the **committed evidence** into a temporary directory and run a full assess through it, then read the resulting results.json:

Slowest cases	Time
test_the_separator_rule_in_force_is_recorded	0.62 s
test_only_does_not_shrink_the_report_in_the_published_directory	0.35 s
test_with_no_flag_the_committed_default_is_used	0.35 s
test_a_full_run_records_no_selection	0.33 s

That is end-to-end assessment against real captured pages, which is why it costs real time — and it is still offline: disk and CPU only, no network and no browser. The trade is deliberate. A matcher tested only against synthetic strings would not have caught a report-scoping defect, and these are the tests that pin the --only fix.

The trade-off in the other direction remains explicit: the suite verifies that *the checklist rules are correctly applied to a page*, never that fetching works. Playwright's own behaviour is not covered, and that gap has cost something — see section 7.

Testing criteria

Six principles run through the suite.

- **Per-point rules with their near-misses.** For each decidable point, a passing case and the ways it can nearly pass. Point 4 has **six** tests because it is the sharpest point in the checklist: a correct node entry passes, the federation index fails, the eosc.eu homepage fails, no link at all fails, a lookalike domain fails, and a domain merely *ending* in eosc.eu fails.
- **Nothing may silently pass.** One test asserts that points the checklist leaves to human judgement can never return PASS. Another asserts exactly one result per checklist point per node, so a point cannot quietly vanish from the matrix. A third blocks a PASS on point 3 when no approved-names list is in force — which now requires --no-approved-names, since a committed default list is used otherwise.
- **Absence is not concluded from a broken collection.** If a page did not render — a cookie overlay, a JavaScript shell — then a missing link cannot be reported as absent, because that describes the tool rather than the node. A companion test stops that safeguard becoming a blanket excuse for pages that did render.
- **Link following must not make PASS cheaper.** A whole block of tests asserts that following a link can only make a verdict better-evidenced, never more generous: a broken policy link fails (unless another link to the policy remains), a navigation stub is not accepted as a policy document, and an About page cannot flip point 2, which asks the landing page itself to state those things.
- **The paperwork cannot drift from the code.** Nineteen tests assert that the checklist YAML and the rules stay in step: the source document is committed and still hashes to what was transcribed, every point names the function that decides it, every function is claimed by exactly one point, a revision must arrive as a new file, and the default revision is selected by one line that the help texts follow. See section 5.

- **Regression pins for real defects.** At least ten tests exist because the tool actually got something wrong. Each carries the reason in its docstring rather than only an assertion. Five are described in section 7.
- **The configuration is part of the software.** Since the node list grew beyond the original nine, thirteen tests treat nodes.yaml as something that can be broken: a missing field, a duplicate id, a malformed URL, two nodes pointing at the same eosc.eu entry, or a node whose official name nothing in the scoped list covers all fail the suite rather than surfacing as a strange verdict later.

A guard that cannot fail is worse than no guard. Both dual-depth guards in test_report.py were confirmed by deliberate mutation — rendering the deep results into the shallow table, and forcing a stray heading back — and each failed exactly one test. A test written against the wrong part of the output passes for the wrong reason: one of these initially asserted against the tally line rather than the table row, and would have stayed green through the bug it was written to catch.

---

3. The ten checklist points

Checklist v3.2, dated 28 September 2026, which replaced v3.1 of 24 September 2026, itself the successor of v3.0 of 15 September 2026 (the header of checklist/v3.2.yaml lists the differences point by point). The tool scores ten columns, because point 1 covers two things, the page and every Node Exchange resource it links to, and is split into 1 and 1R.

Point	Requirement	Can a tool decide it?	Implemented by
1	Landing page publicly accessible, or reachable via EOSC AAI login	Yes, by inspection	check_1
1R	Resources pointed to by the page are also public or behind EOSC AAI	No — human judgement	check_1R
2	Scope, intended users and responsible organization are stated	No — human judgement	check_2
3	EOSC logo and official Tripartite-approved node name are visible	Partly — the name against a list, never the "clearly visible" judgement	check_3
4	Links to the node's own dedicated page on eosc.eu	Yes, by inspection	check_4
5a	Purpose description in English for Node Exchange research resources, on the NLP and in the Catalogue	No — human judgement	check_5a
5b	Acceptable Use Policy (AUP) linked from the NLP and in the Catalogue	Partly — the NLP half; no link at all is FAIL	check_5b

Point	Requirement	Can a tool decide it?	Implemented by
5c	User Access Policy (UAP) linked from the NLP and in the Catalogue	Partly — the NLP half; no link at all is FAIL	check_5c
6	Means of contacting the node helpdesk	Partly	check_6
7	The page is in English	Yes, by inspection	check_7

The last column is not decoration. Each point declares its implementing function in the checklist YAML as implemented_by, and a test asserts the mapping is complete in both directions, so a rule cannot exist without being explained and a point cannot be described without being applied. Run basic-check points to print this mapping from the file itself.

Item 5 under v3.2. The tool never reads the EOSC Catalogue, so for 5a–5c it checks the NLP half only, and every 5a–5c result says so. For 5b and 5c: a policy link that works is PASS, with a reviewer action to confirm the Catalogue half; a link to the other policy (one document may be both) or to a licence (allowed for datasets, archives and software) is MANUAL_REVIEW; a page whose links did not arrive is MANUAL_REVIEW; anything else is FAIL, including a policy named in the text without a link. Under v3.0 and v3.1 the same absence was MANUAL_REVIEW, because the policy could have been in the Catalogue alone. The decision procedure is in section 5 of the analysis workflow.

> **On the honesty of the output.** Three of the ten points cannot be settled by a script at all and four only partly. Those are reported as MANUAL_REVIEW with the evidence attached rather than guessed at. Roughly 60% of cells land in review by design. A confident wrong verdict about a named organisation costs more to retract than an honest "a human must look".

---

4. Link-following depth

Two hops maximum, and the default is one. --depth is validated by the command line as an integer in the range 0 to 2, so an out-of-range value is refused rather than silently clamped.

A link is followed only when its target could settle a specific checklist point: an Acceptable Use Policy (5b), a User Access Policy (5c), a contact page (6), or an about page (2). Since checklist v3.2 accepts the policies on "intermediate web pages linked by the NLP", two more purposes follow a policies, legal or terms page (5p) and a services, catalogue or resources page (5s), last, so they never displace a link that settles a point; privacy and cookie policies are not followed. They are looked for on the landing page only: the second hop follows policy links, never another services page. Everything else is skipped, and every skip is recorded in the evidence so that a later "not found" is accountable rather than merely asserted.

--depth	What is fetched	Requests observed, the 9 published nodes, 21 Sep 2026
0	The landing page only	9
1 (default)	Plus links from it that could settle a point	31 (9 + 22)
2	Plus one further hop — a policy *index* that links on to the actual policy	45 (9 + 22 + 14)

Limit	Value	Purpose
Maximum depth	2	Enforced by the CLI, not by convention
Pages per node at depth 1	8	Configurable via --max-children
Pages per purpose at depth 1	2	MAX_PER_PURPOSE — two candidate AUP links is enough to decide
Pages per purpose at depth 2	1	MAX_PER_PURPOSE_D2
Run-wide second-hop budget	60	Configurable via --fetch-budget. A whole-run ceiling, not per node
Time per node	300 s	Configurable via --node-timeout (0 = none). Landing page and linked pages together; on expiry every point is ERROR and the run continues
Delay between children	1.2 s	CHILD_DELAY_S
Delay between grandchildren	1.5 s	GRANDCHILD_DELAY_S
Delay between nodes	2.0 s	Configurable via --delay
robots.txt	Honoured	Checked per host, since children may sit on other hosts
Excluded targets	—	Third-party hosts, PDFs and other binaries, the landing page itself
Screenshots of children	None	Keeps the extra cost to one request each

The payoff is not breadth but verification: a link labelled "Acceptable Use Policy" that returns 404 now **fails** point 5b, where previously it passed on the strength of its own label.

Is the second hop worth it?

On this federation, so far, no. **A depth-2 run reports both depths**: two summary tables, two explanatory sections, a list of every cell whose verdict differs, and a table of which second-hop pages were fetched. Both tables come from the *same capture* — the shallow view is the deep evidence with the second-hop pages set aside, not a second run — so any difference is the extra hop and not the page changing in between.

Two depth-2 runs on 21 September, of 18 and 14 second-hop requests, each changed **zero** verdicts. That is a finding rather than a disappointment: the points still marked review turn on a judgement ("clearly state") or quantify over things no crawl enumerates ("all research resources offered by the Node"), and no amount of fetching settles either kind. **Depth 2, 28 September 2026 (run web-13, checklist v3.2):** 19 second-hop pages on top of the 31 depth-1 links, and again **zero** verdicts changed: 49 PASS, 14 FAIL and 67 review at both depths. The second hop reached governance, secretariat and news pages, which is also where it met a personal name that depth 1 had never collected (section 10). It should not be assumed to hold for another federation or a later date.

---

5. Configuration and customisation

The node list — a YAML file

The landing pages you want checked live in a configuration file, and that is the intended way to change them. nodes.yaml sits at the repository root and currently lists **fifteen** nodes: bbmri-eric, cern, eosc-cz, eosc-dto, data-terra, eosc-fi, panosc, eudat, egi, geant, eosc-pl, eosc-it, eosc-sk, and, since 9 October 2026, ebrains-ri and life-sciences-connect.

```
nodes:
  - id: bbmri-eric
    name: BBMRI-ERIC
    url: https://dev3.bbmri-eric.eu/eosc-node-bbmri-eric/
    eosc_page: https://eosc.eu/building-the-eosc-federation/eosc-node-bbmri-eric/
```

- id — the short handle used by --only and by the show command, and the filename its evidence is stored under.
- url — must be the URL registered in the EOSC EU Node Contributors Dashboard (section 1.2, field 6, "Website address"), because that registered URL is what the checklist defines as the Node Landing Page.
- eosc_page — the node's dedicated entry on eosc.eu, which point 4 requires the landing page to link to. Supplying it means a point 4 failure names the exact URL that is missing, so the fix is a one-line edit rather than an investigation.

You can also point at an entirely different file without editing the default: --nodes /path/to/my-nodes.yaml, available on collect, assess and run. That is the clean way to keep a separate candidate-node list alongside the production one.

Changing a URL. BBMRI-ERIC's url changed on 25 September 2026, from https://www.bbmri-eric.eu/eosc-node-bbmri-eric/ to https://dev3.bbmri-eric.eu/eosc-node-bbmri-eric/, and was set back to the www. address on 26 September; it was changed and set back again on 1 October, and on 5 October 2026 the dev3. address was made the default (commit 42aacbe). The entry carries a comment recording this. assess takes each node's URL from nodes.yaml and its verdicts from the evidence on disk. So while the dev3. address was configured, a bare assess headed BBMRI-ERIC's row with it, above verdicts taken from the old page. It says so: it compares the configured URL with the requested_url in the evidence, prints a warning, puts an **Evidence from a different URL** banner in results.md and index.html, and records the pair under url_mismatch in results.json. To rebuild the published run, assess it with the node list it was collected with; since 26 September the committed nodes.yaml differs from it only in Italy's URL, which the skipped Italy row never uses. The command below names that list explicitly and stays right if nodes.yaml changes again. It gives no warning, and reproduces the committed results/ exactly, apart from the generation time:

```
git show 53081f6:nodes.yaml > /tmp/nodes-2026-09-24.yaml
uv run basic-check assess --run live-2026-09-24-no-italy --skip Italy --nodes /tmp/nodes-2026-09-24.yaml
```

That command applies to the 24 September run, which is now in the git history at 800d632. The published run web-13 was collected from the committed nodes.yaml, so uv run basic-check assess --run web-13 rebuilds it exactly, both depths included, apart from the generation time, with no URL warning (verified 29 September 2026). Earlier runs are in the git history: restore their results/evidence into a scratch directory and assess with --results. Runs collected before 29 September were published under v3.1, so add -c checklist/v3.1.yaml to rebuild them as published, together with the options below. Run web-10 was collected before CERN's URL changed to https://eosc.cern/, so it needs its own node list: git show 8126aee:nodes.yaml > /tmp/nodes-web-10.yaml, then add --nodes /tmp/nodes-web-10.yaml. Runs published before 28 September 2026 were

also scored with the earlier name list, so pass it too: git show e7da5a8:checklist/approved-names.txt > /tmp/names-before-2026-09-28.txt, then add --approved-names /tmp/names-before-2026-09-28.txt.

The new address also behaves differently. On a trial run on 25 September its robots.txt read User-agent: * / Disallow: /. The tool honours that, so no page was requested and all ten points were ERROR. Section 6 of the run guide explains what ERROR does and does not mean. The step-by-step procedure for a URL change, through to new published results, is example 2 in section 11.

EOSC Node Italy's url changed on 26 September 2026, from https://eosc.it/ to https://eoscnode-it.d4science.org/, and on 1 October 2026 back to https://eosc.it/, which now resolves; the entry carries a comment saying so. BBMRI-ERIC's was changed to the dev3. address again on 1 October and set back the same day, for the same robots.txt reason. Data Terra's changed on 1 October 2026, from https://www.data-terra.org/eosc/ to https://www.earth-data.eu/. The published run skipped Italy, because eosc.it had no address record on 24 September, so it holds no evidence for Italy and no published row depends on the old address.

Adding a node

Adding a node touches **three** files, and the suite fails if you stop after the first.

File	What to add	Enforced by
nodes.yaml	The id, name, url and eosc_page block	test_nodes.py — required fields, unique id, well-formed URL
checklist/approved-names.txt	The node's official Tripartite-approved name	Point 3 cannot match a name that is not in the list
checklist/approved-names-scoped.txt	The same name, bound to the node id	test_nodes.py — every configured node's name must be covered

Then collect evidence for it before the next full assess, because assess exits 2 when a configured node has no evidence — correctly, since an unassessed node must not pass silently:

```
uv run basic-check collect --only <new-id> --depth 1 --delay 2.0 --results /tmp/scratch
```

Use a scratch --results directory while you are trying a node out. results/ holds the reviewed, published run, and a full assess rewrites it. Example 1 in section 11 goes from these edits to a published run that includes the new node.

The approved-names list

Since the list became a committed default, point 3 has a name list **unless you turn it off**. Three flags govern it:

Flag	Effect
(none)	Uses the committed checklist/approved-names.txt. Its SHA-256 is recorded in every report
--approved-names <file>	Replaces the default with your own list
--no-approved-names	Uses no list at all, not even the default — the pre-default behaviour
--strict-separators	Matches the separator glyphs literally. By default an approved name written with a vertical bar also matches a page that writes it with a dash or a plain space

The separator tolerance is the reason test_names.py is the largest file in the suite: a matcher loose enough to accept the punctuation variants real pages use is also loose enough to match the wrong thing, so the boundary is pinned from both sides.

> **A matched name is not a verified name.** The unscoped list does not say which name belongs to which node, so a match establishes only that *some* approved name appears on the page. The evidence line says so explicitly. approved-names-scoped.txt binds names to node ids and removes that ambiguity; the report records which of the two was used.

Ad hoc URLs — straight from the command line

You can check a page without touching configuration at all. --url is repeatable:

```
uv run basic-check run --url https://example.org/our-eosc-node/
uv run basic-check run --url https://a.example/ --url https://b.example/
uv run basic-check show example-org-our-eosc-node --one-off
```

Point 4 needs to know which eosc.eu page the node ought to link to. Without it the point is still decided — a link to the federation index still fails — but the message cannot name the missing URL. Supply it for a single URL with --eosc-page:

```
uv run basic-check run --url https://panosc.eu/panosc-eosc-node \
  --eosc-page https://eosc.eu/building-the-eosc-federation/eosc-node-panosc/
```

> **Two safeguards worth knowing about.** A --url run writes to results/one-off/ rather than results/, because assess() rewrites results.md, index.html and results.json wholesale — a shared directory would replace the published report with a one-row table. And ad hoc reports are titled "Ad hoc page check (not a federation run)" with a marker at the top, since the layout is otherwise identical to the real report and a stray single-node file that looked official would be a liability while a production decision is pending.

--url and --only are rejected together rather than one being quietly ignored: --only filters ids in the nodes file, and an ad hoc URL has no id there. --skip is rejected with --url for the same reason. Node ids are derived from host *and* path, so two pages on one host cannot overwrite each other's evidence.

> ✅ **--only no longer shrinks the report — the defect described in the previous edition is fixed.** It previously scoped the *report* as well as the fetching, so assess --only data-terra left results/results.json containing a single node while index.html still looked like a federation report. --only now narrows **which sites are contacted**, not what the report covers: a subset run refetches only the nodes you named, then rebuilds every row from the evidence already on disk, and records the selection so a reader can see the report is of mixed freshness. Four tests in test_cli.py pin this, including one that runs a real subset assess against the committed evidence and asserts the published directory still has every row.

--skip leaves nodes out, and the report says so. collect, assess and run accept --skip, followed by node ids or names. Names are matched case-insensitively, including the short form, so Italy names "EOSC Node Italy". Values can be comma-separated or the option repeated. Skipped nodes are not fetched, not assessed and not reported. They do not count as missing evidence, so assess does not exit 2 for them. The report is shorter as a result, so it states the omission: a "Skipped by request" banner in results.md and index.html, and a skipped list in results.json. Sixteen cases in test_cli.py pin this behaviour:

- both spellings (comma-separated and repeated) and all three forms of a name;
- that no request is sent to a skipped node by collect or run;
- that a skipped node without evidence does not trigger exit 2;


- that both reports carry the banner, and a run without --skip carries none;
- that a value matching no node is rejected, as are a value matching several nodes, skipping every node, and --skip with --url.

Before the commit, nine deliberate bugs were introduced into the new code one at a time, and the suite caught all nine.

--node checks one configured node at an alternative URL. --node bbmri-eric --url https://alt.example.org/... runs every point against that page while keeping the node's id, name and eosc_page, so its scoped approved name and its own eosc.eu link still apply; nodes.yaml is not changed. The run writes to results/one-off/ (--results results/ is refused, since the evidence file is named after the node), the reports are titled "Alternative URL check (not a federation run)" with a banner naming both addresses, and results.json records the pair under alternative_url. Eighteen cases in test_cli.py cover it, offline:

- the record keeps id, name and eosc_page, fetches the new URL and records configured_url; id or name in any case; --eosc-page replaces the configured page;
- the output folder: results/one-off/ by default, another --results folder honoured, results/ refused;
- rejected: no --url, two --url, a non-http URL, --only, --skip, an unknown node and an ambiguous one;
- collect and run send nothing to the configured URL or to any other node;
- results.json, results.md, index.html and show all say the URL is not the configured one, and the same evidence assessed without --node raises the URL-mismatch warning.

The phases in time, their options, and what to re-run



The phases run strictly in this order, and each one reads only what the one before it wrote to disk. **Collect** is the only phase that contacts the nodes. It reads nodes.yaml and writes evidence/<node>.json and a screenshot per node. **Assess** reads that evidence, the checklist and the approved-name list, and sends no request. **Report** is the last step of assess: it writes results.json, results.md, index.html, results.csv and checklist-v3.2.html. run performs the three in one invocation. With --update-results-for-node, run does the same for one node only, and results.json supplies every other row unchanged. points and show only read, so they never need re-running.

Options of each phase. ✓ means the command accepts the option. Every command also takes --help.

Option	collect	assess	run	What it does
--nodes, -n <file>	✓	✓	✓	Node list to use instead of nodes.yaml
--results <dir>	✓	✓	✓	Folder to write to or read from instead of results/
--only <ids>	✓	✓	✓	Fetch only these node ids
--skip <ids or names>	✓	✓	✓	Leave these nodes out entirely; the report says so
--url <url>	✓	✓	✓	Check a page not in nodes.yaml (writes to results/one-off/)
--eosc-page <url>	✓	✓	✓	With one --url: that node's own eosc.eu page, for point 4
--node <id or name>	✓	✓	✓	One configured node at the alternative page given with --url
--delay <s>	✓	—	✓	Seconds between hosts (default 2.0)
--depth 0/1/2	✓	—	✓	How far to follow links (default 1)
--max-children <n>	✓	—	—	Linked pages followed per node at depth 1 (default 8; run always uses 8)
--fetch-budget <n>	✓	—	✓	Depth 2 only: ceiling on second-hop requests (default 60)
--node-timeout <s>	✓	—	✓	Most seconds per node before it is abandoned as ERROR (default 300; 0 = no limit)
--checklist, -c <file>	—	✓	✓	Checklist revision to apply (default

Option	collect	assess	run	What it does
				checklist/v3.2.yaml)
--approved-names <file>	—	✓	✓	Approved-name list for point 3 (default checklist/approved-names.txt)
--no-approved-names	—	✓	✓	Use no name list at all
--strict-separators	—	✓	✓	Match separators in approved names literally
--run <label>	—	✓	✓	Label recorded in every report (default: UTC time)
--update-results-for-node <node>	—	✓	✓	Update only that node's row in the stored results; assess re-judges its saved evidence, run fetches it again
--accept-error	—	—	✓	With --update-results-for-node: merge the row even if the fetch failed

What to launch again after a change. Which phase has to be repeated depends on which input changed. A change to nodes.yaml needs a new collection for the nodes concerned. A change to the checklist or to the name list needs only a new assessment, which is offline. --update-results-for-node refuses when the checklist or the approved-name list differs from the stored results', because a row judged by other rules would not be comparable with the others. In those cases, every row is assessed again from its stored evidence.

You change	Launch again	Sites contacted	The other nodes' rows
Add a node: an entry in nodes.yaml and its approved name in checklist/approved-names.txt (and -scoped.txt)	collect --only <new id>, then assess without --only	the new node only	Re-judged, offline, from their stored evidence, because the approved-name list used for point 3 changed
Add a node whose approved name is already in checklist/approved-names.txt	run --update-results-for-node <new id>	the new node only	Kept unchanged; the new row is inserted in nodes.yaml order

You change	Launch again	Sites contacted	The other nodes' rows
Change a node's landing page URL (basic-check --update-nlp <id> <URL>, or by hand)	run --update-results-for-node <id>	that node only	Kept unchanged
Go back to the node list as downloaded (basic-check --restore-default-config)	For each node it lists as URL restored: run --update-results-for-node <id>. If it lists nodes added back or removed: assess	the restored nodes only	Kept unchanged; re-judged offline if nodes were added back or removed
Change the reference checklist (a new checklist/vX.Y.yaml, made the default in DEFAULT_CHECKLIST or passed with -c)	assess	none	All re-judged, offline, from the stored evidence

assess alone is not enough after a URL change. The node's evidence still comes from the old page, so assess warns and both reports carry an **Evidence from a different URL** banner. After a checklist change, a new collect (or a full run) is needed only if the new revision asks for something the collector does not record (section 3 of the analysis workflow), or if you want a fresh capture date. For the full procedure of each case, with every file and command, see the worked examples in section 11. Each command writes to results/, the published run, by default. Add --results /tmp/copy to work on a copy first. The published run covers sixteen of the eighteen configured nodes: EOSC Node Latvia and Scholarly Commons, added on 10 November 2026, have no evidence in it yet, so assess on results/ exits 2 until a run collects them. To rebuild the published run as it is, pass the node and name lists it was made with (--nodes and --approved-names, from commit a556394), not --skip. With an explicit --results, --only also narrows the report to those nodes, which is why the table runs assess without it.

The five commands

Command	What it does
collect	Fetch each landing page with Chromium and save the evidence. Needs the network and a browser
assess	Apply the checklist to already-collected evidence and write the reports. Offline, repeatable
run	collect, then assess, in one invocation
points	Print the checklist, its provenance, and which function decides each point
show	Print one node's results in the terminal

Only collect and run need a browser or network access. points, assess, show and the whole test suite need neither.

Command line options

Option	Available on	Default	Effect
--nodes / -n	collect assess run	nodes.yaml	Which node list to read

Option	Available on	Default	Effect
--url	collect assess run	—	Check this URL directly, without configuration. Repeatable. With --node, that node's alternative page
--node	collect assess run	—	One configured node (id or name) at the alternative landing page given with --url; keeps its id, name and eosc_page
--eosc-page	collect assess run	—	With a single --url: the node's own eosc.eu page, for point 4. With --node, replaces the configured one
--results	collect assess run show	results/	Output directory (results/one-off/ for --url and --node runs; --node refuses results/)
--only	collect assess run	all	Comma-separated node ids. Narrows which sites are contacted, not what the report covers
--skip	collect assess run	none	Node ids or names, comma-separated or repeated. Left out of fetch and report; the report says so
--depth	collect run	1	0 = landing page only; 1 = one hop; 2 = two hops, reporting both depths. Range-checked 0–2
--fetch-budget	collect run	60	Depth 2 only: run-wide ceiling on second-hop requests
--node-timeout	collect run	300	Seconds per node, landing page and linked pages together; on expiry the node is ERROR and the run continues
--max-children	collect	8	Cap on followed pages per node
--delay	collect run	2.0	Seconds between hosts

Option	Available on	Default	Effect
--checklist / -c	assess run points	checklist/v3.2.yaml	Which checklist version to apply
--approved-names	assess run	committed default	Text file of Tripartite-approved names, one per line, replacing the committed default
--no-approved-names	assess run	false	Use no name list at all, not even the committed default
--strict-separators	assess run	false	Match the separator glyphs in an approved name literally
--run	assess run	timestamp	Label for the run, recorded in every report
--update-results-for-node	assess run	—	One node (id or name): re-check it and replace only its row in the stored results.json, keeping every other row; run fetches that page again, assess re-judges saved evidence offline
--accept-error	run	false	With --update-results-for-node: merge the row even if the page could not be fetched
--one-off	show	false	Read results/one-off/ instead of results/
--list-nodes, --list-nodes-ids	basic-check alone	—	Node ids in nodes.yaml, one per line; two names for one option
--list-nlps	basic-check alone	—	Each node id with its Node Landing Page URL
--list-approved-names	basic-check alone	—	Each node id with its approved name, from approved-names-scoped.txt
--print-config	basic-check alone	—	Table of id, Node Landing Page URL and approved name, one row per node, with the source files
--show-node	basic-check alone	—	One node's row of that table; id or name, in any

Option	Available on	Default	Effect
			case
--update-nlp	basic-check alone	—	Takes a node id and a new https URL; rewrites that node's url: line in nodes.yaml, with a dated comment giving the old URL
--restore-default-config	basic-check alone	—	Puts nodes.yaml back as downloaded from GitHub (a copy shipped in the package), keeping the replaced file as nodes.yaml.<date-time>.bak

Note that --max-children is on collect but not on run, so a combined run uses the default cap of 8. Use the two commands separately if you need to change it.

Listing the configuration. basic-check --list-nodes, --list-nlps, --list-approved-names and --print-config print what is configured and exit, without contacting any node: the ids, each id with its landing page URL, each id with its approved name, or all three in one table. Approved names come from checklist/approved-names-scoped.txt, the copy that ties each name to a node; the table notes that assess uses the unscoped approved-names.txt by default. Output is plain columns, never wrapped. Twelve cases in test_cli.py check each listing against nodes.yaml and the scoped file row by row, that flags combine, that a long URL stays on one line at 40 columns, that a node with no name shows (none), that an unreadable node list is a clear error, that the flags are refused with a command, that a bare basic-check still asks for one, and that no listing fetches anything.

--list-nodes-ids is a second name for --list-nodes. --show-node NODE prints one node's --print-config row under the same header, taking an id or a name in any case, as --skip does. Ten more cases cover them: that the two listing names print identical output; that --show-node prints exactly each configured node's row, and nothing else; five spellings of one node (eosc-it, EOSC-IT, Italy, EOSC Node Italy, italy); that an unknown value is an error listing the ids and an ambiguous one an error; and that --show-node is refused together with a command.

--update-nlp NODE_ID URL and --restore-default-config are the two options that write, and both write only nodes.yaml. --update-nlp changes a node's url: line. Its eleven cases each work on a copy of nodes.yaml in a temporary directory, so the suite never edits the real file. They check that only that node's url changes, with every other field and comment kept and one dated comment added; that --show-node then shows the new URL; that giving the current URL changes nothing; that a name instead of an id, a non-https, relative or space-containing URL, and another node's URL are all refused with the file unchanged; that both values are required and a command is refused; and that a url: value split over two lines is refused rather than edited.

--restore-default-config has twelve cases in test_cli.py, also on a copy of nodes.yaml in a temporary directory: that an unchanged file is left alone with no backup; that it undoes --update-nlp, keeps the edited file as the .bak and names the restored URL; that it reports nodes added back and removed; that a comment-only difference is restored and said to be one; that a missing file, a malformed file and a file that is not a node list are all restored; that a second restore changes nothing; that --list-nlps after it shows the default URLs; that a command, or --update-nlp in the same call, is refused with the file untouched; and that it contacts no site.

test_nodes.py checks that the shipped default, src/basic_check/defaults/nodes.yaml, is byte-identical to the nodes.yaml committed at git HEAD, so a commit that changes one without the other fails CI.

--update-results-for-node NODE is covered by the twenty-two cases of tests/test_update_row.py, all on a copy of the committed results/ in a temporary directory, with the collector replaced by a stand-in, so no site is contacted and results/ is never written. They check that only the named row changes and every other row stays identical, that the reports gain one **Updated rows** line and nothing else, that run collects exactly one node into a scratch directory and replaces its evidence and screenshot, that a failed fetch leaves the directory byte-identical unless --accept-error is given, that a node the stored run skipped is inserted in nodes.yaml order, that stale evidence from another URL is still flagged, and the refusals: no stored results, a different checklist, three different approved-name settings, an unknown node, an alternative-URL trial, and five conflicting options on both commands.

Exit codes

Code	Meaning
0	The run completed. This does NOT mean every node passed — FAIL verdicts still exit 0
2	Bad usage, or a configured node produced no evidence at all

> **A non-zero exit means the tooling failed, not that a node did.** The only non-zero exit from a completed assessment is missing evidence. A node that violates six checklist points still exits 0, because a compliance finding is the output, not an error. So in CI a red cross means something broke; it never means "a node is non-compliant". Read the matrix, not the exit status.

The reference checklist — the single configuration point

checklist/v3.2.yaml is data, not code, and it is the one place the reference checklist is configured. The tool never downloads the checklist document, so there is no URL to change when it is revised: the document is committed next to the YAML. One line in src/basic_check/cli.py selects the default revision, and --checklist / -c on assess, run and points overrides it for one run:

```
DEFAULT_CHECKLIST = ROOT / "checklist" / "v3.2.yaml"
```

Nothing else in the codebase names the file. The help texts, the name of the generated checklist-v3.2.html and the tests in test_checklist.py all derive from that line.

```
checklist/
  v3.2.yaml                          # the checklist as data (default)
  20260928_Node_Landing_Page_..._v3.2.pdf    # the document it came from
  v3.1.yaml, v3.0.yaml                 # earlier revisions, kept to rebuild older runs
  20260910_Node_Landing_Page_..._v3.1.pdf    # and their documents
  README.md                            # the revision procedure
```

Each point carries its verbatim requirement text, a decidable flag, a decidable_note explaining how the tool treats it and why, and implemented_by naming the function that decides it. The file header records provenance:

```
checklist_version: "3.2"
checklist_date: "2026-09-28"
source_document: 20260928_Node_Landing_Page_Verification_Checklist_v3.2.docx
source_file: 20260928_Node_Landing_Page_Verification_Checklist_v3.2.pdf
```

```
source_sha256: 318c6b71186641273961d3f70f87a92b78f81ccc072f6f6392bf17830d7ad83c
item5_on_nlp: true
```

Three guarantees are enforced by tests rather than by good intentions.

- **The source document is committed and pinned.** A transcription you cannot audit against its source is a rumour. If the document is ever replaced under the same filename, the hash test fails and forces a deliberate decision rather than a silent one.
- **Every point maps to one rule, and every rule to one point.** A check no point claims is either dead code or a rule the reports never explain. A point naming a function that does not exist fails immediately.
- **A revision must be a new file.** The declared `checklist_version` must match the filename, so v3.3 cannot be edited into `v3.2.yaml`. Reports name the file they were generated from, so editing in place would retroactively invalidate every past run.

  What the hash does and does not prove. The committed file is a PDF rendering of the `.docx` named in `source_document`, not that `.docx` itself. It pins the exact bytes the transcription was made from — which is what catches a document being silently swapped — but it is not a signature over the authoritative original. Replacing the PDF with the real `.docx` is a two-line change in the YAML plus a re-hash.

What the YAML governs is the **reporting surface**: titles, the matrix columns and their order, the quoted wording, the decidable/review framing. What it does *not* govern is the logic — `checks.run_all()` calls ten hardcoded functions and never reads the file. There is one deliberate exception: `item5_on_nlp`, which the CLI reads from the file and passes to `run_all()`, selects the item 5 rule. It is declared in `v3.2.yaml` only, so the older files keep the rule they were written for, and it is the pattern to follow whenever a revision changes a rule rather than a wording. The YAML declares the checklist; the Python interprets it. That is precisely why `implemented_by` and its tests exist.

Adding a newer checklist revision

```
# 1 - commit the new source document into checklist/
# 2 - copy the YAML to the new version, never edit in place
cp checklist/v3.2.yaml checklist/v3.3.yaml
shasum -a 256 checklist/<new-source-document>   # macOS spelling

# 3 - update checklist_version, checklist_date, source_document,
#     source_file and source_sha256 in checklist/v3.3.yaml
# 4 - re-read every point against the new document and fix any
#     check_* function whose requirement changed       <-- manual step
#     (a changed rule gets a switch, like item5_on_nlp, so older
#     revisions keep theirs)
# 5 - try it offline against the saved evidence, before switching
uv run basic-check assess -c checklist/v3.3.yaml --results /tmp/v33   # after copying results/evidence there
# 6 - make it the default: in src/basic_check/cli.py
#     DEFAULT_CHECKLIST = ROOT / "checklist" / "v3.3.yaml"

uv run pytest -q                          # consistency
uv run basic-check run --results /tmp/new-run    # then review and publish
```

Example 3 in section 11 gives every command, including publication and the removal of the old `results/checklist-v3.2.html`. Step 4 is the one the tooling cannot do for you. The tests confirm that the

checklist and the code agree about *which* rules exist; they cannot confirm that a rule still means what the revised document says. checklist/README.md repeats this procedure inside the repository.

Personal data in the evidence and the reports

Evidence files and all four report formats are written with personal data masked by src/basic_check/privacy.py. A personal email address keeps only its domain (XXXXX@example.org), and a phone number keeps only its international prefix (+CC XXXXXX, where CC is the country code). A labelled national number of the form tel. (NN) NNN NNNN becomes tel. XXXXXX, and a number whose spaces are written %20 inside a tel: link is masked too. A name is masked when it appears next to a masked address. Role mailboxes such as support@, info@ and it@helpdesk.... are kept, because point 6 depends on them. Nothing about this is configurable: a flag to turn it off would be a way to publish personal data by mistake. The rules and their limits are in section 6 of the run guide ("Personal data is masked"), and tests/test_privacy.py fixes both sides: what must be masked, and what must not be. One test reads the committed results/evidence/ itself and fails if any file contains a personal address or a phone number, so unmasked evidence cannot be committed unnoticed. It was confirmed to bite: restoring one unmasked evidence file makes it fail.

Constants that are not yet flags

Several limits are module constants rather than command line options: in fetch.py, MAX_PER_PURPOSE = 2, MAX_PER_PURPOSE_D2 = 1, CHILD_DELAY_S = 1.2, GRANDCHILD_DELAY_S = 1.5 and the navigation timeouts; in checks.py, the render gate's thresholds DOM_ELEMENT_FLOOR = 10 and EMPTY_DOCUMENT_CHARS = 500. They can be promoted to CLI options if you need to vary them per run.

Two commands, on purpose

collect and assess are deliberately separate. Assessment re-runs offline against saved evidence in results/evidence/, so changing a rule never means re-requesting the nodes' pages. assess also exits non-zero when a configured node has no evidence, so a short table cannot quietly look complete.

---

6. Continuous integration, and running it from the GitHub web interface

There are two workflows, and the distinction between them matters.

Workflow	Trigger	What it does
tests.yml	Every push and pull request, plus manual dispatch	ruff, then pytest, then publishes the JUnit report to GitHub Checks. No browser, no network
compliance.yml	Manual dispatch only — deliberately no schedule	Runs the tests, installs Chromium, then checks the real landing pages and publishes a counts summary plus the full reports as an artifact

The test workflow runs four steps: uv sync --locked, ruff check src tests, pytest -q --junitxml=results/junit.xml, then publication of the JUnit XML to GitHub Checks. Chromium is not installed and does not need to be, because no test opens a browser.

--locked matters more than it looks. It installs exactly what uv.lock pins and **fails** if the lockfile has drifted from pyproject.toml. Plain uv sync would silently re-resolve, so a dependency change could land with a green tick while CI tested a different set of versions than the one committed. The compliance workflow uses --locked for the same reason with sharper stakes: a silently re-resolved Playwright, selectolax or lingua can change what a page looks like to the tool, and the output of that workflow is a set of verdicts about named organisations.

> **A habit worth keeping.** A green tick means "nothing objected", not "everything was verified". A suite that collects zero tests also passes. The test count in the CI log is the thing to read — it currently says "339 passed".

Running the compliance scan from the browser, with no Terminal at all

This is the whole point of the second workflow: the node scan can be launched from the GitHub web interface without a command line anywhere.

- Open the **Actions** tab of the repository.
- Click **compliance run** in the left-hand sidebar.
- Click the **Run workflow** dropdown on the right of the run list.
- Leave the three fields at their defaults for every configured node at depth 1, or fill them in.
- Click the green **Run workflow** button, then refresh.
- Open the run. A **counts summary** is printed on the run page itself, under the job list. The per-node matrix and evidence are in the compliance-results artifact attached to the run.

Input	Default	Meaning
only	empty = every configured node	Comma-separated node ids, e.g. egi,eudat
depth	1	1 follows one hop of checklist-relevant links; 0 checks the landing page only; 2 adds a second hop
delay	2.0	Seconds between nodes

> **The web form now reaches depth 2.** The depth input is a choice offering 1, 0 and 2, so the dual-depth report is available from the Actions tab as well as the command line. The previous edition recorded this as a limitation.
>
> **Why the run page shows counts and not the matrix.** This is a deliberate change since the previous edition. The per-node verdicts are already published in the committed results/results.md, so repeating them leaks nothing new — but a workflow run is *unreviewed output*, and a world-readable page of FAIL verdicts against named organisations, produced automatically and carrying the repository's name, reads as a finding rather than as a draft. The summary therefore carries counts, an explicit "unreviewed automated output" warning, and a pointer to the artifact. It also refuses to summarise results/results.json unless the check step actually succeeded — otherwise a failed run would publish the last *reviewed* run's counts under this run's number, which is the most misleading thing the workflow could do.

The equivalent from a Mac Terminal, if you have the GitHub CLI installed, is:

```
gh workflow run compliance.yml --ref main
gh workflow run compliance.yml --ref main -f only=egi,eudat -f depth=0
```

```
gh run list --workflow compliance.yml --limit 3
gh run view <run-id> --log
```

> **Who can launch it, and who can read the results.** Triggering a workflow requires write access to the repository, so nobody browsing a public repo can start a run — the Run workflow button is not shown to them. The compliance workflow is also workflow_dispatch only, with no schedule and no pull_request trigger, so no fork or pull request can cause it to send requests to the nodes' websites. Note separately that on a public repository the committed reports under results/ are readable by anyone, and the compliance workflow writes the results table into the run summary, which is public too. Both are publication decisions rather than technical ones.

Two design choices in that workflow are worth knowing. It runs pytest before installing Chromium, so a broken rule set cannot send thirty-odd requests to real sites to produce wrong verdicts. And a concurrency group prevents two runs overlapping onto the nodes. Expect three to four minutes, most of it the Chromium download rather than the requests.

One caveat about CI results. GitHub runners use datacenter IP addresses, which are more likely to meet a bot wall than a home or office connection. A 403 from a runner is evidence about the runner, not about the node.

> **Correcting the previous edition.** It stated that the CI run of 18 September "reproduced the local figures exactly, 29 PASS / 6 FAIL / 55 MANUAL_REVIEW". Checking the actual run logs while preparing this edition, that does not hold. There were two compliance runs that day and they disagreed with each other and with the committed results:

18 September run	Source	Tally
13:31 UTC	CI, run 35350733094	29 / 6 / 55
committed results.json	local, commit 062aca3	26 / 6 / 58
14:39 UTC	CI, run 35357569881	24 / 5 / 61

> So 29 / 6 / 55 was a real CI figure, but it was not a reproduction of the committed local run, and an hour later the same workflow produced a third answer — because GÉANT already returned **HTTP 403 to the runner on 18 September**, logged as [8/9] geant HTTP 403. The claim of exact cross-network agreement was wrong.

Treat any single tally as a reading, not a constant. Three runs in one afternoon gave three different numbers without a line of rule code changing between them. What is stable is the *finding* (see section 10), not the count. Any figure quoted in a presentation should name the run it came from.

---

7. Tests that exist because of real defects

These are worth reading as documentation of what the tool got wrong, and each carries its reasoning in the test itself rather than only an assertion. Five are described below, followed by the defects fixed since the previous edition and one found while preparing this one.

test_a_well_rendered_page_still_fails_when_the_link_is_genuinely_absent Reporting "no contact route of any kind was found" from a page that had not rendered. That describes the tool, not the node. Absence-based failures are now gated on the page having actually rendered — and this test stops the gate becoming a blanket excuse.

test_point4_rejects_domains_that_merely_end_in_eosc_eu A domain check written as endswith("eosc.eu") also matched myeosc.eu and not-eosc.eu. Found by probing the function directly, not by the tests.

test_point1_does_not_fail_on_403_with_no_login_offered Originally asserted FAIL. Inverted after GÉANT served HTTP 200 and then 403 once link following made a few more requests to the same host. Nothing about the site had changed; the tool had become more annoying. Turning that into "not publicly accessible" would be the checker blaming a node for its own request volume. This has since paid for itself — see section 10.

test_every_link_a_check_can_use_is_a_link_the_crawler_will_follow The crawler looked for "acceptable use" while the check also accepted "terms of use", so links the checks relied on were never fetched. Four PASSes rested on a link label while the document sat one request away. Nothing failed; the output was quietly weaker than it claimed.

test_run_does_not_pass_typer_descriptors_to_its_helpers basic-check run was documented as working and crashed on every invocation: calling a Typer-decorated function from Python passes its option descriptors, not their values. Nothing tested the CLI, so 53 tests stayed green throughout.

Two patterns recur in that list and are worth carrying into the wider assessment work. First, **a passing suite is evidence about the tests, not about the tool** — three of these five defects were found by probing behaviour, not by a failing test. Second, **the most dangerous failure mode here is not a wrong verdict but an overstated one**: output that reads as verified when the underlying collection was incomplete.

The two latent defects are now fixed — and there were six, not two

The previous edition recorded two latent defects in report.py: a vertical bar in a node **name** producing a misaligned Markdown row, and a newline inside an evidence string breaking the Markdown list. Neither was triggered by the node list at the time. Both are fixed at commit 014682c.

The fix is a boundary rather than a patch at each site. Two helpers now sit where values enter Markdown:

Helper	Does	Used for
_md_text(value)	Collapses all whitespace, so a newline cannot break the structure	Headings, list items, bold runs
_md_cell(value)	_md_text, then escapes the vertical bar	Table cells

Writing the tests first was what made the fix honest. Ten tests were written before any code changed, and **eight of them failed**, as intended. One of the two that passed did so by design: it guards against *over*-fixing, asserting that collapsing whitespace does not mangle ordinary evidence text.

Applying the two helpers at every boundary then revealed four more instances of the same bug class than the two that had been reported: the depth-change table, the followed-link reason, a point title reaching the COLUMN_GLOSS fallback, and a newline in a reviewer action. The reported defects were the two someone had happened to notice; the class was wider.

Two details are worth keeping:

- **Pipes in URLs stay percent-encoded as %7C.** Inside a Markdown autolink a backslash is not an escape character, so escaping would have produced a visibly broken link.

- **Regenerating the published report from the committed evidence changes no cell.** That was checked rather than assumed: the fix is presentational, and the verdicts are unaffected.

A test that counts the wrong thing passes for the wrong reason. The first version of these tests counted raw vertical bars in a rendered row, which an escaped bar also satisfies. The assertions were wrong, not the code. They now count *unescaped* delimiters via a small `_columns(row)` helper, and the escaped output was additionally checked against GitHub's own Markdown renderer rather than trusted to local reasoning.

A URL change relabelled old evidence, silently — fixed on 26 September 2026

`assess` heads each row with the URL in `nodes.yaml` and takes the verdicts from the evidence on disk. After BBMRI-ERIC's URL changed on 25 September, a bare `assess` would have printed the new `dev3.` address above verdicts about the old page, and nothing in the output said so. The address really fetched was only in the evidence file.

`assess` now compares each node's configured URL with the `requested_url` its evidence records. A difference produces a warning on the terminal, an **Evidence from a different URL** banner in `results.md` and `index.html`, and a `url_mismatch` list in `results.json`. Two tests in `test_cli.py` pin both directions: a changed URL is flagged in all three places, and the published run rebuilt with the node list it was collected with gains no banner and no new key. The exit code is unchanged, because the table is complete. Example 2 in section 11 shows how to clear the warning.

A defect found while preparing this edition, since fixed

`check_3` returned a fixed sentence stating that "the tool has no authoritative list of approved names" — **even when a list was supplied and a name matched**. The name finding was appended correctly to the evidence lines, so a single point 3 result could contain both a match and a claim that no list existed. In the published run this affects BBMRI-ERIC and EUDAT, the two nodes whose names matched.

The verdict was never affected: point 3 is `MANUAL_REVIEW` in either case. But this is precisely the failure mode this section opens with — output whose prose is weaker or stranger than the evidence behind it.

The cause was two independent writers. The summary sentence was a literal string in `check_3`, while the evidence line was computed by `_approved_name_note` from the list and the page. Nothing tied them together, so they drifted. The fix is not a reworded sentence: `_approved_name_note` now returns a `_NameNote` carrying both a `state` and its evidence line, and the summary clause is looked up from that same state. A summary that contradicts its own evidence would now require the state to contradict itself.

The six states, and what each tells a reader of the summary alone:

State	The name half of point 3
`absent`	no list was supplied, so the name was not checked
`unscoped-for-node`	the list holds no approved name for this node
`no-body`	names were supplied, but no page body was captured, so the name could not be looked for
`not-found`	looked for and not found in the body — not proof of absence, since the `<title>` is not searched
`matched`	a name written against this node was found in the body
`matched-unscoped`	a name was found, but the list is unscoped and does

State	The name half of point 3
	not say which node it belongs to

Twelve cases pin this — nine test functions, one of them parametrized across all four reachable supplied-list states — asserting that the summary never denies having a list it was given. The reviewer action adapts too: it no longer asks a reviewer to check the name against a list the tool has already matched it against.

Re-running the nine published nodes confirms the blast radius is prose only. Verdicts and evidence lines are byte-identical before and after — the tally is 28 PASS / 7 FAIL / 55 MANUAL_REVIEW either way. Only `message` and `reviewer_action` changed. BBMRI-ERIC and EUDAT now read "an approved name was found in the page body, but the list supplied is unscoped, so it does not say which node the name belongs to" in place of the denial.

One asymmetry is left deliberately. When no EOSC image asset is found, the summary discusses only the logo gap and says nothing about the name, while the evidence line still reports the name state. That summary makes no false claim, so it was not rewritten; EGI, GÉANT and the node listed by mistake take that branch in the published run.

---

8. Running it

```
uv sync
uv run playwright install chromium --with-deps

uv run basic-check points    # checklist, provenance, rule mapping
uv run basic-check collect   # landing page + up to 2 bounded hops
uv run basic-check assess    # evidence -> reports, offline, repeatable
uv run basic-check run       # collect, then assess
uv run basic-check show egi  # one node in the terminal

uv run pytest -q           # 464 cases, ~5-6 s, no network, no browser
uv run ruff check src tests
```

A few combinations that answer most real questions:

```
# two nodes only, landing pages alone, no link following
uv run basic-check run --only egi,eudat --depth 0

# the deeper run, reporting both depths side by side
uv run basic-check run --depth 2
uv run basic-check run --depth 2 --fetch-budget 20   # a stricter ceiling

# gentler on the nodes: 5s between hosts, at most 4 pages each
uv run basic-check collect --delay 5 --max-children 4
uv run basic-check assess --run gentle-run

# re-score saved evidence after editing a rule - no requests at all
uv run basic-check assess

# apply a different checklist revision, e.g. rebuild an older run
uv run basic-check assess -c checklist/v3.0.yaml
```

```
# point 3 uses the committed name list by default; override or disable it
uv run basic-check assess --approved-names ~/Documents/my-names.txt
uv run basic-check assess --no-approved-names
uv run basic-check assess --strict-separators

# a single page, without touching nodes.yaml
uv run basic-check run --url https://example.org/our-node/ \
  --eosc-page https://eosc.eu/building-the-eosc-federation/eosc-node-x/
uv run basic-check show example-org-our-node --one-off

# a separate candidate list, written elsewhere
uv run basic-check run -n ~/Documents/candidate-nodes.yaml \
  --results ~/Documents/candidate-results
```

Outputs land in results/: results.md (renders with colour directly on GitHub), index.html, checklist-v3.2.html, results.csv, results.json, and per-node evidence under results/evidence/.

> **Use a scratch output directory for anything exploratory.** uv run basic-check assess rewrites results/ wholesale, and results/ holds the run that the published report is built from. Pass --results /tmp/scratch for trial runs, and check git status --short results/ before committing.

A fuller treatment — installation, configuration, reading the output, troubleshooting — is in the **installation, configuration and run guide**.

---

9. Setting it up on macOS

Only two things need to be installed on the Mac: git and uv. Everything else — the correct Python, every runtime dependency, pytest and ruff — is installed by uv sync into a project-local .venv/. There is no need to install Python packages by hand, and nothing is installed system-wide.

Prerequisite	How to get it	Notes
git	Xcode Command Line Tools	Running git --version on a clean Mac triggers the install prompt. Or: xcode-select --install
uv	Installer script, or Homebrew	brew install uv, or the curl installer shown in step 2 below
Python 3.12+	Installed by uv	uv sync downloads a suitable Python if the system one is too old. macOS system Python is not used
Chromium	uv run playwright install chromium	Only needed to check real pages. Not needed to run the tests

> **The tests need no browser and no network.** playwright install chromium fetches three components — Chromium, the headless shell and FFmpeg — totalling roughly **660 MB**, not the ~150 MB stated in the previous edition of this document. The cache at ~/.cache/ms-playwright is shared by every project on the machine, so a second checkout downloads nothing. It is only required by the collect step, which visits real node pages. If you only want to run the suite, skip it — exactly as the CI job does, which never installs a browser.

The exact command sequence

Each block can be pasted as-is into Terminal. Lines beginning with # are comments.

```
# 1 - confirm git is present (prompts to install if it is not)
git --version

# 2 - install uv, then make it visible to the current shell
curl -LsSf https://astral.sh/uv/install.sh | sh
exec $SHELL -l
uv --version

# 3 - clone the repository and enter it
cd ~/Documents
git clone https://github.com/marioreale/eosc-basic-compliance.git
cd eosc-basic-compliance

# 4 - confirm you have what you expect
git status
git log --oneline -5

# 5 - create the environment and install every dependency
uv sync

# 6 - run the suite: 464 cases, ~5-6 s, no network, no browser
uv run pytest -q
uv run ruff check src tests
```

At that point the test suite is running locally. The next two commands are only needed if you want to check real landing pages rather than run the tests.

```
# 7 - install the browser used to render pages
uv run playwright install chromium

# 8 - check one page without touching nodes.yaml
uv run basic-check run --url https://panosc.eu/panosc-eosc-node \
  --eosc-page https://eosc.eu/building-the-eosc-federation/eosc-node-panosc/

# 9 - or run the full federation list from nodes.yaml
uv run basic-check run
open results/index.html
```

Keeping it up to date, and pushing changes back

```
# pull later changes
git pull
uv sync                    # in case dependencies changed

# commit and push your own edits (you own the repository)
git add -A
git commit -m "Describe the change"
git push
```

The clone above uses HTTPS, so the first git push will ask for credentials. GitHub no longer accepts account passwords here: use a personal access token as the password, or install the GitHub CLI and run gh auth login,

which configures the credential helper for you. An SSH key works equally well if you clone the git@github.com: URL instead.

> **The reproducibility caveat in the previous edition is resolved.** uv.lock is now committed and no longer in .gitignore. uv sync on your Mac installs the same resolved versions CI uses, and both workflows install with uv sync --locked, which *fails* rather than re-resolving if the lockfile has drifted from pyproject.toml. Dependency versions are now part of what the repository pins, alongside the checklist source hash and the approved-names hash.

---

10. The published figures

> **Two nodes added on 10 November 2026, not yet in the published run. EOSC Node Latvia** (id eosc-lv, landing page https://eosc.lv/en/, approved name "EOSC Node | Latvia", EOSC page https://eosc.eu/building-the-eosc-federation/eosc-node-latvia/) and **Scholarly Commons** (id scholarly-commons, landing page https://eosc.scholarlycommons.eu/home, approved name "EOSC Node | Scholarly Commons", EOSC page https://eosc.eu/building-the-eosc-federation/eosc-node-scholarly-commons/) were added to nodes.yaml, the shipped default copy src/basic_check/defaults/nodes.yaml and both approved-name lists, so **eighteen** nodes are configured (approved-names list SHA-256 b9f0fbec…). Both eosc.eu pages were checked live on 10 November 2026 and carry those titles. The published run web-35 predates them and covers sixteen. A trial collection of only the two nodes at --depth 2, into a scratch folder and not published, gave: **Scholarly Commons** HTTP 200, but only 169 characters rendered (a JavaScript application shell), so points 1 to 6 are review and point 7 passes; its name matches as written "EOSC Node · Scholarly Commons", and its eosc.eu page exists but was not found linked. **Latvia** HTTP 403 with Cloudflare's "Performing security verification" page, as GÉANT's, so points 1 to 6 are review and point 7 passes; nothing in that row describes the page itself. The two enter the published report at the next workflow run. Until then a bare assess on results/ exits 2 and names them, as designed; to rebuild web-35 exactly as published, use the node and name lists it was made with: git show a556394:nodes.yaml > /tmp/nodes16.yaml; git show a556394:checklist/approved-names.txt > /tmp/names16.txt; uv run basic-check assess --run web-35 --nodes /tmp/nodes16.yaml --approved-names /tmp/names16.txt --results /tmp/copy (after copying results/ to /tmp/copy; verified 10 November 2026: identical apart from the generation time and the name-list path).

Current run: web-35 at depth 2, 5 November 2026 (unreviewed, degraded)

From results/results.json, run web-35, collected on 5 November 2026 between 13:59 and 14:10 UTC by the GitHub workflow (run 42040464373, commit fc050b3) at --depth 2, under the re-issued checklist v3.2 and the official unscoped names list of sixteen names (SHA-256 24b816b0…, unchanged). It made 120 page requests: 16 landing pages, 69 direct links and 35 second-hop pages (budget: 37 of 60). Fifteen landing pages returned HTTP 200; GÉANT's returned HTTP 403 with the Cloudflare challenge. EBRAINS-RI hit the per-node limit; the whole job took 12.5 minutes, of which about 11 were collection. Offline, uv run basic-check assess --run web-35 reproduces it exactly, apart from the generation time (verified 5 November 2026, on the masked evidence).

Verdict	Depth 2	Depth 1
🟢 PASS	76	75
🔴 FAIL	6	6
🟠 MANUAL_REVIEW	68	69

Verdict	Depth 2	Depth 1
🟣 ERROR	10	10
Total	**160** (16 nodes × 10 points)	**160**

Published as is, on request. Two nodes changed against web-34, both on the collection side; no cell of the other fourteen nodes changed, and the depths now differ only in Poland 6. For EBRAINS-RI and GÉANT, web-34 (in the git history at 76eeac0) remains the last complete evidence.

Node	Point	Change	Why
EBRAINS-RI	all ten	to ERROR	collection reached the per-node limit of 300 s after the landing page and seven linked pages (TimeoutError), as in the unpublished web-32; the partial evidence is kept but not assessed
GÉANT	1, 4, 5b, 6	PASS to review	https://geant.org/geant-eosc-node/ answered HTTP 403 and redirected to ?ki-cf-botcl=1, Cloudflare's "Performing security verification" page, with 2 links; the tool does not turn bot protection into a verdict, and the page is too small to conclude absence
GÉANT	3, 5c	review (message changed)	no body to match, so "EOSC Node GÉANT" is no longer found: nine approved-name matches instead of ten

The six FAILs are Life Sciences Connect 5b, 5c and 6 (6 still a documented false negative) and Germany 5b, 5c and 6. EBRAINS-RI 4, a FAIL in web-34, is ERROR in this run.

Tests pinned to the published run.
test_names.py::test_the_official_names_match_the_nodes_that_show_them now expects nine matches (GÉANT removed); test_update_row.py still expects sixteen nodes. 462 cases pass on the published evidence.

Masking. The names masked in web-34 were carried over by aligning each placeholder with the new evidence, with the same placeholders, and the same two screenshot regions (CERN's quotation attribution, Life Sciences Connect's video title) were masked at unchanged positions. The new text of every node was then read for names not seen before; two were added: a professor named in an EBRAINS-RI news item and the surname of BBMRI-ERIC's head of public affairs, next to a masked contact line. GÉANT's governance names are not in this run, since its pages were not served. The changed screenshots (Data Terra, Poland,

GÉANT) were checked by eye and show no personal name. Masking changed no verdict, message or evidence line. The privacy check found only role mailboxes and no phone-shaped text.

Previous run: web-34 at depth 2, 27 October 2026 (unreviewed)

From results/results.json, run web-34, collected on 27 October 2026 between 10:20 and 10:29 UTC by the GitHub workflow (run 40486581247, commit 55657ac) at --depth 2, under the re-issued checklist v3.2 and the official unscoped names list of sixteen names (SHA-256 24b816b0…). It made 145 page requests: 16 landing pages, 77 direct links and 52 second-hop pages (budget: 52 of 60). All sixteen landing pages returned HTTP 200. No node hit the per-node limit; the whole job took 17.5 minutes, of which about 8.5 were collection. Offline, uv run basic-check assess --run web-34 reproduces it exactly, apart from the generation time (verified 27 October 2026, on the masked evidence).

Verdict	Depth 2	Depth 1
🟢 PASS	85	83
🔴 FAIL	7	7
🟠 MANUAL_REVIEW	68	70
🟣 ERROR	0	0
Total	**160** (16 nodes × 10 points)	**160**

Only GÉANT changed. Against web-33, the same four cells moved at both depths; no cell of the other fifteen nodes changed, and the depths still differ only in EBRAINS-RI 6 and Poland 6.

Node	Point	Change	Why
GÉANT	1, 4, 5b, 6	review to PASS	the page was served (HTTP 200, final URL https://geant.org/projects/geant-eosc-node/) for the first time since web-22; it is public, links its own eosc.eu entry and the "GÉANT Node Acceptable Use Policy" page (read), and its Contact page gives a support route
GÉANT	3, 5c	review (message changed)	3: the page writes "EOSC Node GÉANT", the tenth approved-name match, and shows two EOSC image assets; 5c: no separate User Access Policy is linked, and v3.2 allows one document for both

The seven FAILs are unchanged: EBRAINS-RI 4, Life Sciences Connect 5b, 5c and 6 (6 still a documented false negative), and Germany 5b, 5c and 6.

Tests pinned to the published run.
test_names.py::test_the_official_names_match_the_nodes_that_show_them now expects ten matches (GÉANT added back); test_update_row.py still expects sixteen nodes. 462 cases pass on the published evidence.

Masking. The names masked in web-33 were masked again with the same placeholders, and the same two screenshot regions (CERN's quotation attribution, Life Sciences Connect's video title) were masked at unchanged positions. GÉANT's second hop reached its executive team, governance and membership pages again: about 120 names of officers, board members and General Assembly representatives, taken from the fixed patterns of those pages and masked everywhere, including one cut short in a control label ("Heidi Fraser-Kr..."). Phone numbers on GÉANT's contact and cookie pages were masked by the automatic rule. The changed screenshots (CERN, Data Terra, EBRAINS-RI, Germany, Poland, EUDAT, GÉANT, PaNOSC) were checked by eye and show no personal name. Masking changed no verdict, message or evidence line. The privacy check found only role mailboxes.

Previous run: web-33 at depth 2, 20 October 2026 (unreviewed)

From results/results.json, run web-33, collected on 20 October 2026 between 20:13 and 20:21 UTC by the GitHub workflow (run 39489960802, commit 1353fda) at --depth 2, under the re-issued checklist v3.2 and the official unscoped names list, now sixteen names (SHA-256 24b816b0...). It made 130 page requests: 16 landing pages, 70 direct links and 44 second-hop pages (budget: 44 of 60). Fifteen landing pages returned HTTP 200; GÉANT's returned HTTP 403 with the Cloudflare challenge. No node hit the per-node limit. Offline, uv run basic-check assess --run web-33 reproduces it exactly, apart from the generation time (verified 20 October 2026).

Verdict	Depth 2	Depth 1
🟢 PASS	81	79
🔴 FAIL	7	7
🟠 MANUAL_REVIEW	72	74
🟣 ERROR	0	0
Total	**160** (16 nodes × 10 points)	**160**

One node added. EOSC Node Germany (eosc-de, https://eosc-node.de, approved name "EOSC Node | Germany", EOSC page eosc-node-germany) was added on 20 October 2026 in commit 1353fda, to nodes.yaml, the shipped default copy, and both approved-name lists. **No cell of the other fifteen nodes changed** against web-31, at either depth; the depths still differ only in EBRAINS-RI 6 and Poland 6.

Node	Point	Verdict	Why
Germany	1, 4, 7	PASS	anonymous access; links its own eosc.eu entry; English, declared
Germany	1R, 2, 3, 5a	review	as for every node; for 3, the page writes "EOSC Node Germany" (the ninth approved-name match) and shows an EOSC logo
Germany	5b, 5c	FAIL	the page is a "Coming soon" placeholder with seven links (EOSC, EOSC

Node	Point	Verdict	Why
			Nodes, its EOSC entry, NFDI twice, a "Details" page on nfdi.de, "Imprint and Data Privacy"); none is a policy pointer or a page that could carry one
Germany	6	FAIL	no mailto: and no contact, support or helpdesk link. The imprint was not followed, since its label matches no point; a reviewer should check it before quoting this FAIL

The seven FAILs are EBRAINS-RI 4, Life Sciences Connect 5b, 5c and 6 (6 still a documented false negative), and Germany 5b, 5c and 6.

One run not published. web-32 (run 39387128370, 20 October, commit dab73b4) was the first run with the per-node time limit. EBRAINS-RI read its landing page and its seven direct links, then stalled at its second hop, whose first page is a form on forms.ebrains.eu, and was stopped at 300 s: its ten points were ERROR, and the run finished the remaining node normally in 12.5 minutes, instead of being cancelled at the job limit as in web-29. Publishing it would have replaced EBRAINS-RI's real verdicts with ERROR. In web-33 EBRAINS-RI completed, with all 16 pages.

Tests pinned to the published run. test_update_row.py::test_published_results_are_the_run_these_tests_copy now expects sixteen nodes, and test_names.py::test_the_official_names_match_the_nodes_that_show_them nine matches (Germany added). 462 cases pass on the published evidence.

Masking. The same names as in web-31 were masked, with the same placeholders, and the same two screenshots (CERN's quotation attribution, Life Sciences Connect's video title, at unchanged positions). Germany's page carries no personal name, address or phone number, and no new personal name was found on the other pages. Masking changed no verdict, message or evidence line. The privacy check found only role mailboxes.

Previous run: web-31 at depth 2, 19 October 2026

From results/results.json, run web-31, collected on 19 October 2026 between 20:44 and 20:51 UTC by the GitHub workflow (run 39321743220, commit e9c5f9c) at --depth 2, under the re-issued checklist v3.2 and the official unscoped names list of fifteen names (SHA-256 e23f7d1c…, unchanged). It made 129 page requests: 15 landing pages, 70 direct links and 44 second-hop pages (budget: 44 of 60). Fourteen landing pages returned HTTP 200; GÉANT's returned HTTP 403 with the Cloudflare challenge. Offline, uv run basic-check assess --run web-31 reproduces it exactly, apart from the generation time (verified 19 October 2026).

Verdict	Depth 2	Depth 1
🟢 PASS	78	76
🔴 FAIL	4	4
🟠 MANUAL_REVIEW	68	70

Verdict	Depth 2	Depth 1
🟣 ERROR	0	0
Total	**150** (15 nodes × 10 points)	**150**

PaNOSC's landing page changed. On 19 October 2026 (commit e9c5f9c, made with basic-check --update-nlp) PaNOSC's URL in nodes.yaml and in the shipped default copy changed from https://eosc.panosc.eu/ to https://panosc.eu/panosc-eosc-node. Both redirect to https://www.panosc.eu/panosc-eosc-node/, which was already the final_url in web-28, so the page read is the same and PaNOSC's ten verdicts did not change (5 PASS, 5 review).

No cell changed at depth 2 against web-28. The depths now differ in two cells:

Node	Point	Depth 1	Depth 2	Why
EBRAINS-RI	6	review	PASS	as in web-28: its Contact page, reached at the second hop from its Media Contact page, uses ticketing wording
Poland	6	review	PASS	new: the landing page shows contact@eosc.pl where it showed support@eosc.pl, a general address; at depth 2 a page it links (/search/software) carries "Helpdesk" wording. In web-28 it passed at both depths

The four FAILs are those of web-28: EBRAINS-RI 4, and Life Sciences Connect 5b, 5c and 6 (6 still a documented false negative; its menu links still have no href, and the tool again captured two links only).

Two runs not published. web-29 (run 39316592630, 19 October, commit 61e4e36) was cancelled by the job's 30-minute timeout-minutes: the first thirteen nodes were collected between 20:08 and 20:14 UTC, then EBRAINS-RI's collection stalled after its screenshot was taken, and Life Sciences Connect was never reached. The log shows no per-node lines, because the progress output is buffered and was lost with the cancelled step. web-30 (run 39321255714, --only ebrains-ri) completed in two minutes, and so did EBRAINS-RI inside web-31. The cause was not found: each navigation has a timeout (45 s for a landing page, 25 s for a child page), but nothing bounds a whole node, page.content() or the robots.txt reads. **Fixed on 20 October 2026:** each node is now bounded as a whole by --node-timeout (default 300 s, NODE_TIMEOUT_S in fetch.py). A node that hits it is abandoned, keeps what it had gathered in its evidence file, reads ERROR on every point with a TimeoutError message (never a FAIL built on half-collected evidence), and the browser is restarted before the next node. The robots.txt reads now run in a worker thread so they cannot freeze the limit, the browser clean-up is itself bounded to 15 s, progress lines are flushed as each node finishes, and the workflow sets PYTHONUNBUFFERED=1, so a future log shows which node stopped.

Masking. The same names as in web-28 were masked, with the same placeholders, and the same two screenshots (CERN's quotation attribution, Life Sciences Connect's video title, both at unchanged positions). New in this run: the author credited in the document log of BBMRI-ERIC's Acceptable Use Policy, and a person interviewed in an EBRAINS-RI news item. Masking changed no verdict, message or evidence line. The privacy check found only role mailboxes. The test suite (453 cases) passes on the published evidence.

Previous run: web-28 at depth 2, 9 October 2026

From results/results.json, run web-28, collected on 9 October 2026 between 14:24 and 14:32 UTC by the GitHub workflow (run 37943784224, commit df4be09) at --depth 2, under the re-issued checklist v3.2 and the official unscoped names list, now fifteen names (SHA-256 e23f7d1c…). It made 129 page requests: 15 landing pages, 70 direct links and 44 second-hop pages. Fourteen landing pages returned HTTP 200; GÉANT's returned HTTP 403 with the Cloudflare challenge. Offline, uv run basic-check assess --run web-28 reproduces it exactly, apart from the generation time (verified 9 October 2026).

Verdict	Depth 2	Depth 1
🟢 PASS	78	77
🔴 FAIL	4	4
🟠 MANUAL_REVIEW	68	69
🟣 ERROR	0	0
Total	**150** (15 nodes × 10 points)	**150**

The depths differ in one cell, EBRAINS-RI point 6: at depth 2 its Contact page, reached from its Media Contact page, uses ticketing wording.

Two nodes added. EBRAINS-RI (https://ebrains.eu/, approved name "EOSC Node | EBRAINS RI") and Life Sciences Connect (https://eosc-lifesciences-connect.eu/home, "EOSC Node | Life Sciences Connect") were added on 9 October 2026 in commit df4be09. All four FAILs are theirs:

Node	Cells	Why
EBRAINS-RI	4: FAIL	none of 126 links goes to eosc.eu; its entry exists at https://eosc.eu/building-the-eosc-federation/eosc-node-ebrains-ri/
Life Sciences Connect	5b, 5c: FAIL	no policy pointer among the two links captured; a hand check of its Home, About and Contact pages found none either, still to be confirmed by a reviewer
Life Sciences Connect	6: FAIL	**a false negative.** Its menu items are <a> elements with no href that navigate by script, so the tool captured two links only and judged the DOM complete. A hand check on 9 October 2026 found help@eosc-lifesciences-connect.eu on its Contact page (/contact-information)

On the thirteen nodes of web-27, one cell changed: EUDAT 6, review to PASS (the page links "Open a request" to https://portal.eudat.eu/helpdesk).

Masking. The same names as before were masked, and CERN's screenshot again. New in this run: on EBRAINS-RI's pages, its CEO, a section head, its press contact, three testimonial authors, and two people named in news items and image captions, including in image file names and link addresses; and in Life Sciences Connect's screenshot, the coordinator named in a video title. All were replaced with same-length placeholders. Masking changed no verdict, message or evidence line. The privacy check found only role mailboxes.

Tests pinned to the published run. test_update_row.py::test_published_results_are_the_run_these_tests_copy now expects fifteen nodes. The stored fixture in test_update_row.py now re-assesses its copy of the published run offline when the default approved-name list has changed since that run, so that adding a node and its name does not break the row-replacement tests before the new run is published. test_names.py::test_the_official_names_match_the_nodes_that_show_them still expects eight matches: neither new page writes its approved name in its text.

Previous run: web-27 at depth 2, 7 October 2026

Run web-27 was collected on 7 October 2026 between 21:59 and 22:05 UTC by the GitHub workflow (run 37692836637, commit 5e0e6ce) at --depth 2, under the re-issued checklist v3.2 and the official unscoped names list. It made 109 page requests: 13 landing pages, 63 direct links and 33 second-hop pages. Twelve landing pages returned HTTP 200; GÉANT's returned HTTP 403 with the Cloudflare challenge. Depth 1 and depth 2 agree in every cell. Offline, uv run basic-check assess --run web-27 reproduces it exactly, apart from the generation time (verified 7 October 2026).

Verdict	Cells
🟢 PASS	69
🔴 FAIL	0
🟠 MANUAL_REVIEW	61
🟣 ERROR	0
Total	**130** (13 nodes × 10 points)

No FAIL, as in web-25 and web-26. Two cells changed against web-26, both Poland's:

Node	Cells	Why
Poland	4: review to PASS	the page rendered in full again (5,403 characters, 37 links; in web-26 420 characters, header and footer only) and links https://eosc.eu/building-the-eosc-federation/eosc-node-poland/
Poland	5c: review to PASS	a new "User Access Policy" link goes to https://eosc.pl/privacy-policy, which was read (HTTP 200, 15,025 characters) and reads like a policy document; a reviewer should confirm that the privacy policy page serves as the

Node	Cells	Why
		User Access Policy

Poland's page also writes "EOSC Node Poland" again, so point 3 has its name match back (it stays review).

Masking. The same names as before were masked, including the fifteen on BBMRI-ERIC's dev3. pages and CERN's screenshot (the attribution moved on the page, so the mask was redrawn at its new position). New in this run: the people named in the captions of two historical public-domain photos on Poland's page, masked with same-length placeholders. Masking changed no verdict, message or evidence line. The privacy check found only role mailboxes.

Tests pinned to the published run.
test_names.py::test_the_official_names_match_the_nodes_that_show_them now expects eight matches (Poland back).

Previous run: web-26 at depth 2, 6 October 2026, afternoon

Run web-26 was collected on 6 October 2026 between 16:07 and 16:14 UTC by the GitHub workflow (run 37492974153, commit 21d8c7d) at --depth 2, under the re-issued checklist v3.2 and the official unscoped names list. It made 109 page requests: 13 landing pages, 62 direct links and 34 second-hop pages. Twelve landing pages returned HTTP 200; GÉANT's returned HTTP 403 with the Cloudflare challenge. Depth 1 and depth 2 agree in every cell. Offline, uv run basic-check assess --run web-26 reproduces it exactly, apart from the generation time (verified 6 October 2026).

Verdict	Cells
🟢 PASS	67
🔴 FAIL	0
🟠 MANUAL_REVIEW	63
🟣 ERROR	0
Total	**130** (13 nodes × 10 points)

No FAIL, as in web-25. One cell changed against web-25:

Node	Cells	Why
Poland	4: PASS to review	the page answered HTTP 200 but rendered only its header and footer (420 characters of text, 21 links, none to eosc.eu); the tool does not read an essentially empty page as an absence, so it asks for review instead of failing. Its "EOSC Node Poland" text was missing too, so point 3 lost its name match (it stays review)

Masking. The same names as before were masked, including the fifteen on BBMRI-ERIC's dev3. pages and CERN's screenshot. No new personal names were found. Masking changed no verdict, message or evidence line. The privacy check found only role mailboxes.

Tests pinned to the published run.
test_names.py::test_the_official_names_match_the_nodes_that_show_them now expects seven matches (Poland out, because its page rendered no main content).

Previous run: web-25 at depth 2, 6 October 2026, morning

Run web-25 was collected on 6 October 2026 between 10:35 and 10:41 UTC by the GitHub workflow (run 37450646487, commit ddb7711) at --depth 2, under the re-issued checklist v3.2 and the official unscoped names list. It made 109 page requests: 13 landing pages, 62 direct links and 34 second-hop pages. Twelve landing pages returned HTTP 200, BBMRI-ERIC's dev3. page among them (its robots.txt no longer excludes the tool); GÉANT's returned HTTP 403 with the Cloudflare challenge. Depth 1 and depth 2 agree in every cell. Offline, uv run basic-check assess --run web-25 reproduces it exactly, apart from the generation time (verified 6 October 2026).

Verdict	Cells
🟢 PASS	68
🔴 FAIL	0
🟠 MANUAL_REVIEW	62
🟣 ERROR	0
Total	**130** (13 nodes × 10 points)

No FAIL is left, for the first time. Thirteen cells changed against web-24:

Node	Cells	Why
BBMRI-ERIC	1, 4, 5b, 6, 7: ERROR to PASS; 1R, 2, 3, 5a, 5c: ERROR to review	the dev3. page was served; it links its own eosc.eu entry ("See the dedicated page on the EOSC website"), an "Acceptable Use Policy" PDF (a pointer) and its Helpdesk; no User Access Policy is linked, so 5c is review; its text writes "EOSC Node – BBMRI-ERIC", which matches the approved list
EOSC Finland	4: FAIL to PASS; 5c: review to PASS	it links "EOSC Node Finland (External link)" to https://eosc.eu/building-the-eosc-federation/eosc-node-finland, and "User Access Policy and the Acceptable Use Policy" to its Node Policies page, which was read; its text now writes "EOSC Node Finland", which matches
Data Terra	5c: review to PASS	the policy link now reads "EOSC Node Data Terra Acceptable Use Policy and User Access Policy" (documentation site, not fetched: a pointer)

Masking. The same names as before were masked, and CERN's screenshot again. BBMRI-ERIC's dev3. pages added fifteen personal names, masked with same-length placeholders: the Director General (legal notice), the seven members of the scientific and ethical advisory board (governance page), the Stakeholder Forum chair and the head of public affairs (contact and stakeholder forum pages), and five finance, project and HR staff listed in capitals (finance and project management page). Its screenshot shows no names. Masking changed no verdict, message or evidence line. The privacy check found only role mailboxes.

Tests pinned to the published run.
test_names.py::test_the_official_names_match_the_nodes_that_show_them now expects eight matches (BBMRI-ERIC back, at its dev3. page, and EOSC Finland new).

Previous run: web-24 at depth 2, 5 October 2026

Run web-24 was collected on 5 October 2026 between 21:17 and 21:23 UTC by the GitHub workflow (run 37374849652, commit 42aacbe) at --depth 2, under the re-issued checklist v3.2 and the official unscoped names list. Commit 42aacbe made BBMRI-ERIC's default landing page https://dev3.bbmri-eric.eu/eosc-node-bbmri-eric/. The run made 94 page requests: 12 landing pages, 54 direct links and 28 second-hop pages. Eleven landing pages returned HTTP 200; GÉANT's returned HTTP 403 with the Cloudflare challenge; BBMRI-ERIC's was not requested, because the dev3. host's robots.txt disallows it. Depth 1 and depth 2 agree in every cell. Offline, uv run basic-check assess --run web-24 reproduces it exactly, apart from the generation time (verified 5 October 2026).

Verdict	Cells
🟢 PASS	60
🔴 FAIL	1
🟠 MANUAL_REVIEW	59
🟣 ERROR	10
Total	**130** (13 nodes × 10 points)

The one FAIL is point 4 for EOSC Finland. Twelve cells changed against web-23:

Node	Cells	Why
BBMRI-ERIC	all ten to ERROR (were 6 PASS, 4 review)	not fetched: robots.txt disallows it, at the new dev3. default, as on 25 September (trial) and 1 October (web-18); this says nothing about compliance
Czechia	5c: PASS to review	no User Access Policy link was found on the landing page or the 12 pages read; it links its AUP ("AP/AUP EOSC Node Czechia", a PDF), and v3.2 allows one document for both
EUDAT	5c: review to PASS	it links "User Access Policy" to https://www.eudat.eu/eudat-cdi-uap, which was read (HTTP 200, policy wording)

Masking. The same names as before were masked, and CERN's screenshot again; BBMRI-ERIC has no evidence to mask in this run. No new personal names were found. The privacy check found only role mailboxes. The workflow carried over BBMRI-ERIC's screenshot from web-23 (its www. page); it does not belong to this run and was not published.

Tests pinned to the published run.
test_names.py::test_the_official_names_match_the_nodes_that_show_them now expects six matches (BBMRI-ERIC left out: no page was read), and
test_update_row.py::test_evidence_from_another_url_is_flagged_on_that_row now configures the www. address against the dev3. evidence.

Previous run: web-23 at depth 2, 2 October 2026

Run web-23 was collected on 2 October 2026 between 16:19 and 16:25 UTC by the GitHub workflow (run 37033017657, commit 142e002) at --depth 2, under the re-issued checklist v3.2 and the official unscoped names list. It made 102 page requests: 13 landing pages, 60 direct links and 29 second-hop pages. Twelve landing pages returned HTTP 200; GÉANT's returned HTTP 403 with the Cloudflare challenge. Depth 1 and depth 2 agree in every cell. Offline, uv run basic-check assess --run web-23 reproduces it exactly, apart from the generation time.

Verdict	Cells
🟢 PASS	66
🔴 FAIL	1
🟠 MANUAL_REVIEW	63
🟣 ERROR	0
Total	**130** (13 nodes × 10 points)

The one FAIL is point 4 for EOSC Finland. Six cells changed against web-22:

Node	Cells	Why
PaNOSC	4: FAIL to PASS	it links "PaNOSC Node" to https://eosc.eu/building-the-eosc-federation/eosc-node-panosc
Poland	4: FAIL to PASS	it links "EOSC Node Poland" to https://eosc.eu/building-the-eosc-federation/eosc-node-poland/; its text now also writes "EOSC Node Poland", which matches the approved list (point 3 stays review)
GÉANT	1, 4, 5b, 6: PASS to review	HTTP 403 with the Cloudflare challenge (?ki-cf-botcl=1), as before web-22; bot protection is not turned into a verdict

Masking. The same names as before were masked, and CERN's screenshot again. No new personal names were found; GÉANT's pages were not reached. The privacy check found only role mailboxes.

Previous run: web-22 at depth 2, 2 October 2026

Run web-22 was collected on 2 October 2026 between 15:42 and 15:49 UTC by the GitHub workflow (run 37028804263, commit aa2f7a8) at --depth 2, under the re-issued checklist v3.2 and the official unscoped names list. It made 118 page requests: 13 landing pages, 68 direct links and 37 second-hop pages. All thirteen landing pages returned HTTP 200. Depth 1 and depth 2 agree in every cell. Offline, uv run basic-check assess --run web-22 reproduces it exactly, apart from the generation time.

Verdict	Cells
🟢 PASS	68
🔴 FAIL	3
🟠 MANUAL_REVIEW	59
🟣 ERROR	0
Total	**130** (13 nodes × 10 points)

The three FAILs are point 4 for EOSC Finland, PaNOSC and Poland. Seven cells changed against web-21:

Node	Cells	Why
GÉANT	1, 4, 5b, 6: review to PASS	the page was served (HTTP 200), as in web-16; it links its own eosc.eu entry, the "GÉANT Node Acceptable Use Policy" page (fetched) and a Contact page that names a helpdesk
PaNOSC	5c: review to PASS	it links "Acceptable User Policy and User Access Policy" to a PaNOSC Node User Policies page, fetched and reading like a policy; 5b stays review because "Acceptable User Policy" is not the vocabulary's "Acceptable Use Policy"
PaNOSC	6: review to PASS	it links "PaNOSC Helpdesk", helpdesk.panosc.eu
EUDAT	6: PASS to review	the redesigned landing page no longer links "Helpdesk"; it links info@eudat.eu, and a "Help Desk" support-request form is two hops away

Masking. The same names as before were masked, and CERN's screenshot again. GÉANT's governance and membership pages were reached again: the same names, plus one more additional observer. EUDAT's new page carries a news item naming two new staff members; both were masked. The privacy check found only role mailboxes.

Previous run: web-21 at depth 2, 1 October 2026

Run web-21 was collected on 1 October 2026 between 20:18 and 20:24 UTC by the GitHub workflow (run 36920498532, commit fc023b7) at --depth 2, under the re-issued checklist v3.2 and the official unscoped names list, with Data Terra's new Node Landing Page, https://www.earth-data.eu/. It made 98 page requests: 13 landing pages, 58 direct links and 27 second-hop pages. Twelve landing pages returned HTTP 200 and GÉANT's HTTP 403 (the Cloudflare challenge). Depth 1 and depth 2 agree in every cell. Offline, uv run basic-check assess --run web-21 reproduces it exactly, apart from the generation time.

Verdict	Cells
🟢 PASS	63
🔴 FAIL	3
🟠 MANUAL_REVIEW	64
🟣 ERROR	0
Total	**130** (13 nodes × 10 points)

The three FAILs are point 4 for EOSC Finland, PaNOSC and Poland. Only Data Terra's row changed against web-18:

Node	Cells	Why
Data Terra	4: FAIL to PASS	the new page links its own entry, eosc.eu/building-the-eosc-federation/eosc-node-data-terra
Data Terra	5b: FAIL to PASS	it links "EOSC Node Data Terra Acceptable Use Policy" on its documentation site (another site, so a pointer, not fetched)
Data Terra	5c: FAIL to review	no User Access Policy is linked, but an AUP is, and v3.2 allows one document for both; the AUP link's address ends in /policies/user-access/
Data Terra	6: review to PASS	it links helpdesk@earth-data.eu

The new page is in English (en-GB), so the French-vocabulary caveat of the old address no longer applies. At depth 2 the tool followed the page's "Français" link as an About page; it changed no verdict.

Masking. The same names as before were masked, and CERN's screenshot again. Data Terra's new page carries one personal name, a photo credit in an image description; it was masked like the others. The privacy check found only role mailboxes.

Previous run: web-18 at depth 2, 1 October 2026

Run web-18 was collected on 1 October 2026 between 16:05 and 16:10 UTC by the GitHub workflow (run 36888865559, commit 46b5cad) at --depth 2, under the re-issued checklist v3.2 and the official unscoped names list. Two things were done to it before publishing:

- **BBMRI-ERIC's row was collected again.** 46b5cad had set its URL to https://dev3.bbmri-eric.eu/eosc-node-bbmri-eric/, whose robots.txt disallows the page, so all ten cells were ERROR. The URL was set

back to the www. address and BBMRI-ERIC collected alone (run 36899901060, commit 1418f05, 17:31 UTC); its evidence replaced the ERROR row.

- **It was scored with the fix in 1418f05.** Italy's landing page links "Infrastructure AUP/UAP" to D4Science's policy page, and "Review resource access conditions" to a page that returns 404. The tool had followed the second for 5c and failed the point on it. Now a broken policy link fails 5b or 5c only when no other link to the policy remains, on the landing page or on a linked page; otherwise the point is judged on the others and the broken link is reported in the evidence. Three tests cover it. Re-scoring web-16 with the fix changes nothing; re-scoring web-18 changes only Italy's 5c, at both depths.

The published evidence holds 96 page requests: 13 landing pages, 57 direct links and 26 second-hop pages. Twelve landing pages returned HTTP 200 and GÉANT's HTTP 403 (the Cloudflare challenge). Depth 1 and depth 2 agree in every cell. Offline, uv run basic-check assess --run web-18 reproduces it exactly, apart from the generation time.

Verdict	Cells
🟢 PASS	60
🔴 FAIL	6
🟠 MANUAL_REVIEW	64
🟣 ERROR	0
Total	**130** (13 nodes × 10 points)

The six FAILs are the same as in web-16: point 4 for Data Terra, EOSC Finland, PaNOSC and Poland, and Data Terra's 5b and 5c. Eleven cells changed against web-16:

Node	Cells	Why
Italy	1, 4, 5b, 5c, 6, 7: review to PASS	read for the first time at https://eosc.it/ (HTTP 200, English); it links its own eosc.eu entry, "Infrastructure AUP/UAP", a Terms of Use page (fetched) and a D4Science helpdesk; web-16 got HTTP 503 from the old address
GÉANT	1, 4, 5b, 6: PASS to review	HTTP 403, the Cloudflare challenge, as before web-16
EOSC DTO	5c: review to PASS	its Catalogue page now links "AUP and access policy"

Masking. The same names as before were masked, and CERN's screenshot again. Italy's new pages carry no personal names; BBMRI-ERIC's pages changed only in layout. The privacy check found only role mailboxes.

Previous run: web-16 at depth 2, 30 September 2026

Run web-16 was collected on 30 September 2026 between 14:58 and 15:04 UTC by the GitHub workflow (run 36732900487, commit a83c0f1, unit tests passing) at --depth 2, under the re-issued checklist v3.2 and the official unscoped names list. It made 109 page requests: 13 landing pages, 62 direct links and 34 second-hop pages. Twelve landing pages returned HTTP 200 and Italy's HTTP 503. Depth 1 and depth 2 agree in every cell. Offline, uv run basic-check assess --run web-16 reproduces it exactly, apart from the generation time.

Verdict	Cells
🟢 PASS	57
🔴 FAIL	6
🟠 MANUAL_REVIEW	67
🟣 ERROR	0
Total	**130** (13 nodes × 10 points)

Four FAILs are point 4 (Data Terra, EOSC Finland, PaNOSC, Poland) and two are Data Terra's 5b and 5c. Twelve cells changed against web-15:

Node	Cells	Why
GÉANT	1, 4, 5b, 6: review to PASS	the page was served (HTTP 200) for the first time since 24 September; it links its own eosc.eu entry, a "GÉANT Node Acceptable Use Policy" page (fetched) and a contact page
Czechia	4, 5c: to PASS	it now links "DETAILED DESCRIPTION OF EOSC NODE CZECHIA" to its own entry, and a "User Access Policy" (a CESNET PDF, not read)
EGI	5c: review to PASS	it links "EGI User Access Policy (UAP)", a PDF, not read
Italy	1, 4, 5b, 6, 7: to review	HTTP 503 "No server is available", again when Italy alone was re-collected at 15:05:54 UTC (run 36733978874); an unserved page is never a FAIL

Masking. The same names as in web-15 were masked again, and CERN's screenshot. GÉANT's second hop reached its executive team, governance and membership pages, with about 120 names of officers, board members and General Assembly representatives; they were masked everywhere, including forms cut short at the end of a link label. The privacy check found only role mailboxes.

Two wasted requests. On GÉANT's page the tool followed the cookie banner's "Manage services" button as a services page (5s), and at the second hop a "Security contact for this AUP" link as an AUP (5b). Neither changed a verdict; the AUP verdict rests on the policy page itself.

Previous run: web-15 at depth 2, 29 September 2026

Run web-15 was collected on 29 September 2026 between 16:44 and 16:50 UTC by the GitHub workflow (run 36599759210, commit 2bab16b, unit tests passing) at --depth 2, under the re-issued checklist v3.2 and the official unscoped names list, with the two crawl fixes described below. It made 95 page requests: 13 landing pages, 56 direct links and 26 second-hop pages, 26 of the 60 the run allows for the second hop. Twelve landing pages returned HTTP 200 and GÉANT HTTP 403. Depth 1 and depth 2 agree in every cell. Offline, uv run basic-check assess --run web-15 reproduces it exactly, apart from the generation time.

Verdict	Cells
🟢 PASS	53
🔴 FAIL	9
🟠 MANUAL_REVIEW	68
🟣 ERROR	0
Total	**130** (13 nodes × 10 points)

Only one cell differs from web-14: **EGI's point 4 passes**, because its landing page now links "EGI EOSC Node on EOSC Association's website", https://eosc.eu/building-the-eosc-federation/eosc-node-egi. Six FAILs are point 4, one is Italy's point 6 and two are Data Terra's 5b and 5c. Data Terra's services page /services/ was read and links no AUP or UAP; /offre-de-services/, which web-14 reached one hop further, is no longer followed, and gave the same result then. 5b and 5c per node are as in web-14, below. The masking is the same as for web-14: every name masked there was found again and masked, no new name appeared, and CERN's screenshot was masked again.

Previous run: web-14 at depth 2, 28 September 2026

From run web-14, collected on 28 September 2026 between 23:43 and 23:50 UTC (run 36499442323, commit 9c291f9). It made 136 page requests: 13 landing pages, 63 direct links and 60 second-hop pages, the whole run budget, so Italy and Slovakia got no second hop. It gave 52 PASS, 10 FAIL and 68 MANUAL_REVIEW, with EGI's point 4 still FAIL. Per node, 5b and 5c:

5b / 5c	Nodes	Why
PASS / PASS	CERN	its "Policies" page links /policies/aup and /policies/uap, both fetched and read as policies; its "Services" page links both too
PASS / PASS	BBMRI-ERIC	its Access Policies page is the UAP and links the "Acceptable Use Policy of BBMRI-ERIC Services" (a PDF, not fetched)
PASS / PASS	Slovakia	one "Terms of Use (incl. AUP and UAP)" document
PASS / review	Czechia, EOSC DTO, EOSC Finland, EUDAT, EGI, Poland, Italy	an AUP or terms of use is linked; one document may be both, so the UAP is left to a reviewer
FAIL / FAIL	Data Terra	/services/ and /offre-de-services/ were read and link no AUP or UAP. The pages are in French and the vocabulary is English, so check by hand
review / review	PaNOSC	its services site, services.panosc.eu, was not read
review / review	GÉANT	HTTP 403, the page was not served

Against web-13-rescored, only four cells changed: CERN's 5b and 5c (review to PASS) and Data Terra's (review to FAIL).

Two crawl defects, fixed after the run. Privacy and cookie policies whose address spells the words with a hyphen (/privacy-policy, /cookie-policy) were followed as policies pages, because the exclusion was written for the label. And the second hop also looked for services and policies pages, fetching up to 12 more pages per node (EOSC Finland). Now the exclusion reads the whole label and address, and the intermediate pages are looked for on the landing page only. Re-assessing web-14 with the fix changes no verdict or evidence line; the next collection will make fewer requests.

Masking. The privacy check found only role mailboxes. Names that the automatic masking does not cover were removed by hand with same-length placeholders: CERN's quotation attribution (text and screenshot), EGI's coordinator (text and link address), a person quoted on a Czechia news page, about thirty staff, board and news-author names on BBMRI-ERIC's and EGI's service and federation pages, and the author lists of publication citations on Czechia's, D4Science's (EOSC DTO and Italy) and PaNOSC's pages. Masking changed no verdict, message or evidence line. Two of the citation lists (Czechia and D4Science) were already in the evidence published as web-13 and were missed then; they remain in the git history.

Previous run: web-13-rescored, 29 September 2026

results/ held web-13-rescored briefly: the evidence of run web-13, described next, scored again on 29 September 2026 against the re-issued checklist v3.2 without contacting any node, with 50 PASS, 8 FAIL and 72 MANUAL_REVIEW. CERN, Data Terra and PaNOSC were review on 5b and 5c, because each linked to a services or policies page that web-13 had not read; web-14 read them.

Run web-13 at depth 2, 28 September 2026

From results/results.json as committed at 8346079, run web-13, collected on 28 September 2026 between 22:53 and 22:57 UTC by the GitHub workflow (run 36494907672, commit b0ad261) at --depth 2, under checklist v3.2 and the official unscoped names list. It made 63 page requests: 13 landing pages, 31 direct links and 19 second-hop pages (EOSC Node Czechia 4, EUDAT 4, EOSC DTO 3, EOSC Finland 3, BBMRI-ERIC 2, CERN 1, EGI 1, PaNOSC 1). The report has a table for each depth, and they are identical: **the second hop changed no verdict**, 49 PASS, 14 FAIL and 67 MANUAL_REVIEW in both, under the first copy of v3.2. Every cell also equals run web-12, described next. The direct links returned the same text as in web-12, apart from a language menu on Data Terra's contact page and a search-box label on EUDAT's documentation.

The privacy check found no personal address or phone number (the only addresses left are role mailboxes). By hand, the same two names as in web-12 were removed, and one new one: a person quoted in a news item on the Czechia page eosc-cz-in-data, reached only at depth 2, whose name was in the quotation and, as a surname, in the address of the linked interview (interview-…). All were replaced by same-length placeholders, and re-assessing after the masking changed no verdict, message or evidence line. It was scored under the discarded first copy of v3.2, so it no longer rebuilds from the current checklist.

Run web-12 was collected on 28 September 2026 between 22:34 and 22:38 UTC by the GitHub workflow (run 36493197701, commit d3de829, unit tests passing first), the first under checklist v3.2, at --depth 1 and against the official unscoped names list (13 names, SHA-256 46af586b…). All thirteen nodes were assessed and none was skipped; twelve landing pages returned HTTP 200 and GÉANT returned HTTP 403 with the Cloudflare challenge; 31 links were followed. The evidence was masked as it was collected, and a search of every evidence file and report found no personal address or phone number; the only addresses left are EGI role mailboxes. The same two personal names as in web-11 were then removed by hand with same-length placeholders: CERN's quotation attribution (in cern.json and its screenshot) and EGI's coordinator, whose name was also in the address of the link to their profile page (/person/…/), masked this time too. Re-assessing

after the masking changed no verdict, message or evidence line. Offline, uv run basic-check assess --run web-12 reproduces it exactly, apart from the generation time.

Every one of its 130 cells equals web-11-v3.2: the evidence of run web-11, described in the next paragraph, scored again on 29 September 2026 against v3.2 without contacting any node, and published briefly before web-12 (commit d3de829). Compared with web-11, the page text changed only in a script fragment on EOSC DTO's page and the Cloudflare ray identifier on GÉANT's.

Run web-11 was collected on 28 September 2026 at 13:48 UTC by the GitHub workflow (run 36431202625, commit f4eaebd, unit tests passing first) against checklist v3.1 at --depth 1 and assessed against the official unscoped names list (13 names, SHA-256 46af586b…). It is the first run with CERN's new Node Landing Page, https://eosc.cern/, which replaced the INDIGO IAM sign-in URL https://eosc-auth.cern.ch/login in the same commit. All thirteen nodes were assessed and none was skipped. The run made 44 requests (13 landing pages and 31 child pages). Twelve landing pages returned HTTP 200. GÉANT returned HTTP 403 with the Cloudflare challenge. The evidence was masked as it was collected, and a search of every evidence file and report found no personal address or phone number. Two personal names that the masking does not cover were then removed by hand from the evidence, each replaced by a placeholder of the same length so every character count and verdict stays as collected: a quotation attribution on CERN's page (in cern.json and in its screenshot) and the node coordinator named on EGI's page (in egi.json, where it had also been in earlier published runs). The masking handles addresses and phone numbers only, so a new run needs the same check for names. Its evidence, restored from commit d3de829, reproduces it with -c checklist/v3.1.yaml --run web-11 as published on 28 September (49 PASS, 8 FAIL, 73 MANUAL_REVIEW), apart from the generation time.

The run before it, web-10 (run 36429362417, commit c90761b), was the first with EOSC Node Poland (eosc-pl, https://eosc.pl/), which replaced a node listed by mistake on 28 September 2026; the name list changed in the same commit ("EOSC Node | Poland" in place of that node's name). Apart from Poland's new row, its verdicts repeated run web-9 of 26 September cell for cell, and web-11 repeats web-10 apart from CERN's row.

Verdict	Cells
🟢 PASS	49
🔴 FAIL	14
🟠 MANUAL_REVIEW	67
🟣 ERROR	0
Total	**130** (13 nodes × 10 points)

Seven FAILs are point 4. Four landing pages have no eosc.eu link at all (Data Terra, EOSC Finland, EGI, Italy), two link only to the federation index (PaNOSC, Czechia), and one only to the eosc.eu homepage (Poland). The eighth is Italy's point 6: none of its links is a contact route. Italy's page rendered with 15 links, but its main text is short, so both of its FAILs should be looked at by hand.

The other six FAILs were new with the first copy of v3.2: points 5b and 5c for CERN, Data Terra and PaNOSC, whose landing pages link to no AUP, no UAP and no licence. Under v3.1 all six were review, and under the re-issued v3.2 they are review again (above). Per node, 5b and 5c under the first copy of v3.2:

5b / 5c	Nodes	Why
FAIL / FAIL	CERN, Data Terra, PaNOSC	no policy link on the NLP
PASS / PASS	Slovakia	one "Terms of Use (incl. AUP and UAP)" document

5b / 5c	Nodes	Why
PASS / review	Czechia, EOSC DTO, EOSC Finland, EUDAT, EGI, Poland, Italy	an AUP or terms of use is linked; one document may be both, so the UAP is left to a reviewer
review / PASS	BBMRI-ERIC	a UAP is linked, the AUP is left to a reviewer
review / review	GÉANT	HTTP 403, the page was not served

Every PASS here settles only the NLP half of item 5: the tool does not read the Catalogue metadata, and the reviewer action says so.

CERN, new landing page: 4 PASS (1, 4, 6 via its Contact page, 7), 2 FAIL (5b, 5c, under the first copy of v3.2; review under the re-issued one) and 4 review. Points 1 and 4 moved from review to PASS against the sign-in URL of web-10: the page is public, renders about 6,000 characters, and links to https://eosc.eu/building-the-eosc-federation/eosc-node-cern. Point 3 is review: the logo reads "EOSC Node | CERN", but the approved name is not in the page text.

Poland, first assessed in web-10: 4 PASS (1, 5b on its Terms of use, 6 on support@eosc.pl, 7), 1 FAIL (4) and 5 review. Point 3 is review: the header logo reads "EOSC Node | Poland", but the approved name is not in the page text.

Compared with the reviewed run below, the runs of 26 September found (Poland was not yet configured):

Node	Point	24 September	26 September	Why
EOSC Node Czechia	4	PASS	FAIL	links only to the federation index now
EOSC Node Czechia	5b	MANUAL_REVIEW	PASS	
EOSC Node Czechia	6	MANUAL_REVIEW	PASS	
GÉANT	1, 5b, 6	PASS	MANUAL_REVIEW	HTTP 403, Cloudflare challenge
GÉANT	4	FAIL	MANUAL_REVIEW	HTTP 403, Cloudflare challenge
EOSC Node Italy	all	skipped	3 PASS, 2 FAIL, 5 review	first assessment

No other cell changed. BBMRI-ERIC was collected again from its www. address with the same verdicts.

Not reviewed. Unlike the run below, this one was published without a hand review, by decision of the maintainer. results/REVIEW-2026-09-24.md is kept as history: its determinations apply where a page has not changed, but not to Italy, to Czechia's changed cells or to GÉANT.

Tests pinned to the published run. Four tests were updated in the same commit. test_names.py::test_the_official_names_match_the_nodes_that_show_them now expects four matching nodes (BBMRI-ERIC, Czechia, EUDAT, Slovakia): GÉANT's page was not served, so there was no body to match. The node-scoped list finds the same four, and --strict-separators finds none.

test_update_row.py::test_published_results_are_the_run_these_tests_copy expects 13 nodes and no skip. Two tests that need a node without evidence, one in test_cli.py and one in test_update_row.py, now remove Italy from their copy of the run instead of relying on the published run to lack it.

Previous run: 24 September 2026 (reviewed)

This subsection is kept as the record of the reviewed run that web-4 (and then web-5 to web-11) replaced. Its files are in the git history at 800d632.

From results/results.json as it stood at 800d632, run live-2026-09-24-no-italy, collected live on 24 September 2026 at --depth 1 and assessed against the official unscoped names list (13 names, SHA-256 871161a5…). Twelve nodes were assessed, and EOSC Node Italy was skipped with --skip Italy because eosc.it had no address record. The run made 44 requests (12 landing pages and 32 child pages), and all 12 landing pages returned HTTP 200. The figures below are from the re-assessment at commit 29dead8, made from the same evidence after the point 6 and 5b/5c fixes. The first assessment gave 45 / 6 / 69.

> **Masked on 25 September 2026.** Commit ada1b4a masked the personal data in results/evidence/ and rebuilt the reports offline, with the node list the run was collected with (from commit 53081f6), so BBMRI-ERIC is still shown against the www. address its evidence came from. All 120 verdicts and the tally below are unchanged. The only other differences are the generation time and a few character counts, which drop by the length of the masked text. The unmasked versions remain in the git history.

Verdict	Cells
🟢 PASS	44
🔴 FAIL	6
🟠 MANUAL_REVIEW	70
Total	**120** (12 nodes × 10 points)

All six FAILs are point 4. Four landing pages have no eosc.eu link at all (Data Terra, EOSC Finland, EGI, and a node that was listed by mistake and was replaced by EOSC Node Poland on 28 September 2026), and two link only to the federation index (PaNOSC, GÉANT). Compared with the run below, EOSC DTO moved from FAIL to PASS on points 4 and 6. GÉANT was served this time, which settled points 1, 6 and 7 as PASS and point 4 as FAIL. CERN, Czechia and Slovakia appear for the first time. The point 6 and 5b/5c fixes account for the other two differences: GÉANT 5b is now PASS, and point 6 of the node listed by mistake, which passed on 21 September, is now MANUAL_REVIEW. No other cell changed.

The run was reviewed by hand before publication. The review is in results/REVIEW-2026-09-24.md, and it leaves the tool's output untouched. It found three point 6 PASSes that rest on link text alone: Czechia's "National Support" is a funding page, the node listed by mistake's is a EuroHPC proposal service, and BBMRI-ERIC's is a service overview. BBMRI-ERIC's PASS was later upheld, because its contact page lists helpdesk mailboxes. It also found one AUP link the tool missed, on GÉANT, whose link text is prose. Those limitations were recorded there and have since been fixed in the checks; see "Point 6 and 5b/5c after the review" below. The committed results/ was then re-assessed with the fixed checks from the same evidence. The review also records that the configured URLs for CERN (a sign-in form) and the node listed by mistake (a general homepage) are not descriptive landing pages, and both rows are published with that caveat.

test_names.py::test_the_official_names_match_the_nodes_that_show_them was pinned to that evidence. It then expected five matching nodes (BBMRI-ERIC, Czechia, EUDAT, GÉANT, Slovakia) in place of two. Re-measured on 25 September against the masked evidence: the node-scoped list finds the same five, and --

strict-separators finds none of the twelve, because every one of the five writes the name with a different separator from the official list.

Since the published run

A trial run on 25 September 2026, with BBMRI-ERIC's new URL, is **not published** and has not been reviewed. Two things it showed concern the tool rather than the nodes, and are recorded here for whoever runs the next collection:

- BBMRI-ERIC's dev3. address disallows every path in robots.txt, so all ten of its points were ERROR. The next published run needs either the public address or an exception for the checker. On 26 September nodes.yaml was set back to the public www. address.
- GÉANT answered HTTP 403 with the Cloudflare challenge again, and its decided cells moved to review, as on 21 September.

Point 6 and 5b/5c after the review

The review of the 24 September run found four tool issues. The three below are fixed in the checks. The fourth, noting the accepted name separators next to each point 3 match, is still open. The fixes change the assessment only, so the committed evidence was re-assessed offline and no node was contacted again.

- **Point 6 passed on link text alone.** Any link whose label contained "support" was a PASS. Now a bare "support" link is still followed but settles nothing. A PASS needs one of three things: a label or address that names a helpdesk, service desk, ticket system, support team or request; a helpdesk host (hd., support., helpdesk.) or mailbox (support@, it@helpdesk....); or a followed page that names a helpdesk, service desk or ticket system, or gives such an address. Page prose about "support" no longer counts, because the EuroHPC proposal page of the node listed by mistake says "Technical Support" and "Application Support team". Every followed page is now read, where before only the first was. BBMRI-ERIC's helpdesk mailboxes are on the second.
- **5b/5c ignored words spelled with hyphens in the address.** GÉANT links its AUP with a sentence as the label, and the words appear only in /geant-node-acceptable-use-policy/. Link matching now also reads the address with its separators turned into spaces. The crawler and the checks share that matcher (patterns.link_haystack), so a future collection will fetch the page as well.
- **The 5b/5c hint said "re-run with --depth 1" in every case.** Now it gives the actual reason the target was not fetched: the run did not follow links, the target is a PDF, a cap was reached, the target is on another site, or it was not selected when the evidence was collected. It suggests a re-run only when one would help.

Re-assessing the committed evidence with the fixed checks gives 44 PASS, 6 FAIL and 70 MANUAL_REVIEW, against 45/6/69 as first published. Exactly three cells change:

Node	Point	First assessment	Re-assessment (published)	Review determination
EOSC Node Czechia	6	PASS	MANUAL_REVIEW	not met
Node listed by mistake	6	PASS	MANUAL_REVIEW	review
GÉANT	5b	MANUAL_REVIEW	PASS (pointer)	met as a pointer

BBMRI-ERIC's point 6 stays PASS, now on the helpdesk mailboxes its contact page lists (it@helpdesk.bbmri-eric.eu, elsi-helpdesk@..., rd@helpdesk....) rather than on the "Services & Support" label. The review first proposed "review", considering only contact@bbmri-eric.eu. It was revised to "met" on this evidence.

Previous run: 21 September 2026

The rest of this section is kept as the record of the earlier published run. It no longer describes results/, which the runs above replaced; that run's files are in the git history at 47f08af.

From results/results.json as it stood at 47f08af, run 2026-09-21-1738, checklist v3.0 of 15 September 2026.

Two timestamps matter here and they are not the same. The **evidence was collected** on 21 September between 13:04 and 13:07 UTC. The **report was regenerated** from that same evidence at 17:38 UTC, after the name-matching and report-scoping work landed. No node was contacted again in between — which is the point of keeping collect and assess separate.

> **Nine nodes, not thirteen.** nodes.yaml configures thirteen nodes, but the published report covers the original **nine**. CERN, EOSC Node Czechia, EOSC Node Italy and EOSC Node Slovakia have been added to the configuration and have not been collected into the reviewed run. assess names all four as missing evidence and exits 2 rather than quietly producing a nine-row table that looks complete.

Verdict	Cells
🟢 PASS	28
🔴 FAIL	7
🟠 MANUAL_REVIEW	55
Total	**90** (9 published nodes × 10 points)

Eight of the nine landing pages answered HTTP 200; geant.org returned **HTTP 403**, redirecting to a Cloudflare bot-protection challenge, having served 200 at 12:09 the same afternoon after several runs.

Against the results committed on 18 September (26 / 6 / 58), **eleven cells changed**, from three separate causes — so this is not a single story about GÉANT:

Node	Cells	Change	Why
GÉANT	4	decided → review (point 1 PASS, 4 FAIL, 6 PASS, 7 PASS all now review)	HTTP 403. The tool declines to assess a page it cannot see
EUDAT	5	review → PASS (points 1, 4, 5b, 6, 7)	EUDAT returned HTTP 500 on 18 September and 200 now. The node was unreachable then, not non-compliant
EOSC DTO	2	review → FAIL (points 4, 6)	The render-gate fix in commit 5d347c7: a consent banner no longer excuses a missing link

Two of those three causes are the *tool's own reach* changing, not the nodes changing. Only the EOSC DTO pair reflects a corrected rule.

That GÉANT row is the safeguard from section 7 working as designed: the tool declines to assess a node it cannot see rather than publishing a block as a compliance failure. It also means the published tally is not a

like-for-like comparison with any earlier figure — one node is unassessed rather than compliant, and one node was unreachable last time.

> **The stable finding, across every run since 17 September, is point 4.** Individual verdicts move with network conditions; the point-4 column does not. Six nodes fail it outright in this run — EOSC DTO, Data Terra, EOSC Finland, PaNOSC, EGI and the node listed by mistake — and GÉANT failed it on index-only grounds at 12:09 before the block, leaving BBMRI-ERIC and EUDAT as the only two that link correctly to their own eosc.eu page. That is the finding worth taking to a self-assessment discussion, not the tally.

The run was collected at --depth 2, and **the depth-1 and depth-2 tallies are identical, cell for cell**: 28 / 7 / 55 both ways.

Node	HTTP	Pages followed	of which second-hop
BBMRI-ERIC	200	6	2
EOSC DTO (D4Science)	200	1	0
Data Terra	200	1	0
EOSC Finland	200	4	1
PaNOSC	200	4	1
EUDAT	200	7	4
EGI	200	4	1
GÉANT	**403**	0	0
Node listed by mistake	200	9	5

Point 3 in the 21 September run, and a correction to the previous edition

The previous edition stated that point 3 was review for every node "because --approved-names was not supplied". That is **not** what the published run records. A name list *was* used — the committed default, whose SHA-256 the report pins — and the run metadata says so: default_used: true, nine names.

Point 3 is MANUAL_REVIEW for all nine nodes for a different and more durable reason: **the logo half of the point is a human judgement**. The checklist asks whether the EOSC logo is "clearly and visibly" shown, and no list of names settles that. What the name list changed is the *evidence*, not the verdict:

Outcome	Nodes
An approved name matched on the page	2 — BBMRI-ERIC, EUDAT
No approved name found in the page body	6 — EOSC DTO, Data Terra, EOSC Finland, PaNOSC, EGI, the node listed by mistake
Names supplied but no page body captured (HTTP 403)	1 — GÉANT

Three caveats the tool states itself, and which matter more than the count:

- The unscoped list does not bind a name to a node, so a match shows only that *some* approved name appears — not that it is this node's own name.
- The <title> element is not searched, only the page body. Several of the six "not found" results say so explicitly.
- Most of those six pages *do* contain the phrase "EOSC Node"; what is absent is the full approved form.

The current default list carries **eighteen** names (since 10 November 2026, when Latvia and Scholarly Commons were added), one per configured node, with a scoped variant that binds each name to its node id. The 21 September run predates that and used the nine-name version. The published run of 24 September used the thirteen-name list, and point 3 is MANUAL_REVIEW for all twelve of its nodes, for the same reason.

11. Worked examples

Three step-by-step procedures, one for each change that comes up most often: adding a node, changing a node's URL, and adopting a new revision of the checklist. Each lists which files to edit, the exact commands, and how to put the result into the published results/ directory.

Four rules apply to all three:

- **Try it in a scratch folder first.** --results /tmp/trial writes nowhere near results/, so nothing published changes until you decide it should.
- **Run uv run pytest -q after every edit.** It needs no network, takes a few seconds, and names the file you got wrong.
- **Contact as few sites as possible.** Only collect and run send requests. assess works on saved evidence, so it can be repeated as often as you like.
- **A new published run needs a human review before it is committed.** The tool's verdicts are not a compliance statement (see "Reading the output" in the run guide). Write the review down, as results/REVIEW-2026-09-24.md does for the 24 September run, and commit only then.

The run labels below (live-2026-10-01-...) are examples. Use the date of your own run.

Example 1 — adding a node and publishing it

The example adds a node with the placeholder id eosc-example. Replace every value with the real ones.

Step 1: edit three files. All three are at the repository root or in checklist/, and all are edited by hand.

nodes.yaml: add the entry. url is the landing page as registered in the EOSC EU Node Contributors Dashboard ("Website address", section 1.2, field 6). Copy eosc_page from the federation index; do not guess it.

```
- id: eosc-example
  name: EOSC Node Example
  url: https://eosc-node.example.org/
  eosc_page: https://eosc.eu/building-the-eosc-federation/eosc-node-example/
```

checklist/approved-names.txt: add the approved name exactly as the Tripartite list writes it:

```
EOSC Node | Example
```

checklist/approved-names-scoped.txt: add the same name, with the node id in front:

```
eosc-example: EOSC Node | Example
```

If the Tripartite list does not include the node yet, do not make a name up. Leave both name files alone. test_nodes.py::test_every_node_has_a_scoped_approved_name then fails and names the node, which is intended: the node is not ready to be published. In the meantime, check it in a scratch folder with --url https://eosc-node.example.org/ (see "Ad hoc URLs" in section 5), which needs no configuration.

Step 2: check the configuration, offline.

```
uv run pytest -q
```

A missing scoped name, an id that is not a valid filename, a URL that is not https, an eosc_page outside eosc.eu, or a landing page already used by another node each fail with a message naming the problem.

Step 3: trial run for the new node only. This contacts one site.

```
uv run basic-check collect --only eosc-example --results /tmp/trial
uv run basic-check assess  --only eosc-example --results /tmp/trial
uv run basic-check show eosc-example --results /tmp/trial
```

Open /tmp/trial/index.html or /tmp/trial/results.md and read the new row. If the page returned ERROR (robots.txt, a 403, a DNS failure), stop there. An ERROR row is not a result worth publishing.

Step 4: put the node into the published run. There are two ways.

A — add the one node to the current run (one site contacted, and already done). Reuse the evidence from step 3 rather than fetching the page again:

```
cp /tmp/trial/evidence/eosc-example.json results/evidence/
cp /tmp/trial/evidence/screenshots/eosc-example.png results/evidence/screenshots/
uv run basic-check assess --only eosc-example --skip Italy \
  --run live-2026-10-01-plus-eosc-example
```

The report covers every node. A **Mixed freshness** banner says that only eosc-example is new and that the other rows are reused from the earlier capture, with its date. The published run includes Italy, read at https://eosc.it/ since 1 October 2026, so no --skip is needed; skip a node only while a trial collection (collect --only <id> --results /tmp/trial) shows its page does not load.

B — a complete new run (every node contacted once). Use this when the existing evidence is old enough that a single timestamp is worth more than leaving the other sites alone:

```
uv run basic-check run --skip Italy --results /tmp/new-run --run live-2026-10-01
# review /tmp/new-run/results.md and index.html, then:
rm -rf results/evidence
cp -r /tmp/new-run/evidence results/evidence
uv run basic-check assess --skip Italy --run live-2026-10-01
```

The last command re-renders the reports in results/ from the evidence you reviewed. It makes no requests.

Either way, assess must end with **exit code 0**. Exit 2 means a configured node has no evidence, so the table is incomplete.

> **If assess warns "Evidence from a different URL".** It means a node's URL in nodes.yaml is not the page its evidence was collected from. That is the case for BBMRI-ERIC from 25 to 26 September 2026, when nodes.yaml had the dev3. address but the published evidence was from the www. one. The warning also appears as a banner in both reports. Either collect that node again first (example 2), or assess with the node list the evidence was collected with, plus the new entry:

```
git show 53081f6:nodes.yaml > /tmp/nodes-published.yaml
# append the eosc-example entry from step 1 to /tmp/nodes-published.yaml
uv run basic-check assess --nodes /tmp/nodes-published.yaml --only eosc-example \
  --skip Italy --run live-2026-10-01-plus-eosc-example
```

Step 5: re-run the tests against the new published run.

```
uv run pytest -q
```

Two tests read the committed evidence. Each exists to make a change visible, not to be satisfied mechanically:

- test_privacy.py::test_the_committed_evidence_publishes_no_personal_address_or_phone must pass as it stands. If it fails, personal data is about to be published. Stop and find out why; never change the test to let it through.
- test_names.py::test_the_official_names_match_the_nodes_that_show_them pins which nodes display their approved name (four for the 26 September run; five on 24 September, when GÉANT's page was served). If the new page shows its name, add its id to the expected set and update the docstring to say why.
- test_update_row.py::test_published_results_are_the_run_these_tests_copy pins how many nodes the run has and which were skipped (13 and none, for run web-13). Update it to the new run's shape.

Step 6: update what quotes the published figures, then commit. results/ is regenerated, but these are written by hand:

- a review document for the new run, like results/REVIEW-2026-09-24.md;
- the headline tally in README.md ("130 cells: 69 PASS · 0 FAIL · 61 review");
- section 10 of this document ("The published figures"), and the node list in section 5 ("The node list — a YAML file").

```
git status
git add nodes.yaml checklist/approved-names.txt checklist/approved-names-scoped.txt \
      results README.md docs tests
git commit -m "Add eosc-example; publish run live-2026-10-01-plus-eosc-example"
git push
```

Example 2 — changing a node's landing page URL

The example is the change actually made on 25 September 2026: BBMRI-ERIC moved from https://www.bbmri-eric.eu/eosc-node-bbmri-eric/ to https://dev3.bbmri-eric.eu/eosc-node-bbmri-eric/. It was set back on 26 September, because the dev3. host's robots.txt excludes the checker, so nodes.yaml has the www. address again.

Which files change. One line in one file: url for that node in nodes.yaml. Nothing else in the repository stores a node's URL. Add a comment recording the old address and the date, so the published evidence can still be traced:

```
- id: bbmri-eric
  name: BBMRI-ERIC
  # URL changed on 25 September 2026, from
  # https://www.bbmri-eric.eu/eosc-node-bbmri-eric/
  url: https://dev3.bbmri-eric.eu/eosc-node-bbmri-eric/
  eosc_page: https://eosc.eu/building-the-eosc-federation/eosc-node-bbmri-eric/
```

Change eosc_page as well only if the node's own entry on eosc.eu moved; a new landing page does not usually mean a new eosc.eu entry. The name files change only if the node's approved name changed. Keep the id: it names the evidence file, and changing it would make the node look new.

Step 1: check the configuration.

```
uv run pytest -q
```

Step 2: trial run for that node only. This contacts one site.

```
uv run basic-check collect --only bbmri-eric --results /tmp/trial
uv run basic-check assess  --only bbmri-eric --results /tmp/trial
uv run basic-check show bbmri-eric --results /tmp/trial
```

Check that the page actually loaded before going further. On 25 September the dev3. host's robots.txt disallowed every path, the tool honoured it, and all ten points were ERROR. A result like that is not worth publishing: ask the node for its public address, or for the checker to be allowed, and stop there.

Step 3: update that node's row in the published run. Only BBMRI-ERIC is fetched again; the other rows are copied from results/results.json as they are, neither re-fetched nor re-judged:

```
uv run basic-check run --update-results-for-node bbmri-eric
```

That fetches the one page into a scratch directory, and only if the page loaded does it replace bbmri-eric's evidence, screenshot and row, then rebuild results.md, index.html and results.csv from the stored rows. A failed fetch changes nothing (add --accept-error to record it anyway). It prints each point's old and new verdict, and both reports gain an **Updated rows** banner naming the node, the date and the previous URL. The run id and time in the header stay those of the original run. To reuse the evidence from step 2 instead of fetching again, copy it into results/evidence/ and run uv run basic-check assess --update-results-for-node bbmri-eric, which is offline. To see the outcome before touching the published run, try it on a copy first: cp -r results /tmp/copy and add --results /tmp/copy. For a completely fresh table instead, follow path B of example 1 step 4.

Why the order matters. assess labels each row with the URL in nodes.yaml, but takes the verdicts from the evidence on disk. Between step 1 and step 3, the two describe different pages. assess now detects this. It prints a warning naming the node and both URLs, puts an **Evidence from a different URL** banner in results.md and index.html, and records the pair under url_mismatch in results.json. Step 3 clears it, because the evidence now comes from the configured URL.

To rebuild a run collected with an older node list, without the warning, use that list. For the reviewed run of 24 September (in the git history at 800d632), assessed in a scratch copy of its results/:

```
git show 53081f6:nodes.yaml > /tmp/nodes-2026-09-24.yaml
uv run basic-check assess --run live-2026-09-24-no-italy --skip Italy \
  --nodes /tmp/nodes-2026-09-24.yaml
```

Step 4: tests, review, commit. As in example 1, steps 5 and 6: run uv run pytest -q, check the two tests that read the committed evidence, write the review, update the quoted figures, and commit nodes.yaml, results/ and the documents together.

Example 3 — moving to a new revision of the checklist

There is no URL to change. The tool never downloads the checklist document. A copy of it is committed in checklist/, and three things connect the tool to it:

Where	What it says
src/basic_check/cli.py, the line DEFAULT_CHECKLIST = ROOT / "checklist" / "v3.2.yaml"	Which checklist revision is used when --checklist is not given. **This is the one line to change** to make a new revision the default. The help texts, the tests and the reports all follow it.
checklist/vX.Y.yaml: checklist_version, checklist_date, source_document, source_file, source_sha256	Which document that revision was transcribed from, and its SHA-256 hash.

Where	What it says
--checklist / -c <file> on assess, run and points	A different revision for a single run, without changing the default.

When the originating document changes, you therefore add a new file for the new revision and point the default at it. v3.2.yaml is never edited: the published reports name the file they were produced from.

The example assumes a v3.3 dated 15 October 2026. Use the real version, date and filenames. This procedure was last applied on 29 September 2026, to move from v3.1 to v3.2 (and before that on 26 September, from v3.0 to v3.1); the header of checklist/v3.2.yaml records what changed, point by point.

Step 1: commit the new document next to the old one.

```
cp ~/Downloads/20261015_Node_Landing_Page_Verification_Checklist_v3.3.pdf checklist/
sha256sum checklist/20261015_Node_Landing_Page_Verification_Checklist_v3.3.pdf
# on macOS: shasum -a 256 checklist/20261015_Node_Landing_Page_Verification_Checklist_v3.3.pdf
```

The committed v3.2 file is a PDF rendering of the circulated .docx. Commit the .docx itself if you prefer: source_file may name either.

Step 2: create the new revision's file from the old one.

```
cp checklist/v3.2.yaml checklist/v3.3.yaml
```

In checklist/v3.3.yaml, change the header:

```
checklist_version: "3.3"
checklist_date: "2026-10-15"
source_document: 20261015_Node_Landing_Page_Verification_Checklist_v3.3.docx
source_file: 20261015_Node_Landing_Page_Verification_Checklist_v3.3.pdf
source_sha256: <the hash printed in step 1>
```

The version must match the filename (v3.3.yaml declares "3.3"); a test enforces this.

Step 3: compare every point with the new document. No tool can do this step for you. For each point in v3.3.yaml:

- If the wording changed, update title and requirement, which are quoted word for word. Then read the check_* function named in implemented_by, in src/basic_check/checks.py, and change it if it no longer applies the new wording.
- If what a script can decide changed, update decidable and decidable_note.
- If a point was **added**, write a new check_<id> function in checks.py, call it from run_all() in checklist order, name it in the point's implemented_by, and add tests for it to tests/test_checks.py.
- If a point was **removed**, delete its entry, its function and its tests.
- If a rule became **stricter or looser**, older runs must keep the rule they were made under. Do not simply change the function: give it a switch, pass the switch from run_all(), and declare it in the new YAML only, so the older files select the old rule by its absence. v3.2 did this for item 5: item5_on_nlp: true in v3.2.yaml, read by _item5_on_nlp in cli.py, selects the rule that the AUP and UAP must be linked from the NLP, and v3.0.yaml/v3.1.yaml, which lack the key, keep "on the NLP or in the Catalogue". Add tests for both rules, and rebuild the published run with the old file to prove it is unchanged.

Step 4: try the new revision offline, before switching. -c applies it to one run only. Re-scoring saved evidence contacts no one:

```
uv run basic-check points -c checklist/v3.3.yaml
mkdir -p /tmp/v33 && cp -r results/evidence /tmp/v33/
uv run basic-check assess -c checklist/v3.3.yaml --results /tmp/v33 --run trial-v3.3
```

Compare /tmp/v33/results.md with results/results.md. Any difference comes from the new rules alone, since the evidence is the same. If the published run skipped a node or used an older nodes.yaml, pass the same --skip and --nodes here.

Step 5: make it the default, and run the tests. In src/basic_check/cli.py:

```
DEFAULT_CHECKLIST = ROOT / "checklist" / "v3.3.yaml"
uv run pytest -q
uv run basic-check --help     # now says "against checklist v3.3"
```

The tests check the new file's hash, that its version matches its filename, and that every point maps to exactly one check_* function and every function to one point. They also check that v3.2.yaml and its document are still intact, so older runs can still be rebuilt with -c checklist/v3.2.yaml. What they cannot check is whether a rule is right: that is step 3.

Step 6: produce and publish the results. The default revision is now v3.3, so no -c is needed. Choose between the same two paths as in example 1:

```
# fresh evidence from every node:
uv run basic-check run --results /tmp/new-run --run live-2026-10-20-v3.3
# review, then:
rm -rf results/evidence && cp -r /tmp/new-run/evidence results/evidence
uv run basic-check assess --run live-2026-10-20-v3.3
```

Alternatively, re-score the published evidence against v3.3 without contacting anyone, as in step 4 but writing to results/. The report then says v3.3, while the capture date is still that of the evidence.

The reports now link to results/checklist-v3.3.html. The old results/checklist-v3.2.html stays behind; remove it, and update the places that name v3.2 in prose or links:

```
git rm results/checklist-v3.2.html
rg -n "v3\.2" README.md docs checklist/README.md .github
```

In README.md, the table of checklist points links each point to results/checklist-v3.2.html#p…. Those links break once the file is removed, so change them to v3.3.

Step 7: tests, review, commit. As in example 1, steps 5 and 6. If any check_* function changed in step 3, also update its decision procedure in section 5 of ANALYSIS-WORKFLOW.md, which describes each point's rule branch by branch. Commit the new document, checklist/v3.3.yaml, cli.py, any changed checks and tests, results/ and the documents together, so the commit shows the whole change.

Sources

- Checklist: *Node Landing Page Verification Checklist v3.2*, 28 September 2026, committed as checklist/20260928_Node_Landing_Page_Verification_Checklist_v3.2.pdf and transcribed to checklist/v3.2.yaml with its SHA-256 pinned

- EOSC Federation node index: https://eosc.eu/building-the-eosc-federation/
- Repository: https://github.com/marioreale/eosc-basic-compliance
- Figures in section 10, current run: results/results.json, run web-13, collected 28 September 2026 at depth 2 by workflow run 36494907672 under checklist v3.2, not reviewed; the same verdicts as run web-12 (workflow run 36493197701) and the same verdicts as run web-11 (workflow run 36431202625) re-scored offline against v3.2
- Figures in section 10, 24 September run: results/results.json at commit 800d632, run live-2026-09-24-no-italy, reviewed in results/REVIEW-2026-09-24.md
- Figures in section 10, previous run: results/results.json at commit 47f08af (unchanged since 014682c) — evidence collected 21 September 2026 13:04–13:07 UTC, report regenerated 17:38 UTC
- Approved node names: checklist/approved-names.txt (eighteen names, SHA-256 b9f0fbec…, since 10 November 2026; sixteen, 24b816b0…, from 20 October 2026; fifteen, e23f7d1c…, from 9 October 2026; thirteen names, 46af586b…, from 28 September 2026; 871161a5… before, with the name of the node listed by mistake) and the node-scoped variant checklist/approved-names-scoped.txt
- Test counts, line counts, runtimes, name-list results and command options in this document were measured on 25 September 2026 against a clean clone of the repository state it is committed with (the test count re-checked on 26 September at 4c5dea7), not carried over from the previous edition