Contrasting a Model Against Its Own Interventions: Hop-Graph Contrastive Decoding for Causally Grounded Multi-Hop Reasoning

Anonymous Authors

Abstract

Language models often reach the right answer without using the reasoning chain they write, and fail when spurious context or parametric shortcuts dominate. Context-aware decoding (CAD) and its variants counter this by contrasting the next-token distribution with and without the context. We give a causal reading of CAD: its contrast estimates the *total* effect of the *whole* context, including paths through distractors that have no causal edge to the answer. We propose HGCD (Hop-Graph Contrastive Decoding), a training-free decoding rule that contrasts the model against *interventions on its own reasoning graph*. HGCD (i) parses the model's chain into a directed reasoning graph (DRG), (ii) intervenes on each answer-relevant hop together with its graph descendants, and (iii) re-weights answers by their probability plus α times the average *total effect* of the chain on them, computed in probability space. Under explicit and testable assumptions we show that (a) the common "mask one step" estimator measures a controlled direct effect that vanishes on bridge-entity chains, (b) probability-space contrast cancels shortcut and distractor components of a mixture reader exactly, whereas CAD amplifies distractor components, and (c) in the $\alpha \to \infty$ limit HGCD selects the answer with maximal hop-level probability of necessity and sufficiency (PNS). We pair the method with an evaluation protocol in which every intervention is a binary, programmatic manipulation with a *known* ground-truth effect (renaming, reordering, distractor injection, placebo insertion: true effect 0; inserted redundant hops: true necessity 0), on CLUTRR (controlled kinship graphs, ID $k \leq 4$ / OOD $k \geq 5$) and MuSiQue (real text, bridge-entity chains). All code runs end to end on a free Kaggle GPU.

1 Introduction

Chain-of-thought prompting [31] makes models write intermediate steps, but writing a step is not the same as *using* it. Causal tests show that models frequently ignore or post-rationalise their own chains [9, 14, 26, 27], answer multi-hop questions through single-hop shortcuts [2, 12, 33], and are easily derailed by irrelevant context [19]. Two families of remedies exist. *Training* remedies (counterfactual preference objectives [8, 14], PNS-filtered supervision [34], causality-aware post-training [6]) are effective but costly. *Decoding* remedies are training-free: contrastive decoding [11, 13], classifier-free guidance [18], and context-aware decoding (CAD) [20] with its adaptive and gated successors [23, 29].

CAD scores tokens by $(1+\alpha)\log \pi(\cdot \mid c, x) - \alpha \log \pi(\cdot \mid x)$. Read causally, the log-ratio is the effect of $\mathrm{do}(C{=}c)$ versus $\mathrm{do}(C{=}\varnothing)$: the total effect of the *entire* context. In multi-hop QA the context contains supporting paragraphs on the causal path to the answer and distractors that are not; CAD amplifies both. This offers a causal explanation for the empirical failures of CAD on uninformative or distracting context that motivated AdaCAD and NWCAD [23, 29].

Idea. Instead of contrasting *with versus without context*, contrast the model's answer distribution *given its own chain* against the distribution under *interventions on the hops of that chain*, keeping the context fixed. Because the context is held fixed in both terms, distractor and parametric components cancel; because interventions follow the chain's own graph, the contrast measures the *path-specific* contribution of the reasoning steps.

Contributions.

1. **A causal account of contrastive decoding** for multi-hop reasoning: CAD estimates a total context effect that includes non-causal distractor paths (proposition 3).
2. **HGCD**, a training-free rule that contrasts the model against graph-aware interventions on its own reasoning chain, with an optional evidence-level variant (L1) that uses a *type-matched counterfactual context* instead of an empty one (section 4).
3. **Theory**: naive step masking measures a controlled direct effect that is zero on bridge chains (proposition 1); probability-space contrast cancels shortcut and distractor mixture components exactly (proposition 2); HGCD converges to a hop-level PNS rule (proposition 4), connecting decoding to the identifiability results of Yu et al. [34].
4. **A verifiable evaluation protocol**: binary, programmatic interventions with known ground-truth effects, an estimator-validation benchmark with known necessity labels, placebo controls, and paired statistics; everything reproducible on one free T4 GPU.

2 Related Work

Faithfulness of reasoning chains. Lanham et al. [9] intervene on model-written chains (truncation, inserted mistakes, paraphrases); Turpin et al. [26] show biased features steer answers without being verbalised; FRODO [14] uses causal mediation [28] and trains small models with counterfactual preferences; FUR [27] measures faithfulness by unlearning steps; Thought Anchors [3] measures step importance by counterfactual resampling. We use interventions not only to *measure* but to *decode*.

Necessity and sufficiency. Yu et al. [34] define step-level probabilities of necessity and sufficiency for chain-of-thought, prove identifiability under exogeneity and monotonicity (building on Pearl [16], Tian and Pearl [24]), and use PNS to prune chains for in-context learning and fine-tuning. We show the same quantity arises as the limit of a decoding rule, and we separate direct from total effects [15].

Contrastive and guided decoding. Contrastive decoding [11, 13], DoLa [4], CFG [18], CAD and its adaptive/gated variants [20, 23, 29] contrast distributions under different models, layers or contexts. Visual contrastive decoding [10] uses a *distorted* rather than empty input; our L1 variant is the textual analogue with a type-matched counterfactual. Pced [5] treats each retrieved document as an expert contrasted with a no-context baseline; RED [32] multiplies image- and rationale-conditional distributions in vision-language models. None of these intervene on the hops of the model's own reasoning graph, distinguish direct from total effects, or relate the contrast to PNS.




Figure 1: Task SCM. Solid: bridge chain. Dashed blue: extra edges of compositional chains. Red dotted: spurious distractor path that the *reader* may use but the task graph forbids. Gray: parametric shortcut. CAD's contrast includes the red path; HGCD holds P fixed and contrasts interventions on H_j only.

Causal analyses of reasoning. Stolfo et al. [22] quantify robustness of mathematical reasoning through interventions on a causal graph of the input; Zečević et al. [35] argue models "talk" causality without being causal; text-intervention effect estimation [7] uses LLM rewrites as treatments. Our interventions are programmatic, so their ground-truth effects are known exactly.

3 Setup: a Structural Causal Model of Multi-Hop Reasoning

Variables. A question Q, a context $P = (P_{\text{sup}}, P_{\text{dist}})$ of supporting and distractor passages, a chain of hops $H_1, \ldots, H_k$, and an answer A. Each hop is rendered as `Hop` i`:` ⟨`body`⟩ `=>` ⟨`result`⟩. The model acts as a *reader* mechanism $\pi(a \mid Q, P, h_{1:k})$ over a finite candidate set $\mathcal{A}$.

Two task graphs. In *bridge* chains (MuSiQue), hop j resolves an entity that the next hop consumes and the answer is the result of the last hop: $Q \to H_1 \to \cdots \to H_k \to A$, with $P_{\text{sup},j} \to H_j$. In *compositional* chains (CLUTRR), every hop contributes a relation that is composed into the answer: $H_j \to A$ for all j and $H_j \to H_{j+1}$ through the shared entity. Distractors have no edge to A in either task graph (fig. 1).

Directed reasoning graph (DRG). Given a generated chain $y = (h_1, \ldots, h_k)$ we add an edge $i \to j$ $(i < j)$ if the result of h_i is mentioned in the body of h_j. Terminal hops are those whose result is the query target (CLUTRR) or the last hop (MuSiQue); the *relevant set* $\mathcal{R}(y)$ contains the terminal hops and their DRG ancestors. Hops outside $\mathcal{R}(y)$ have no directed path to the answer.

Interventions on hops.

Definition 1 (Naive and graph-aware interventions)**.** y_j^{nai} *replaces hop* j *by a mask token and leaves all other hops unchanged.* y_j^{tot} *masks hop* j *and, in every DRG descendant* d *of* j*, masks every mention of the results of* j *and of* d*. The latter is a deterministic, rollout-free approximation of* $\text{do}(H_j{=}\perp)$*: descendant values are functions of* h_j*, hence unknown under the intervention. A* placebo *rewrites hop* j *without changing its entities or relation.*

For an answer a we write $\Delta_j^{\text{nai}}(a) = \pi(a \mid y) - \pi(a \mid y_j^{\text{nai}})$ and $\Delta_j^{\text{tot}}(a) = \pi(a \mid y) - \pi(a \mid y_j^{\text{tot}})$, suppressing Q, P.

Algorithm 1 HGCD (L2) for one question

$y \leftarrow$ greedy chain from the model (optionally with L1 contrast on result tokens)
Parse hops; build DRG; compute relevant set $\mathcal{R}(y)$
$p \leftarrow \pi(\cdot \mid Q, P, y)$ over $\mathcal{A}$ ▷ one forward + KV-cached candidates
for $j \in \mathcal{R}(y)$ **do**
    $p_j \leftarrow \pi(\cdot \mid Q, P, y_j^{\text{tot}})$
end for
return $\arg\max_{a \in \mathcal{V}_\beta} (1+\alpha) p(a) - \alpha \operatorname{mean}_j p_j(a)$

What is (and is not) causal here. We do not assume the language model *is* an SCM of the task. The reader π is a deterministic function of its input, so editing hops in the prompt is an exact intervention on the reader's input, and Δ_j is an exact (not estimated) effect *on the reader*. The task SCM only supplies ground truth: which hops are necessary, and which input changes should have no effect on the answer.

Mask-token artifacts. Replacing text by `[MASKED]` is itself out of distribution. Our estimator benchmark controls for this: the inserted redundant hop is masked in exactly the same way, so any effect caused by the mask token alone appears as a non-zero Δ on redundant hops and lowers the AUC. In addition, a *mask-marker* control inserts `[MASKED]` into hop j while keeping all of its content; its effect Δ_j^{marker} measures the mask-token artifact directly and should be ≈ 0.

4 Method: Hop-Graph Contrastive Decoding

Answer-level rule (L2). With uniform weights $w_j = 1/|\mathcal{R}(y)|$ on relevant hops and a plausibility set $\mathcal{V}_\beta = \{a : \pi(a \mid y) \geq \beta \max_{a'} \pi(a' \mid y)\}$ [11],

$$\hat{a} = \arg\max_{a \in \mathcal{V}_\beta} s_\alpha(a),$$
$$s_\alpha(a) = (1+\alpha)\,\pi(a \mid y) - \alpha \sum_{j \in \mathcal{R}(y)} w_j\, \pi(a \mid y_j^{\text{tot}}) = \pi(a \mid y) + \alpha \sum_{j \in \mathcal{R}(y)} w_j\, \Delta_j^{\text{tot}}(a). \tag{1}$$

The score is the answer probability plus α times the average total effect of the answer-relevant hops on that answer. Redundant hops ($j \notin \mathcal{R}(y)$) are never contrasted.

Evidence-level rule (L1). While emitting the *result* tokens of a hop, we contrast the real context P with a type-matched counterfactual $\tilde{P}$ of identical length and entity types in which the relational content differs (on CLUTRR: names permuted within each gender group, so every sentence and entity type is kept but who-is-related-to-whom changes; we evaluate L1 on CLUTRR only, where $\tilde{P}$ is exactly type-matched): $t^\star = \arg\max_{t \in \mathcal{V}_\beta} (1+\alpha)\pi(t \mid P, \cdot) - \alpha\pi(t \mid \tilde{P}, \cdot)$. Unlike an empty context, $\tilde{P}$ is in-distribution and controls for length and type cues.

Remark 1 (What each level can fix)**.** *L2 makes the answer depend* more *on the chain; it therefore repairs* readout *errors (chain correct, answer wrong because a shortcut or distractor dominates the readout) but cannot repair a wrong chain—it may even commit harder to one. Chain errors are the target of L1, which acts while the hops are produced. We test this split directly (hypothesis 4).*

Cost. L2 needs $1 + |\mathcal{R}(y)|$ prefix forwards and a KV-cached pass over the candidate tokens; no extra generation. L1 doubles the forward cost of result tokens only.

Choice of α. α is selected on the CLUTRR validation split and frozen (ties broken toward the smaller α, so HGCD reduces to CoT absent evidence); an adaptive variant sets $\alpha \cdot \mathrm{JSD}(p, \bar{p}_j)$ as in AdaCAD [29].

5 Theory

All proofs are short and given in appendix A; the propositions make predictions that our protocol tests directly.

Assumption 1 (Markov reader on bridge chains)**.** *For bridge chains, $\pi(a \mid h_{1:k})$ depends on $h_{1:j}$ only through $h_{j+1:k}$ whenever h_{j+1} restates the result of h_j $(j < k)$.*

Proposition 1 (Naive masking is a direct effect)**.** $\Delta_j^{\mathrm{nai}}(a)$ *equals the controlled direct effect of H_j on A with $H_{j+1:k}$ held at their observed values. Under assumption 1, $\Delta_j^{\mathrm{nai}}(a) = 0$ for every $j < k$ on bridge chains, whereas $\Delta_j^{\mathrm{tot}}(a)$ is not constrained to zero. On compositional chains, where A reads each hop's relation, the direct effect is generally non-zero.*

Prediction. On CLUTRR both estimators separate necessary from redundant hops; on MuSiQue, $\Delta^{\mathrm{nai}} \approx 0$ on non-final gold hops while Δ^{tot} remains large, so the gap between the two appears in the position breakdown of table 1.

Assumption 2 (Mixture reader)**.** $\pi(a \mid Q, P, y) = \lambda_c \pi_c(a \mid y, P_{\mathrm{sup}}) + \lambda_s \pi_s(a \mid Q) + \lambda_d \pi_d(a \mid P_{\mathrm{dist}})$*, with λ's non-negative, summing to one, and invariant to interventions on hops.*

Proposition 2 (Exact cancellation in probability space)**.** *Under assumption 2,*

$$s_\alpha(a) = \pi(a \mid y) + \alpha\lambda_c \sum_j w_j \big[\pi_c(a \mid y) - \pi_c(a \mid y_j^{\mathrm{tot}})\big],$$

i.e. the shortcut π_s and distractor π_d components cancel in the contrast for every α. The log-space analogue does not cancel them.

Proposition 3 (CAD amplifies distractor paths)**.** *Under assumption 2 applied to direct answering, with no-context distribution $\pi_s(a \mid Q)$, CAD's score is $(1{+}\alpha)\log\big[\lambda_c\pi_c{+}\lambda_s\pi_s{+}\lambda_d\pi_d\big](a){-}\alpha\log\pi_s(a \mid Q)$. For any $\alpha > 0$ and any gold answer g, a distractor answer a_d with $\pi_d(a_d) = 1$ is preferred by CAD whenever $\pi_s(a_d \mid Q)$ is small enough, even if $\pi(g \mid Q, P) > \pi(a_d \mid Q, P)$. In contrast, HGCD's contrast term does not depend on π_d at all (proposition 2).*

Prediction. Under distractor injection, CAD's accuracy degrades more than HGCD's, i.e. $|\mathrm{ATE}_{\mathrm{distract}}|$ is larger for CAD.

Proposition 4 (PNS limit)**.** *Interpret $\pi(a \mid y_j^{\mathrm{tot}})$ as $P(A{=}a \mid \mathrm{do}(H_j{=}\perp))$ and assume exogeneity and monotonicity as in Yu et al. [34]. Then $\Delta_j^{\mathrm{tot}}(a) = \mathrm{PNS}_j(a)$ and $\lim_{\alpha\to\infty} s_\alpha(a)/\alpha = \sum_{j\in\mathcal{R}(y)} w_j \,\mathrm{PNS}_j(a)$. Hence, within $\mathcal{V}_\beta$, HGCD interpolates between the most probable answer ($\alpha{=}0$) and the answer for which the relevant hops are, on average, most necessary and sufficient.*

6 Experimental Protocol

Data. CLUTRR [21] (`gen_train234_test2to10`), restricted to clean simple-path stories (the filter is reported), gives exact gold paths; ID $k \in \{2, 3, 4\}$, OOD $k \geq 5$; answers are scored over the 20 kinship relations. **MuSiQue-Ans** [25] gives real text with gold decompositions; the context holds

the supporting paragraphs plus 4 distractors. MuSiQue was built to resist single-hop shortcuts [12], which is why we prefer it to HotpotQA. Candidates for MuSiQue are built without the gold answer: the model's own answer and hop results, then paragraph titles, capitalised spans and dates/numbers from the context, in order of appearance, capped at 64 (recall of the gold answer is 56% on 600 dev questions before adding the model's strings, versus 10.5% for titles alone). All methods share the same candidate set and we report its recall.

Binary interventions with known effects.

Intervention	Definition (programmatic, seeded)	True effect on A
`rename`	all names $\to$ fresh fictional names (gender-preserving)	0
`order`	shuffle story sentences / paragraphs	0
`distract` / `dist8`	insert a disconnected family / 4 extra distractor paragraphs	0
`placebo_input`	insert two neutral sentences without entities	0
redundant hop	insert a true but off-path fact as a hop of a gold chain	necessity 0

For each method we report the paired ATE $\mathbb{E}[Y(1) - Y(0)]$ on accuracy with bootstrap 95% CIs; a robust method has ATE ≈ 0. `placebo_input` controls for "any change hurts".

Estimator validation. Gold chains with one inserted redundant hop give hop-level labels (necessary = 1, redundant = 0). We report AUC of Δ^{tot}, Δ^{nai}, the placebo and mask-marker Δ, rollout PNS [34] and the DRG path indicator, overall and on chains the model answers correctly (PS = 1), and mean effects by hop position.

Methods. Direct answering; CoT; self-consistency [30] with 5 sampled chains (strictly more compute than HGCD, which generates nothing extra); CAD [20]; AdaCAD [29]; CAD-chain (contrast with vs. without the chain, a text analogue of rationale-conditioned decoding); HGCD and ablations: naive masking, no graph (all hops), log space, adaptive α, placebo contrast (the key control); L1 chains decoded with CoT or HGCD.

Hypotheses. The following hypotheses and decision criteria were fixed in the repository before any GPU experiment was run (verifiable in the commit history).

Hypothesis 1 (Estimator)**.** *AUC*$(\Delta^{\text{tot}}) \geq 0.75$ *on both datasets;* Δ^{nai} *near zero on MuSiQue non-final gold hops; placebo and mask-marker* $\Delta \approx 0$ *on all hops.*

Hypothesis 2 (Accuracy)**.** *HGCD > CoT and > CAD-chain on OOD CLUTRR (*$k \geq 5$*) and on MuSiQue, with paired bootstrap CIs excluding zero.*

Hypothesis 3 (Robustness)**.** $|\text{ATE}_{\text{distract}}|$ *of HGCD < that of CAD (proposition 3); ATE of* `placebo_input` ≈ 0 *for all methods.*

Hypothesis 4 (Readout)**.** *The gain of HGCD over CoT is concentrated on questions whose greedy chain reaches every gold-path entity, and is* ≈ 0 *(or negative) on the others (remark 1).*

Hypothesis 5 (Ablations)**.** *HGCD* $\geq$ *naive-mask and no-graph variants; probability space* $\geq$ *log space; and, crucially, HGCD > placebo contrast. Contrasting against* any *perturbation can move decisions (our CPU pilot shows this), so the placebo contrast, not CoT, is the control that isolates the causal content of the intervention.*

Models and compute. Qwen2.5-1.5B-Instruct [17] (main) and SmolLM2-1.7B-Instruct [1] (second family) on two Kaggle T4 GPUs in fp16; Qwen2.5-7B-Instruct on one A100 for the scale point. Greedy decoding; $\beta = 0.1$; $\alpha \in \{0, 0.25, 0.5, 1, 2, 4\}$ chosen per method on the CLUTRR validation split and transferred unchanged to MuSiQue (no MuSiQue data is used for tuning).

Statistics. Bootstrap CIs (2,000 resamples), paired bootstrap differences and exact McNemar tests on the same questions. The three *primary* comparisons are HGCD vs. CoT, vs. CAD-chain and vs. the placebo contrast, on OOD CLUTRR and on MuSiQue; all other contrasts are exploratory and are reported without multiplicity claims. With n questions per split, the half-width of a 95% CI on accuracy is about $1/\sqrt{n}$; paired tests are considerably tighter.

7 Results

All tables in this section are generated by the notebook; nothing is typed by hand.

Table 1: Estimator validation (AUC for separating necessary from inserted redundant hops).

Pending: run `notebooks/hgcd_kaggle.ipynb` and copy its output folder to `results/kaggle_main`.

Pending: run `notebooks/hgcd_kaggle.ipynb` and copy its output folder to `results/kaggle_main`.

Table 2: CLUTRR accuracy (%) with bootstrap 95% CIs. ID: $k \leq 4$; OOD: $k \geq 5$.

Pending: run `notebooks/hgcd_kaggle.ipynb` and copy its output folder to `results/kaggle_main`.

Table 3: CLUTRR paired ATE (accuracy points) of binary interventions whose true effect is 0.

Pending: run `notebooks/hgcd_kaggle.ipynb` and copy its output folder to `results/kaggle_main`.

8 Limitations

Assumptions. ?? 1?? 2 idealise the reader; we treat the propositions as testable predictions rather than guarantees, and the protocol is designed to falsify them. **Rollout-free interventions.** y_j^{tot} approximates $\text{do}(H_j)$ by masking rather than re-generating descendants; we validate it against rollout PNS where compute allows. **Format dependence.** The DRG requires hop-structured chains linked by explicit mentions; pronouns break links and shrink $\mathcal{R}(y)$ to the terminal hop. We report format success, hop fidelity against the gold path and the fraction of fully connected DRGs, and fall back to CoT when parsing fails. **Closed-set scoring.** All CLUTRR methods, including CoT, are scored over the same 20 relations, so differences are not due to answer extraction. **Candidate sets.** Answer-level contrast needs a finite candidate set; it is exact on CLUTRR and approximate on MuSiQue (we report candidate recall). **Scale.** Main experiments use 1.5–7B models; larger models may rely less on shortcuts. **Data filter.** We use CLUTRR stories whose gold graph is a simple path; stories with back-edges contain known label ambiguities.

Table 4: CLUTRR accuracy (%) split by whether the greedy chain reaches every gold-path entity (hypothesis 4).

Pending: run `notebooks/hgcd_kaggle.ipynb` and copy its output folder to `results/kaggle_main`.

Table 5: MuSiQue exact match (%) and paired ATE.

Pending: run `notebooks/hgcd_kaggle.ipynb` and copy its output folder to `results/kaggle_main`.

Pending: run `notebooks/hgcd_kaggle.ipynb` and copy its output folder to `results/kaggle_main`.

9 Conclusion

Contrasting a model against interventions on its own reasoning graph turns step-level causal measurement into a training-free decoding rule. The rule is cheap, comes with falsifiable predictions, and is evaluated with interventions whose true effects are known.

References

[1] Loubna Ben Allal, Anton Lozhkov, Elie Bakouch, et al. SmolLM2: When smol goes big – data-centric training of a small language model. *arXiv preprint arXiv:2502.02737*, 2025.

[2] Eden Biran, Daniela Gottesman, Sohee Yang, Mor Geva, and Amir Globerson. Hopping too late: Exploring the limitations of large language models on multi-hop queries. In *Proceedings of EMNLP*, pages 14113–14130, 2024.

[3] Paul C. Bogdan, Uzay Macar, Neel Nanda, and Arthur Conmy. Thought anchors: Which LLM reasoning steps matter? *arXiv preprint arXiv:2506.19143*, 2025.

[4] Yung-Sung Chuang, Yujia Xie, Hongyin Luo, Yoon Kim, James Glass, and Pengcheng He. DoLa: Decoding by contrasting layers improves factuality in large language models. In *Proceedings of ICLR*, 2024.

[5] Giulio Corallo and Paolo Papotti. Parallel context-of-experts decoding for retrieval augmented generation. *arXiv preprint arXiv:2601.08670*, 2026.

[6] Shurui Gui and Shuiwang Ji. Mitigating spurious correlations in LLMs via causality-aware post-training. *arXiv preprint arXiv:2506.09433*, 2025.

[7] Siyi Guo, Myrl G. Marmarelis, Fred Morstatter, and Kristina Lerman. Estimating causal effects of text interventions leveraging LLMs. *arXiv preprint arXiv:2410.21474*, 2024.

[8] Alihan Hüyük, Xinnuo Xu, Jacqueline Maasch, Aditya V. Nori, and Javier González. Reasoning elicitation in language models via counterfactual feedback. In *Proceedings of ICLR*, 2025.

[9] Tamera Lanham, Anna Chen, Ansh Radhakrishnan, Benoit Steiner, Carson Denison, Danny Hernandez, et al. Measuring faithfulness in chain-of-thought reasoning. *arXiv preprint arXiv:2307.13702*, 2023.

[10] Sicong Leng, Hang Zhang, Guanzheng Chen, Xin Li, Shijian Lu, Chunyan Miao, and Lidong Bing. Mitigating object hallucinations in large vision-language models through visual contrastive decoding. In *Proceedings of CVPR*, 2024.

[11] Xiang Lisa Li, Ari Holtzman, Daniel Fried, Percy Liang, Jason Eisner, Tatsunori Hashimoto, Luke Zettlemoyer, and Mike Lewis. Contrastive decoding: Open-ended text generation as optimization. In *Proceedings of ACL*, 2023.

[12] Sewon Min, Eric Wallace, Sameer Singh, Matt Gardner, Hannaneh Hajishirzi, and Luke Zettlemoyer. Compositional questions do not necessitate multi-hop reasoning. In *Proceedings of ACL*, 2019.

[13] Sean O'Brien and Mike Lewis. Contrastive decoding improves reasoning in large language models. *arXiv preprint arXiv:2309.09117*, 2023.

[14] Debjit Paul, Robert West, Antoine Bosselut, and Boi Faltings. Making reasoning matter: Measuring and improving faithfulness of chain-of-thought reasoning. In *Findings of EMNLP*, pages 15012–15032, 2024.

[15] Judea Pearl. Direct and indirect effects. In *Proceedings of UAI*, pages 411–420, 2001.

[16] Judea Pearl. *Causality: Models, Reasoning, and Inference*. Cambridge University Press, 2 edition, 2009.

[17] Qwen Team. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*, 2024.

[18] Guillaume Sanchez, Alexander Spangher, Honglu Fan, Elad Levi, and Stella Biderman. Stay on topic with classifier-free guidance. In *Proceedings of ICML*, 2024.

[19] Freda Shi, Xinyun Chen, Kanishka Misra, Nathan Scales, David Dohan, Ed H. Chi, Nathanael Schärli, and Denny Zhou. Large language models can be easily distracted by irrelevant context. In *Proceedings of ICML*, 2023.

[20] Weijia Shi, Xiaochuang Han, Mike Lewis, Yulia Tsvetkov, Luke Zettlemoyer, and Wen-tau Yih. Trusting your evidence: Hallucinate less with context-aware decoding. In *Proceedings of NAACL (Short Papers)*, pages 783–791, 2024.

[21] Koustuv Sinha, Shagun Sodhani, Jin Dong, Joelle Pineau, and William L. Hamilton. CLUTRR: A diagnostic benchmark for inductive reasoning from text. In *Proceedings of EMNLP-IJCNLP*, 2019.

[22] Alessandro Stolfo, Zhijing Jin, Kumar Shridhar, Bernhard Schölkopf, and Mrinmaya Sachan. A causal framework to quantify the robustness of mathematical reasoning with language models. In *Proceedings of ACL*, pages 545–561, 2023.

[23] Yufei Tao and Ameeta Agrawal. No-worse context-aware decoding: Preventing neutral regression in context-conditioned generation. In *Findings of ACL*, 2026.

[24] Jin Tian and Judea Pearl. Probabilities of causation: Bounds and identification. *Annals of Mathematics and Artificial Intelligence*, 28:287–313, 2000.

[25] Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. MuSiQue: Multihop questions via single-hop question composition. *Transactions of the Association for Computational Linguistics*, 10:539–554, 2022.

[26] Miles Turpin, Julian Michael, Ethan Perez, and Samuel R. Bowman. Language models don't always say what they think: Unfaithful explanations in chain-of-thought prompting. In *Proceedings of NeurIPS*, 2023.

[27] Martin Tutek, Fateme Hashemi Chaleshtori, Ana Marasović, and Yonatan Belinkov. Measuring chain of thought faithfulness by unlearning reasoning steps. In *Proceedings of EMNLP*, 2025.

[28] Jesse Vig, Sebastian Gehrmann, Yonatan Belinkov, Sharon Qian, Daniel Nevo, Yaron Singer, and Stuart Shieber. Investigating gender bias in language models using causal mediation analysis. In *Proceedings of NeurIPS*, 2020.

[29] Han Wang, Archiki Prasad, Elias Stengel-Eskin, and Mohit Bansal. AdaCAD: Adaptively decoding to balance conflicts between contextual and parametric knowledge. In *Proceedings of NAACL*, 2025.

[30] Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. In *Proceedings of ICLR*, 2023.

[31] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc Le, and Denny Zhou. Chain-of-thought prompting elicits reasoning in large language models. In *Proceedings of NeurIPS*, 2022.

[32] Shin'ya Yamaguchi, Kosuke Nishida, and Daiki Chijiwa. Rationale-enhanced decoding for multi-modal chain-of-thought. In *Proceedings of CVPR*, 2026.

[33] Sohee Yang, Elena Gribovskaya, Nora Kassner, Mor Geva, and Sebastian Riedel. Do large language models latently perform multi-hop reasoning? In *Proceedings of ACL*, pages 10210–10229, 2024.

[34] Xiangning Yu, Zhuohan Wang, Linyi Yang, Haoxuan Li, Anjie Liu, Xiao Xue, Jun Wang, and Mengyue Yang. Causal sufficiency and necessity improves chain-of-thought reasoning. In *Proceedings of NeurIPS*, 2025.

[35] Matej Zečević, Moritz Willig, Devendra Singh Dhami, and Kristian Kersting. Causal parrots: Large language models may talk causality but are not causal. *Transactions on Machine Learning Research*, 2023.

A Proofs

Proposition 1. y_j^{nai} changes only h_j and keeps $h_{j+1:k}$ at their observed values, so Δ_j^{nai} is by definition the controlled direct effect $\pi(a \mid h_j, h_{-j}) - \pi(a \mid \perp, h_{-j})$ [15]. Under assumption 1, $\pi(a \mid h_{1:k}) = g(a \mid h_{j+1:k})$ for $j < k$, so both terms equal $g(a \mid h_{j+1:k})$ and the difference is zero. y_j^{tot} additionally changes $h_{j+1:k}$ (their results are masked), so g is evaluated at a different argument and the difference is unconstrained. On compositional chains π reads the relation of every hop, so removing h_j alone changes the composed relation. □

Proposition 2. Substituting assumption 2 into eq. (1), with $\sum_j w_j = 1$ and π_s, π_d unaffected by interventions on hops: $s_\alpha(a) = (1+\alpha)[\lambda_c \pi_c(a \mid y) + \lambda_s \pi_s + \lambda_d \pi_d] - \alpha \sum_j w_j [\lambda_c \pi_c(a \mid y_j^{\text{tot}}) + \lambda_s \pi_s + \lambda_d \pi_d] = \pi(a \mid y) + \alpha \lambda_c \sum_j w_j [\pi_c(a \mid y) - \pi_c(a \mid y_j^{\text{tot}})]$. In log space, $\log(\lambda_c u + r) - \log(\lambda_c v + r)$ depends on $r = \lambda_s \pi_s + \lambda_d \pi_d$ unless $u = v$, so the shortcut terms do not cancel. □

Proposition 3. Let $m(a) = \pi(a \mid Q, P)$. CAD prefers a_d over g iff $(1+\alpha)\log\frac{m(a_d)}{m(g)} > \alpha \log\frac{\pi_s(a_d)}{\pi_s(g)}$. The left side is bounded below by $(1+\alpha)\log\frac{\lambda_d}{m(g)}$ since $m(a_d) \geq \lambda_d$, while the right side tends to $-\infty$ as $\pi_s(a_d) \to 0$. For HGCD, both terms of eq. (1) condition on the same P, so $\lambda_d \pi_d$ enters both and cancels (proposition 2). □

Proposition 4. Under exogeneity and monotonicity, Lemma 2 of Yu et al. [34] gives PNS = $P(A{=}a \mid \mathrm{do}(S)) - P(A{=}a \mid \mathrm{do}(S'))$. With $S = y$ and $S' = y_j^{\mathrm{tot}}$ this is $\Delta_j^{\mathrm{tot}}(a)$. Dividing eq. (1) by α and letting $\alpha \to \infty$ removes the $\pi(a \mid y)/\alpha$ term. □

B Implementation and Reproducibility

Candidate log-probabilities are computed with one prefix forward and a KV-cached pass over the candidate tokens (verified against full recomputation to 2×10^{-5}). Prompts are two-shot, hop-structured; the second CLUTRR shot uses a relation outside the label set to avoid leaking label statistics. All interventions are seeded functions of the example id. The Kaggle notebook embeds the full package and writes every table in this paper.

C Pilot run (pipeline sanity check)

The following tables come from a CPU smoke run with Qwen2.5-0.5B-Instruct on a handful of examples. They verify that the pipeline runs end to end and are **not** evidence for or against any hypothesis.

Estimator	clutrr		musique	
	all	PS=1	all	PS=1
Δ^{naive} (mask hop only)	0.900	1.000	0.802	0.862
Δ^{total} (graph-aware mask)	0.881	1.000	1.000	1.000
DRG path indicator	1.000	1.000	1.000	1.000
$\Delta^{\mathrm{placebo}}$ (content-preserving)	0.469	0.300	0.521	0.538
Δ^{marker} (mask token, content kept)	0.581	0.700	0.469	0.462

Dataset	Hop type	Δ^{total}	Δ^{naive}	$\Delta^{\mathrm{placebo}}$	Δ^{marker}
clutrr	gold-final	0.079	0.079	0.036	0.023
clutrr	gold-nonfinal	0.037	0.011	-0.048	-0.029
clutrr	redundant	-0.072	-0.072	-0.007	-0.018
musique	gold-final	0.682	0.682	-0.077	-0.062
musique	gold-nonfinal	0.423	-0.036	-0.050	-0.012
musique	redundant	-0.112	-0.112	-0.074	-0.018

Method	ID (n=8)	OOD (n=4)	All (n=12)
Direct (no CoT)	25.0 [0.0,62.5]	0.0 [0.0,0.0]	16.7 [0.0,41.7]
CoT	25.0 [0.0,62.5]	0.0 [0.0,0.0]	16.7 [0.0,41.7]
Self-consistency	12.5 [0.0,37.5]	0.0 [0.0,0.0]	8.3 [0.0,25.0]
CAD	25.0 [0.0,62.5]	0.0 [0.0,0.0]	16.7 [0.0,41.7]
AdaCAD	37.5 [12.5,75.0]	0.0 [0.0,0.0]	25.0 [0.0,50.0]
CAD-chain	25.0 [0.0,62.5]	0.0 [0.0,0.0]	16.7 [0.0,41.7]
HGCD (naive mask)	25.0 [0.0,62.5]	0.0 [0.0,0.0]	16.7 [0.0,41.7]
HGCD (no graph)	25.0 [0.0,62.5]	0.0 [0.0,0.0]	16.7 [0.0,41.7]
HGCD (log-space)	37.5 [12.5,75.0]	25.0 [0.0,75.0]	33.3 [8.3,58.3]
HGCD (adaptive α)	25.0 [0.0,62.5]	0.0 [0.0,0.0]	16.7 [0.0,41.7]
HGCD (placebo)	25.0 [0.0,62.5]	0.0 [0.0,0.0]	16.7 [0.0,41.7]
HGCD	25.0 [0.0,62.5]	0.0 [0.0,0.0]	16.7 [0.0,41.7]
L1 + CoT	25.0 [0.0,50.0]	0.0 [0.0,0.0]	16.7 [0.0,41.7]
L1 + HGCD	25.0 [0.0,50.0]	0.0 [0.0,0.0]	16.7 [0.0,41.7]

Even at this scale, the position breakdown shows the qualitative pattern predicted by proposition 1 on MuSiQue: naive masking leaves the answer probability of non-final gold hops nearly unchanged, whereas graph-aware masking reduces it substantially. With a few dozen hops this is an illustration, not a test.