

Onde Operator API v2.0

Contents

Contents	1
Document history	3
Introduction	4
Troubleshooting	5
What's new in 2.0	6
Objects	6
OrderRequestObject	7
WaypointObject	10
LatLngObject	11
CustomerObject	11
OrderResponseObject	12
CompanyObject	12
OrderOfferObject	12
DriverObject	14
CarObject	14
TariffObject	16
OrderUpdateObject	19
LocationObject	20
TripSummaryObject	20
PaymentObject	22
OrderStatusObject	22
VehicleObject	23
OrderPrepareRequestObject	24
OrderPrepareResponseObject	25
OrderPreparationDataObject	26
TripEstimationObject	26
OrderConfirmRequestObject	27
OrderConfirmResponseObject	29
HTTP methods	29
Create an order	29
Get company details	31
Get order request	32
Get order offer	34
Get order update	35
Get trip summary	36
Update passenger's location	38
Change order status	39
Get tariff	39
Get vehicle	42
HTTP methods 2.0	44
Get tariff	44
Prepare an order	46

Update prepared data for an order	48
Confirm an order	50
Websocket	53
Order updates notifications	53

Document history

Version	Date	Changelog
1.0	03.03.2020	Initial version
1.1	28.05.2021	Added pickupLocation and dropoffLocation to TripSummary object
1.2	05.11.2023	Added manual driver assign function
1.3	05.06.2024	Added orderSource parameter to OrderRequestObject & TripSummaryObject
2.0	13.11.2024	Added new order creation flow
2.0	07.08.2025	Add details to WaypointObject: required fields and usage.

Introduction

Welcome! In this document, you can find API methods that reflect the functionality of Onde Operator App. To start testing API you need to:

1. Request an invite to our sandbox environment through your Onde contact person
2. Register your company at <https://my-sandbox.onde.app>
3. Go to Company management > Application & Services and subscribe to Dispatch API extra service
4. Go to Company management > Operators, add a new operator and generate an Operator API token
5. Pass the authorization header with your Operator API token in every query

Notes:

- Please read the documentation carefully
- Use the Driver App to switch order statuses
- SMS verification code at Sandbox is always 000000
- Always check the Operator API token you've generated
- {HOSTNAME} in request URLs stands for the server address. For sandbox please use api-sandbox.onde.app, when switching to production - api.onde.app
- Utilize request URLs only from the original documentation
- Header User-Agent must be present and filled in HTTP requests
- GET requests should not contain body and Content-Length Header

As soon as you finish your Operator API integration apply for a review. You will be provided with the production endpoint and credentials afterward.

Troubleshooting

If you are facing troubles with Operator API, please do this:

1. Ensure first that you compose requests correctly
2. Check error response messages and study how to fix requests according to this documentation

If nothing helps, please contact support@onde.app and provide as many details as your problem as you can:

1. Exact timestamp
2. URL including protocol, hostname, port, and all parameters
3. HTTP method
4. Request payload (body) for all non-GET HTTP methods
5. Request headers: used API token (last part of it)
6. Timestamp when the response was received
7. Response HTTP code
8. Response body
9. Response headers

What's new in 2.0

- New order creation flow:
 - Previously you used [Get tariffs](#) request to get a list of tariffs (and estimation price of an order) and then [Create an order](#). Now all you need to do is send [Prepare an order](#) (0 or more [Update prepared data for an order](#) and then) and then [Confirm an order](#).
 - In case you would like to update data prepared for order creation you can send [Update prepared data for an order](#) request with orderId received in [Prepare an order](#).
 - [Prepare an order](#) fixes estimation price for an order until [Confirm an order](#) is sent. It is guaranteed that the order will be created with a price, received in the last [Prepare an order](#) or [Update prepared data for an order](#).
 - The price fixed for the order can be considered relevant for 3 minutes since last [Prepare an order](#) or [Update prepared data for an order](#) request. Otherwise [Confirm an order](#) will return an error and you'll have to update the estimation price with [Update prepared data for an order](#) request.
- Request for getting tariffs now simply returns tariffs available in origin location and does not return cost based on destination, tripDistance and tripDuration.

Objects

OrderRequestObject

Fields

Field name	Type	Description
waypoints	Array of WaypointObject	Geodata of pickup, intermediate, and drop-off points like coordinates, addresses, etc. Up to 5 points can be mentioned.
extraOptions	Array of Enum	AIR_CONDITION NON_SMOKING SMOKING_ALLOWED EXTRA_LUGGAGE_SPACE CHILD_SEAT DISABLED_PEOPLE PETS_ALLOWED BIKE_MOUNT
client	CustomerObject	Customer info like name, UUID, image, etc.
notes	String	Text notes for an order.
unitOfLength	Enum	METER KILOMETER MILE
specialCost	Number	Special price for the order
tripDistance	Number	Trip distance in units specified in “unitOfLength” param for price estimation.
tripDuration	Integer	Trip duration in milliseconds for price estimation.
pickupTime	String	Pick up time for arrival according to RFC3339 standard
numberOfSeats	Integer	Number of seats needed
vehicleType	Enum	ECONOMY CLASSIC BUSINESS LUXURY RICKSHAW MOTO TESLA BLACK_CAR BLACK_CAB SUV MINIVAN VAN

		BUS LIMOUSINE HELICOPTER SPEED_BOAT YACHT TOW_TRUCK AMBULANCE PARATRANSIT DELIVERY_TRUCK MOTO_XL COURIER PEDICAB TOW_TRUCK_SMALL TOW_TRUCK_INDUSTRIAL ELECTRIC_VEHICLE HANDYMAN PLUMBER ELECTRICIAN LOCKSMITH DOCTOR NURSE MAID BABYSITTER LAWYER INSURANCE_INSPECTOR CLAIMS_ADJUSTER
tariffType	Enum	PRECISE HOURLY
paymentMethods	Enum	CASH TERMINAL THIRD_PARTY
prepaid	Boolean	If true - the trip was paid before it started (currently not supported)
tariffId	String	Service type UUID
manualAssignDriver	String	Driver Id that is used for manual assign
orderSource	Enum	PASSENGER_APP DISPATCH_PANEL DISPATCH_API

Code sample

```
{
  "waypoints": [
    {
      "exactLatLng": {
        "lat": 37.5,
        "lng": -122.1
      },
    },
  ],
}
```

```

    "premise": "Google Store",
    "houseNumber": "22",
    "street": "Avenue",
    "subLocality": "California",
    "locality": "California",
    "city": "Mountain view",
    "district": "California",
    "province": "California",
    "country": "United States",
    "postalCode": "94043",
    "countryCode": "US",
    "poiName": "Google Store",
    "placeLatLng": {
      "lat": 37.5192,
      "lng": -122.0574
    }
  },
  "extraOptions": [
    "CHILD_SEAT"
  ],
  "client": {
    "clientId": "12345678-1234-1234-1234-1234567890AB",
    "name": "John Smith",
    "phone": "+123121231212",
    "imageUrl": "https://image.com/"
  },
  "notes": "Some text",
  "unitOfLength": "KILOMETER",
  "specialCost": 33.34,
  "tripDistance": 0,
  "tripDuration": 0,
  "pickupTime": "2000-01-01T12:00:27.87+00:20",
  "numberOfSeats": 4,
  "vehicleType": "BUS",
  "tariffType": "PRECISE",
  "paymentMethods": [
    "CASH",
    "TERMINAL"
  ],
  "prepaid": false,
  "tariffId": "12345678-1234-1234-1234-1234567890AB",
  "manualAssignDriver": "12345678-1234-1234-1234-1234567890AB"
}

```

WaypointObject

Fields

Field name	Type	Description	Required
exactLatLng	LatLngObject	Coordinates of the customer	yes
premise	String	A named location, usually a building or collection of buildings with a common name	no
houseNumber	String	House number	no
street	String	Street name	no
subLocality	String	A first-order civil entity below a locality	no
locality	String	An incorporated city or town political entity	no
city	String	City name	no
district	String	District (a subdivision of city)	no
province	String	Province name	no
country	String	Country name	no
postalCode	String	Postal code	no
countryCode	String	Two-letter country code ISO 3166-1 alpha-2	no
poiName	String	A named point of interest	no
googleJson	String	Raw Google Place JSON. When supplied you may omit the individual address fields.	no
placeLatLng	LatLngObject	Coordinates of the place which are used for further geocoding	yes

Features of use

Address waypoint – both coordinates must be identical (`placeLatLng == exactLatLng`). Fill as many address fields as possible so the driver sees a clear, readable destination.

Map pin (coordinate-only) – coordinates may differ (e.g. `placeLatLng` = building entrance, `exactLatLng` = loading dock). In this case the other address fields are optional.

For a pure pin you may send only `placeLatLng` and `exactLatLng`.

For an address, populate either the individual address fields or a single googleJson blob—never both.

Code sample

```
{
  "exactLatLng": {
    "lat": 37.5,
    "lng": -122.1
  },
  "premise": "Google Store",
  "houseNumber": "22",
  "street": "Avenue",
  "subLocality": "California",
  "locality": "California",
  "city": "Mountain view",
  "district": "California",
  "province": "California",
  "country": "United States",
  "postalCode": "94043",
  "countryCode": "US",
  "poiName": "Google Store",
  "placeLatLng": {
    "lat": 37.4192,
    "lng": -122.0574
  }
}
```

LatLngObject

Fields

Field name	Type	Description
lat	Number	Latitude data
lng	Number	Longitude data

Code sample

```
{
  "lat": 37.4192,
  "lng": -122.0574
}
```

CustomerObject

Fields

Field name	Type	Description
clientId	String	Customer UUID
name	String	Customer name
phone	String	Customer mobile phone number
imageUrl	String	Customer profile image
email	String	Customer email (from Customer app)

Code sample

```
{
  "clientId": "12345678-1234-1234-1234-1234567890AB",
  "name": "John Smith",
  "phone": "+123121231212",
  "imageUrl": "https://image.com/",
  "email": "smith@mail.com"
}
```

OrderResponseObject

Fields

Field name	Type	Description
orderId	String	Order UUID

Code sample

```
{
  "orderId": "12345678-1234-1234-1234-1234567890AB"
}
```

CompanyObject

Fields

Field name	Type	Description
name	String	Company name

logo	String	Company profile image
------	--------	-----------------------

Code sample

```
{
  "name": "My Company",
  "logo": "https://image.com/"
}
```

OrderOfferObject

Fields

Field name	Type	Description
eta	String	Estimated time of arrival according to RFC3339 standard
driver	DriverObject	Driver info like name, UUID, profile image, etc.
car	CarObject	Driver's car info like model, colour, year, etc.
tariff	TariffObject	Service type info like name, UUID, currency, etc.

Code sample

```
{
  "eta": "2000-01-01T12:00:27.87+00:20",
  "driver": {
    "driverId": "12345678-1234-1234-1234-1234567890AB",
    "name": "John Smith",
    "phone": "+123121231212",
    "email": "smith@mail.com",
    "imageUrl": "https://image.com/"
  },
  "car": {
    "model": "Mercedes Benz",
    "color": "Black",
    "year": 2000,
    "imageUrl": "https://image.com/",
    "plateNumber": "1234AB",
    "numberOfSeats": 4,
    "vehicleType": "BUSINESS",
    "options": [
      "AIR_CONDITION"
    ]
  }
}
```

```

},
"tariff": {
  "tariffId": "12345678-1234-1234-1234-1234567890AB",
  "name": "Classic",
  "companyName": "My Company",
  "vehicleType": "CLASSIC",
  "tariffType": "PRECISE",
  "numberOfSeats": 4,
  "paymentMethods": [
    "CREDIT_CARD",
    "CASH"
  ],
  "currency": "USD",
  "unitOfLength": "KILOMETER",
  "minimumCharge": 1,
  "maximumCharge": 10,
  "flagDownFee": 1,
  "perDistanceUnitFee": 1,
  "perHourFee": 60,
  "taximeterMode": "TIME_AND_MILEAGE",
  "speedBreakPoint": 5,
  "tariffMode": "AUTO",
  "driverCanSetCost": true,
  "fixedFaresAvailable": false,
  "cost": 33.34,
  "fixedCost": true,
  "prepaidSupported": false,
  "asapBooking": true,
  "preBooking": true,
  "minimumPreBookingDelay": 900000
}
}

```

DriverObject

Fields

Field name	Type	Description
driverId	String	Driver UUID
name	String	Driver name
phone	String	Driver mobile phone number
email	String	Driver email
imageUrl	String	Driver profile image

Code sample

```
{
  "driverId": "12345678-1234-1234-1234-1234567890AB",
  "name": "John Smith",
  "phone": "+123121231212",
  "email": "smith@mail.com",
  "imageUrl": "https://image.com/"
}
```

CarObject

Fields

Field name	Type	Description
model	String	Car model
color	String	Car color
year	Integer	Car issue year
imageUrl	String	Car image
plateNumber	String	Car number
numberOfSeats	Integer	Number of seats
vehicleType	Enum	ECONOMY CLASSIC BUSINESS LUXURY RICKSHAW MOTO TESLA BLACK_CAR BLACK_CAB SUV MINIVAN VAN BUS LIMOUSINE HELICOPTER SPEED_BOAT YACHT TOW_TRUCK AMBULANCE PARATRANSIT DELIVERY_TRUCK MOTO_XL COURIER PEDICAB TOW_TRUCK_SMALL

		TOW_TRUCK_INDUSTRIAL ELECTRIC_VEHICLE HANDYMAN PLUMBER ELECTRICIAN LOCKSMITH DOCTOR NURSE MAID BABYSITTER LAWYER INSURANCE_INSPECTOR CLAIMS_ADJUSTER
options	Array of Enum	AIR_CONDITION NON_SMOKING SMOKING_ALLOWED EXTRA_LUGGAGE_SPACE CHILD_SEAT DISABLED_PEOPLE PETS_ALLOWED BIKE_MOUNT

Code sample

```
{
  "model": "Mercedes Benz",
  "color": "Black",
  "year": 2000,
  "imageUrl": "https://image.com/",
  "plateNumber": "1234AB",
  "numberOfSeats": 4,
  "vehicleType": "BUSINESS",
  "options": [
    "AIR_CONDITION",
    "CHILD_SEAT"
  ]
}
```

TariffObject

Fields

Field name	Type	Description
tariffId	String	Service type UUID
name	String	Service type name
companyName	String	Driver company name

vehicleType	Enum	ECONOMY CLASSIC BUSINESS LUXURY RICKSHAW MOTO TESLA BLACK_CAR BLACK_CAB SUV MINIVAN VAN BUS LIMOUSINE HELICOPTER SPEED_BOAT YACHT TOW_TRUCK AMBULANCE PARATRANSIT DELIVERY_TRUCK MOTO_XL COURIER PEDICAB TOW_TRUCK_SMALL TOW_TRUCK_INDUSTRIAL ELECTRIC_VEHICLE HANDYMAN PLUMBER ELECTRICIAN LOCKSMITH DOCTOR NURSE MAID BABYSITTER LAWYER INSURANCE_INSPECTOR CLAIMS_ADJUSTER
tariffType	Enum	PRECISE HOURLY
numberOfSeats	Integer	Number of passenger seats
paymentMethods	Array of Enum	CASH CREDIT_CARD TERMINAL THIRD_PARTY
currency	Enum	Currency code according to ISO 4217 standard
unitOfLength	Enum	METER KILOMETER MILE

minimumCharge	Number	Minimum trip cost
maximumCharge	Number	Maximum trip cost
flagDownFee	Number	Flag down fee (seat price)
perDistanceUnitFee	Number	Cost of a kilometer (mile) of a trip
perHourFee	Number	Cost of an hour of a trip
taximeterMode	Enum	TIME_AND_MILEAGE TIME_OR_MILEAGE TIME_HOURLY
speedBreakPoint	Number	Speed threshold (for taximeterMode = TIME_OR_MILEAGE)
tariffMode	Enum	DISABLED AUTO AUTO_FIXED_COST
driverCanSetCost	Boolean	Allow driver to add extra expenses
fixedFaresAvailable	Boolean	If true - prepared prices will be applied for fixed zones (this parameter is set on production only)
fixedFareName	String	Fixed fare name (this parameter is set on production only)
cost	Number	Estimated trip cost
fixedCost	Boolean	Fixed trip cost option
prepaidSupported	Boolean	If true - the trip was paid before it started (currently not supported)
asapBooking	Boolean	ASAP booking option
preBooking	Boolean	Pre-booking option
minimumPreBookingDelay	Integer	The minimum period for preorder (milliseconds)

Code sample

```
{
  "tariffId": "12345678-1234-1234-1234-1234567890AB",
  "name": "Classic",
  "companyName": "My Company",
  "vehicleType": "CLASSIC",
  "tariffType": "PRECISE",
  "numberOfSeats": 4,
  "paymentMethods": [
```

```

    "CREDIT_CARD",
    "CASH"
  ],
  "currency": "USD",
  "unitOfLength": "KILOMETER",
  "minimumCharge": 1,
  "maximumCharge": 10,
  "flagDownFee": 1,
  "perDistanceUnitFee": 1,
  "perHourFee": 60,
  "taximeterMode": "TIME_AND_MILEAGE",
  "speedBreakPoint": 5,
  "tariffMode": "AUTO",
  "driverCanSetCost": true,
  "fixedFaresAvailable": false,
  "cost": 33.34,
  "fixedCost": true,
  "prepaidSupported": false,
  "asapBooking": true,
  "preBooking": true,
  "minimumPreBookingDelay": 900000
}

```

OrderUpdateObject

Fields

Field name	Type	Description
driverId	String	Driver UUID
driverLocation	LocationObject	Driver location info like coordinates, speed, etc.
status	String	CANCELLED_BY_DISPATCH CANCELLED_BY_DRIVER CANCELLED_NO_PASSENGER CANCELLED_DECIDED_NOT_TO_GO CANCELLED_NO_TAXI CANCELLED_DRIVER_OFFLINE CANCELLED_SEARCH_EXCEEDED SEARCH ASSIGNED STARTED ARRIVED TRANSFERRING REVIEW_SUMMARY PAYMENT FINISHED_PAID FINISHED_UNPAID

Code sample

```
{
  "driverId": "12345678-1234-1234-1234-1234567890AB",
  "driverLocation": {
    "accuracy": 20,
    "time": "2000-01-01T12:00:27.87+00:20",
    "bearing": 180,
    "speed": 20,
    "lat": 37.4192,
    "lng": -122.0574
  },
  "status": "TRANSFERRING"
}
```

LocationObject

Fields

Field name	Type	Description
accuracy	Number	Object estimated location radius, in meters
time	String	Time of location calculation according to RFC3339 standard
bearing	Number	The horizontal direction of the mobile device in degrees (0.0, 360.0]
speed	Number	Object speed (meters per second)
lat	Number	Object latitude
lng	Number	Object longitude

Code sample

```
{
  "accuracy": 20,
  "time": "2000-01-01T12:00:27.87+00:20",
  "bearing": 180,
  "speed": 20,
  "lat": 37.4192,
  "lng": -122.0574
}
```

TripSummaryObject

Fields

Field name	Type	Description
createTime	String	Order creation time according to RFC3339 standard
pickupTime	String	Customer pickup time according to RFC3339 standard
dropoffTime	String	Customer dropoff time according to RFC3339 standard
currency	Enum	Currency code according to ISO 4217 standard
unitOfLength	Enum	METER KILOMETER MILE
tripDistance	Number	Trip distance in units specified in "unitOfLength" field.
tripDuration	Integer	Trip duration in milliseconds.
tripCost	Number	Estimated trip cost
extraCost	Number	Additional fees
finalCost	Number	Total trip cost with fees
payments	Array of PaymentObject	Trip payment info like payment method, amount, etc.
ratingByDriver	Integer	Customer's rating by the driver
pickupLocation	LatLngObject	Passenger pickup coordinates
dropoffLocation	LatLngObject	Passenger final dropoff coordinates
orderSource	Enum	PASSENGER_APP DISPATCH_PANEL DISPATCH_API

Code sample

```
{
  "createTime": "2000-09-29T12:56:26.834+03:00",
  "pickupTime": "2000-09-29T12:57:05.214+03:00",
  "dropoffTime": "2000-09-29T12:57:12.975+03:00",
  "currency": "USD",
  "unitOfLength": "KILOMETER",
```

```

"tripDistance":55,
"tripDuration":775400,
"tripCost":1.13,
"finalCost":1.13,
"payments":[
  {
    "time":"2000-09-29T12:57:12.975+03:00",
    "amount":1.13,
    "method":"CREDIT_CARD"
  }
],
"ratingByDriver":5,
"pickupLocation":{
  "lat":56.8632431,
  "lng":27.6422327
},
"dropoffLocation":{
  "lat":56.8632431,
  "lng":27.6422327
}
}

```

PaymentObject

Fields

Field name	Type	Description
time	String	Time of payment according to RFC3339 standard
amount	Number	Amount of money paid
method	ENUM	CASH CREDIT_CARD TERMINAL THIRD_PARTY

Code sample

```

{
  "time": "2000-09-29T12:56:26.834+03:00",
  "amount": 1.13,
  "method": "CREDIT_CARD"
}

```

OrderStatusObject

Fields

Field name	Type	Description
status	String	CANCELLED_BY_DISPATCH CANCELLED_BY_DRIVER CANCELLED_NO_PASSENGER CANCELLED_DECIDED_NOT_TO_GO CANCELLED_NO_TAXI CANCELLED_DRIVER_OFFLINE CANCELLED_SEARCH_EXCEEDED SEARCH ASSIGNED STARTED ARRIVED TRANSFERRING REVIEW_SUMMARY PAYMENT FINISHED_PAID FINISHED_UNPAID

Code sample

```
{  
  "status": "CANCELLED_BY_DISPATCH"  
}
```

VehicleObject

Fields

Field name	Type	Description
location	LocationObject	Driver location info like coordinates, accuracy, etc.
vehicleType	Enum	ECONOMY CLASSIC BUSINESS LUXURY RICKSHAW MOTO TESLA BLACK_CAR BLACK_CAB SUV MINIVAN VAN BUS

		LIMOUSINE HELICOPTER SPEED_BOAT YACHT TOW_TRUCK AMBULANCE PARATRANSIT DELIVERY_TRUCK MOTO_XL COURIER PEDICAB TOW_TRUCK_SMALL TOW_TRUCK_INDUSTRIAL ELECTRIC_VEHICLE HANDYMAN PLUMBER ELECTRICIAN LOCKSMITH DOCTOR NURSE MAID BABYSITTER LAWYER INSURANCE_INSPECTOR CLAIMS_ADJUSTER
--	--	---

Code sample

```
{
  "location": {
    "accuracy": 20,
    "time": "2000-01-01T12:00:27.87+00:20",
    "bearing": 180,
    "speed": 20,
    "lat": 37.4192,
    "lng": -122.0574
  },
  "vehicleType": "CLASSIC"
}
```

OrderPrepareRequestObject

Fields

Field name	Type	Description
waypoints	Array of WaypointObject	Geodata of pickup, intermediate, and drop-off points like coordinates, addresses, etc. Up to 5 points can be mentioned.

unitOfLength	Enum	METER KILOMETER MILE
pickupTime	String	Pick up time for arrival according to RFC3339 standard
currency	Enum	Currency code according to ISO 4217 standard
specialCost	Number	Special price for the order
includedDistance	Number	Included in special price distance (special cost applied for the whole trip if not specified)
includedDuration	Integer	Included in special price duration in millis (special cost applied for the whole trip if not specified)

Code sample

```
{
  "waypoints": [
    {
      "exactLatLng": {
        "lat": 37.5,
        "lng": -122.1
      },
      "premise": "Google Store",
      "houseNumber": "22",
      "street": "Avenue",
      "subLocality": "California",
      "locality": "California",
      "city": "Mountain view",
      "district": "California",
      "province": "California",
      "country": "United States",
      "postalCode": "94043",
      "countryCode": "US",
      "poiName": "Google Store",
      "placeLatLng": {
        "lat": 37.5192,
        "lng": -122.0574
      }
    }
  ],
  "unitOfLength": "METER",
  "pickupTime": "2000-01-01T12:00:27.87+00:20",
  "currency": "USD",
```

```

    "specialCost": 33.34,
    "includedDistance": 1500,
    "includedDuration": 60000,
  }

```

OrderPrepareResponseObject

Fields

Field name	Type	Description
orderId	String	Order UUID
confirmationId	String	Identifier of the operation
orderPreparationData	OrderPreparationDataObject	Prepared data for order creation

Code sample

```

{
  "orderId": "12345678-1234-1234-1234-1234567890AB",
  "confirmationId": "12345678-1234-1234-1234-1234567890AB",
  "orderPreparationData": {
    "allTariffsTripEstimations": [
      {
        "cost": 33.34,
        "fixedCost": true,
        "priceMultiplier": 2.1,
        "tariffId": "12345678-1234-1234-1234-1234567890AB",
      }
    ]
  }
}

```

OrderPreparationDataObject

Fields

Field name	Type	Description
allTariffsTripEstimations	Array of TripEstimationObject	Order UUID

Code sample

```
{
  "allTariffsTripEstimations": [
    {
      "cost": 33.34,
      "fixedCost": true,
      "priceMultiplier": 2.1,
      "tariffId": "12345678-1234-1234-1234-1234567890AB",
    }
  ]
}
```

TripEstimationObject

Fields

Field name	Type	Description
cost	Number	Estimated trip cost
fixedCost	Boolean	Fixed trip cost option
priceMultiplier	Number	Price multiplier
tariffId	String	Service type UUID

Code sample

```
{
  "cost": 33.34,
  "fixedCost": true,
  "priceMultiplier": 2.1,
  "tariffId": "12345678-1234-1234-1234-1234567890AB",
}
```

OrderConfirmRequestObject

Fields

Field name	Type	Description
confirmationId	String	Identifier of the operation
extraOptions	Array of Enum	AIR_CONDITION NON_SMOKING SMOKING_ALLOWED EXTRA_LUGGAGE_SPACE

		CHILD_SEAT DISABLED_PEOPLE PETS_ALLOWED BIKE_MOUNT
client	CustomerObject	Customer info like name, UUID, image, etc.
notes	String	Text notes for an order.
numberOfSeats	Integer	Number of seats needed
vehicleType	Enum	ECONOMY CLASSIC BUSINESS LUXURY RICKSHAW MOTO TESLA BLACK_CAR BLACK_CAB SUV MINIVAN VAN BUS LIMOUSINE HELICOPTER SPEED_BOAT YACHT TOW_TRUCK AMBULANCE PARATRANSIT DELIVERY_TRUCK MOTO_XL COURIER PEDICAB TOW_TRUCK_SMALL TOW_TRUCK_INDUSTRIAL ELECTRIC_VEHICLE HANDYMAN PLUMBER ELECTRICIAN LOCKSMITH DOCTOR NURSE MAID BABYSITTER LAWYER INSURANCE_INSPECTOR CLAIMS_ADJUSTER
tariffType	Enum	PRECISE HOURLY
paymentMethods	Enum	CASH TERMINAL THIRD_PARTY

prepaid	Boolean	If true - the trip was paid before it started (currently not supported)
manualAssignDriver	String	Driver Id that is used for manual assign

Code sample

```
{
  "confirmationId": "12345678-1234-1234-1234-1234567890AB",
  "extraOptions": [
    "CHILD_SEAT"
  ],
  "client": {
    "clientId": "12345678-1234-1234-1234-1234567890AB",
    "name": "John Smith",
    "phone": "+123121231212",
    "imageUrl": "https://image.com/"
  },
  "notes": "Some text",
  "numberOfSeats": 4,
  "vehicleType": "BUS",
  "tariffType": "PRECISE",
  "paymentMethods": [
    "CASH",
    "TERMINAL"
  ],
  "prepaid": false,
  "manualAssignDriver": "12345678-1234-1234-1234-1234567890AB"
}
```

OrderConfirmResponseObject

Fields

Field name	Type	Description
orderId	String	Order UUID

Code sample

```
{
  "orderId": "12345678-1234-1234-1234-1234567890AB"
}
```

HTTP methods (old version)

Create an order

Description

Create a new order. When you create an order you can see it in the Dispatch panel at <https://operator-sandbox.onde.app>. For paymentMethods: "THIRD_PARTY" please use a different operator (Partner access operator) and his API token.

For manual driver assign just add a needed driver id to the order creation request body. The assign logic is the same as it is in Operator App, except there are no re-assign/remove driver functions.

1. The payment method 'CREDIT_CARD' is not available to set while order creation in Operator API.
2. Manual driver assign is available only for Operator users with Full Access or Limited Access permissions.

Request

URL	https://{HOSTNAME}/dispatch/v1/order
Method	POST
Content-type	JSON
Body	OrderRequestObject

Response

Content-type	JSON
Body	OrderResponseObject

HTTP response codes

Code	Message	Solution
200	Standard response for successful HTTP requests.	No solution required
400	Bad request	Check the correctness of the request fields
401	Authorization failure	Check your Operator API token
404	Not found	Check the request URL
500	Internal server error	Check the correctness of the request fields

502	Bad gateway	Check the correctness of the request fields
-----	-------------	---

Request sample

```
{
  "waypoints": [
    {
      "exactLatLng": {
        "lat": 37.4192,
        "lng": -122.0574
      },
      "houseNumber": "21",
      "street": "Avenue",
      "city": "Mountain View",
      "country": "USA",
      "countryCode": "US",
      "poiName": "Google Store",
      "placeLatLng": {
        "lat": 37.4192,
        "lng": -122.0574
      }
    }
  ],
  "extraOptions": [
    "BIKE_MOUNT"
  ],
  "client": {
    "clientId": "12345678-1234-1234-1234-1234567890AB",
    "name": "John Smith",
    "phone": "+123121231212",
    "imageUrl": "https://image.com/"
  },
  "unitOfLength": "METER",
  "currency": "USD",
  "vehicleType": "CLASSIC",
  "tariffType": "PRECISE",
  "paymentMethods": [
    "CASH"
  ],
  "prepaid": false
}
```

Response sample

```
{
  "orderId": "12345678-1234-1234-1234-1234567890AB"
```



```
}
```

Get company details

Description

Get company information, this method can be used to test API access.

Request

URL	https://{HOSTNAME}/dispatch/v1/company
Method	GET
Content-type	JSON

Response

Content-type	JSON
Body	CompanyObject

HTTP response codes

Code	Message	Solution
200	Standard response for successful HTTP requests.	No solution required
401	Authorization failure	Check your Operator API token
404	Not found	Check the request URL

Response sample

```
{
  "name": "My Company",
  "logo": "https://image.com/"
}
```

Get order request

Description

Get request data for the order . Customer email is shown in case it's been initially set in the Customer app (not during customer creation via Operator API).

Request

URL	https://{HOSTNAME}/dispatch/v1/order/{ORDER_ID}/request
Method	GET
Content-type	JSON

Response

Content-type	JSON
Body	OrderRequestObject

HTTP response codes

Code	Message	Solution
200	Standard response for successful HTTP requests.	No solution required
401	Authorization failure	Check your Operator API token
404	Not found	Check the request URL or order existence

Response sample

```
{
  "waypoints": [
    {
      "exactLatLng": {
        "lat": 37.4192,
        "lng": -122.0574
      },
      "houseNumber": "21",
      "street": "Avenue",
      "city": "Mountain View",
      "country": "USA",
      "countryCode": "US",
      "poiName": "Google Store",
      "placeLatLng": {
        "lat": 37.4192,
        "lng": -122.0574
      }
    }
  ],
  "extraOptions": [
    "BIKE_MOUNT"
  ]
}
```

```

],
"client": {
  "clientId": "12345678-1234-1234-1234-1234567890AB",
  "name": "John Smith",
  "phone": "+123121231212",
  "imageUrl": "https://image.com/",
  "email": "smith@mail.com"
},
"unitOfLength": "METER",
"currency": "USD",
"vehicleType": "CLASSIC",
"tariffType": "PRECISE",
"orderSource": "DISPATCH_PANEL",
"paymentMethods": [
  "CASH"
],
"prepaid": false
}

```

Get order offer

Description

When a driver accepts an order it transforms to offer. This method lets you get the offer information that consists of a driver and car details, tariff, and ETA.

Request

URL	https://{HOSTNAME}/dispatch/v1/order/{ORDER_ID}/offer
Method	GET
Content-type	JSON

Response

Content-type	JSON
Body	OrderOfferObject

HTTP response codes

Code	Message	Solution
200	Standard response for successful HTTP requests.	No solution required

204	No content	The driver hasn't accepted an order
401	Authorization failure	Check your Operator API token
404	Not found	Check the request URL, offer existence

Response sample

```
{
  "eta": "2000-01-01T12:00:27.87+00:20",
  "driver": {
    "driverId": "12345678-1234-1234-1234-1234567890AB",
    "name": "John Smith",
    "phone": "+123121231212",
    "email": "smith@mail.com",
    "imageUrl": "https://image.com/"
  },
  "car": {
    "model": "Mercedes Benz",
    "color": "Black",
    "year": 2020,
    "plateNumber": "ABC123",
    "numberOfSeats": 4,
    "vehicleType": "CLASSIC",
    "options": [
      "AIR_CONDITION",
      "NON_SMOKING"
    ]
  },
  "tariff": {
    "tariffId": "12345678-1234-1234-1234-1234567890AB",
    "name": "Classic",
    "companyName": "My Company",
    "vehicleType": "CLASSIC",
    "tariffType": "PRECISE",
    "numberOfSeats": 4,
    "paymentMethods": [
      "CREDIT_CARD",
      "CASH"
    ],
    "currency": "USD",
    "unitOfLength": "KILOMETER",
    "minimumCharge": 4,
    "maximumCharge": 5,
    "flagDownFee": 3,
    "perDistanceUnitFee": 2,
    "perHourFee": 60,
    "taximeterMode": "TIME_AND_MILEAGE",
  }
}
```

```

    "tariffMode": "AUTO",
    "driverCanSetCost": true,
    "fixedFaresAvailable": false,
    "cost": 33.34,
    "fixedCost": true,
    "prepaidSupported": false,
    "asapBooking": true,
    "preBooking": false,
    "minimumPreBookingDelay": 0
  }
}

```

Get order update

Description

Get order status and driver's location update.

For successful integration, you should use the notification channel over a WebSocket connection to get real time updates on orders. Periodic pooling for order updates is an ineffective method.

Request

URL	https://{HOSTNAME}/dispatch/v1/order/{ORDER_ID}/update
Method	GET
Content-type	JSON

Response

Content-type	JSON
Body	OrderUpdateObject

HTTP response codes

Code	Message	Solution
200	Standard response for successful HTTP requests.	No solution required
401	Authorization failure	Check your Operator API token
404	Not found	Check the request URL, offer existence

Response sample

```
{
  "driverId": "12345678-1234-1234-1234-1234567890AB",
  "driverLocation": {
    "accuracy": 20,
    "time": "2000-01-01T12:00:27.87+00:20",
    "lat": 37.4192,
    "lng": -122.0574
  },
  "status": "TRANSFERRING"
}
```

Get trip summary

Description

Get trip summary information.

Request

URL	https://{HOSTNAME}/dispatch/v1/order/{ORDER_ID}/summary
Method	GET
Content-type	JSON

Response

Content-type	JSON
Body	TripSummaryObject

HTTP response codes

Code	Message	Solution
200	Standard response for successful HTTP requests.	No solution required
401	Authorization failure	Check your Operator API token
404	Not found	Check the request URL, order existence

Response sample

```
{
```

```

"createTime":"2000-09-29T12:56:26.834+03:00",
"pickupTime":"2000-09-29T12:57:05.214+03:00",
"dropoffTime":"2000-09-29T12:57:12.975+03:00",
"currency":"USD",
"unitOfLength":"KILOMETER",
"tripDistance":55,
"tripDuration":775400,
"tripCost":1.13,
"finalCost":1.13,
"orderSource":"DISPATCH_PANEL",
"payments":[
  {
    "time":"2000-09-29T12:57:12.975+03:00",
    "amount":1.13,
    "method":"CREDIT_CARD"
  }
],
"ratingByDriver":5,
"pickupLocation":{
  "lat":56.8632431,
  "lng":27.6422327
},
"dropoffLocation":{
  "lat":56.8632431,
  "lng":27.6422327
}
}

```

Update passenger's location

Description

Update the passenger's location. To check the location, please use the Driver App.

Request

URL	https://{HOSTNAME}/dispatch/v1/order/{ORDER_ID}/passenger/location
Method	PUT
Content type	JSON
Body	LocationObject

HTTP response codes

Code	Message	Solution
------	---------	----------

204	Standard response for successful HTTP requests.	No solution required
401	Authorization failure	Check your Operator API token
404	Not found	Check the request URL, order existence

Request sample

```
{
  "accuracy": 20,
  "time": "2000-09-29T12:56:26.834+03:00",
  "lat": 37.4192,
  "lng": -122.0574
}
```

Change order status

Description

Change order status. Only canceling ("status": "CANCELLED_BY_DISPATCH") is available for Operator API.

Request

URL	https://{HOSTNAME}/dispatch/v1/order/{ORDER_ID}/status
Method	PUT
Content-type	JSON
Body	OrderStatusObject

HTTP response codes

Code	Message	Solution
204	Standard response for successful HTTP requests.	No solution required
401	Authorization failure	Check your Operator API token
403	Forbidden	Check if the order is active or status correctness
404	Not found	Check the request URL, order existence

Request sample

```
{
  "status": "CANCELLED_BY_DISPATCH"
}
```

Get tariff

Description

Searching for tariffs at some location filtered by the provided parameter. In each request, there should be at least an origin or destination parameter. To use parameters, put them into the request URL.

Request

URL	https://{HOSTNAME}/dispatch/v1/tariff
Method	GET
Content-type	JSON

Parameters

Parameter	Description	Example
origin	Origin location (latitude & longitude) where service is ordered from.	origin=37.4192,-122.0574
destination	Destination location (latitude & longitude)) where service gets to. This field is required to receive fixed fares from origin to destination.	destination=37.4192,-122.0574
unitOfLength	Specify measure for request units, METER is by default	unitOfLength=KILOMETER
tripDistance	Trip distance in units specified in 'unitOfLength' parameter for price estimation.	tripDistance=25
tripDuration	Trip duration in milliseconds for price estimation.	tripDuration=7888
pickupTime	Filter tariffs that allow booking the order now, at a specified time with timezone. Please use proper URL encoding	pickupTime=2020-09-29T12%3A56%3A26.834%2B03%3A00

numberOfSeats	Filter tariffs with not less than a specified number of seats.	numberOfSeats=4
vehicleType	Filter for tariffs only of specified vehicle class	vehicleType=CLASSIC
tariffType	Filter for tariffs only of specified tariff type	tariffType=HOURLY
paymentMethods	If true - search only for prepaid tariff.	paymentMethods=CASH
prepaid	If true - search only for prepaid tariff.	prepaid=true
tariffId	Get estimation for a single tariff only	tariffId=12345678-1234-1234-1234-1234567890AB

Response

Content-type	JSON
Body	Array of TariffObject

HTTP response codes

Code	Message	Solution
200	Standard response for successful HTTP requests.	No solution required
401	Authorization failure	Check your Operator API token
404	Not found	Check the request URL, order existence
500	Internal server error	Check that origin or destination parameters are mentioned in the request.

Response sample

```
{
  "tariffs": [
    {
      "tariffId": "12345678-1234-1234-1234-1234567890AB",
      "name": "Classic",
      "companyName": "My company",
      "vehicleType": "CLASSIC",
      "tariffType": "PRECISE",
      "numberOfSeats": 4,
      "paymentMethods": [
```

```

        "CREDIT_CARD",
        "THIRD_PARTY"
    ],
    "currency": "USD",
    "unitOfLength": "KILOMETER",
    "minimumCharge": 4,
    "maximumCharge": 5,
    "flagDownFee": 3,
    "perDistanceUnitFee": 2,
    "perHourFee": 60,
    "taximeterMode": "TIME_AND_MILEAGE",
    "tariffMode": "AUTO",
    "driverCanSetCost": true,
    "fixedFaresAvailable": false,
    "fixedCost": false,
    "prepaidSupported": false,
    "asapBooking": true,
    "preBooking": false,
    "minimumPreBookingDelay": 0
},
{
    "tariffId": "12345678-1234-1234-1234-1234567890AB",
    "companyName": "My Company",
    "vehicleType": "BUSINESS",
    "tariffType": "PRECISE",
    "numberOfSeats": 3,
    "paymentMethods": [
        "CASH",
        "CREDIT_CARD"
    ],
    "currency": "USD",
    "unitOfLength": "KILOMETER",
    "minimumCharge": 2,
    "flagDownFee": 2,
    "perDistanceUnitFee": 2,
    "perHourFee": 120,
    "taximeterMode": "TIME_AND_MILEAGE",
    "tariffMode": "AUTO",
    "driverCanSetCost": false,
    "fixedFaresAvailable": false,
    "fixedCost": false,
    "prepaidSupported": false,
    "asapBooking": true,
    "preBooking": true,
    "minimumPreBookingDelay": 900000
}
]

```

```
}
```

Get vehicle

Description

Searching for active vehicles at some location filtered by the provided parameter. In each request, there should be at least an origin or destination parameter. To use parameters, put them into the request URL. Please ensure first that your drivers are **online**.

Request

URL	https://{HOSTNAME}/dispatch/v1/vehicle
Method	GET
Content-type	JSON

Parameters

Query parameters are the same as for [Get Tariff](#) request, except there is no destination point.

Response

Content-type	JSON
Body	Array of VehicleObject

HTTP response codes

Code	Message	Solution
200	Standard response for successful HTTP requests.	No solution required
401	Authorization failure	Check your Operator API token
404	Not found	Check the request URL, order existence
500	Internal server error	Check that origin parameter is mentioned in the request.

Response sample

```
{
  "vehicles":[
    {
      "location":{
```

```

    "accuracy":20.0,
    "time":"2020-10-30T11:49:43.761Z",
    "bearing":143.26556,
    "speed":24.873869,
    "lat":144.8997145,
    "lng":27.5600882
  },
  "vehicleType":"CLASSIC"
}
]
}

```

HTTP methods 2.0 (Current version)

Get tariff

Description

Searching for tariffs at some location filtered by the provided parameters. In each request, there should be at least an origin parameter. To use parameters, put them into the request URL.

Request

URL	https://{HOSTNAME}/dispatch/v2/tariff
Method	GET
Content-type	JSON

Parameters

Parameter	Description	Example
origin	Origin location (latitude & longitude) where service is ordered from.	origin=37.4192,-122.0574
pickupTime	Filter tariffs that allow booking the order now, at a specified time with timezone. Please use proper URL encoding	pickupTime=2020-09-29T12%3A56%3A26.834%2B03%3A00
numberOfSeats	Filter tariffs with not less than a specified number of seats.	numberOfSeats=4
vehicleType	Filter for tariffs only of specified vehicle class	vehicleType=CLASSIC

tariffType	Filter for tariffs only of specified tariff type	tariffType=HOURLY
paymentMethods	Search only for tariffs with given payment methods	paymentMethods=CASH
prepaid	If true - search only for prepaid tariff.	prepaid=true
tariffId	Get single tariff	tariffId=12345678-1234-1234-1234-1234567890AB

Response

Content-type	JSON
Body	Array of TariffObject

HTTP response codes

Code	Message	Solution
200	Standard response for successful HTTP requests.	No solution required
401	Authorization failure	Check your Operator API token
404	Not found	Check the request URL, order existence
500	Internal server error	Check that origin or destination parameters are mentioned in the request.

Response sample

```
{
  "tariffs": [
    {
      "tariffId": "12345678-1234-1234-1234-1234567890AB",
      "name": "Classic",
      "companyName": "My company",
      "vehicleType": "CLASSIC",
      "tariffType": "PRECISE",
      "numberOfSeats": 4,
      "paymentMethods": [
        "CREDIT_CARD",
        "THIRD_PARTY"
      ],
      "currency": "USD",
      "unitOfLength": "KILOMETER",
    }
  ]
}
```

```

    "minimumCharge": 4,
    "maximumCharge": 5,
    "flagDownFee": 3,
    "perDistanceUnitFee": 2,
    "perHourFee": 60,
    "taximeterMode": "TIME_AND_MILEAGE",
    "tariffMode": "AUTO",
    "driverCanSetCost": true,
    "fixedFaresAvailable": false,
    "fixedCost": false,
    "prepaidSupported": false,
    "asapBooking": true,
    "preBooking": false,
    "minimumPreBookingDelay": 0
  },
  {
    "tariffId": "12345678-1234-1234-1234-1234567890AB",
    "companyName": "My Company",
    "vehicleType": "BUSINESS",
    "tariffType": "PRECISE",
    "numberOfSeats": 3,
    "paymentMethods": [
      "CASH",
      "CREDIT_CARD"
    ],
    "currency": "USD",
    "unitOfLength": "KILOMETER",
    "minimumCharge": 2,
    "flagDownFee": 2,
    "perDistanceUnitFee": 2,
    "perHourFee": 120,
    "taximeterMode": "TIME_AND_MILEAGE",
    "tariffMode": "AUTO",
    "driverCanSetCost": false,
    "fixedFaresAvailable": false,
    "fixedCost": false,
    "prepaidSupported": false,
    "asapBooking": true,
    "preBooking": true,
    "minimumPreBookingDelay": 900000
  }
]
}

```

Prepare an order

Description

Prepares data for a new order. Preparation request is needed to fix estimation price, which in the first version of API was received from [Get tariff](#). It returns `confirmationId` which is passed to confirmation request later. The confirmation request actually creates an order with the price, fixed and returned in this request.

Request

URL	<code>https://{HOSTNAME}/dispatch/v2/order/prepare</code>
Method	POST
Content-type	JSON
Body	OrderPrepareRequestObject

Response

Content-type	JSON
Body	OrderPrepareResponseObject

HTTP response codes

Code	Message	Solution
200	Standard response for successful HTTP requests.	No solution required
400	Bad request	Check the correctness of the request fields
401	Authorization failure	Check your Operator API token
404	Not found	Check the request URL
500	Internal server error	Check the correctness of the request fields
502	Bad gateway	Check the correctness of the request fields

Request sample

```
{
  "waypoints": [
    {
      "exactLatLng": {
```



```

        "lat": 37.5,
        "lng": -122.1
    },
    "premise": "Google Store",
    "houseNumber": "22",
    "street": "Avenue",
    "subLocality": "California",
    "locality": "California",
    "city": "Mountain view",
    "district": "California",
    "province": "California",
    "country": "United States",
    "postalCode": "94043",
    "countryCode": "US",
    "poiName": "Google Store",
    "placeLatLng": {
        "lat": 37.5192,
        "lng": -122.0574
    }
}
],
"unitOfLength": "METER",
"pickupTime": "2000-01-01T12:00:27.87+00:20",
"currency": "USD",
"specialCost": 33.34,
"includedDistance": 1500,
"includedDuration": 60000,
}

```

Response sample

```

{
  "orderId": "12345678-1234-1234-1234-1234567890AB",
  "confirmationId": "12345678-1234-1234-1234-1234567890AB",
  "orderPreparationData": {
    "allTariffsTripEstimations": [
      {
        "cost": 33.34,
        "fixedCost": true,
        "priceMultiplier": 2.1,
        "tariffId": "12345678-1234-1234-1234-1234567890AB",
      }
    ]
  }
}

```

Update prepared data for an order

Description

Updates data prepared in [Prepare an order V2](#) for a new order. Path variable here is retrieved from a request above. Preparation request is needed to fix estimation price, which in the first version of API was received from [Get tariff](#). It returns `confirmationId` which is passed to confirmation request later. The confirmation request actually creates an order with the price, fixed and returned in this request.

Request

URL	https://{HOSTNAME}/dispatch/v2/order/prepare/{ORDER_ID}
Method	PUT
Content-type	JSON
Body	OrderPrepareRequestObject

Response

Content-type	JSON
Body	OrderPrepareResponseObject

HTTP response codes

Code	Message	Solution
200	Standard response for successful HTTP requests.	No solution required
400	Bad request	Check the correctness of the request fields
401	Authorization failure	Check your Operator API token
404	Not found	Check the request URL
500	Internal server error	Check the correctness of the request fields
502	Bad gateway	Check the correctness of the request fields

Request sample

```
{
  "waypoints": [
    {
```

```

    "exactLatLng": {
      "lat": 37.5,
      "lng": -122.1
    },
    "premise": "Google Store",
    "houseNumber": "22",
    "street": "Avenue",
    "subLocality": "California",
    "locality": "California",
    "city": "Mountain view",
    "district": "California",
    "province": "California",
    "country": "United States",
    "postalCode": "94043",
    "countryCode": "US",
    "poiName": "Google Store",
    "placeLatLng": {
      "lat": 37.5192,
      "lng": -122.0574
    }
  }
],
"unitOfLength": "METER",
"pickupTime": "2000-01-01T12:00:27.87+00:20",
"currency": "USD",
"specialCost": 33.34,
"includedDistance": 1500,
"includedDuration": 60000,
}

```

Response sample

```

{
  "orderId": "12345678-1234-1234-1234-1234567890AB",
  "confirmationId": "12345678-1234-1234-1234-1234567890AB",
  "orderPreparationData": {
    "allTariffsTripEstimations": [
      {
        "cost": 33.34,
        "fixedCost": true,
        "priceMultiplier": 2.1,
        "tariffId": "12345678-1234-1234-1234-1234567890AB",
      }
    ]
  }
}

```

Confirm an order

Description

Confirm order creation. When you create an order you can see it in the Dispatch panel at <https://operator-sandbox.onde.app>. For paymentMethods: "THIRD_PARTY" please use a different operator (Partner access operator) and his API token.

For manual driver assign just add a needed driver id to the order creation request body. The assign logic is the same as it is in Operator App, except there are no re-assign/remove driver functions.

3. The payment method 'CREDIT_CARD' is not available to set while order creation in Operator API.
4. Manual driver assign is available only for Operator users with Full Access or Limited Access permissions.

Request

URL	https://{HOSTNAME}/dispatch/v2/order/confirm/{ORDER_ID}
Method	POST
Content-type	JSON
Body	OrderConfirmRequestObject

Response

Content-type	JSON
Body	OrderConfirmResponseObject

HTTP response codes

Code	Message	Solution
200	Standard response for successful HTTP requests.	No solution required
400	Bad request	Check the correctness of the request fields
401	Authorization failure	Check your Operator API token
404	Not found	Check the request URL
500	Internal server error	Check the correctness of the request fields
502	Bad gateway	Check the correctness of the request fields

Request sample

```
{
  "waypoints": [
    {
      "exactLatLng": {
        "lat": 37.4192,
        "lng": -122.0574
      },
      "houseNumber": "21",
      "street": "Avenue",
      "city": "Mountain View",
      "country": "USA",
      "countryCode": "US",
      "poiName": "Google Store",
      "placeLatLng": {
        "lat": 37.4192,
        "lng": -122.0574
      }
    }
  ],
  "extraOptions": [
    "BIKE_MOUNT"
  ],
  "client": {
    "clientId": "12345678-1234-1234-1234-1234567890AB",
    "name": "John Smith",
    "phone": "+123121231212",
    "imageUrl": "https://image.com/"
  },
  "unitOfLength": "METER",
  "currency": "USD",
  "vehicleType": "CLASSIC",
  "tariffType": "PRECISE",
  "paymentMethods": [
    "CASH"
  ],
  "prepaid": false
}
```

Response sample

```
{
  "orderId": "12345678-1234-1234-1234-1234567890AB"
}
```


Websocket

Order updates notifications

Description

WebSocket to listen for order update notifications. To test it simply run HTTP GET request with an inserted Operator API token.

Please note, that websocket connection limit is set to 100 connections/hour. To properly utilize websocket you need to connect once and maintain this active connection by sending "keep alive" messages. There is no need for constant reconnection.

Request

URL	https://{HOSTNAME}/dispatch/v1/notification/{AUTH_TOKEN}
Method	GET
Content-type	JSON

Response

The response will return an HTML code with a script. Save this code as an HTML file and open it in a browser. When you open this code in a browser you will see 3 buttons with commands and a message log.

Websocket request messages

Message	Description
{}	Keep alive message. Websocket connection is automatically closed after 30 secs of inactivity since the last message. Send this message within 20 secs to support active connection.
{tracking:true}	Enable drivers tracking. When enabled - websocket will periodically send LocationObject of a driver (typically every 5-10 seconds)
{tracking:false}	Disable drivers tracking and stop receiving driver location

Websocket response messages

Message	Description
Order	Order statuses - messages are sent when order is created. See OrderUpdateObject & OrderResponseObject for field description.
Offer	Offer status - messages are sent when a driver accepts an order. Same message structure as for "Order", but "driverId" is added

Driver location	driverId & LocationObject of a driver. Enable “tracking” for message receiving
-----------------	--

Order message sample

```
{
  "orderId": "12345678-1234-1234-1234-1234567890AB",
  "status": "SEARCH"
}
```

Offer message sample

```
{
  "driverId": "12345678-1234-1234-1234-1234567890AB",
  "orderId": "12345678-1234-1234-1234-1234567890AB",
  "status": "FINISHED_PAID"
}
```

Driver location message sample

```
{
  "driverId": "12345678-1234-1234-1234-1234567890AB",
  "driverLocation": {
    "accuracy": 20.0,
    "time": "2020-10-30T11:49:43.761Z",
    "bearing": 52.80334,
    "speed": 9.211584,
    "lat": 144.9233219,
    "lng": 27.5201351
  }
}
```