

A RANK-TRANSFER ATLAS FOR PARALLEL ODD-VERTEX PRUNING

ANONYMOUS

ABSTRACT. Fix an ambient label set and iterate the deterministic rule that deletes all currently odd-degree vertices simultaneously. We count every inverse layer of this map. If a fixed target has s vertices and a strict predecessor has $m = s + d$ vertices, then the predecessor fibre is empty for odd d and, for positive even d , has size

$$\binom{n-s}{d} 2^{s(d-1) + \binom{d-1}{2}},$$

independently of the target edges. The proof is a rank-nullity calculation for one connected binary incidence system. Orienting this strict transfer with target rank as row and source rank as column makes its powers literal all-time fibres: a non-even target uses B_n^t , whereas an even target uses $I + B_n + \dots + B_n^t$. This yields the exact time- t image, the depth distribution, and all fixed-state counts. Every orbit stabilizes in at most $\lfloor n/2 \rfloor$ rounds, sharply for a path. A paper-local exact audit checks 3,167,525 assertions, including all states through ambient order six and independent incidence systems through total order nine. Classical parity, incidence, and parallel-peeling facts are used only as zero-credit inputs.

1. THE LABELLED MAP AND ITS COMPLETE TRANSFER STATEMENT

Put $[n] = \{1, \dots, n\}$, with $[0] = \emptyset$. Let $\mathcal{X}_n$ be the set of all simple graphs whose vertex set is an arbitrary subset of $[n]$, including the empty graph. For $G \in \mathcal{X}_n$, write

$$(1.1) \quad D(G) = \{v \in V(G) : \deg_G(v) \text{ is odd}\}, \quad F(G) = G[V(G) \setminus D(G)].$$

Thus the vertices in $D(G)$ are evaluated in the same current graph and then deleted simultaneously. Set $\rho(G) = |V(G)|$. A graph is called *even* when all its degrees are even; connectivity is not required. The entrance time is

$$\tau(G) = \min\{t \geq 0 : F^t(G) \text{ is even}\}.$$

For $0 \leq s, m \leq n$, define the strict rank-transfer matrix B_n by

$$(1) \quad B_n(s, m) = \begin{cases} \binom{n-s}{d} 2^{s(d-1) + \binom{d-1}{2}}, & d = m - s > 0 \text{ is even,} \\ 0, & \text{otherwise.} \end{cases}$$

Rows are target ranks and columns are source ranks. In particular, B_n is strictly upper triangular; its zero diagonal does not encode fixed self-predecessors. Let

$$C_{n,t} = I + B_n + \dots + B_n^t, \quad e_0 = e_1 = 1, \quad e_s = 2^{\binom{s-1}{2}} \ (s \geq 2).$$

Parity-restricted vertex deletion has been studied as a sequential combinatorial game [5, 6]. Eulerian and prescribed-parity deletion instead choose edits to meet an optimization or decision constraint [1, 2]. Parallel peeling usually refers to simultaneous threshold deletion, for example in random hypergraph core processes [4]. These sources own the neighbouring language and mechanisms, not the claims assigned here. The standard handshaking, incidence-rank, and cycle-space facts used below also receive no contribution credit; see, for example, [3].

Theorem 1 (strict inverse and every temporal layer). *For every $n \geq 0$, the map F has the following properties.*

- (i) *Its recurrent states are exactly the even graphs, all fixed. Every orbit satisfies $\tau(G) \leq \lfloor n/2 \rfloor$, and the labelled path on $[n]$ attains equality.*
- (ii) *Fix a graph H on a particular s -set. For every $m > s$, the number of rank- m graphs sent to H in one step is $B_n(s, m)$, independently of the edges of H . At $m = s$ the full one-step fibre has size one if H is even and zero otherwise. For a fixed deleted pair over the empty target there is one source, K_2 ; hence $B_n(0, 2) = \binom{n}{2}$.*

(iii) For every $t \geq 0$ and $0 \leq m \leq n$,

$$(2) \quad \#\{G \in \mathcal{X}_n : \rho(G) = m, F^t(G) = H\} = \begin{cases} (B_n^t)(s, m), & H \text{ is not even,} \\ C_{n,t}(s, m), & H \text{ is even.} \end{cases}$$

(iv) At time $t = 0$, every state occurs. For $t \geq 1$, a rank- s graph H lies in $\text{im}(F^t)$ if and only if

$$(3) \quad H \text{ is even} \quad \text{or} \quad n - s \geq 2t.$$

(v) The phase size, fixed count, depth CDF, and image size are

$$(4) \quad |\mathcal{X}_n| = \sum_{s=0}^n \binom{n}{s} 2^{\binom{s}{2}},$$

$$(5) \quad |\text{Fix } F| = \sum_{s=0}^n \binom{n}{s} e_s,$$

$$(6) \quad \#\{G : \tau(G) \leq t\} = \sum_{s=0}^n \binom{n}{s} e_s \sum_{m=0}^n C_{n,t}(s, m),$$

$$(7) \quad |\text{im}(F^t)| = \sum_{s=0}^n \binom{n}{s} \left[e_s + \mathbf{1}_{\{n-s \geq 2t\}} \left(2^{\binom{s}{2}} - e_s \right) \right], \quad t \geq 1.$$

Exact depth shells are successive differences of (6). For $t = 0$, the image size is instead (4).

The theorem is boundary-complete. For $n = 0$ there is one fixed empty state; for $n = 1$ the empty and singleton states are both fixed. These carriers have clock zero, as does the formula $\lfloor n/2 \rfloor$.

2. FORWARD LOSS AND THE SHARP CLOCK

Proof of Theorem 1(i). The handshaking lemma gives $|D(G)| \equiv 0 \pmod{2}$. If G is not even, then $D(G)$ is nonempty and has at least two elements, so an active update lowers $\rho(G)$ by at least two. If G is even, then $D(G) = \emptyset$ and $F(G) = G$. Strict rank loss at every other state rules out nontrivial cycles and proves the upper bound $\tau(G) \leq \lfloor \rho(G)/2 \rfloor$.

For the path P_n , the two endpoints are the only odd-degree vertices. Deleting them leaves P_{n-2} until the empty graph or a singleton remains. Thus $\tau(P_n) = \lfloor n/2 \rfloor$, including the $n = 0, 1$ boundaries. $\square$

This clock is a supporting invariant only. The same argument is common to many pruning processes and does not explain the inverse fibres.

3. THE PARITY-EXTENSION SPACE

Fix a target H on a labelled set S , $|S| = s$, and a prospective deleted set $D \subseteq [n] \setminus S$, $|D| = d > 0$. A predecessor must agree with H on $\binom{S}{2}$. Its free variables $x_{uv} \in \mathbb{F}_2$ correspond to the

$$sd + \binom{d}{2}$$

edges having at least one endpoint in D . Exact deletion of D and survival of S are equivalent to

$$(8) \quad \sum_{v \in D} x_{uv} = \deg_H(u) \pmod{2}, \quad u \in S,$$

$$(9) \quad \sum_{w \in (S \cup D) \setminus \{v\}} x_{vw} = 1 \pmod{2}, \quad v \in D.$$

Proof of Theorem 1(ii). Let $Q_{S,D}$ be the graph on $S \cup D$ containing precisely the possible variable edges. It is connected when $d > 0$, including the one-vertex boundary. The coefficient matrix of (8)–(9) is its unoriented incidence matrix over $\mathbb{F}_2$. Its rank is $s + d - 1$: a row vector lies in the left kernel exactly when its endpoint values agree along every edge, hence exactly when it is constant on the connected graph.

Every incidence column has even weight, and the rank calculation shows that the column space is the full even-weight subspace of $\mathbb{F}_2^{s+d}$. The sum of the right-hand sides is

$$\sum_{u \in S} \deg_H(u) + d \equiv d \pmod{2}.$$

Consequently the system is consistent exactly for even d . For positive even d , rank-nullity gives

$$2^{sd + \binom{d}{2} - (s+d-1)} = 2^{s(d-1) + \binom{d-1}{2}}$$

solutions for the fixed set D . Choosing D among the $n-s$ unused labels proves (1). The count depends on H only through the parity-vector sum, which is automatically zero, proving target independence.

When $d = 0$, a same-rank preimage deletes nothing. It must therefore be even and fixed, so it equals H ; this gives exactly the separate diagonal rule in the theorem. When $s = 0, d = 2$ and D is fixed, the two odd-degree equations force the sole possible edge, so the unique source is K_2 . $\square$

4. POWERS, IMAGES, AND CENSUSES

The orientation of B_n is load-bearing. With target ranks as rows and source ranks as columns,

$$(10) \quad (B_n^2)(s, m) = \sum_{k=0}^n B_n(s, k) B_n(k, m).$$

For example,

$$B_4(0, 2) = 6, \quad B_4(2, 0) = 0, \quad (B_4^2)(0, 4) = 24.$$

The reversed convention fails already at the middle value.

Proof of Theorem 1(iii). A strict predecessor contains the nonempty set of odd vertices deleted by its next update, so it is not even and cannot wait. For a fixed target and an intermediate source rank k , Theorem 1(ii) supplies $B_n(s, k)$ choices; every such intermediate graph has $B_n(k, m)$ strict rank- m predecessors. Target independence makes this second factor uniform, and the deterministic forward orbit gives each inverse chain a unique intermediate graph. Equation (10) therefore counts literal two-step chains. Induction gives B_n^t for t strict steps.

If H is not even, every one of the t forward steps ending at H must be strict: an earlier fixed state could never leave itself. If H is even, a source may first reach it after any $j \in \{0, \dots, t\}$ strict steps and then wait. These first-arrival cases are disjoint and sum to $C_{n,t}$. This proves (2), including $t = 0$ through $B_n^0 = I$. $\square$

Proof of Theorem 1(iv)–(v). A reverse strict step adds a positive even number of labels. Hence a non-even rank- s target can have a t -step predecessor only if $n - s \geq 2t$. Conversely, under this inequality use t rank increments of two; every corresponding transfer entry in (1) is positive. Even targets lie in every image through their fixed self-predecessor. This proves (3); the identity map supplies the separate $t = 0$ case.

Equation (4) follows by choosing a vertex set and then its edge set. On a fixed s -set, even graphs form the kernel of the incidence map of K_s . Its dimension is $\binom{s}{2} - (s-1) = \binom{s-1}{2}$ for $s \geq 1$, with the empty case separate, giving e_s and (5). A graph has $\tau(G) \leq t$ exactly when $F^t(G)$ is one of these even targets. Summing their rank-refined fibres proves (6). Finally, (3) admits all even rank- s targets and, precisely when $n - s \geq 2t$, all remaining rank- s targets. This gives (7) and completes the proof. $\square$

Since every nonzero entry of B_n advances rank by at least two, $B_n^{\lfloor n/2 \rfloor + 1} = 0$. Nilpotence here records finite rank loss; it is not an additional contribution axis.

5. EXACT PRESSURE, COLLISION FIREWALL, AND LIMITS

The paper-local verifier constructs every graph state through ambient order six using immutable labelled vertex and edge tuples. Independently, it row-reduces every parity system of total order at most nine and every attainable target degree-parity vector. It compares literal strict and full one-step fibres, all iterates through stabilization and beyond, images, image counts, temporal CDFs and shells, fixed counts, path clocks, matrix orientation, and nilpotence.

The enumeration covers 41,658 states, including all 40,069 states at $n = 6$, and 511 independently formed parity systems. It uses exact integer and $\mathbb{F}_2$ arithmetic, no randomness, network access, or third-party package. Finite agreement is counterexample pressure, not proof, owner clearance, novelty evidence, or release authorization.

The internal collision firewall is proof-engine based. Rooted-forest leaf peeling (P114) uses height, Cayley enumeration, and attachment inclusion-exclusion; odd-component complementation (P123) preserves vertices and uses a component/co-component split tree; weighted threshold MIS (P141) uses a random exponential race; random ear deletion (P146) uses dual-tree hook orders; even-level plane-tree contraction (P148) uses depth divisibility and an ordered tree grammar. None mechanically yields

TABLE 1. Deterministic exact falsification. These checks do not replace the all-parameter proofs.

Lane	Exact assertions
Binary incidence rank, consistency, and nullity	726
Literal one-step fibres and boundary cases	869,751
Clock and fixed-state census	112,319
All-time fibres, images, CDFs, and shells	2,184,715
Matrix orientation and nilpotence	14
Total	3,167,525

the connected binary incidence extension or its rank-only powers. The common silhouette “clock–fibre–image” and all generic pruning language receive zero credit.

LIMITATIONS

The results concern finite, simple, labelled graphs on all subsets of one fixed ambient set. They do not treat asynchronous or random odd-vertex deletion, directed graphs, multigraphs, relabelling or isomorphism classes, weighted edges, asymptotic random-graph laws, or optimization over a chosen deletion set. The bounded source audit does not establish novelty or priority; any direct owner of the simultaneous transfer atlas would require renewed subtraction. The clock, fixed locus, standard parity algebra, and generic matrix multiplication are not claimed contributions.

DATA AVAILABILITY

No external data were used. The paper-local verifier and frozen transcript contain the complete deterministic exact control.

ETHICS STATEMENT

This mathematical study involved no human participants, animals, personal data, or field intervention.

AUTHOR CONTRIBUTIONS

The anonymous author performed the derivations, exact checks, source-boundary audit, and manuscript preparation.

CONFLICT OF INTEREST

The author declares no conflict of interest.

FUNDING

No external funding is declared.

TOOL-USE STATEMENT

Automated language and code-generation tools assisted with drafting and verifier implementation. The anonymous author checked the derivations, source metadata, executable controls, and final text and remains responsible for all claims.

EXTERNAL STATUS

This Round-0 artifact remains `HOLD_EXTERNAL`; it is not cleared for posting, submission, circulation, or author contact.

REFERENCES

- [1] Marek Cygan, Dániel Marx, Marcin Pilipczuk, Michał Pilipczuk, and Ildikó Schlotter. Parameterized complexity of eulerian deletion problems. *Algorithmica*, 68(1):41–61, 2014. doi: 10.1007/s00453-012-9667-x. URL <https://doi.org/10.1007/s00453-012-9667-x>.
- [2] Konrad K. Dabrowski, Petr A. Golovach, Pim van 't Hof, and Daniël Paulusma. Editing to eulerian graphs. *Journal of Computer and System Sciences*, 82(2):213–228, 2016. doi: 10.1016/j.jcss.2015.10.003. URL <https://arxiv.org/abs/1410.6863>.
- [3] Reinhard Diestel. *Graph Theory*, volume 173 of *Graduate Texts in Mathematics*. Springer, Berlin, Heidelberg, 5 edition, 2017. doi: 10.1007/978-3-662-53622-3. URL <https://doi.org/10.1007/978-3-662-53622-3>.
- [4] Jiayang Jiang, Michael Mitzenmacher, and Justin Thaler. Parallel peeling algorithms. In *Proceedings of the 26th ACM Symposium on Parallelism in Algorithms and Architectures*, pages 319–330, 2014. doi: 10.1145/2612669.2612674. URL <https://arxiv.org/abs/1302.7014>.
- [5] Oliver Krüger. Note on odd/odd vertex removal games on bipartite graphs. *Integers*, 14:G07, 2014. URL <https://arxiv.org/abs/1304.7997>.
- [6] Richard J. Nowakowski and Paul Ottaway. Vertex deletion games with parity rules. *Integers*, 5(2):A15, 2005. URL <https://eudml.org/doc/129047>.