

EVEN-LEVEL CONTRACTION OF PLANE ROOTED TREES: DIVISIBILITY ITERATES AND COMPLETE SIZE-REFINED FIBRES

ANONYMOUS

ABSTRACT. Delete every odd generation of a plane rooted tree, promote each deleted vertex's ordered child block to its parent, reset parity, and repeat. We analyze this literal map on the finite carrier of trees with at most N vertices while keeping its exact-size source layers distinct. After k steps, precisely the original depths divisible by 2^k survive. Hence a tree of height h reaches the singleton after $\lceil \log_2(h+1) \rceil$ steps, and the sharp maximum on n vertices is $\lceil \log_2 n \rceil$. For every target U with m vertices and $I(U)$ internal vertices, a reversible ordered block-and-gap construction gives

$$\sum_{E(T)=U} y^{|T|-m} = \frac{y^{I(U)}}{(1-y)^{2m-1}}.$$

Thus U occurs from the exact n -vertex layer exactly when $m + I(U) \leq n$, with an explicit binomial fibre. Weighting a target by its minimum predecessor size yields the algebraic series $H = z + z^2 H / (1 - H)$, and $H / (1 - z)$ counts exact-layer images. An exact audit of all 23,714 plane trees through 11 vertices supplies counterexample pressure but is not used as proof.

1. THE FINITE MAP AND THE EXACT-LAYER QUESTION

Let $\mathcal{PT}_n$ be the set of plane rooted trees with n vertices, and fix $N \geq 1$. The literal dynamical carrier is the finite disjoint union

$$\mathcal{PT}_{\leq N} := \bigsqcup_{1 \leq n \leq N} \mathcal{PT}_n.$$

A tree is an ordered list of its child trees. If $T = (T_1, \dots, T_d)$ and $T_i = (T_{i1}, \dots, T_{ir_i})$, define recursively

$$(1) \quad E(T) := (E(T_{11}), \dots, E(T_{1r_1}), \dots, E(T_{d1}), \dots, E(T_{dr_d})).$$

Geometrically, the root and every even-depth vertex are retained. Each odd-depth child is deleted, its child block is promoted, and the blocks are concatenated in the original plane order. Equation (1) then resets parity within every retained grandchild subtree. The singleton $\cdot$ is fixed.

The output uses a subset of the input vertices, so E is a self-map of $\mathcal{PT}_{\leq N}$. It is generally not a self-map of $\mathcal{PT}_n$. We therefore use $\mathcal{PT}_n$ only as an *exact source layer*: expressions such as $E(\mathcal{PT}_n)$ always mean the image of that subset inside the finite carrier. The formal fibre series below ranges coefficientwise over all finite source layers; for fixed N , it is truncated after source size N .

Plane-tree decompositions and parity-sensitive statistics have a mature enumerative literature [2]. Ordered child promotion also occurs inside generic forest contractions [1], while simultaneous plane-tree transitions [4] and Horton-style leaf pruning [3] give nearby but different dynamics. We assign Catalan enumeration, parity statistics, generic contraction, transition vocabulary, and pruning clocks zero contribution credit. The claims here concern the reset-parity iterate law and its complete target inverse.

2. DIVISIBLE-DEPTH SKELETONS AND THE SHARP CLOCK

Write $h(T)$ for the maximum root depth and let $\tau(T)$ be the least $k \geq 0$ such that $E^k(T) = \cdot$.

Theorem 1 (iterate skeleton and clock). *For every plane rooted tree T and $k \geq 0$, the vertices of $E^k(T)$ are exactly the original vertices whose depths are divisible by 2^k . Each is joined to its nearest retained ancestor, and the plane order is induced by the original contour order. Consequently*

$$(2) \quad h(E(T)) = \left\lfloor \frac{h(T)}{2} \right\rfloor, \quad \tau(T) = \lceil \log_2(h(T) + 1) \rceil.$$

The singleton is the unique recurrent state, and for every $n \geq 1$,

$$(3) \quad \max_{T \in \mathcal{PT}_n} \tau(T) = \lceil \log_2 n \rceil.$$

Proof. Track original vertex identities. The assertion at $k = 0$ is immediate. Assume that at rank k an original vertex of depth d survives precisely when $2^k \mid d$, in which case its current depth is $d/2^k$. The next contraction retains it precisely when this current depth is even, or equivalently when $2^{k+1} \mid d$. Promoting across the deleted current level joins nearest retained ancestors. Since concatenation of ordered blocks is associative, the resulting order is the one induced from the original contour. This proves the iterate assertion by induction.

A deepest root path contains a vertex at every depth from 0 through $h(T)$. It follows that $h(E^k(T)) = \lfloor h(T)/2^k \rfloor$. Thus $E^k(T)$ is the singleton exactly when $2^k > h(T)$, whose least solution is the second formula in (2). Every nonsingleton loses at least one depth-one vertex, so it cannot be recurrent. Finally $h(T) \leq n - 1$, and the n -vertex path has height $n - 1$; this proves (3), including non-powers of two. $\square$

3. A COMPLETE ORDERED BLOCK-AND-GAP INVERSE

For a target tree U , let $m = |U|$, let $d_U(v)$ be the outdegree of v , and let

$$I(U) := |\{v \in U : d_U(v) > 0\}|.$$

Weight every source vertex deleted in one contraction by y .

Lemma 2 (local inverse factor). *At a target vertex of outdegree d , the generating function for its inserted odd children is*

$$(4) \quad A_0(y) = \frac{1}{1-y}, \quad A_d(y) = \frac{y}{(1-y)^{d+1}} \quad (d > 0).$$

These choices form a reversible local construction.

Proof. For $d = 0$, every odd child must be a leaf; an arbitrary number gives $A_0(y)$. Suppose $d > 0$ and exactly r odd children are productive. Their grandchildren split the ordered target child list into r nonempty consecutive blocks, in $\binom{d-1}{r-1}$ ways. Any number of empty odd leaves may occupy each of the $r + 1$ gaps before, between, and after those productive children. Hence

$$\begin{aligned} A_d(y) &= \sum_{r=1}^d \binom{d-1}{r-1} \frac{y^r}{(1-y)^{r+1}} \\ &= \frac{y}{(1-y)^2} \left(1 + \frac{y}{1-y}\right)^{d-1} = \frac{y}{(1-y)^{d+1}}. \end{aligned}$$

The predecessor child list uniquely recovers which odd children are empty and which consecutive block each productive child carries. Thus the construction is reversible. $\square$

Theorem 3 (every-target fibre). *For every target U with m vertices,*

$$(5) \quad \sum_{E(T)=U} y^{|T|-m} = \frac{y^{I(U)}}{(1-y)^{2m-1}}.$$

Consequently, among sources in $\mathcal{PT}_n$ the fibre size is

$$(6) \quad |E^{-1}(U) \cap \mathcal{PT}_n| = \begin{cases} \binom{n-m-I(U)+2m-2}{2m-2}, & n-m \geq I(U), \\ 0, & n-m < I(U). \end{cases}$$

Proof. Apply Lemma 2 independently at every target vertex, working from its child subtrees upward. Internal vertices contribute one numerator factor y and leaves contribute none. Since a rooted tree satisfies $\sum_v d_U(v) = m - 1$, the total denominator exponent is

$$\sum_{v \in U} (d_U(v) + 1) = (m - 1) + m = 2m - 1.$$

This proves (5). Extracting the coefficient of y^{n-m} gives (6) by the negative-binomial expansion. For the singleton target, the formula correctly gives one source of every size: the corresponding star. $\square$

The temporal and inverse proofs use different structures. The first tracks depth divisibility, whereas the second reconstructs ordered child lists; the fibre is not inferred from the clock or a state census.

4. EXACT-SIZE IMAGES AND AN ALGEBRAIC SERIES

Corollary 4 (image criterion). *A target U lies in $E(\mathcal{PT}_n)$ if and only if*

$$(7) \quad |U| + I(U) \leq n.$$

Proof. The coefficient in (6) is positive exactly under condition (7). $\square$

Define the minimum-source-weight series

$$(8) \quad H(z) := \sum_U z^{|U|+I(U)},$$

where the sum is over all finite plane rooted trees. A leaf contributes z . An internal root contributes z^2 and has a nonempty ordered sequence of child trees. Therefore

$$(9) \quad H = z + z^2 \sum_{d \geq 1} H^d = z + \frac{z^2 H}{1 - H}.$$

Equivalently, H is the root with zero constant term of

$$H^2 - (1 + z - z^2)H + z = 0.$$

Corollary 4 now gives

$$(10) \quad \sum_{n \geq 1} |E(\mathcal{PT}_n)| z^n = \frac{H(z)}{1 - z}.$$

The factor $(1 - z)^{-1}$ takes cumulative sums of the minimum source weights; it does not turn E into a size-preserving map.

5. EXACT AUDIT AND CONCLUSION

An independent standard-library verifier generates every plane tree through 11 vertices. For every state it labels original vertices, compares each iterate with the predicted divisible-depth skeleton, and checks the clock. For every target and source size it compares observed fibres with (6); it also checks the local factors coefficientwise and solves (9) as a formal series. The 216,905 exact assertions all pass. Table 1 records the main profile; it is falsification pressure, not proof evidence.

TABLE 1. Exact source-layer profile. The state column is the Catalan carrier count; it receives no contribution credit.

n	1	2	3	4	5	6	7	8	9	10	11
$ \mathcal{PT}_n $	1	1	2	5	14	42	132	429	1430	4862	16796
$ E(\mathcal{PT}_n) $	1	1	2	3	5	9	17	34	71	153	338
$\max \tau$	0	1	2	2	3	3	3	3	4	4	4

The result identifies both what survives repeated reset-parity contraction and exactly how every target can be expanded one step. Its source-layer image series follows from the same local inverse threshold, while the literal dynamics remains on $\mathcal{PT}_{\leq N}$.

LIMITATIONS

The theorem is specific to finite plane rooted trees and the simultaneous deletion of every odd generation. It does not cover unordered trees, arbitrary selected levels, weighted contractions, or asymptotic random-tree questions. The literature audit was bounded; no novelty or priority claim is made. Enumeration through 11 vertices cannot replace the proofs. The manuscript remains under HOLD_EXTERNAL.

DATA AVAILABILITY

No external data were used. The anonymous artifact contains the standard-library verifier and its frozen exact output. External release of the artifact is not authorized at this stage.

ETHICS STATEMENT

The work uses no human participants, animals, personal data, or deployed decision system.

AUTHOR CONTRIBUTIONS

Contributor identities are withheld for anonymous review. The anonymous author team takes responsibility for conceptualization, formal analysis, software, validation, and writing.

CONFLICT OF INTEREST

The authors declare no known conflict of interest relevant to this internal mathematical study.

FUNDING

No funding claim is made in this anonymous internal draft.

REFERENCES

- [1] Sarah J. Berkemer, Christian H"oner zu Siederdisen, and Peter F. Stadler. Compositional properties of alignments. *Mathematics in Computer Science*, 15(4):609–630, 2020. doi: 10.1007/s11786-020-00496-8.
- [2] William Y. C. Chen, Nelson Y. Li, and Louis W. Shapiro. The butterfly decomposition of plane trees. *Discrete Applied Mathematics*, 155(17):2187–2201, 2007. doi: 10.1016/j.dam.2007.04.020. URL <https://arxiv.org/abs/math/0511045>.
- [3] Yevgeniy Kovchegov and Ilya Zaliapin. Horton law in self-similar trees. *Fractals*, 24(2):1650017, 2016. doi: 10.1142/S0218348X16500171. URL <https://arxiv.org/abs/1511.01558>.
- [4] Torrie L. Nichols, Alexander Pilz, Csaba D. Tóth, and Ahad N. Zehmakan. Transition operations over plane trees. *Discrete Mathematics*, 343(8):111929, 2020. doi: 10.1016/j.disc.2020.111929. URL <https://arxiv.org/abs/1810.02839>.