

Exact Sign-Itinerary Pruning in a Rational Lozi Pilot

Anonymous Route-A report

Abstract

We study a finite exact pilot for a nonsmooth Lozi map. Every binary branch word through length eight is converted to an affine return, solved over the rationals, and checked against strict sign domains. The resulting ledger has 37 primitive cyclic classes. This is a certified finite orbit atlas, not a claim of a global Markov partition or analytic transfer operator.

1 Frozen nonsmooth map

We freeze

$$L(x, y) = \left(1 - 2|x| + \frac{1}{2}y, x\right)$$

and assign symbol 0 to $x < 0$ and symbol 1 to $x > 0$. The switching line $x = 0$ is excluded before enumeration. On the two open half-planes the map is affine with matrices

$$B_0 = \begin{pmatrix} 2 & 1/2 \\ 1 & 0 \end{pmatrix}, \quad B_1 = \begin{pmatrix} -2 & 1/2 \\ 1 & 0 \end{pmatrix}, \quad d = \begin{pmatrix} 1 \\ 0 \end{pmatrix}.$$

Both determinants are $-1/2$, but their chronology is retained in every return matrix.

2 Exact return test

For a word $w = s_0 \cdots s_{n-1}$, composition gives $L_w(q) = M_w q + t_w$. Exact Gaussian elimination produces the unique candidate

$$q_w = (I - M_w)^{-1} t_w$$

whenever the return is nonsingular. We then iterate q_w and require the k th coordinate to lie strictly in the half-plane declared by s_k . Algebraic solvability alone is therefore not counted as admissibility.

The rooted strict counts for periods one through eight are

$$(2, 4, 2, 8, 22, 40, 58, 128).$$

After restricting to primitive words and quotienting only by cyclic rotation, the primitive counts are

$$(2, 1, 0, 1, 4, 6, 8, 15),$$

for a total of 37 certified classes. No return is singular and no candidate hits the switching line in this prefix; all rejected words fail a sign test.

n	binary	strict	sign fail	primitive	primitive pruned
1	2	2	0	2	0
2	4	4	0	1	0
3	8	2	6	0	2
4	16	8	8	1	2
5	32	22	10	4	2
6	64	40	24	6	3
7	128	58	70	8	10
8	256	128	128	15	15

Proposition 1. *The table is an exact strict-sign classification of all 510 words in the frozen prefix. Its rooted and primitive columns obey $t_n = \sum_{d|n} dp_d$ for every $n \leq 8$.*

Proof. The return solver uses rational matrix arithmetic. For each nonsingular candidate, direct branch iteration checks every strict inequality and closure. Primitive words are identified before taking the lexicographically minimal cyclic rotation. Substituting the eight displayed values verifies the finite necklace identity. $\square$

3 Route-A boundary

The strict finite ledger earns the partial-certified A1 label. A finite cycle-atlas construction earns only the certified-prefix A2 label. A global invariant set, global Markov partition, analytic Fredholm determinant, arithmetic data, and Route B are not claimed. In full, the ledger records

A1_PARTIAL_CERTIFIED, A2_CERTIFIED_PREFIX,
A3_NOT_ADDRESSED, A4_FAIL.

The NO_BAD_EULER_OR_ROOT_NUMBER scope firewall remains active.