

A Minimal Four-Block Refinement of a Directed-Edge Nonlattice Suspension

Route-A structural certificate C139

Abstract

We add one cyclic four-block marker to a directed-edge roof on the full binary shift. An exact eight-state determinant owns the rooted trace and primitive product at every period. The primitive words 001011 and 001101 have the same cyclic block populations through width three, but different 0011 counts; hence the frozen marker gives a coding-relative minimal forward-memory refinement. The improvement is deliberately limited: two primitive period- seven necklaces retain the same complete clock vector. This is an intrinsic symbolic-dynamical certificate, not a target or arithmetic factorization.

1 Frozen suspension and exact determinant

Let $\Sigma = \{0, 1\}^{\mathbb{Z}}$ with the left shift. Freeze

$$\tau = \begin{pmatrix} 1 & \sqrt{2} \\ \sqrt{3} & \sqrt{6} \end{pmatrix}, \quad r(x) = \tau_{x_0 x_1} + \sqrt{5} \mathbf{1}_{\{x_0 x_1 x_2 x_3 = 0011\}},$$

and form the suspension by $(x, t + r(x)) \sim (\sigma x, t)$. On the ordered three-block states 000, 001, $\dots$, 111, define

$$M_{abc, bcd}(x, y) = x_{ab} y^{\mathbf{1}_{\{abcd=0011\}}}, \quad d \in \{0, 1\}. \quad (1)$$

All other entries vanish. Direct sparse expansion gives

$$\Delta_{139}(x, y) = \det(I - M) = 1 - x_{00} - x_{11} - x_{01}x_{10} + x_{00}x_{11} + (1 - y)x_{00}x_{01}x_{10}x_{11}. \quad (2)$$

At $y = 1$, this is exactly the two-state directed-edge determinant. Indeed, the map sending a cyclic word w to the states $w_j w_{j+1} w_{j+2}$ is a bijection of closed paths and preserves edge weights. The presentations therefore have equal traces in every positive power; the formal log-determinant identity and constant term one give $\det(I - M(x, 1)) = 1 - x_{00} - x_{11} + x_{00}x_{11} - x_{01}x_{10}$. Only $(I - M)_{001, 011} = -x_{00}y$ depends on y , so the determinant is affine. Deleting that row and column and expanding the sparse minor along its forced transitions gives cofactor $x_{01}x_{10}x_{11}$; hence $\partial_y \Delta = -x_{00}x_{01}x_{10}x_{11}$ and integration from $y = 1$ proves (2), including its sign.

2 All-period product and clock sectors

For every $n \geq 1$, closed state paths in (1) are bijective with rooted cyclic binary words. Matrix multiplication therefore proves

$$\text{Tr } M(x, y)^n = \sum_{|w|=n} y^{N_{0011}(w)} \prod_{a,b} x_{ab}^{N_{ab}(w)}. \quad (3)$$

In the total-transition-degree completion, $-\log \det(I - M) = \sum_{n \geq 1} \text{Tr}(M^n)/n$. Grouping each rooted word by its unique primitive root gives the cutoff-free identity

$$\Delta_{139}(x, y) = \prod_{[\gamma] \text{ primitive}} \left(1 - y^{N_{0011}(\gamma)} \prod_{a,b} x_{ab}^{N_{ab}(\gamma)} \right). \quad (4)$$

Every coefficient is a finite regrouping because only finitely many necklaces have a fixed total degree.

With $x_{ab} = ze^{-s\tau_{ab}}$ and $y = e^{-\sqrt{5}s}$, (4) becomes

$$\Delta_{139}(z, s) = \prod_{[\gamma]} \left(1 - z^{|\gamma|} e^{-s\ell(\gamma)} \right), \quad \ell = N_{00} + \sqrt{2}N_{01} + \sqrt{3}N_{10} + \sqrt{6}N_{11} + \sqrt{5}N_{0011}.$$

The identity is formal in z . It is also absolutely convergent wherever the entrywise absolute-value matrix has spectral radius below one, because its trace logarithm then is dominated by the corresponding nonnegative matrix series.

The five displayed clock numbers are rationally independent. Sign changes of $\sqrt{2}$ and $\sqrt{3}$ isolate the first four coefficients. If $\sqrt{5}$ lay in $K = \mathbb{Q}(\sqrt{2}, \sqrt{3})$, its four conjugates would be only $\pm\sqrt{5}$, so a nontrivial automorphism would fix it. It would then lie in one of $\mathbb{Q}(\sqrt{2})$, $\mathbb{Q}(\sqrt{3})$, or $\mathbb{Q}(\sqrt{6})$. Squaring $\sqrt{5} = a + b\sqrt{m}$ forces $2ab = 0$ and gives an immediate contradiction for $m \in \{2, 3, 6\}$. Thus equal times force equal complete feature vectors. The fixed cycles $[0]$ and $[1]$ have lengths 1 and $\sqrt{6}$, so the roof is nonlattice.

3 The minimal-memory advance

For a forward roof depending on k consecutive symbols, its periodic sum is the dot product of its values with the cyclic k -block population. The two primitive words below have the exact counts

word	$k = 1$	$k = 2$ in order 00, 01, 10, 11	N_{0011}
001011	(3, 3)	(1, 2, 2, 1)	0
001101	(3, 3)	(1, 2, 2, 1)	1

Their common $k = 3$ vector, in lexicographic order, is $(0, 1, 1, 1, 1, 1, 0)$. Therefore no forward roof of memory at most three separates their periodic sums. The frozen four-block roof does:

$$\ell(001101) - \ell(001011) = \sqrt{5} \neq 0. \quad (5)$$

Both words are primitive and have different least rotations, so they are distinct primitive necklaces. This is minimality relative to the frozen forward binary coding; it is not claimed to survive arbitrary recoding or roof cohomology.

4 Residual collision, validation, and boundary

The primitive words 0101111 and 0110111 are not cyclic rotations, yet both have feature vector

$$(N_{00}, N_{01}, N_{10}, N_{11}, N_{0011}) = (0, 2, 2, 3, 0).$$

Thus the new clock is not orbit injective. Exact replay through period twelve contains 8,190 rooted words, 747 primitive cycles, 258 rooted feature cells, and 229 primitive feature cells; it locates the first such collision at period seven but is not used to prove (2)–(4). The independent checker passes 16,467 assertions, SymPy passes 35 checks, byte replay passes, and all 49 hostile cases (48 repaired-hash and one stale-hash) are rejected.

The strict tuple is (A1_WEAK, A2_FAIL, A3_FAIL, A4_FAIL), overall ROUTE_A_EXPLORATORY. We claim no target divisor, target functional equation or counting law, arithmetic/local factor, Euler factor, root number, automorphy, natural self-adjoint or unitary lift, Hilbert–Pólya operator, or Route-B authorization. The scope literal is NO_BAD_EULER_OR_ROOT_NUMBER.