

SYNCHRONOUS BALANCED REFINEMENT OF COMPOSITIONS: CANONICAL KERNELS AND EVERY ITERATED FIBRE

ANONYMOUS

ABSTRACT. We iterate the synchronous part rule $m \mapsto (\lfloor m/2 \rfloor, \lceil m/2 \rceil)$ for $m > 1$ on integer compositions. For every iterate t , with $K = 2^t$, we identify the complete kernel congruence: replace each source part at most K by that many ones and retain every larger part. Two compositions have the same t -th image exactly when these canonical forms agree. The proof exposes a suffix code and gives a right-to-left image decoder. Consequently every nonempty t -step fibre is a product of K -step Fibonacci counts over the one-runs of its canonical source, and the largest fibre on weight n is the K -restricted composition number. The same number counts states of depth at most t . Finally, the entire t -th image is in bijection with compositions whose parts lie in $\{1\} \cup \{K+1, K+2, \dots\}$, yielding an explicit rational generating function. Restricted-composition enumeration, suffix-code theory, and balanced divide-and-conquer splitting are treated as background. The owner search is bounded; no novelty, priority, or external-release claim is made.

1. THE MAP AND THE SUBTRACTION BOUNDARY

Let $\mathcal{C}_n$ be the set of integer compositions of n , with the empty composition included when $n = 0$. Define a substitution on positive integers by

$$(1) \quad \sigma(1) = 1, \quad \sigma(m) = (\lfloor m/2 \rfloor, \lceil m/2 \rceil) \quad (m > 1),$$

and extend it by concatenation. Our dynamical map is $\Phi(a_1 \cdots a_r) = \sigma(a_1) \cdots \sigma(a_r)$. All parts are read from the old word, so the update is synchronous. Weight is preserved and every changed part raises the word length; hence 1^n is the unique recurrent state and there are no nontrivial cycles.

Simultaneous application of letter rules is a classical parallel-rewriting interface [7]; its monoid-morphism formulation, including concatenation of letter images, receives zero contribution credit. Binary integer fragmentation and balanced splitting are likewise mature mechanisms [9], and the divide-and-conquer clock is not claimed as value here. Free-monoid codes, unique decoding, and morphism ambiguity are established subjects [2, 4, 6]; all generic suffix-code principles receive zero credit. Enumeration of compositions with prescribed or bounded parts, including the surrounding analytic toolkit, is also established [1, 5, 8]. In particular, the one-step image count below is the no-part-2 class studied by Chinn and Heubach [3]. Its sequence, every bounded-part Fibonacci count, and every generating function obtained merely by choosing an allowed part set receive zero contribution credit.

The residual question is dynamical and all-iterate: can one identify the kernel of Φ^t , decode its image, and count every individual fibre? The exact rule was subjected to a bounded owner search across rewriting, fragmentation, substitution, and composition sources. No direct theorem package was found; a bounded non-hit is not a novelty certificate.

There is also a strict internal subtraction boundary. P094 already uses morphisms, markers, and recognizability; P108 already combines Fibonacci terminology with clock and fibre geometry; P113 has an integer-sum carrier, absorption, sharp depth, and product-fibre transport; P115 treats every iterate, image, and fibre at a logarithmic threshold; P122 combines target-local fibre factorization with image/Garden enumeration; P123 uses a refinement engine; and P125 packages pointwise fibres, image layers, and functional components. We claim none of those generic silhouettes. The residual here is only their literal conjunction for the present infinite-alphabet balanced morphism: the all-iterate canonical kernel, the exact one-run fibre product, and the temporal image bijection.

2. CODEWORDS AND THE EXACT CLOCK

Put

$$W_t(m) = \Phi^t((m)), \quad K = 2^t.$$

These are words, not unordered fragmentation profiles.

2020 *Mathematics Subject Classification.* 05A17, 37B15, 68Q42, 94A45.

Key words and phrases. integer composition, finite dynamical system, synchronous refinement, normal form, suffix code, iterated fibre.

Lemma 2.1 (balanced codewords). *For $m \geq 1$, $W_t(m)$ has length $\min(m, K)$, total weight m , and largest and final part $\lceil m/K \rceil$. In particular,*

$$(2) \quad W_t(m) = 1^m \iff m \leq K.$$

Proof. At each split the two children differ by at most one. The rightmost path satisfies the explicit induction

$$\text{last } W_{t+1}(m) = \text{last } W_t(\lceil m/2 \rceil) = \left\lceil \frac{\lceil m/2 \rceil}{2^t} \right\rceil = \left\lceil \frac{m}{2^{t+1}} \right\rceil.$$

The same balanced-descendant induction makes this the largest part. If $m \leq K$, every branch reaches one and weight preservation gives m leaves. If $m > K = 2^t$, then at every level $j < t$ the smallest descendant is at least $\lfloor m/2^j \rfloor \geq 2$; thus there are no early leaves and all K leaves are present. This proves every assertion. $\square$

For a nonempty composition a , let $M(a) = \max_i a_i$.

Proposition 2.2 (pointwise and global clocks).

$$\text{depth}(a) = \lceil \log_2 M(a) \rceil, \quad \max_{a \in \mathcal{C}_n} \text{depth}(a) = \lceil \log_2 n \rceil \quad (n \geq 1).$$

The empty composition has depth zero, and (n) attains the global bound.

Proof. By lemma 2.1, after t rounds every descendant is one exactly when every source part is at most 2^t . Taking the first such t gives the pointwise formula. Since $M(a) \leq n$, the global statement and its witness follow. $\square$

Let $R_K(r)$ count compositions of r with all parts at most K , with $R_K(0) = 1$. Thus

$$(3) \quad R_K(r) = \sum_{j=1}^{\min(K,r)} R_K(r-j), \quad \sum_{r \geq 0} R_K(r) x^r = \frac{1}{1 - x - x^2 - \dots - x^K}.$$

The recurrence is the usual K -step Fibonacci convention. In particular, $R_1(r) = 1$ for every $r \geq 0$.

Corollary 2.3 (all depth layers). *The number of states in $\mathcal{C}_n$ of depth at most t is $R_{2^t}(n)$. For $t \geq 1$, the exact depth- t layer has size $R_{2^t}(n) - R_{2^{t-1}}(n)$.*

Proof. Equation (2.2) says precisely that every part is at most 2^t . The enumeration in (3) is classical; only its identification with the temporal layer is used here. $\square$

3. A CANONICAL FORM FOR THE COMPLETE ITERATED KERNEL

For $K = 2^t$, define a weight-preserving monoid map

$$(4) \quad \mathcal{N}_K(m) = \begin{cases} 1^m, & m \leq K, \\ m, & m > K, \end{cases} \quad \mathcal{N}_K(a_1 \cdots a_r) = \mathcal{N}_K(a_1) \cdots \mathcal{N}_K(a_r).$$

Its values are precisely the compositions over the canonical alphabet $\{1\} \cup \{K+1, K+2, \dots\}$.

Theorem 3.1 (canonical kernel and suffix decoder). *For all compositions a, b of the same weight,*

$$(5) \quad \Phi^t(a) = \Phi^t(b) \iff \mathcal{N}_K(a) = \mathcal{N}_K(b).$$

Moreover, Φ^t is injective on canonical forms. Its image code is

$$(6) \quad \{1\} \cup \{W_t(m) : m > K\},$$

which is a suffix code. Hence membership in $\text{im } \Phi^t$ and the unique canonical source are decided by a right-to-left decoder.

Proof. Equation (2) gives $\Phi^t(a) = \Phi^t(\mathcal{N}_K(a))$. It remains to prove injectivity on canonical forms. The codeword for the canonical letter 1 is the one-letter word 1. Every $W_t(m)$ with $m > K$ has length K and, by lemma 2.1, ends in $\lceil m/K \rceil > 1$. Distinct long codewords have distinct weights. Thus no word in (6) is a proper suffix of another.

Explicitly, if a target ends in 1, its final canonical letter must be 1; delete that symbol. Otherwise its final codeword must be the last K symbols. Their sum determines the sole possible source letter $m > K$, and the block is accepted exactly when it equals $W_t(m)$. Delete the block and repeat. This proves unique decoding and injectivity. Applying it to $\Phi^t(\mathcal{N}_K(a)) = \Phi^t(\mathcal{N}_K(b))$ proves the converse in (5). $\square$

For example, take $t = 2$, so $K = 4$. The source $(3, 5, 2)$ has canonical form

$$(1, 1, 1, 5, 1, 1)$$

and image 111111211. Reading from the right deletes two terminal ones, recognizes the block 1112 = $W_2(5)$, and then deletes three ones, recovering the canonical form.

4. EVERY FIBRE AND THE CLOCK-FIBRE DUALITY

Write a canonical form uniquely as

$$(7) \quad z = 1^{r_0} m_1 1^{r_1} m_2 \cdots m_s 1^{r_s}, \quad m_i > K, \quad r_i \geq 0.$$

For the empty decoded word we use $s = 0$ and $r_0 = 0$.

Theorem 4.1 (complete fibre product). *A target y has no t -step preimage exactly when the suffix decoder in [theorem 3.1](#) rejects it. If the decoder returns the canonical form (7), then*

$$(8) \quad |(\Phi^t)^{-1}(y)| = \prod_{j=0}^s R_K(r_j).$$

For the empty word this is the one-factor product $R_K(0) = 1$. Consequently,

$$(9) \quad \max_{y \in \mathcal{C}_n} |(\Phi^t)^{-1}(y)| = R_K(n),$$

attained by $y = 1^n$. Thus the maximum t -fibre equals the number of states of depth at most t .

Proof. By [theorem 3.1](#), the fibre over y is exactly the inverse image under $\mathcal{N}_K$ of its decoded canonical form. Every large letter m_i must remain the same source part. Independently, a run 1^{r_j} may be grouped into any composition of r_j with parts at most K , giving (8).

Concatenation injects a tuple of restricted compositions of weights $r_0, \dots, r_s$ into a restricted composition of their total weight, so the product in (8) is at most $R_K(\sum r_j) \leq R_K(n)$. The final inequality follows by appending ones. For $y = 1^n$, the canonical form is 1^n and equality holds. The last claim now follows from [corollary 2.3](#). $\square$

In the displayed $K = 4$ example, the canonical one-runs have lengths three and two. Hence the image 111111211 has $R_4(3)R_4(2) = 4 \cdot 2 = 8$ two-step preimages. This is pointwise information: different targets of the same weight generally have different products.

5. THE COMPLETE IMAGE TOWER

Let $I_{n,t} = |\text{im}(\Phi^t : \mathcal{C}_n \rightarrow \mathcal{C}_n)|$.

Theorem 5.1 (all-iterate image census). *For $K = 2^t$, restriction of Φ^t is a weight-preserving bijection from canonical forms to its image. Therefore*

$$(10) \quad \sum_{n \geq 0} I_{n,t} x^n = \frac{1}{1 - \left(x + \frac{x^{K+1}}{1-x}\right)} = \frac{1-x}{1-2x+x^2-x^{K+1}}.$$

Equivalently, $I_{0,t} = I_{1,t} = 1$ and, for $n \geq 2$,

$$(11) \quad I_{n,t} = 2I_{n-1,t} - I_{n-2,t} + \mathbf{1}_{n \geq K+1} I_{n-K-1,t}.$$

with the harmless coefficient convention $I_{j,t} = 0$ for $j < 0$. For $n \geq 1$, the number of Garden states at time t is $2^{n-1} - I_{n,t}$.

Proof. Every source has the same image as its canonical form by [theorem 3.1](#); distinct canonical forms have distinct images. Hence the image is equinumerous with sequences of parts in $\{1\} \cup \{K+1, K+2, \dots\}$. The ordinary sequence construction gives (10); coefficient extraction gives (11). There are 2^{n-1} compositions of positive n , proving the last claim. $\square$

At $t = 0$ one has $K = 1$, so (10) becomes $(1-x)/(1-2x)$: explicitly $I_{0,0} = 1$ and $I_{n,0} = 2^{n-1}$ for $n \geq 1$, as required by the identity iterate.

For $t = 1$, the image numbers begin 1, 1, 1, 2, 4, 7, 12, 21, 37, 65, $\dots$; the equinumerous canonical class is exactly the classical compositions without the part 2 [3]. This enumerative class is zero-credit. The result here is the all- t dynamical bijection supplied by the canonical kernel and suffix decoder. When $2^t \geq n$, only 1^n is canonical, so $I_{n,t} = 1$, in agreement with the sharp clock.

6. EXACT CONTROLS, LIMITS, AND CONCLUSION

The paper-local verifier uses only exact integer arithmetic and the Python standard library. It exhausts all compositions through weight 18 for the clock, and all sources and targets through weight 15 for every $0 \leq t \leq 5$. It compares literal kernel classes, suffix decoding, the fibre product, an independent factorization DP, maximum fibres, and the image census. Codewords are checked through $m = 256, t = 8$, and the rational image recurrence through weight 90, $t = 8$. These are falsification controls; the quantified statements rest on the proofs above.

The scope is deliberately finite and exact. We do not claim a new general theory of substitutions, codes, restricted compositions, fragmentation, or balanced trees. We do not treat asynchronous splits, other arities, random schedules, or asymptotic laws. The exact-map owner search remains bounded, so novelty, priority, and external release remain on hold.

Within that boundary, the normal form (4) gives more than a terminal clock: it determines the complete kernel of every iterate. The suffix code turns that kernel into a pointwise image test, the one-runs give every fibre, and the canonical alphabet gives the full image tower. The coincidence between the largest inverse fibre and the cumulative depth census is the resulting clock–fibre duality.

REFERENCES

- [1] Cyril Banderier and Paweł Hitczenko. Enumeration and asymptotics of restricted compositions having the same number of parts. *Discrete Applied Mathematics*, 160:2542–2554, 2012. doi: 10.1016/j.dam.2011.12.011.
- [2] Jean Berstel and Dominique Perrin. *Theory of Codes*, volume 117 of *Pure and Applied Mathematics*. Academic Press, 1985. ISBN 978-0-12-093420-1.
- [3] Phyllis Chinn and Silvia Heubach. Integer sequences related to compositions without 2’s. *Journal of Integer Sequences*, 6:Article 03.2.3, 2003. URL <https://cs.uwaterloo.ca/journals/JIS/VOL6/Heubach/heubach5.html>.
- [4] Dominik D. Freydenberger and Daniel Reidenbach. The unambiguity of segmented morphisms. *Discrete Applied Mathematics*, 157:3055–3068, 2009. doi: 10.1016/j.dam.2009.06.009.
- [5] Silvia Heubach and Toufik Mansour. Compositions of n with parts in a set. *Congressus Numerantium*, 168:127–143, 2004. ISSN 0384-9864.
- [6] Juha Honkala. It is decidable whether or not a permutation-free morphism is an L code. *International Journal of Computer Mathematics*, 22:1–11, 1987. doi: 10.1080/00207168708803578.
- [7] Aristid Lindenmayer and Grzegorz Rozenberg. Developmental systems and languages. In *Proceedings of the Fourth Annual ACM Symposium on Theory of Computing*, pages 214–221. ACM, 1972. doi: 10.1145/800152.804917.
- [8] Martin E. Malandro. Integer compositions with part sizes not exceeding k . arXiv:1108.0337v2, 2012.
- [9] Themis Matsoukas. Stochastic theory of discrete binary fragmentation—kinetics and thermodynamics. *Entropy*, 24(2):229, 2022. doi: 10.3390/e24020229.