

ACTIVATION DISTANCES AND EXTREMAL FIBRES OF CONFLICT-TRIGGERED CYCLIC INCREMENTS

ANONYMOUS

ABSTRACT. We determine the forward dynamics and time-one inverse of a synchronous colour update on an arbitrary finite simple undirected graph: a vertex increments modulo $q \geq 3$ exactly when a neighbor has the same colour. Equal-colour edges persist, so each vertex is stationary until activation and advances forever afterwards. We prove that its first activation time is a shortest-path distance from the initial conflicts, with directed edge weights given by initial colour differences. This yields every iterate, the recurrent core and the sharp maximum entrance time $(q-1)(n-2)$ for $n \geq 3$. Independently, all predecessors of a target are reconstructed by binary masks satisfying a total-cover condition and directed predecessor closure. Using a self-contained static bound, we show that the largest time-one fibre over all n -vertex graphs and targets is $2^{n-1} - 1$ for $n \geq 4$, attained exactly by constant targets on stars. The three-vertex exception is a constant target on a triangle, with four predecessors. The inverse characterization does not assume efficient general cover counting.

1. THE UPDATE AND ITS SCOPE

Let $G = (V, E)$ be a finite simple undirected graph, $n = |V| \geq 0$, and $q \geq 3$. For $x \in (\mathbb{Z}/q\mathbb{Z})^V$, define the simultaneous update

$$(1) \quad F(x)_v = x_v + \mathbf{1}\{\text{some } u \sim v \text{ has } x_u = x_v\} \pmod{q}.$$

Isolated vertices hold. We call an equal-colour edge a conflict and its endpoints active. All tests in (1) use the old state. The entrance $h(x)$ is the least $t \geq 0$ for which $F^t(x)$ is periodic. Unlike a proper-colouring algorithm, this update never removes a conflict: both endpoints increment together. The issue is how the resulting clocks activate stationary vertices, and which old conflict sets can produce a given target.

The conflict-detection model of Motskin et al. [4, Section II-A] already allows a local function of the current colour and one conflict bit; (1) is one deterministic choice in that model. Their Algorithm 1 uses randomized recolouring. We do not claim a new information model or transfer that algorithm's convergence result. The successor-colour trigger in the cyclic cellular automaton differs from our equality trigger [2, Section 1]: on a monochromatic edge it holds, whereas (1) rotates. This literal distinction is not a claim excluding every possible enriched representation.

We give two explicit descriptions of (1). The first uses initial-colour directed arrival distances to determine every forward coordinate, exact entrance and recurrent action. The second uses target colours to characterize all active masks in a one-step inverse and to find its uniform extremizers. Shortest paths and binary reconstruction are standard tools. The inverse uses the established class of 2-total vertex covers [1]; general total-cover counting already has complexity results [3, Corollary 2.5]. Our elementary static bound below is supporting material, not a separately claimed new graph-counting theory. Section 2 proves the forward formula and Section 3 proves the inverse statements.

2. EXACT ACTIVATION DISTANCES

Let $S(x)$ be the endpoints of the initial conflicts. Give both directed versions of each edge the weights

$$w_x(u, v) = (x_v - x_u) \bmod q \in \{0, \dots, q-1\}.$$

Write $d_x(v)$ for the minimum total weight of a directed path from $S(x)$ to v , and set it to ∞ if no such path exists. Paths of length zero are allowed. A maximum over no finite distances means zero.

Theorem 2.1. *The first conflict time of v is $d_x(v)$. For every integer $t \geq 0$,*

$$(2) \quad F^t(x)_v = \begin{cases} x_v + \max\{0, t - d_x(v)\} \pmod{q}, & d_x(v) < \infty, \\ x_v, & d_x(v) = \infty. \end{cases}$$

Moreover, $h(x) = \max_{d_x(v) < \infty} d_x(v)$. A state is recurrent exactly when each connected component is either properly coloured, hence fixed, or has a same-coloured neighbor at every vertex, hence increments

Key words and phrases. finite dynamics, synchronous graph colouring, activation time, inverse fibre, total vertex cover.

globally. Every nonfixed recurrent orbit has exact period q . The maximum entrance over all graphs and sources on n vertices is

$$H_q(n) = \begin{cases} 0, & n \leq 2, \\ (q-1)(n-2), & n \geq 3. \end{cases}$$

Proof. An active edge remains active after an update, since its two colours increment equally. Thus the active set only grows. If $\tau(v)$ is the first conflict time, then v is stationary through time $\tau(v)$ and increments at each subsequent update. This gives (2) with τ in place of d_x .

Suppose u first activates at time $a < \infty$. Its colour at that time is x_u . Unless a neighbor v activates earlier, its colour is still x_v , and it meets the advancing colour of u at time $a + w_x(u, v)$. Consequently $\tau(v) \leq \tau(u) + w_x(u, v)$. A zero-weight edge is initially monochromatic, so both its endpoints already have time zero; it cannot spontaneously activate an unseeded region. The edge inequality along every seed path proves $\tau(v) \leq d_x(v)$ whenever the latter is finite.

Conversely, suppose $\tau(v) = s > 0$. A neighbor u meeting v at time s must have activated earlier. Indeed, if both first activated at s , both would still have their initial colours, making their equality an initial conflict. With $a = \tau(u) < s$, the first meeting of that advancing color with the stationary v occurs after exactly $w_x(u, v)$ steps: an earlier congruent meeting would already activate v . Hence $s = a + w_x(u, v)$. Repeating backwards strictly decreases activation times until reaching a seed and yields a path of total weight s . Thus $d_x(v) \leq \tau(v)$. This also excludes finite activation in a seedless component, and proves the first assertion including infinite distances.

Every vertex in a seeded component has finite distance. At the last such arrival all its vertices are active and hence advance together forever; unseeded components are proper and hold forever. Before the last arrival, the active set will strictly increase at a future time, so monotonicity excludes periodicity. These observations prove the exact entrance and the stated recurrent core. If any component advances, a return after p steps forces $p \equiv 0 \pmod{q}$ at an advancing vertex, proving its exact period.

A seeded component contains at least two seeds. A minimum-weight path to a nonseed can be chosen simple and with no seed after its starting vertex. It therefore has at most $n - 2$ edges, each of weight at most $q - 1$. For $n \leq 2$ there is no seeded component containing a nonseed, giving height zero. For $n \geq 3$ take the path $0 - 1 - \dots - (n - 1)$ with $x_0 = x_1 = 0$ and $x_i = -(i - 1) \pmod{q}$ for $i \geq 2$. Only the first edge is initially monochromatic. The unique simple seed route to vertex $n - 1$ has $n - 2$ forward edges of weight $q - 1$; deleting any backtracking cannot increase a path's weight. Its distance is $(q - 1)(n - 2)$, attaining the bound. $\square$

3. A TARGET DECODER AND SHARP FIBRES

For a target y , let H_y be the spanning graph of its monochromatic edges. Let D_y have an arc $u \rightarrow v$ when $u \sim v$ and $y_v = y_u + 1 \pmod{q}$. A vertex cover whose induced graph has no isolated vertex is called a 2-total cover; we allow the empty cover. In particular, isolates of H_y must be outside such a cover.

Theorem 3.1. *The predecessors of y are, uniquely, $x_v = y_v - \mathbf{1}_A(v) \pmod{q}$, where $A \subseteq V$ satisfies:*

- (1) *A is a vertex cover of H_y ;*
- (2) *every vertex of A has a neighbor in A in H_y ;*
- (3) *an arc $u \rightarrow v$ in D_y with $v \in A$ implies $u \in A$.*

Proof. Let A be the advancing set of any predecessor. Its old colours are necessarily $y - \mathbf{1}_A$. Every old equal-colour edge has both endpoints in A . For two endpoints in A , old equality is exactly target equality; each vertex in A therefore needs an internal H_y neighbor. Two endpoints outside A cannot be equal in the target, since both held. Finally, when $u \notin A$ and $v \in A$, old equality is equivalent to $y_v = y_u + 1 \pmod{q}$, which would contradict u holding. These are the three conditions. Conversely they ensure that the endpoints of the old equal-colour edges in $y - \mathbf{1}_A$ are exactly A . Thus precisely these vertices advance and the image is y . Different masks give different old states, completing the bijection. $\square$

Write $T(H)$ for the number of 2-total covers of a simple graph H , with our empty-cover convention. Equivalently it counts independent sets I for which $H - I$ has no isolated vertex. The decoder gives

$$(3) \quad |F^{-1}(y)| \leq T(H_y).$$

For a constant target, $H_y = G$ and D_y has no arcs, so equality holds. We include the following elementary static support proof to make the dynamical extremum self-contained.

Lemma 3.2. *For a graph H on $n \geq 4$ vertices, $T(H) \leq 2^{n-1} - 1$, with equality exactly for a star $K_{1,n-1}$. On three vertices, $T(H) \leq 4$, with equality exactly for a triangle.*

Proof. For a star on $k \geq 3$ vertices the covers consist of the centre and any nonempty set of leaves, giving $2^{k-1} - 1$. A single edge has one such cover; on three connected vertices the path has three and the triangle four.

A connected nonstar with at least four vertices contains a four-vertex path as a subgraph. To see this, if a longest path were a, b, c , any further vertex can attach only to b : attachment to a or c , or a longer route from the path, extends it. An edge between leaves, including a, c , would also create a four-vertex path. The graph would therefore be a star.

Now suppose a connected nonstar has $k \geq 5$ vertices. Choose a four-vertex path and an edge uv from a vertex u of the path to a vertex v outside it. The path has eight independent sets, at least two containing each chosen u . Ignoring other edges gives $8 \cdot 2^{k-4}$ independent sets; the extra edge forbids at least $2 \cdot 2^{k-5}$ of them. Hence

$$T(H) \leq i(H) \leq 7 \cdot 2^{k-4} < 2^{k-1} - 1,$$

where $i(H)$ is the number of independent sets and the strict inequality uses $2^{k-4} \geq 2$. For $k = 4$, the connected graphs are the star, path, paw, four-cycle, diamond and complete graph. Listing independent complements with no isolated vertex left gives, respectively, 7, 4, 6, 5, 6, 5. Thus only the star attains seven.

The count T multiplies over components, and an isolate contributes one. A nontrivial component of size k has $T \leq 2^{k-1}$. Two or more nontrivial components therefore give at most $2^{n-2} < 2^{n-1} - 1$. One such component with isolates has strictly smaller order and again gives a strict bound, including the triangle count four. An edgeless graph has $T = 1$. The three-vertex disconnected cases also have $T = 1$. These cases complete the proof and the equality classification. $\square$

Theorem 3.3. *For any $q \geq 3$, the maximum time-one fibre over all graphs and targets on n vertices is*

$$M(n) = \begin{cases} 1, & n \leq 2, \\ 4, & n = 3, \\ 2^{n-1} - 1, & n \geq 4. \end{cases}$$

For $n = 3$ the extremizers are exactly constant targets on triangles, and for $n \geq 4$ exactly constant targets on stars.

Proof. Combine (3) with Lemma 3.2. At equality H_y is a spanning star, or a triangle when $n = 3$. Since this monochromatic graph is connected, y is constant on all vertices. Then $H_y = G$, so no extra nonmonochromatic edges are possible. Conversely every constant target on the claimed graph attains $T(G)$. For $n \leq 2$, an edgeless graph has the identity update; on a single edge, unequal colours hold and equal colours rotate together. This is a permutation and every fibre has size one, including the empty state. $\square$

4. SCOPE AND REPRODUCIBILITY

The forward formula holds at every time, while the inverse theorem concerns one step only. The cover/closure characterization does not provide an efficient algorithm for counting covers on arbitrary graphs, and no complete basin or recurrent-state census is asserted. The static cover class and counting complexity are prior; the support lemma is not offered as a separate originality claim. The conclusions concern the literal equality-triggered rule, not convergence to a proper colouring.

The accompanying standalone `verify.py` compares literal finite orbits with weighted distances and every target's exact source set with the mask decoder. It covers all graphs through four vertices at $q = 3, 4, 5$, all static graphs through six vertices, and the sharp paths for $2 \leq n \leq 20$, $3 \leq q \leq 9$. Its complete `CANONICAL.json` records 1,029,769 assertions. These finite checks pressure the deductions; the all-parameter results follow from the proofs above.

REFERENCES

- [1] Henning Fernau, Fedor V. Fomin, Geevarghese Philip, and Saket Saurabh. On the parameterized complexity of vertex cover and edge cover with connectivity constraints. *Theoretical Computer Science*, 565:1–15, 2015. doi: 10.1016/j.tcs.2014.10.035.
- [2] Janko Gravner, Hanbaek Lyu, and David Sivakoff. Limiting behavior of 3-color excitable media on arbitrary graphs. *The Annals of Applied Probability*, 28(6):3324–3357, 2018. doi: 10.1214/17-AAP1350.
- [3] Xavier Molinero, Fabián Riquelme, and Maria Serna. Satisfaction and power in unanimous majority influence decision models. *Electronic Notes in Discrete Mathematics*, 68:197–202, 2018. doi: 10.1016/j.endm.2018.06.034.

- [4] Arik Motskin, Tim Roughgarden, Primož Skraba, and Leonidas Guibas. Lightweight coloring and desynchronization for networks. In *IEEE INFOCOM 2009*, pages 2383–2391. IEEE, 2009. doi: 10.1109/INFCOM.2009.5062165.