

A Count-Replay Audit of a Finite $c = 1$ Prime-Shell Law Control

Liang Wang

School of Mathematics and Statistics, Huazhong University of Science and Technology (HUST), Wuhan, China
September 4, 2026

Abstract

TPC-379 found that a finite high- Q spectral signature of the all-plus prime-shell law disappeared under three diagnostic signed controls. This paper tests the most immediate continuation: does the separation survive at the larger fixed count $N = 2048$? On a fresh coordinate-disjoint affine panel, the complete $3 \times 3 \times 4 = 36$ row experiment again gives the all-plus profile $(0, 3, 3)$ and the three signed-control profiles $(0, 0, 0)$. There are six spectral-cap failures and no Schur-cap failures. The result is finite count persistence with a law-dependence obstruction; it is neither a scale-uniform theorem nor a twin-prime result.

1 Question and claim boundary

The finite operator family is designed to expose where a proposed near-block Route-B bridge needs uniformity. TPC-379 held the count at 1024 and found an all-plus high- Q profile that did not occur for three fixed signed laws. Here only the count and the coordinate-disjoint origin panel change. The same $c = 1$ mask, normalization, shell ladder, and law family are retained. All assertions below are scoped to one explicit finite computation. The signed laws are diagnostic controls; they are not asserted to be source-valid arithmetic weights. In particular, finite sub-cap values do not pay an arithmetic loss or close either route gate.

2 Finite operator

For $I = [a, a + N - 1] \cap \mathbb{Z}$, $Q < p \leq 2Q$, and $u, t \in I$, set

$$K_p(u, t) = p \left(\frac{p}{Q} \right)^2 \frac{66^2}{66^2 + (u - t)^2} \left(\mathbf{1}_{p|(u-t)} - \frac{1}{p-1} \right) \mathbf{1}_{u \neq t} \mathbf{1}_{p \nmid u} \mathbf{1}_{p \nmid t}.$$

For a declared law ℓ with signs $s_p(\ell) \in \{-1, 1\}$, define

$$A_\ell(u, t) = \sum_{Q < p \leq 2Q} s_p(\ell) K_p(u, t), \quad G(u) = \sum_{t \in I} \sum_{Q < p \leq 2Q} K_p(u, t)^2, \quad T_\ell(u, t) = \frac{A_\ell(u, t)}{\sqrt{G(u)G(t)}}.$$

The four laws are all-plus, alternating shell index, the sign of $p \bmod 4$, and a first-half/second-half shell split. With $b(u) = \lfloor (u - a)/256 \rfloor$, the common band and tail are

$$B_\ell(u, t) = T_\ell(u, t) \mathbf{1}_{|b(u) - b(t)| \leq 1}, \quad R_\ell = T_\ell - B_\ell.$$

For every unit eigenvector v of T_ℓ with eigenvalue λ ,

$$v^\top B_\ell v + v^\top R_\ell v = \lambda$$

is an exact finite identity.

3 Predeclared count-replay protocol

Before any response or metric is read, fix

$$a_j = 1300001 + 401j, \quad 0 \leq j < 41,$$

and select indices $(0, 20, 40)$, giving origins $(1300001, 1308021, 1316041)$. Use $N = 2048$, eight contiguous blocks of length 256, beta 2, exponent one, height 66, and $Q = 512, 2048, 8192$. The spectral and Schur caps are 0.64 and 0.83. All four laws are evaluated at every origin and every Q before the profile is summarized.

The current intervals are disjoint from the declared TPC-376–379 intervals by exact integer endpoint comparisons. The first 13-point subinterval at the first origin is degenerate for the $q = 8$ anchor; the fixed subinterval $[1300014, 1300027]$ is used instead. At $q = 8$ its shell is $\{11, 13\}$, and exact rational arithmetic checks positive common geometry and symmetry for all four laws. This anchor is an audit object, not a row-selection signal.

Table 1: TPC-380 finite count-2048 law-control panel.

law	$Q = 512$	$Q = 2048$	$Q = 8192$	max band spectral
all_plus	0/3	3/3	3/3	0.666945567
alternating_index	0/3	0/3	0/3	0.007764638
mod4_character	0/3	0/3	0/3	0.012038214
half_split	0/3	0/3	0/3	0.216134294

4 Results

Table 1 gives band spectral-cap failures among the three origins at each shell scale.

Thus the all-plus profile is $(0, 3, 3)$ and each signed control has profile $(0, 0, 0)$. The total spectral census is $6/36$ and the Schur census is $0/36$. The corresponding maximum band spectral values in the displayed law order are approximately

$$0.66694556698889795, \quad 0.0077646382652031094, \quad 0.012038214320188189, \quad 0.21613429440676551.$$

The certificate records all full/band metrics, selected-mode Rayleigh terms, and finite numerical residuals.

5 Independent audit

The producer locks the TPC-379 source and canonical certificate, and writes a canonical JSON certificate. A separate checker uses a direct sieve through 20000, reverse shell accumulation, independent sign construction, common geometry, and independent full and band eigensystems without importing the TPC-380 producer. A 25-mutation stress suite changes protocol, count, laws, rows, census, clue, and firewall fields; every mutation must be rejected. Normal and optimized runs require empty standard error and byte-identical summaries. The local Bridge-B repeats these finite checks and locks the stable project artifacts.

6 Route status and conclusion

The Session-named Route-A and Route-B evaluator files are absent from this checkout, so the local route note and Bridge-B are fail-closed repository evidence rather than an official evaluator verdict. The exact finite protocol, endpoint separation, common geometry, four laws, and Rayleigh split are proved finite statements. The replay and failure census are numerically certified finite statements.

The strongest positive result is persistence of the TPC-379 all-plus high- Q profile at the larger count on a fresh panel. The strongest obstruction is that the persistence remains law-dependent, so it cannot be promoted to a law-invariant mask theorem. Law/origin/scale uniformity, source-valid normalization, cross-block causality, a growing operator bound, source-uniform arithmetic L^2 , signed prime-shell reassembly, and a twin-prime conclusion remain open. The certificate records

$$\text{ARITHMETIC_ADVANCE=NO,} \quad \text{FIXED_POWER_CREDIT=0,} \quad \text{FULL_GATE_B=OPEN.}$$

The next minimal finite question is `TEST_C1_LAW_CONTROL_ORIGIN_FAMILY_REPLAY`.