Module Interface Specification for FBP CT Image Reconstruction

Qianlin Chen

April 13, 2025

1 Revision History

Date	Version	Notes
March 11	1.0	Initial document

2 Symbols, Abbreviations and Acronyms

See SRS Documentation at SRS.

symbol	unit	description	
\mathcal{F}	None	Fourier Transform	
\mathcal{F}^{-1}	None	Inverse Fourier Transform	
d	None	diagonal length of padded image	

Contents

1	Rev	rision I	History	i							
2	Syn	Symbols, Abbreviations and Acronyms									
3	Intr	Introduction									
4	Not	ation		1							
5	Mo	dule D	Decomposition	1							
6	MIS of Filter Module										
	6.1	Modu	de	3							
	6.2	Uses		3							
	6.3	Syntax	x	3							
		6.3.1	Exported Constants	3							
		6.3.2	Exported Access Programs	3							
	6.4	Seman	ntics^{-}	3							
		6.4.1	State Variables	3							
		6.4.2	Environment Variables	3							
		6.4.3	Assumptions	3							
		6.4.4	Access Routine Semantics	3							
		6.4.5	Local Functions	4							
7	MIS	of FE	BP Module	5							
	7.1	Modul	de	5							
	7.2	Uses		5							
	7.3	Syntax	X	5							
		7.3.1	Exported Constants	5							
		7.3.2	Exported Access Programs	5							
	7.4	Seman	ntics	5							
		7.4.1	State Variables	5							
		7.4.2	Environment Variables	5							
		7.4.3	Assumptions	5							
		7.4.4	Access Routine Semantics	5							
		7.4.5	Local Functions	6							
8	MIS	of Si	nogram Simulation Module	7							
	8.1	Modul		7							
	8.2	Uses		7							
	8.3	Syntax	X	7							
		8.3.1	Exported Constants								
		8.3.2	Exported Access Programs								

	8.4	Seman	tics	7
		8.4.1	State Variables	7
		8.4.2	Environment Variables	7
		8.4.3	Assumptions	7
		8.4.4	Access Routine Semantics	7
		8.4.5	Local Functions	7
9	MIS	of IO	Handler Module	9
	9.1	Module	e	9
	9.2	Uses .		9
	9.3	Syntax		9
		9.3.1	Exported Constants	9
		9.3.2	Exported Access Programs	9
	9.4	Seman	tics	9
		9.4.1	State Variables	9
		9.4.2	Environment Variables	9
		9.4.3	Assumptions	10
		9.4.4	Access Routine Semantics	10
		9.4.5	Local Functions	10
10	MIS	of Ser	rvices Module	11
	10.1	Module	e	11
	10.2	Uses .		11
	10.3	Syntax	[11
		10.3.1	Exported Constants	11
		10.3.2	Exported Access Programs	11
	10.4	Seman	tics	11
		10.4.1	State Variables	11
		10.4.2	Environment Variables	11
		10.4.3	Assumptions	11
		10.4.4	Access Routine Semantics	11
		10.4.5	Local Functions	11
11	App	endix		14

3 Introduction

The following document details the Module Interface Specifications for FBP CT Image Reconstruction. Complementary documents include the System Requirement Specifications and Module Guide. The full documentation and implementation can be found at MIS.

4 Notation

The structure of the MIS for modules comes from Hoffman and Strooper (1995), with the addition that template modules have been adapted from Ghezzi et al. (2003). The mathematical notation comes from Chapter 3 of Hoffman and Strooper (1995). For instance, the symbol := is used for a multiple assignment statement and conditional rules follow the form $(c_1 \Rightarrow r_1|c_2 \Rightarrow r_2|...|c_n \Rightarrow r_n)$.

The following table summarizes the primitive data types used by FBP CT Image Reconstruction.

Data Type	Notation	Description
character	char	a single symbol or digit
String	None	a char array
integer	\mathbb{Z}	a number without a fractional component
		in $(-\infty, \infty)$
real	\mathbb{R}	any number in $(-\infty, \infty)$
1D real number array with size s	$\mathbb{R}^(s)$	any number in $(-\infty, \infty)$
2D real number array with size m	$\mathbb{R}^{m \times m}$	any number in $(-\infty, \infty)$

The specification of FBP CT Image Reconstruction uses some derived data types: sequences, strings, and tuples. Sequences are lists filled with elements of the same data type. Strings are sequences of characters. Tuples contain a list of values, potentially of different types. In addition, FBP CT Image Reconstruction uses functions, which are defined by the data types of their inputs and outputs. Local functions are described by giving their type signature followed by their specification.

5 Module Decomposition

The following table is taken directly from the Module Guide document for this project.

Level 1	Level 2
Hardware-Hiding	Hardware-Hiding Module
Behaviour-Hiding	Filter Module FBP Module Sinogram Simulation Module IO Handler Module
Software Decision	Services Module IO Handler ModuleSinogram Simulation Module

Table 1: Module Hierarchy

6 MIS of Filter Module

6.1 Module

Filter

- 6.2 Uses
- 6.3 Syntax
- 6.3.1 Exported Constants

None

6.3.2 Exported Access Programs

Name	In		Exceptions
get_fourier_filter	s: \mathbb{Z} , filter_name: EnumString	filter: \mathbb{R}^s	ValueError, NULL

6.4 Semantics

6.4.1 State Variables

None

6.4.2 Environment Variables

None

6.4.3 Assumptions

NoneInput size s is a positive number.

6.4.4 Access Routine Semantics

get_filter(s, filter_name):

• output: (filter_name = SHEPP $\Rightarrow f(s)$ || filter_name = RAMP $\Rightarrow g(s)$ || filter_name = NONE $\Rightarrow None$) where:

1.

$$f(s) = \begin{cases} 0.25, & s = 0\\ \frac{-1}{\pi s^2}, & \text{s is odd} \\ 0, & \text{s is even} \end{cases}$$
 (1)

2.

$$g(s) = \frac{\sin \pi \cdot freq(n)}{\pi \cdot freq(n)} \cdot freq(n)$$
 (2)

freq(n) corresponds to the frequency bins in the discrete Fourier domain:

$$freq(n) = \begin{cases} \frac{n}{s}, & 0 \le n < \frac{s}{2} \\ \frac{n-s}{s}, & \frac{s}{2} \le n < s \end{cases}$$
 (3)

• exception: $exc := (s < 0 \Rightarrow ValueError \mid filter_name \notin \{\texttt{SHEPP, RAMP, NONE}\} \Rightarrow NULL)$

6.4.5 Local Functions

7 MIS of FBP Module

7.1 Module

FBP

7.2 Uses

Filter Module

7.3 Syntax

7.3.1 Exported Constants

None

7.3.2 Exported Access Programs

Name	In	Out	Exceptions
reconstruct	sinogram: $\mathbb{R}^{m \times m}$, θ : \mathbb{R}^n , filter_name:	image: $\mathbb{R}^{os \times os}$	ValueError, EmptyArray-
reconstruct	enum, os: int	Image. I	Error

7.4 Semantics

7.4.1 State Variables

2D array with size s as the fourier filter. None

7.4.2 Environment Variables

None

7.4.3 Assumptions

NoneInput sinogram are valid 2D frequency spectra.

7.4.4 Access Routine Semantics

reconstruct(sinogram, theta, filter_name, os):

• output: $\mathcal{F}^{-1}(\mathcal{F}(sinogram))$ where:

Fourier Transform

$$F(\omega) = \int_{-\infty}^{\infty} f(t) e^{-i\omega t} dt$$

Inverse Fourier Transform

$$f(t) = \frac{1}{2\pi} \int_{-\infty}^{\infty} F(\omega) e^{i\omega t} d\omega$$

 $\omega\colon\operatorname{rad/s}$ and t is the (x,y) position in spatial domain

• exception: exc :=

Exceptions	Description	
$os < 0 \mid\mid theta < 0 \Rightarrow ValueError$	Valid output size and interpolation	
$0s < 0 \mid theta < 0 \Rightarrow varaeE1101$	angle should not be negative.	
$sinogram.size < 0 \Rightarrow$	The input sinogram is invalid if the	
EmptyArrayError	input array size is smaller than 0.	

7.4.5 Local Functions

8 MIS of Sinogram Simulation Module

8.1 Module

Sinogram Simulation

8.2 Uses

None

8.3 Syntax

8.3.1 Exported Constants

None

8.3.2 Exported Access Programs

Name	In	Out	Exceptions	
radon	image: $\mathbb{R}^{m \times m}$, preserve_angle: Boolean, θ : \mathbb{R}^n	sinogram: $\mathbb{R}^{m \times m}$	None	

8.4 Semantics

8.4.1 State Variables

None

8.4.2 Environment Variables

None

8.4.3 Assumptions

Input Image are valid 2D frequency spectra.

8.4.4 Access Routine Semantics

radon(image, preserve_angle, theta):

- output:= $image \Rightarrow \int_{-\infty}^{\infty} imgae(x\cos(\theta) + y\sin(\theta), x\sin(\theta) y\cos(\theta))dy$
- exception: None

8.4.5 Local Functions

padding_radon(image, preserve_angle):

• output: padded image and center.

padded_image :=

- The diagonal length of the padded square image is calculated as: $d = \sqrt{2} \cdot max(image.size)$
- The required padding size for each dimension is: $|d-s|, \forall s \in image.size$

 $\mathbf{center} := \frac{padded_image[0]}{2}$

exception: If image is not an 2D array, raise ValueError

9 MIS of IO Handler Module

9.1 Module

IO Handler

9.2 Uses

FBP Module Sinogram Simulation Module Services Module Hardware Handling Module

9.3 Syntax

9.3.1 Exported Constants

None

9.3.2 Exported Access Programs

Name	In	Out	Exceptions
process_service	file: $\mathbb{R}^{m \times m}$, theta: \mathbb{R}^m , filter_name: String, os: int, preserve_angle: Boolean	None	None
get reconstruction	None	reconstruction: $\mathbb{R}^{os \times os}$	None

None

9.4 Semantics

9.4.1 State Variables

-service: service type sinogram: a 2D array with size m reconstructed_image: a 2D array with size os

9.4.2 Environment Variables

9.4.3 Assumptions

NoneInput Image are valid 2D frequency spectra.

9.4.4 Access Routine Semantics

select_services(op):

- transition: service := $op = reconstruction \Rightarrow 0 \mid\mid op = verification \Rightarrow 1$
- exception: $exc := op \notin ['reconstruction', 'verification'] \Rightarrow Value Fror$

process_service(file, theta, filter_name, os, preserve_angle):

• transition:

```
sinogram := service = 0 \Rightarrow load\_image(file, preserve\_angle) || service = 1 \Rightarrow simulation.radon()
```

reconstructed_image := fbp.reconstruct() from Module 7.

• exception: None

get_reconstruction(None):

- output: out := reconstructed_image
- exception: None

9.4.5 Local Functions

load_image(file, preserve_angle):

- output: read user-input image file and return a 2D numpy array.
- exception: exc := file does not exit then FileNotFound.

save_image(image):

- output: read reconstructed image (2D numpy array) from fbp and save jpg image file to selected local path.
- exception: exc := path does not exit then PathNotFound.

10 MIS of Services Module

10.1 Module

Services

10.2 Uses

FBP Module, Simulation Module, IO Handler Module

10.3 Syntax

10.3.1 Exported Constants

None VERIFICATION = 0
RECONSTRUCTION = 1

10.3.2 Exported Access Programs

None

10.4 Semantics

10.4.1 State Variables

None

10.4.2 Environment Variables

None

10.4.3 Assumptions

None

10.4.4 Access Routine Semantics

None

10.4.5 Local Functions

reconstruct(sinogram: $\mathbb{R}^{m \times m}$, $\theta : \mathbb{R}^n$, filter_name: enum, os: int):

• it is just a API Gateway for user calling the reconstruction service in Module7 and provide saving result option using Module9.

• output: None.

• exception: None

simulate(image: $\mathbb{R}^{m \times m}$, $\theta : \mathbb{R}^n$, filter_name: enum, os: int):

• it is just a API Gateway for user calling the simulation service in Module8 and provide saving result option using Module9.

• output: None.

• exception: None

References

Carlo Ghezzi, Mehdi Jazayeri, and Dino Mandrioli. Fundamentals of Software Engineering. Prentice Hall, Upper Saddle River, NJ, USA, 2nd edition, 2003.

Daniel M. Hoffman and Paul A. Strooper. Software Design, Automated Testing, and Maintenance: A Practical Approach. International Thomson Computer Press, New York, NY, USA, 1995. URL http://citeseer.ist.psu.edu/428727.html.

11 Appendix

 $[{\bf Extra~information~if~required~-\!SS}]$