

Setting up the MCP Identity Registry

Table of Contents

Prerequisites.....	1
Introduction.....	2
Setting up the PKI.....	2
Generate root and intermediate CA.....	3
Using PKCS#11 to generate root and intermediate CA.....	4
Using MCP PKI.....	5
Using OpenSSL.....	7
Setting up NGINX.....	9
Setting up database.....	9
Setting up Keycloak.....	10
Using a Docker container.....	10
Setting up Realms in Keycloak.....	11
Setting up the Identity Registry API.....	11
Using a Docker container.....	11
Directly on the system.....	12
Making an application.yaml file.....	12
Putting everything together.....	12
Finish setting up NGINX.....	13
Setting up synchronization between MIR API and Keycloak.....	13
Upgrading.....	16
Upgrading from versions older than 1.0.0.....	16
Upgrading from versions older than 1.2.0.....	16
Changes in Keycloak.....	16
MIR API.....	18

Prerequisites

- Java JDK 17 (A distribution of OpenJDK is recommended due to Oracle Licensing, but not a requirement)
- Maven 3.8.5+
- A running PostgreSQL database instance with version ≥ 10
 - Alternatively a running MySQL/MariaDB instance can also be used (MySQL 8.0+ and MariaDB 10.4 have been verified to work, but newer versions should also work)
- Keycloak (Only needed if not using the Docker image)
- NGINX
- Docker (if you want to run the identity registry using Docker containers)
- An SMTP server

Introduction

The MCP Identity Registry (MIR) is an identity solution targeted against actors of the maritime domain. It consists of three parts – an identity broker for logging in and federating users from other identity providers, a public key infrastructure for issuing and managing digital certificates and an API for management and access to the two first parts.

For the identity broker Keycloak has been chosen as it is open source and because it is based on OpenID Connect which is a widely used protocol for token based authentication.

This document will provide a generic guideline of how to setup and deploy the MIR on a local system.

The MCP is formerly known as the Maritime Cloud and therefore there will still be references to that in this document.

As the different components of the MIR rely on each other the configuration of one component may rely on the configuration of another component, but this will be documented as thoroughly as possible. <https://management.maritimeconnectivity.net/>

Complementary documentation of setup can be found at <https://github.com/maritimeconnectivity/IdentityRegistry>, <https://github.com/maritimeconnectivity/MCP-PKI> and <https://github.com/maritimeconnectivity/MCPKeycloakSpi>

For easier management of the MIR API it is advised to also setup the MCP management portal. The code for this can be found at <https://github.com/maritimeconnectivity/ManagementPortal>. A running instance of this can be found at <https://management.maritimeconnectivity.net/>.

Setting up the PKI

A part of the MIR is based on public key certificates. For this a custom PKI has been developed to issue and manage certificates for stakeholders.

To set up the PKI you must get the source code for it from <https://github.com/maritimeconnectivity/MCP-PKI/archive/master.zip> or ‘git clone <https://github.com/maritimeconnectivity/MCP-PKI.git>’.

Alternatively you can also get the needed executable from <https://github.com/maritimeconnectivity/MCP-PKI/releases/download/v1.2.0/mcp-pki-cli-1.2.0-jar-with-dependencies.jar>. Please note that this executable may not be the same as the current HEAD of the master Git branch, and therefore some of the commands that are described below might not work.

Please note that the name of the executable differs between the different versions.

After you have done this you can build the project from the directory storing the code using the following command:

mvn clean install

After this has finished there should now be a new folder called **target** under **mcp-pki-cli**. This folder contains the resulting artifacts of the build process, including the jar file **mcp-pki-cli-1.2.0-**

jar-with-dependencies.jar which is the artifact that is going to be used to generate the root certificate authority (CA) and sub-CAs for the PKI.

Generate root and intermediate CA

The next step is to generate the root CA. This can be done using the following command where you should of course replace the different fields with information relevant to your setup. For example here `root` will be the alias for the root CA, where you might want it to be called something else in your setup:

```
java -jar mcp-pki-cli-1.2.0-jar-with-dependencies.jar \
  --init \
  --root-ca-alias root \
  --truststore-path mcp-truststore.jks \
  --truststore-password changeit \
  --root-keystore-path root-ca-keystore.jks \
  --root-keystore-password changeit \
  --root-key-password changeit \
  --x500-name "C=DK, ST=Denmark, L=Copenhagen, O=MCP Test, OU=MCP Test, CN=MCP
Test Root Certificate, E=info@maritimeconnectivity.net" \
  --crl-endpoint "http://api.example.com/x509/api/certificates/crl/root" \
  --validity-period 120
```

The unit of the value of the `validity-period` parameter is months, meaning that the root CA certificate will be valid for 10 years. The validity period of a root CA certificate must not be any longer than this.

Please note that the last sub-path in the `crl-endpoint` parameter should match the value of the `root-ca-alias` parameter, so in this case the string **root**.

Be aware that the value of the `root-keystore-password` and `root-key-password` parameters need to be the same as that is expected by the MIR API.

Also note that if you use any special characters in the `root-ca-alias` they will need to be URL encoded in the `crl-endpoint`.

Finally it is highly recommended to NOT use HTTPS and only normal HTTP for the CRL endpoint due to compatibility reasons.

You should now have two different keystore files called `mcp-truststore.jks`, which contains the root CA certificate, and `root-ca-keystore.jks`, which contains both the root CA certificate and the root CA private key. The password for both of these is 'changeit', but can be set to something else by changing the values of `truststore-password` and `root-keystore-password`.

Now you will need to create a certificate revocation list (CRL) for the root CA. This can be done using the following command:

```
java -jar mcp-pki-cli-1.2.0-jar-with-dependencies.jar \
  --generate-root-crl \
  --root-ca-alias root \
  --root-keystore-path root-ca-keystore.jks \
  --root-keystore-password changeit \
  --root-key-password changeit \
  --revoked-subca-file revoked-subca.csv \
  --root-crl-path root-ca.crl
```

The file **revoked-subca.csv** should either be empty or contain the sub CAs that have been revoked separated by commas and should have a format like this

```
<serial-number>;<revocation-reason>;<revocation-date>
```

The resulting file **root-ca.crl** contains the list of sub CAs that have been revoked. Please note that the signature on this file is only valid for **one** year which means that a new root CRL must be generated and replace the current root CRL before this expires. To do this you only need to repeat the above command.

The next step is then to generate the sub CA(s) that is going to be used for issuing client certificates. The command below shows an example of how to do this:

```
java -jar mcp-pki-cli-1.2.0-jar-with-dependencies.jar \
  --create-subca \
  --root-ca-alias root \
  --root-keystore-path root-ca-keystore.jks \
  --root-keystore-password changeit \
  --root-key-password changeit \
  --truststore-path mcp-truststore.jks \
  --truststore-password changeit \
  --subca-keystore subca-keystore.jks \
  --subca-keystore-password changeit \
  --subca-key-password changeit \
  --x500-name "UID=mcp-idreg, C=DK, ST=Denmark, L=Copenhagen, O=MCP Test,
OU=MCP Test, CN=MCP Test Identity Registry, E=info@maritimeconnectivity.net" \
  --validity-period 60
```

This creates a sub CA that contains the information given in x500-name and signed by the root CA. The validity period of the created sub CA is in this example is 5 years, which is half of the validity period of the root CA. The validity period of a sub CA must not be any longer than half of the validity period of its root CA.

The sub CA certificate is added to mcp-truststore.jks and the keys of the sub CA are stored in subca-keystore.jks.

Similar, as notes above for the generation of the root CA, the values of the subca-keystore-password and subca-key-password should be the same.

All the files generated in this section should be stored for later usage.

Using PKCS#11 to generate root and intermediate CA

Storing and handling of root and intermediate CAs and their private keys on hardware security modules (HSM) instead of keystores is also supported by the MCP PKI library using the PKCS#11 standard.

If you are going to use an HSM please make sure that you have the drivers installed for it, and that a PKCS#11 connector shared library is also available for it – this usually comes in the form of a DLL for Windows or a .so file for Unix-like operating systems (Linux, MacOS, etc.). If there are any issues regarding this, please refer to the manufacturer of the HSM. Note that even though PKCS#11 is the one of PKI standards for interfacing to different types of HSM, the implementation of it may differ by manufacturers which can impact the compatibility to the MCP PKI PKCS#11 support. The policy of an HSM may impact it as well.

Before you move on you will need to prepare a token slot in the HSM – how this can be done will usually be described in the documentation of the HSM. In an ideal setting you will also need to have two different HSMs – one for the root CA and one for the intermediate CA. If that is not possible, then the root and intermediate CA should at least be stored in different slots with different passwords in the HSM.

Using MCP PKI

Generation of root and intermediate CA's using the MCP PKI is possible as long as the HSM supports modifying objects over PKCS#11. An example of an HSM that does not support this is the YubiHSM 2 (see https://developers.yubico.com/YubiHSM2/Component_Reference/PKCS_11/).

For Java, to be able to use the PKCS#11 connector you will need to make a file called pkcs11.cfg. The structure of it and what should be included in this file is described at <https://docs.oracle.com/en/java/javase/17/security/pkcs11-reference-guide1.html#GUID-C4ABFACB-B2C9-4E71-A313-79F881488BB9>.

An example of how this file could look like when using [SoftHSMv2](#) is shown below:

```
name = RootCA
library = /usr/lib/softhsm/libsofthsm2.so
showInfo = true
slot = 1418149817
```

This tells the Java to make a PKCS#11 provider called 'RootCA', that the shared library for the PKCS#11 connector is located at the absolute path '/usr/lib/softhsm/libsofthsm2.so', that info about the HSM should be written to the log on initialization and that slot 1418149817 should be used in the HSM.

Note that sometimes it might be necessary to add additional attributes in the file to be able to use certain features. The snippet below can be added to the file to allow any private key to be able to sign data:

```
attributes(*,CKO_PRIVATE_KEY,*) = {
    CKA_SIGN = true
}
```

A bit of experimentation might be necessary to find the correct configuration for your HSM before going into production.

Generation of the root CA can then be done using the following command:

```
java -jar mcp-pki-cli-1.2.0-jar-with-dependencies.jar \
  --init \
  --pkcs11 \
  --pkcs11-conf pkcs11.cfg \
  --pkcs11-pin 2468 \
  --truststore-path mcp-truststore.jks \
  --truststore-password changeit \
  --root-ca-alias root \
  --x500-name "C=DK, ST=Denmark, L=Copenhagen, O=MCP Test, OU=MCP Test, CN=MCP Test Root Certificate, E=info@maritimeconnectivity.net" \
  --crl-endpoint "http://api.example.com/x509/api/certificates/crl/root" \
  --validity-period 120
```

This will use the configuration that you specified in `pkcs11.cfg` to interact with the HSM and use the pin “2468” to use slot that is defined. Note that this also assumes that `pkcs11.cfg` is located in your current working directory, so if it is not you will need to set the value of the `pkcs11-conf` parameter to the absolute path of the file. If you have used another pin when setting up the slot in your HSM (which you definitely should do!) you should change the value of the `pkcs11-pin` parameter to the pin that you chose.

Given that this succeeded you will now have a file called ‘`mcp-truststore.jks`’ in your current working directory. If it failed you might either have to change things in your configuration, or in some cases you might need to use procedure using OpenSSL that is described in the next section.

The next step is to generate the root CA certificate revocation list (CRL). For this you will need a file called **revoked-subca.csv** which should contain the list of revoked intermediate CA’s. When you are initially setting up everything this will of course be empty, so therefore the file should also be empty in that case. If you have to revoke an intermediate CA you will need to include that and any other revoked intermediate CAs separated by commas in the format

```
<serial-number>;<revocation-reason>;<revocation-date>
```

Then to generate the root CA CRL the following command can be used:

```
java -jar mcp-pki-cli-1.2.0-jar-with-dependencies.jar \
  --generate-root-crl \
  --root-ca-alias root \
  --pkcs11 \
  --pkcs11-conf pkcs11.cfg \
  --pkcs11-pin 2468 \
  --revoked-subca-file revoked-subca.csv \
  --root-crl-path root-ca.crl
```

Given that this succeeded you will now have a file called ‘`root-ca.crl`’ which is the actual root CA CRL which is signed using the private key of the root CA.

The next step is now to generate the intermediate CA that is going to be used to sign end user certificates. Before this can be done it is assumed that the root CA and the intermediate CA will be stored in either two different HSM’s or two different slots in the same HSM. This also means that there needs to be different PKCS#11 configurations for the two – for the root CA the `pkcs11.cfg` can be reused from previously, but for the intermediate CA you will need to make a new file ‘`pkcs11_sub.cfg`’ that should contain the configuration for it. To then generate the intermediate CA the following command can be used:

```
java -jar mcp-pki-cli-1.2.0-jar-with-dependencies.jar \
  --create-subca \
  --root-ca-alias root \
  --pkcs11 \
  --pkcs11-root-conf pkcs11.cfg \
  --pkcs11-root-pin 2468 \
  --pkcs11-sub-conf pkcs11_sub.cfg \
  --pkcs11-sub-pin 2468 \
  --truststore-path mcp-truststore.jks \
  --truststore-password changeit \
  --x500-name "UID=mcp-idreg, C=DK, ST=Denmark, L=Copenhagen, O=MCP Test, OU=MCP Test, CN=MCP Test Identity Registry, E=info@maritimeconnectivity.net" \
  --validity-period 60
```

Given that this succeeded, the intermediate CA will now have been generated and stored in the HSM and the certificate of it will have been added to the 'mcp-truststore.jks' file. This file along with the .cfg file for the intermediate CA and the root CA CRL should all be kept for later usage.

Using OpenSSL

To use OpenSSL to generate the root and intermediate CA's you will need to first install a PKCS#11 provider. An example of one such provider is the one that is included in [libp11](#). On Ubuntu this can be installed using the command

```
sudo apt install libengine-pkcs11-openssl
```

When that has been installed you will need to generate the private key that you will be using for your root CA. The following command can be used to generate an elliptic curve key pair using the secp384r1 curve:

```
pkcs11-tool --module /usr/lib/softhsm/libsofthsm2.so --login --pin <password> \
--keypairgen --slot <slot id> --key-type EC:secp384r1 --label root --usage-sign
```

This command uses the path for the SoftHSMv2 connector, so if you are using another HSM you will of course need to change the path given to the 'module' parameter to its PKCS#11 connector. Please verify yourself with the documentation of both pkcs11-tool and your specific HSM whether you need to specify additional parameters. After execution of the command please take note of the ID that is given to the private key object in the output of the command as it will be needed in the later stages.

The next step now is to make a configuration file that specifies how OpenSSL should be able to use PKCS#11. The easiest way to do this is to first make a copy of OpenSSL's default configuration file to a suitable working directory and call it engine.conf. The default configuration file is usually located in /usr/lib/ssl/openssl.cnf or /etc/ssl/openssl.cnf in Linux based systems. Next you will need to append some additional configuration to the file. At the top of the file you should add the line:

```
openssl_conf = openssl_init
```

At the bottom of the file you should add:

```
[ v3_intermediate_ca ]
# Extensions for a typical intermediate CA (`man x509v3_config`).
subjectKeyIdentifier = hash
authorityKeyIdentifier = keyid:always,issuer
basicConstraints = critical, CA:true, pathlen:0
keyUsage = critical, digitalSignature, cRLSign, keyCertSign

[openssl_init]
engines = engine_section

[engine_section]
```

```
pkcs11 = pkcs11_section
```

```
[pkcs11_section]
```

```
engine_id = pkcs11
```

```
#dynamic_path is not required if you have installed
```

```
#the appropriate pkcs11 engines to your openssl directory
```

```
#dynamic_path = /path/to/engine_pkcs11.{so|dylib}
```

```
MODULE_PATH = /path/to/pkcs11_driver_library.so
```

```
#INIT_ARGS = <any needed init args>
```

```
init = 0
```

Next you will need to generate your self signed root CA using the key pair that you generated earlier. This can be done using the following command:

```
openssl req -new -x509 -days 3650 -sha384 -config engine.conf -engine pkcs11 \
-subj '/C=DK/ST=Denmark/O=MCP/OU=MCP/CN=MCP Root \
/E=info@maritimeconnectivity.net' \
-keyform engine -key <pkcs11-uri> -out root.pem
```

The value of <pkcs11-uri> can be formatted like <slot-id>:<key-id> or

"pkcs11:object=root-ca;type=private;pin-value=changeit" if the HSM follows [RFC7512 PKCS #11 URI scheme](#). Remember to change the content of the subject string to what you need and use the slot id and key id of the key pair that you generated earlier. If this succeeded you will now have a file called root.pem containing your root CA certificate. This file you will need to import into your HSM and store it under the same ID as the corresponding private key. How this can be done depends on the HSM itself and the interface to it. An example on how to do this with the YubiHSM can be found at https://developers.yubico.com/YubiHSM2/Commands/Put_Opaque.html. Then it is time to generate the root CA CRL:

```
openssl ca -config engine.conf -engine pkcs11 -keyform engine -keyfile <pkcs11-
uri> -gencrl -out root-ca.crl
```

The next step is then to generate the intermediate CA. To do that you must first generate a key pair for it. This can be in the same way as described for the root CA above. Then you must generate a certificate signing request (CSR) for the intermediate CA. This can be done using the command:

```
openssl req -new -days 1825 -sha384 -config engine.conf -engine pkcs11 \
-subj '/C=DK/ST=Denmark/O=MCP/OU=MCP/CN=MCP/E=info@maritimeconnectivity.net' \
-keyform engine -key <pkcs11-uri> -out intermediate.csr
```

Again, remember to change subject to what you need, and use the slot id and key id for the

Next you will need to sign the CSR with the private key of the root CA. This can be done using the following command:

```
openssl ca -config engine.conf -extensions v3_intermediate_ca -notext \
-md sha384 -in intermediate.csr -out intermediate.pem -engine pkcs11 \
-keyfile <pkcs11-uri> -keyform engine
```


The resulting intermediate CA certificate will then be output to the file `intermediate.pem`. Again you will need to remember to import the file into the HSM. The certificate chain can be created as following:

```
cat intermediate.pem root.pem > mcp-ca-chain.pem
```

The truststore should be created manually for the MIR integration using the following command:

```
keytool -import -keystore truststore.jks -file root.pem -alias <root-ca-alias>
```

For the registration of the intermediate CA to the truststore:

```
keytool -import -keystore truststore.jks -file intermediate.pem -alias  
<intermediate-ca-alias>
```

Remember the values `<root-ca-alias>` and `<intermediate-ca-alias>` need to be matched with the corresponding value in the `application.yaml` of MIR.

Setting up NGINX

The next step is to set up NGINX. This is not required, but it is highly recommended to use NGINX as a reverse proxy because it makes handling of TLS and client certificate authentication a lot easier.

In the supplied file `nginx.conf` is an example of how NGINX can be used to proxy incoming requests to the Identity Registry API and Keycloak assuming that they are running on the same machine.

There are some requirements that need to be met to use the configuration.

The first one is that you need to have a domain registered with the sub-domains **api**, **api-x509**, **maritimeid**, **maritimeid-x509**. These can of course be changed to something else in the configuration is necessary.

The second requirement is that you need to have a TLS certificate for your domain. The path to the certificate should then be defined in the variable `ssl_certificate` and then the path to the corresponding private key should be defined in the variable `ssl_certificate_key`.

The third requirement is that the variable `ssl_crl` should point to an up-to-date file that contains the CRLs of the root CA and the sub CAs concatenated together. How to set this up will be described later in this document.

The fourth requirement is that the variable `ssl_client_certificate` must point to a file that contains the certificates of the root CA and the sub CAs in PEM format. These can be extracted from the `mc-truststore.jks` generated in the previous step using a tool like KeyStore Explorer.

NGINX can either be installed and run directly on the machine or in a Docker container. Note that if you choose to run it in a Docker container it is recommended to run it with the option `--net=host` so it binds directly to the network interface of the host instead of using the default bridge driver.

Setting up database

Prerequisite of installing both Keycloak and the Identity Registry API is an installation of PostgreSQL. Alternatively MySQL or MariaDB can also be used. Additionally, you should also setup users and databases for both Keycloak the Identity Registry API. For the latter, convenience scripts are provided as `'create-database-and-user-<db>.sql'` where `<db>` is either `mysql` or `postgres`.

Setting up Keycloak

The next step is to setup Keycloak. This can be done using either a standalone installation of Keycloak or using the prebuilt Docker container. Using the Docker container is recommended, but if a standalone installation is required a guide on how to use this can be found at <https://github.com/maritimeconnectivity/MCPKeycloakSpi>.

Using a Docker container

A prebuilt Docker container for Keycloak with MCP specific functionality can be found at <https://github.com/maritimeconnectivity/MCPKeycloakSpi/pkgs/container/mcpkeycloakspi>. At the time of writing the latest tag for this is **1.2.0**. The **latest** tag is built from the latest code from the main git branch and is therefore not guaranteed to be stable.

For creating the Docker container using the **1.2.0** tag you can use the following command:

```
docker create --name=mir-keycloak --restart=unless-stopped -p 8080:8080 \
-v <directory for configurations>:/mc-eventprovider-conf \
-e KC_SPI_EVENTS_LISTENER_MCP_EVENT_LISTENER_SERVER_ROOT=https://api-
x509.example.com \
-e KC_DB_URL=jdbc:postgresql://<IP or host of database>/keycloak
ghcr.io/maritimeconnectivity/mcpkeycloakspi:1.2.0
```

The directory that is mounted to ‘/mc-eventprovider-conf’ in the container must contain the following file:

- idbroker-updater.jks

This file is used by Keycloak to get specific attributes from the Identity Registry API for users when they login. How this file is generated is described later in this document and does not need to be present to begin with.

The URL given as value for the variable

KC_SPI_EVENTS_LISTENER_MCP_EVENT_LISTENER_SERVER_ROOT must be set to the same value as the one set in the NGINX configuration.

As default the database and the user that is to be used for it are set to be **keycloak** and the password for the database user is set to be **password** and the database type is set as PostgreSQL. If you want to use other values than these you can set them as variables in the above command as described at <https://www.keycloak.org/server/all-config#category-database>. Additionally, you can also see the default values that are set at

<https://github.com/maritimeconnectivity/MCPKeycloakSpi/blob/master/docker/Dockerfile>.

Alternatively, Keycloak also supports creating optimized builds where startup is faster and configuration is baked in – a guide on how to do this can be found at https://www.keycloak.org/server/containers#_creating_a_customized_and_optimized_container_image and the Dockerfile in the previous link can be used as inspiration.

To start Keycloak you can then use the command

```
docker start mir-keycloak
```

Setting up Realms in Keycloak

When you have gotten Keycloak up and running you will need to setup the needed Realms. To login to the admin interface of Keycloak go to <http://localhost:8080> if you have Keycloak running on localhost or else use the domain set in your NGINX configuration. The first time you login you will need to setup an admin user and password.

After that you will need to import the three *-realm.json files from <https://github.com/maritimeconnectivity/IdentityRegistry/tree/master/setup>.

This can be done in the admin interface of Keycloak by hovering the mouse over the dropdown 'Select realm' and then click 'Add realm'. Here you can then import the *-realm.json files one by one.

Note that the URLs to OIDC clients, identity providers, etc. are set to localhost in the *-realm.json files so these will need to be updated to the correct URLs after the files have been imported. Please refer to Keycloak's own documentation at <https://www.keycloak.org/documentation.html>.

Setting up the Identity Registry API

The next step then is to set up the Identity Registry API (MIR API). There are two ways this can be done – either by setting it up directly on the system or by running it in a Docker container. Running in a Docker container is recommended, but both methods will be described in separate sections.

The source code for the Identity Registry API can be found at <https://github.com/maritimeconnectivity/IdentityRegistry>.

Using a Docker container

A prebuilt Docker image for the Identity Registry API can be found at <https://github.com/maritimeconnectivity/IdentityRegistry/pkgs/container/identityregistry>. At the time of writing the latest tag for this is **1.2.0**. The **latest** tag is built from the latest code from the main git branch and is therefore not guaranteed to be stable.

For creating the Docker container using the **1.2.0** tag you can use the following command:

```
docker create --name=mir-api --restart=unless-stopped -p 8443:8443 \
-v <directory for configurations>:/conf
ghcr.io/maritimeconnectivity/identityregistry:1.2.0
```

The folder that has been mounted to 'conf' in the container needs to contain the following files:

- An application.yaml file
- mcp-truststore.jks
- root-ca.crl
- mcp-sub-ca-keystore.jks

How to make the two first files will be described later on. The three other files were the ones that were generated in the first step.

Directly on the system

For the standalone method you need to first download the newest version of the Identity Registry API from <https://github.com/maritimeconnectivity/IdentityRegistry>. When you have done that you

can compile the source code by going into the root directory of the project and issue the following command:

```
mvn clean install
```

After this has finished you will now have a new directory called 'target' that should contain a file called mcp-identityregistry-core-latest.jar. This can then be executed using the following command:

```
java -jar mcp-identityregistry-core-latest.jar \
--spring.config.location=<location for an application.yaml file>
```

Again how to make the two needed files will be described later.

Making an application.yaml file

An example of an application.yaml file can be found at

<https://github.com/maritimeconnectivity/IdentityRegistry/blob/master/src/main/resources/application.yaml>.

It is important that this file is configured according to the correct URLs, database connections, name of the default sub CA, name of the root CA, mail sending settings, etc.

When all of this has been configured the resulting file should then be put in the configuration directory of the MIR API.

Putting everything together

You can now also start up the MIR API. If you have set it up using the Docker container you can start it using the command

```
docker start mir-api
```

If you are not running it in a Docker container you can start it as described earlier.

If everything has been configured correctly all tables for the database should be generated automatically while the program starts.

After the program has finished starting up, indicated in the log by the entry 'Started McIdregApplication in X seconds (JVM running for Y)', you now need to create an organization that is going to be used to bootstrap everything. To do this you need to insert the values from <https://github.com/maritimeconnectivity/IdentityRegistry/blob/master/setup/create-mc-org.sql> into the database that is used for MIR API. This will create an organization called 'Bootstrap Org' and a permission called MCPADMIN for the organization that maps to the role ROLE_SITE_ADMIN which is a kind of 'superadmin' role that is able to administrate all entities in the MIR. Please be aware that before executing 'create-mc-org.sql' you need to update the MRN of the bootstrap organization according to your IPID, for example "urn:mrn:mcp:org:[\$IPID]:bootstrap" and the value of the 'certificate_authority' field should match the UID of the intermediate CA you created earlier.

When this has been done we can move on to creating the organization that is going to be managing the MIR instance. A description on how to do this is given at <https://github.com/maritimeconnectivity/IdentityRegistry#insert-data>. Note that this description assumes that both the MIR API and Keycloak are running on localhost so you might need to change

the URL to fit your own setup. Also note that the organization that is going to be created is called 'Danish Maritime Authority' which you might also want to change. Finally the role mapping that is created from dma.json contains the role ROLE_ORG_ADMIN and the permission MCPADMIN. This gives users from the DMA organization with the permission MCPADMIN admin permissions for entities in the DMA organization. Like for the 'Bootstrap Org' organization you might also want to create another role with a different name and the role ROLE_SITE_ADMIN for the organization if you want it to be able to have 'superadmin' permissions. Note that this cannot be created using the API and needs to be created directly in the database as was done earlier when creating the 'Bootstrap Org' organization.

Finish setting up NGINX

Now that the MIR API is up and running it is time to finish the setup of NGINX for it to be able to validate client certificates. This is done by setting up a CRON job that executes a script that gets the CRL for the root CA and for the sub CA(s) and combines them in a single file. If you want the CRON job to be run every 5 minutes and redirect the console output to a log file the CRON configuration could look like this:

```
*/5 * * * * update-crl.sh &>> update-crl.log
```

An example of this script can be seen in the supplied update-crl.sh.

In the NGINX configuration you should then change the value of `ssl_crl` to the location of the file that contains the CRLs. After that you should then restart NGINX for the change to take effect.

Setting up synchronization between MIR API and Keycloak

The next step now is to setup synchronization between the MIR API and Keycloak. This needs to be setup so that when a user authenticates in Keycloak, information about the user, like name, permissions and so on, can be fetched from the MIR API by Keycloak in order to make sure that the information that Keycloak has stored about the user is synchronized with the information that the MIR API has stored about the same user.

To do this you need to create a 'device' entity in the organization that you have setup to have the 'superadmin' permissions. This 'device' will then be used to facilitate the authentication of Keycloak against the MIR API using a client certificate.

If you create the device directly using the MIR API you can take inspiration from the given sync-device.json. The details of this device corresponds to the default configuration in the user-sync part of the MIR API application.yaml. You can also consider setting up the MCP management portal so you don't need to use the APIs directly. A manual on how to use this can be found here <https://manual.maritimeconnectivity.net/>.

If you are using the MIR API directly you can reuse the authentication that you used previously to insert data. An example of the values for the identity of this device can be found at <https://github.com/maritimeconnectivity/IdentityRegistry/blob/master/setup/guide/sample-conf/sync-device.json>. If using this you will of course need to change the values to fit your use case. The device can then be created using the following command:

```
curl -k -H "Content-Type: application/json" -H "Authorization: Bearer $TOKEN" \
--data @sync-device.json
https://example.com/oidc/api/org/urn:mrn:mcp:org:idp1:dma/device
```

When you have then created this device you will need to issue a certificate for it. This can either be done using the management portal or again using the API directly. To do the latter the following command can be used if the MIR API is configured to allow server generated keys:

```
curl -k -H "Authorization: Bearer $TOKEN"
https://example.com/oidc/api/org/urn:mrn:mcp:org:idp1:dma/device/urn:mrn:mcp:device:idp1:dma:sync/issue-new
```

The format of the returned JSON object is described at

<https://github.com/maritimeconnectivity/IdentityRegistry#insert-data>. The parts of the object that need to be used are the JKS keystore and the keystore password. The JKS keystore is BASE64 encoded so therefore it needs to be decoded and saved in a file called idbroker-updater.jks. This file should then be put in the directory that corresponds to the /conf directory for the Keycloak Docker container or in the directory that corresponds to the 'keystore-path' variable if using a standalone installation of Keycloak. In the default configuration of Keycloak the password for the keystore file is set to be 'changeit' so Keycloak to be able to open the keystore you might need to either change the password of it or set the 'keystore-password' variable to the correct password.

If the MIR API is NOT configured to allow server generated keys you will need to generate a key pair and a certificate signing request (CSR) for the device you just created.

To do that you can use OpenSSL as follows:

```
openssl ecparam -out private.key -name secp384r1 -genkey

openssl req -new -key private.key -out request.csr
```

What the first command did was that it created an elliptic curve private key and saved it in the file 'private.key', which is then used by the second command to generate a CSR that is signed using the private key and saved in the file 'request.csr'.

The next step is then to send the CSR to the MIR API to get it signed. This can be using for example cURL in the following way:

```
curl -k -H "Authorization: Bearer $TOKEN" -H "Content-Type: text/plain" \
--data-binary @request.csr \
https://localhost/oidc/api/org/urn:mrn:mcp:org:idp1:dma/user/urn:mrn:mcp:device:
idp1:dma:sync/certificate/issue-new/csr
```

If this worked correctly the MIR should have returned a signed certificate chain which looks similar to this:

```
-----BEGIN CERTIFICATE-----
....
-----END CERTIFICATE-----
-----BEGIN CERTIFICATE-----
....
-----END CERTIFICATE-----
```

This should be saved in a file called certificate.pem.

The next step then is to first combine the certificate chain and private key into one file and then generate a keystore that enables Keycloak to use the generated certificate. This can be done in the following way:

```
openssl pkcs12 -export -out keystore.p12 -in certificate.pem -inkey private.key
```

```
keytool -importkeystore -deststorepass changeit -destkeystore \
idbroker-updater.jks -srckeystore keystore.p12 -srcstoretype PKCS12
```

The resulting file 'idbroker-updater.jks' should then be put in the directory that corresponds to the /conf directory for the Keycloak Docker container or in the directory that corresponds to the 'keystore-path' variable if using a standalone installation of Keycloak. In the default configuration of Keycloak the password for the keystore file is set to be 'changeit' so Keycloak to be able to open the keystore you might need to either change the password of it or set the 'keystore-password' variable to the correct password.

The final step you will need to do is to configure the MIR API to accept this newly created certificate. For this you will need to find the section that is shown in the image below in the application.yaml file of the MIR API.

A screenshot of a code editor showing a YAML configuration file. The file has a dark background with light-colored text. On the left side, there are line numbers 67 through 72. The configuration is for a 'user-sync' section. It includes a comment in green: '# The DN of the certificate used to sync users from keycloak'. Below this, the 'user-sync' section is defined with several key-value pairs: 'c' is 'DK', 'o' is 'urn:mrn:mcp:org:idp1:dma', 'ou' is 'device', and 'mrn' is 'urn:mrn:mcp:device:idp1:dma:sync'.

```
67 # The DN of the certificate used to sync users from keycloak
68 user-sync:
69   c: DK
70   o: "urn:mrn:mcp:org:idp1:dma"
71   ou: device
72   mrn: "urn:mrn:mcp:device:idp1:dma:sync"
```

In this section you will need to change the value of the **c**, **o**, **ou** and **mrn** variables to match the values of the **C**, **O**, **OU** and **UID** fields of the certificate you just issued. If you are not sure about what these are you can use OpenSSL to print out the contents of the certificate:

```
openssl x509 -in certificate.pem -noout -text
```

In the output from this command you should look for the line that looks something like:

Subject: C = ...

After you have changed the configuration you will need to restart the MIR API.

After the MIR API has been restarted everything should now be good to go and ready to be used.

Upgrading

WARNING

Even though upgrades in most cases should not cause any problems, there is always the possibility that something can go wrong. Therefore it is always a good idea to backup your databases and any external configuration before performing the upgrade.

For database backups you should make sure that you don't include any database locks. An example of how this can be done for MySQL can be found at [this](#) StackExchange post.

Upgrading from versions older than 1.0.0

Upgrading from an older version to a newer one of the MIR API and Keycloak can in most cases be done by just stopping the old version of the components and then starting the new ones with the same configurations and attributes.

For the upgrade of Keycloak there are unfortunately some MCP specific configurations that cannot be updated automatically. For this purpose a Bash script has been made. The script can be found [here](#) and requires that the user has the Keycloak Admin CLI and jq installed.

Upgrading from versions older than 1.2.0

Changes in Keycloak

If you are running Keycloak as a Docker container you need to be aware that environmental variables have changed quite a lot. You should therefore compare your current setup with the section of setting up Keycloak in this document.

Version 1.2.0 of the MIR introduces Keycloak being based on Quarkus instead of Wildfly. As part of this, one of the custom MCP Keycloak providers has been renamed from 'mc-event-listener' to 'mcpEventListener'. This needs to be reflected in the configuration of Keycloak after being updated:

To do this you need to go to the Admin console of Keycloak → choose the MCP realm → click on 'Realm settings' → click on the 'Events' tab → click on the x on 'mc-event-listeners' in the 'Event listeners' box → choose 'mcpEventListener' in the dropdown → click 'Save'.

Additionally, the functionality of the Javascript authentication provider that automatically merged users from identity providers is no longer functional, but the same functionality can easily be configured as an Authentication flow directly in Keycloak:

To do this you need to go to the Admin console of Keycloak → choose the MCP realm → click on 'Authentication' → click on 'Create flow' → create the new flow similarly to the first image below → create two steps as shown in the second image using the 'Add step' button.

Create flow

You can create a top level flow within this from

Name *	<input type="text" value="Auto broker login"/>
Description ?	<input type="text"/>
Flow type ?	<div>Basic flow ▼</div>
<div>Create Cancel</div>	

Auto broker login Specific providers

<div><div></div><div></div><div>Add step</div><div>Add sub-flow</div></div>	
Steps	Requirement
<div>⌵</div> <div>Create User if Unique</div>	<div>Alternative ▼</div> <div>⚙️ 🗑️</div>
<div>⌵</div> <div>Automatically set existing user</div>	<div>Alternative ▼</div> <div>🗑️</div>

After having created the new authentication flow you need to apply it to your identity providers:

Go to 'Identity providers' → click on 'Users' → scroll down to the 'First login flow' dropdown → change the value to the new authentication flow you created before → click 'Save' → go back, and repeat for the 'Certificates' identity provider.

The last thing to configure in Keycloak is the base URL of the 'Certificates' realm:

Go to the 'Certificates' realm → click on 'Realm settings' → fill out the 'Frontend URL' box with the base URL of your 'Certificates' realm similarly as shown in the image below → click 'Save'.

Certificates

Realm settings are settings that control the options for users, applications, roles, and groups in the current realm. [Learn more](#)

General

Login

Email

Themes

Keys

Events

Localization

Security defenses

Sessions

Tokens

Client policies

User registration

Realm ID *	Certificates
Display name	
HTML Display name	
Frontend URL ?	https://maritimeid-x509.example.com/auth/
Require SSL ?	External requests
ACR to LoA Mapping ?	No attributes have been defined yet. Click the below button to add attributes, key and value are required for a key pair. Add an attribute
User-managed access ?	<input type="checkbox"/> Off
Endpoints ?	OpenID Endpoint Configuration SAML 2.0 Identity Provider Metadata
Save Revert	

MIR API

Some small changes need to be done in the 'application.yaml' file of the MIR API:

1. You need to add the URL of your 'MCP' Keycloak realm. The format of how this should look like can be seen in the image below. The purpose of this is also described [here](#).
2. All occurrences of the string 'javax' need to be changed to 'jakarta'.

```

# Email setup
spring.mail:
  default-encoding: UTF-8
  host: localhost
  port: 1025
  #username:
  #password:
  # Additional JavaMail session properties.
  #properties.*=
  protocol: smtp
  # Test that the mail server is available on startup.
  test-connection: false

spring.security:
  oauth2:
    resourceserver:
      jwt:
        issuer-uri: http://localhost:8080/auth/realms/MCP

# Do not "leak" internal setup details in http X-Application-Context header
management.server.add-application-context-header: false
---
spring:
  config:
    activate:

```