

AccessPlan.prototype

(/js/AccessPlan).validateDoc

```
AccessPlan.prototype.validateDoc(  
  validateDocCol as String,  
  schemaDef as Object  
) as ModifyPlan
```

Summary

Validate the document based on a supplied schema. This schema needs to be stored in the schema database. Check appserver error log for validate errors.

Parameters	
validateDocCol	This is the column which contains the document to validate. This can be a string of the column name or an op.col (./op.col). Use op.viewCol (./op.viewCol) or op.schemaCol (./op.schemaCol) if you need to identify columns in the two views that have the same column name.
schemaDef	This is an object. The required 'kind' property of the schema object must be 'jsonSchema', 'schematron', or 'xmlSchema'. When 'kind' is 'jsonSchema' or 'schematron' then a property 'schemaUri' is required. Property 'mode' takes 'strict', 'lax' or 'type' (refer to xdm.validate).

See Also

- [Optic API for Multi-Model Data Access \(/guide/app-dev/OpticAPI#id_93259\)](/guide/app-dev/OpticAPI#id_93259) in the *Application Developer's Guide*

Example

```
const op = require('/MarkLogic/optic');  
op.fromDocDescriptors([uri: '/optic/validateDoc/toValidate1.xml'])  
  .joinDocCols(null, op.col('uri'))  
  .validateDoc('doc', {kind: 'xmlSchema', mode: 'strict'})  
  .result();
```

Example

```
const op = require('/MarkLogic/optic');
op.fromDocDescriptors([uri: '/optic/validateDoc/toValidate1.xml'},
                      {uri: "/optic/validateDoc/toValidate2.xml"},
                      {uri: "/optic/validateDoc/toValidate3.xml"}]])
  .joinDocCols(null, op.col('uri'))
  .orderBy('uri')
  .validateDoc('doc', {kind: 'xmlSchema', mode: 'type', type: fn.QName("http://marklogic.com/xdmp/group")
  .result();
```

Example

```
const op = require('/MarkLogic/optic');
op.fromDocDescriptors([uri: "/optic/validateDoc/validate4.json"}]])
  .joinDocCols(null, op.col('uri'))
  .validateDoc('doc', {kind: 'jsonSchema', schemaUri: '/validateDoc-test.json', mode: "full"})
  .result();
```

Example

```
const op = require('/MarkLogic/optic');
op.fromDocDescriptors([uri: '/optic/validateDoc/toValidateSchematron1.xml'},
                      {uri: "/optic/validateDoc/toValidateSchematron2.xml"},
                      {uri: "/optic/validateDoc/toValidateSchematron3.xml"}]], 'view')
  .joinDocCols(op.docCols('view'), op.viewCol('view', 'uri'))
  .orderBy(op.viewCol('view', 'uri'))
  .validateDoc(op.viewCol('view', 'doc'), {kind: 'schematron', schemaUri: "/validateDoc-test.sch"})
  .result();
```