

3V3 VOLTAGE REGULATOR

The diagram illustrates a 3V3 voltage regulator circuit. The input is a 3V3 supply, which is filtered by a 100nF capacitor (C1) and a 22uF capacitor (C2). The input is connected to the NC pin (pin 4) of the XC6210B332MR (U1). The GND pin (pin 3) is connected to ground. The OUT pin (pin 5) is connected to the output of the regulator, which is also connected to a 5.1kΩ resistor (R1) and a diode (D1). The output is connected to USB_5V and BATP. A MOSFET (Q1, NTA4151PT1G) is connected to the output. A 1uF capacitor (C3) is connected to the output. A callout box shows an alternative diode (D4 BAS 52-02V H6327) with a smaller footprint.

[illegible]

USB-C

BATTERY CONNECTORS

The diagram illustrates the electrical connections for battery connectors J1 and J2. Connector J2 is connected to a ground symbol labeled (BATN). Connector J1 is connected to a battery symbol. A component labeled CN1 PH2.0-2PWB is connected to J1.

[illegible]

The diagram shows the pin headers for the ZX-PZ22 module. It consists of two headers, U3 and U5, both labeled ZX-PZ22.54-1-16PZZ.

Header U3: This header is connected to a +3V3 supply. The pins are labeled as follows:

Pin	Label
1	IO4
2	IO5
3	IO6
4	IO7
5	IO13
6	IO18
7	IO1
8	IO18
9	IO1
10	IO18
11	IO8
12	IO3
13	IO9
14	IO10
15	IO11
16	IO12

Header U5: This header is connected to a USB_5V supply. The pins are labeled as follows:

Pin	Label
1	IO1
2	IO2
3	TXD0
4	RXD0
5	IO38
6	IO37
7	IO36
8	IO35
9	IO0
10	IO48
11	IO47
12	IO21
13	IO14
14	IO13
15	IO15
16	USB_5V

BOOT BUTTON

SW1
TSA343G00D-250J2

5 G2 IO0