



Product Code	29520
Unit of sale	1 pc
Minimum order	1
Type	Medical device
Class	II B

UK-REP	No
RDM (NSIS)	213420
CND	Z12080103
EAN/UPC	8023279295207
UMDNS	12610
PARAF	903141430

Description

- Cost-effective single foetal monitor
- Extreme ultrasound doppler sensitivity:
- high-accuracy with 1 Mhz frequency
 - automatic/manual Foetal Movement detection
 - auto NST (Non-stress test) function from 10 min. to 1 hour
- Data printout
- CTG analysis printing
 - A4 size chart paper with perforation line
 - plain thermal fax paper usable
 - print speed 1, 2, 3 cm/min
- Easy-to-use
- one- touch operation and easy setup
 - alarm function (FHR high-low)
 - s/w upgrade via internet

Technical Specifications

- Dimensions 296x92.5xh 305.5 - approx. 2.9 kg
Display 7 segment LED - 2 channels (FHR, UC)
Thermal printer print speed: 1, 2, 3 cm/min / paper feeding function
Power adaptor input: 100-240 VAC, 50-60 Hz, 1.2 A / output: 18 VDC, 2.5 A
External link RS-232C
- Foetal heart rate
input signal: ultrasound pulsed doppler
ultrasound frequency: 1.0 Mhz
ultrasound power: <10 mW/cm2
FHR detection method: auto correlation
FHR range: 50-240 bpm $\pm$ 1 bpm (120-160)
- Uterine contraction
reference (zero) control: one touch switch
measurement range: 0-99 units
Foetal movement measurement detection source: ultrasound pulsed doppler
- Auto CTG analysis
average baseline FHR
number of UC

number of acceleration
number of deceleration (late, early, variable)
Tachycardia (moderate, severe)
Bradychardia (moderate, severe)