

DM74AS74

Dual D Positive-Edge-Triggered Flip-Flop with Preset and Clear

General Description

The AS74 is a dual edge-triggered flip-flops. Each flip-flop has individual D, clock, clear and preset inputs, and also complementary Q and \bar{Q} outputs.


Information at input D is transferred to the Q output on the positive going edge of the clock pulse. Clock triggering occurs at a voltage level of the clock pulse and is not directly related to the transition time of the positive going pulse. When the clock input is at either the high or low level, the D input signal has no effect.

Asynchronous preset and clear inputs will set or clear Q output respectively upon the application of low level signal.

Features

- Switching specifications at 50 pF
- Switching specifications guaranteed over full temperature and V_{CC} range
- Advanced oxide-isolated, ion-implanted Schottky TTL process
- Functionally and pin-for-pin compatible with Schottky and LS TTL counterpart
- Improved AC performance over S74 at approximately half the power

Connection Diagram



Order Number DM74AS74M, N
See Package Number M14A or N14A

Function Table

| Inputs | | | | Outputs | |
|--------|-----|-----|---|------------|-------------|
| PR | CLR | CLK | D | Q | \bar{Q} |
| L | H | X | X | H | L |
| H | L | X | X | L | H |
| L | L | X | X | H (Note 1) | H (Note 1) |
| H | H | ↑ | H | H | L |
| H | H | ↑ | L | L | H |
| H | H | L | X | Q_0 | \bar{Q}_0 |

L = Low State, H = High State, X = Don't Care

↑ = Positive Edge Transition

Q_0 = Previous Condition of Q

Note 1: This condition is nonstable; it will not persist when preset and clear inputs return to their inactive (high) level. The output levels in this condition are not guaranteed to meet the V_{OH} specification.

Absolute Maximum Ratings (Note 2)

| | |
|--------------------------------------|--------------|
| Supply Voltage | 7V |
| Input Voltage | 7V |
| Operating Free Air Temperature Range | 0°C to +70°C |

Storage Temperature Range

–65°C to +150°C

Typical θ_{JA}

N Package

76.0°C/W

M Package

107.0°C/W

Recommended Operating Conditions

| Symbol | Parameter | Min | Nom | Max | Units |
|--------------|--------------------------------|----------------|-----|-----|-------|
| V_{CC} | Supply Voltage | 4.5 | 5 | 5.5 | V |
| V_{IH} | High Level Input Voltage | 2 | | | V |
| V_{IL} | Low Level Input Voltage | | | 0.8 | V |
| I_{OH} | High Level Output Current | | | –2 | mA |
| I_{OL} | Low Level Output Current | | | 20 | mA |
| f_{CLK} | Clock Frequency | 0 | | 105 | MHz |
| $t_{W(CLK)}$ | Width of Clock Pulse | High | 4 | | ns |
| | | Low | 5.5 | | ns |
| t_W | Pulse Width Preset & Clear Low | 4 | | | ns |
| t_{SU} | Data Setup Time (Note 3) | 4.5 \uparrow | | | ns |
| t_{SU} | PRE or CLR Setup-Time (Note 3) | 2 \uparrow | | | ns |
| t_H | Data Hold Time (Note 3) | 0 \uparrow | | | ns |
| T_A | Free Air Operating Temperature | 0 | | 70 | °C |

Note 2: The "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the "Electrical Characteristics" table are not guaranteed at the absolute maximum ratings. The "Recommended Operating Conditions" table will define the conditions for actual device operation.

Note 3: The (\uparrow) arrow indicates the positive edge of the Clock is used for reference.

Electrical Characteristics

over recommended operating free air temperature range. All typical values are measured at $V_{CC} = 5V$, $T_A = 25^\circ C$.

| Symbol | Parameter | Conditions | Min | Typ | Max | Units |
|----------|-----------------------------------|--|---------------|------|------|---------|
| V_{IK} | Input Clamp Voltage | $V_{CC} = 4.5V$, $I_I = -18\text{ mA}$ | | | –1.2 | V |
| V_{OH} | High Level Output Voltage | $V_{CC} = 4.5V$ to $5.5V$, $I_{OH} = -2\text{ mA}$ | $V_{CC} - 2$ | | | V |
| V_{OL} | Low Level Output Voltage | $V_{CC} = 4.5V$, $V_{IH} = \text{Max}$, $I_{OL} = 20\text{ mA}$ | | 0.35 | 0.5 | V |
| I_I | Input Current @ Max Input Voltage | $V_{CC} = 5.5V$, $V_{IH} = 7V$ | | | 0.1 | mA |
| I_{IH} | High Level Input Current | $V_{CC} = 5.5V$, $V_{IH} = 2.7V$ | Clock, D | | 20 | μA |
| | | | Preset, Clear | | 40 | μA |
| I_{IL} | Low Level Input Current | $V_{CC} = 5.5V$, $V_{IL} = 0.4V$ | Clock, D | | –0.5 | mA |
| | | | Preset, Clear | | –1.8 | mA |
| I_O | Output Drive Current | $V_{CC} = 5.5V$, $V_O = 2.25V$ | –30 | | –112 | mA |
| I_{CC} | Supply Current | $V_{CC} = 5.5V$ | | 10.5 | 16 | mA |


Switching Characteristics


over recommended operating free air temperature range (Note 4)

| Symbol | Parameter | Conditions | From | To | Min | Max | Units |
|-----------|--|------------------------------------|--------------------|---------------------|-----|------|-------|
| f_{MAX} | Maximum Clock Frequency | $V_{CC} = 4.5V$ to $5.5V$ | | | 105 | | MHz |
| t_{PLH} | Propagation Delay Time Low to High Level Output | $R_L = 500\Omega$ $C_L = 50$ pF | Preset or Clear | Q or \overline{Q} | 3 | 7.5 | ns |
| t_{PHL} | Propagation Delay Time High to Low Level Output | | Preset or Clear | Q or \overline{Q} | 3.5 | 10.5 | ns |
| t_{PLH} | Propagation Delay Time Low to High Level Output | | Clock | Q or \overline{Q} | 3.5 | 8 | ns |
| t_{PHL} | Propagation Delay Time High to Low Level Output | | Clock | Q or \overline{Q} | 4.5 | 9 | ns |


Note 4: See Section 1 for test waveforms and output load.

Logic Diagram








Physical Dimensions inches (millimeters) unless otherwise noted



S.O. Package (M)
Order Number DM74AS74M
Package Number M14A



OPTION 02



Molded Dual-In-Line Package (N)
Order Number DM74AS74N
Package Number N14A

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Fairchild Semiconductor
Corporation
Americas
Customer Response Center
Tel: 1-888-522-5372

www.fairchildsemi.com

Fairchild Semiconductor
Europe
Fax: +49 (0) 1 80-530 85 86
Email: europe.support@nsc.com
Deutsch Tel: +49 (0) 8 141-35-0
English Tel: +44 (0) 1 793-85-68-56
Italy Tel: +39 (0) 2 57 5631

Fairchild Semiconductor
Hong Kong Ltd.
13th Floor, Straight Block,
Ocean Centre, 5 Canton Rd.
Tsimshatsui, Kowloon
Hong Kong
Tel: +852 2737-7200
Fax: +852 2314-0061

National Semiconductor
Japan Ltd.
Tel: 81-3-5620-6175
Fax: 81-3-5620-6179