

# Some Elements of Learning Theory

Nicolò Cesa-Bianchi

Università degli Studi di Milano


# Contents

- ▶ A brief introduction to statistical learning



# Contents

- ▶ A brief introduction to statistical learning
- ▶ From statistical learning to sequential decision making



# Contents

- ▶ A brief introduction to statistical learning
- ▶ From statistical learning to sequential decision making
- ▶ Prediction with expert advice and multiarmed bandits



# Contents

- ▶ A brief introduction to statistical learning
- ▶ From statistical learning to sequential decision making
- ▶ Prediction with expert advice and multiarmed bandits
- ▶ Online convex optimization



# Contents

- ▶ A brief introduction to statistical learning
- ▶ From statistical learning to sequential decision making
- ▶ Prediction with expert advice and multiarmed bandits
- ▶ Online convex optimization
- ▶ Contextual bandits



# Contents

- ▶ A brief introduction to statistical learning
- ▶ From statistical learning to sequential decision making
- ▶ Prediction with expert advice and multiarmed bandits
- ▶ Online convex optimization
- ▶ Contextual bandits
- ▶ We do some (short) proofs



# Statistical learning



- ▶ One of the most important mathematical frameworks for the analysis of learning algorithms (mainly supervised learning)






# Statistical learning




- ▶ One of the most important mathematical frameworks for the analysis of learning algorithms (mainly supervised learning)
- ▶ Pioneered by Vladimir Vapnik in the Seventies



# Statistical learning



- ▶ One of the most important mathematical frameworks for the analysis of learning algorithms (mainly supervised learning)
- ▶ Pioneered by Vladimir Vapnik in the Seventies
- ▶ Later —and independently— Leslie Valiant introduces computational learning theory (A theory of the learnable, 1984)




# Statistical learning



- ▶ One of the most important mathematical frameworks for the analysis of learning algorithms (mainly supervised learning)
- ▶ Pioneered by Vladimir Vapnik in the Seventies
- ▶ Later —and independently— Leslie Valiant introduces computational learning theory (A theory of the learnable, 1984)

Main contributions:




# Statistical learning



- ▶ One of the most important mathematical frameworks for the analysis of learning algorithms (mainly supervised learning)
- ▶ Pioneered by Vladimir Vapnik in the Seventies
- ▶ Later —and independently— Leslie Valiant introduces computational learning theory (A theory of the learnable, 1984)

## Main contributions:

- ▶ Mathematical model of learning and conditions characterizing what can be learned




# Statistical learning



- ▶ One of the most important mathematical frameworks for the analysis of learning algorithms (mainly supervised learning)
- ▶ Pioneered by Vladimir Vapnik in the Seventies
- ▶ Later —and independently— Leslie Valiant introduces computational learning theory (A theory of the learnable, 1984)

## Main contributions:

- ▶ Mathematical model of learning and conditions characterizing what can be learned
- ▶ Guidelines to practitioners (e.g., choice of learning bias, control of overfitting)




# Statistical learning



- ▶ One of the most important mathematical frameworks for the analysis of learning algorithms (mainly supervised learning)
- ▶ Pioneered by Vladimir Vapnik in the Seventies
- ▶ Later —and independently— Leslie Valiant introduces computational learning theory (A theory of the learnable, 1984)

## Main contributions:

- ▶ Mathematical model of learning and conditions characterizing what can be learned
- ▶ Guidelines to practitioners (e.g., choice of learning bias, control of overfitting)
- ▶ Principled and successful algorithms (SVM, Boosting)



# Ingredients

- Data space  $\mathcal{X}$  (often  $\mathcal{X} = \mathbb{R}^d$ )



# Ingredients


- ▶ Data space  $\mathcal{X}$  (often  $\mathcal{X} = \mathbb{R}^d$ )
- ▶ Label space  $\mathcal{Y}$ 
  - ▶  $\mathcal{Y} = \mathbb{R}$  for regression
  - ▶  $\mathcal{Y} = \{-1, 1\}$  for binary classification






# Ingredients

- ▶ Data space  $\mathcal{X}$  (often  $\mathcal{X} = \mathbb{R}^d$ )
- ▶ Label space  $\mathcal{Y}$ 
  - ▶  $\mathcal{Y} = \mathbb{R}$  for regression
  - ▶  $\mathcal{Y} = \{-1, 1\}$  for binary classification
- ▶ Loss function  $\ell : \mathcal{Y} \times \mathcal{Y} \rightarrow \mathbb{R}$ 
  - ▶ Quadratic  $\ell(y, \hat{y}) = (\hat{y} - y)^2$  for regression
  - ▶ Zero-one  $\ell(y, \hat{y}) = \mathbb{I}\{\hat{y} \neq y\}$  for binary classification
  - ▶ Hinge  $\ell(y, \hat{y}) = [1 - y\hat{y}]_+$  convex proxy for binary classification




# Ingredients

- ▶ Data space  $\mathcal{X}$  (often  $\mathcal{X} = \mathbb{R}^d$ )
- ▶ Label space  $\mathcal{Y}$ 
  - ▶  $\mathcal{Y} = \mathbb{R}$  for regression
  - ▶  $\mathcal{Y} = \{-1, 1\}$  for binary classification
- ▶ Loss function  $\ell : \mathcal{Y} \times \mathcal{Y} \rightarrow \mathbb{R}$ 
  - ▶ Quadratic  $\ell(y, \hat{y}) = (\hat{y} - y)^2$  for regression
  - ▶ Zero-one  $\ell(y, \hat{y}) = \mathbb{I}\{\hat{y} \neq y\}$  for binary classification
  - ▶ Hinge  $\ell(y, \hat{y}) = [1 - y\hat{y}]_+$  convex proxy for binary classification
- ▶ Predictor  $f : \mathcal{X} \rightarrow \mathcal{Y}$  maps data points to labels




# Ingredients

- ▶ Data space  $\mathcal{X}$  (often  $\mathcal{X} = \mathbb{R}^d$ )
- ▶ Label space  $\mathcal{Y}$ 
  - ▶  $\mathcal{Y} = \mathbb{R}$  for regression
  - ▶  $\mathcal{Y} = \{-1, 1\}$  for binary classification
- ▶ Loss function  $\ell : \mathcal{Y} \times \mathcal{Y} \rightarrow \mathbb{R}$ 
  - ▶ Quadratic  $\ell(y, \hat{y}) = (\hat{y} - y)^2$  for regression
  - ▶ Zero-one  $\ell(y, \hat{y}) = \mathbb{I}\{\hat{y} \neq y\}$  for binary classification
  - ▶ Hinge  $\ell(y, \hat{y}) = [1 - y\hat{y}]_+$  convex proxy for binary classification
- ▶ Predictor  $f : \mathcal{X} \rightarrow \mathcal{Y}$  maps data points to labels
- ▶ Training set  $(\mathbf{x}_1, y_1), \dots, (\mathbf{x}_m, y_m)$  a (multi)set  $S$  of labeled data points



# Ingredients

- ▶ Data space  $\mathcal{X}$  (often  $\mathcal{X} = \mathbb{R}^d$ )
- ▶ Label space  $\mathcal{Y}$ 
  - ▶  $\mathcal{Y} = \mathbb{R}$  for regression
  - ▶  $\mathcal{Y} = \{-1, 1\}$  for binary classification
- ▶ Loss function  $\ell : \mathcal{Y} \times \mathcal{Y} \rightarrow \mathbb{R}$ 
  - ▶ Quadratic  $\ell(y, \hat{y}) = (\hat{y} - y)^2$  for regression
  - ▶ Zero-one  $\ell(y, \hat{y}) = \mathbb{I}\{\hat{y} \neq y\}$  for binary classification
  - ▶ Hinge  $\ell(y, \hat{y}) = [1 - y\hat{y}]_+$  convex proxy for binary classification
- ▶ Predictor  $f : \mathcal{X} \rightarrow \mathcal{Y}$  maps data points to labels
- ▶ Training set  $(\mathbf{x}_1, y_1), \dots, (\mathbf{x}_m, y_m)$  a (multi)set  $\mathcal{S}$  of labeled data points
- ▶ **Learning algorithm:** given a loss function, maps finite training sets to predictors



# Statistical learning

- ▶ A learning problem is defined by an **unknown distribution**  $\mathcal{D}$  on  $\mathcal{X} \times \mathcal{Y}$



# Statistical learning

- ▶ A learning problem is defined by an **unknown distribution**  $\mathcal{D}$  on  $\mathcal{X} \times \mathcal{Y}$
- ▶ Any data point  $(\mathbf{x}, y)$  is the realization of an **independent random draw**  $(\mathbf{X}, Y)$  from  $\mathcal{D}$




# Statistical learning

- ▶ A learning problem is defined by an **unknown distribution**  $\mathcal{D}$  on  $\mathcal{X} \times \mathcal{Y}$
- ▶ Any data point  $(\mathbf{x}, y)$  is the realization of an **independent random draw**  $(\mathbf{X}, Y)$  from  $\mathcal{D}$
- ▶ Therefore, the training set  $S$  is a **random sample** from  $\mathcal{D}$



# Statistical learning


- ▶ A learning problem is defined by an **unknown distribution**  $\mathcal{D}$  on  $\mathcal{X} \times \mathcal{Y}$
- ▶ Any data point  $(\mathbf{x}, y)$  is the realization of an **independent random draw**  $(\mathbf{X}, Y)$  from  $\mathcal{D}$
- ▶ Therefore, the training set  $S$  is a **random sample** from  $\mathcal{D}$
- ▶ Given a loss, the **statistical risk** of predictor  $f$  is  $\ell_{\mathcal{D}}(f) = \mathbb{E}[\ell(Y, f(\mathbf{X}))]$






# Statistical learning

- ▶ A learning problem is defined by an **unknown distribution**  $\mathcal{D}$  on  $\mathcal{X} \times \mathcal{Y}$
- ▶ Any data point  $(\mathbf{x}, y)$  is the realization of an **independent random draw**  $(\mathbf{X}, Y)$  from  $\mathcal{D}$
- ▶ Therefore, the training set  $S$  is a **random sample** from  $\mathcal{D}$
- ▶ Given a loss, the **statistical risk** of predictor  $f$  is  $\ell_{\mathcal{D}}(f) = \mathbb{E}[\ell(Y, f(\mathbf{X}))]$
- ▶ **Bayes optimal predictor**  $f^* : \mathcal{X} \rightarrow \mathcal{Y}$  is  $f^*(\mathbf{x}) = \underset{\hat{y} \in \mathcal{Y}}{\operatorname{argmin}} \mathbb{E}[\ell(Y, \hat{y}) \mid \mathbf{X} = \mathbf{x}]$




# Statistical learning

- ▶ A learning problem is defined by an **unknown distribution**  $\mathcal{D}$  on  $\mathcal{X} \times \mathcal{Y}$
- ▶ Any data point  $(\mathbf{x}, y)$  is the realization of an **independent random draw**  $(\mathbf{X}, Y)$  from  $\mathcal{D}$
- ▶ Therefore, the training set  $S$  is a **random sample** from  $\mathcal{D}$
- ▶ Given a loss, the **statistical risk** of predictor  $f$  is  $\ell_{\mathcal{D}}(f) = \mathbb{E}[\ell(Y, f(\mathbf{X}))]$
- ▶ **Bayes optimal predictor**  $f^* : \mathcal{X} \rightarrow \mathcal{Y}$  is  $f^*(\mathbf{x}) = \underset{\hat{y} \in \mathcal{Y}}{\operatorname{argmin}} \mathbb{E}[\ell(Y, \hat{y}) \mid \mathbf{X} = \mathbf{x}]$
- ▶ **Bayes risk**  $\ell_{\mathcal{D}}(f^*)$



# Statistical learning

- ▶ A learning problem is defined by an **unknown distribution**  $\mathcal{D}$  on  $\mathcal{X} \times \mathcal{Y}$
- ▶ Any data point  $(\mathbf{x}, y)$  is the realization of an **independent random draw**  $(\mathbf{X}, Y)$  from  $\mathcal{D}$
- ▶ Therefore, the training set  $S$  is a **random sample** from  $\mathcal{D}$
- ▶ Given a loss, the **statistical risk** of predictor  $f$  is  $\ell_{\mathcal{D}}(f) = \mathbb{E}[\ell(Y, f(\mathbf{X}))]$
- ▶ **Bayes optimal predictor**  $f^* : \mathcal{X} \rightarrow \mathcal{Y}$  is  $f^*(\mathbf{x}) = \underset{\hat{y} \in \mathcal{Y}}{\operatorname{argmin}} \mathbb{E}[\ell(Y, \hat{y}) \mid \mathbf{X} = \mathbf{x}]$
- ▶ **Bayes risk**  $\ell_{\mathcal{D}}(f^*)$
- ▶ Square loss:  $f^*(\mathbf{x}) = \mathbb{E}[Y \mid \mathbf{X} = \mathbf{x}]$  and  $\ell_{\mathcal{D}}(f^*) = \mathbb{E}[\operatorname{Var}[Y \mid \mathbf{X}]]$



# Statistical learning

- ▶ A learning problem is defined by an **unknown distribution**  $\mathcal{D}$  on  $\mathcal{X} \times \mathcal{Y}$
- ▶ Any data point  $(\mathbf{x}, y)$  is the realization of an **independent random draw**  $(\mathbf{X}, Y)$  from  $\mathcal{D}$
- ▶ Therefore, the training set  $S$  is a **random sample** from  $\mathcal{D}$
- ▶ Given a loss, the **statistical risk** of predictor  $f$  is  $\ell_{\mathcal{D}}(f) = \mathbb{E}[\ell(Y, f(\mathbf{X}))]$
- ▶ **Bayes optimal predictor**  $f^* : \mathcal{X} \rightarrow \mathcal{Y}$  is  $f^*(\mathbf{x}) = \underset{\hat{y} \in \mathcal{Y}}{\operatorname{argmin}} \mathbb{E}[\ell(Y, \hat{y}) \mid \mathbf{X} = \mathbf{x}]$
- ▶ **Bayes risk**  $\ell_{\mathcal{D}}(f^*)$
- ▶ Square loss:  $f^*(\mathbf{x}) = \mathbb{E}[Y \mid \mathbf{X} = \mathbf{x}]$  and  $\ell_{\mathcal{D}}(f^*) = \mathbb{E}[\operatorname{Var}[Y \mid \mathbf{X}]]$
- ▶ Zero-one loss:  $f^*(\mathbf{x}) = 2\mathbb{I}\{\eta(\mathbf{x}) \geq 1/2\} - 1$  and  $\ell_{\mathcal{D}}(f^*) = \mathbb{E}[\min\{\eta(\mathbf{X}), 1 - \eta(\mathbf{X})\}]$   
where  $\eta(\mathbf{x}) = \mathbb{P}(Y = 1 \mid \mathbf{X} = \mathbf{x})$

## The bias-variance decomposition

Suppose  $h_S \in \mathcal{H}$  is the predictor output by a learning algorithm  $A$  with training set  $S$   
( $h_S \in \mathcal{H}$  is a random variable)



# The bias-variance decomposition

Suppose  $h_S \in \mathcal{H}$  is the predictor output by a learning algorithm  $A$  with training set  $S$   
( $h_S \in \mathcal{H}$  is a random variable)


$$\begin{aligned}\ell_{\mathcal{D}}(h_S) &= \ell_{\mathcal{D}}(h_S) - \inf_{h \in \mathcal{H}} \ell_{\mathcal{D}}(h) \\ &\quad + \inf_{h \in \mathcal{H}} \ell_{\mathcal{D}}(h) - \ell_{\mathcal{D}}(f^*) \\ &\quad + \ell_{\mathcal{D}}(f^*)\end{aligned}$$

(estimation error  $\rightarrow$  overfitting)

(approximation error  $\rightarrow$  underfitting)

(Bayes risk)

Trade-offs



# The bias-variance decomposition

Suppose  $h_S \in \mathcal{H}$  is the predictor output by a learning algorithm  $A$  with training set  $S$   
( $h_S \in \mathcal{H}$  is a random variable)

$$\begin{aligned}\ell_{\mathcal{D}}(h_S) &= \ell_{\mathcal{D}}(h_S) - \inf_{h \in \mathcal{H}} \ell_{\mathcal{D}}(h) \\ &\quad + \inf_{h \in \mathcal{H}} \ell_{\mathcal{D}}(h) - \ell_{\mathcal{D}}(f^*) \\ &\quad + \ell_{\mathcal{D}}(f^*)\end{aligned}$$


(estimation error  $\rightarrow$  overfitting)

(approximation error  $\rightarrow$  underfitting)

(Bayes risk)

## Trade-offs

- **Underfitting control:** Let  $\mathcal{H}$  be as large as possible



# The bias-variance decomposition

Suppose  $h_S \in \mathcal{H}$  is the predictor output by a learning algorithm  $A$  with training set  $S$   
( $h_S \in \mathcal{H}$  is a random variable)

$$\begin{aligned}\ell_{\mathcal{D}}(h_S) &= \ell_{\mathcal{D}}(h_S) - \inf_{h \in \mathcal{H}} \ell_{\mathcal{D}}(h) \\ &\quad + \inf_{h \in \mathcal{H}} \ell_{\mathcal{D}}(h) - \ell_{\mathcal{D}}(f^*) \\ &\quad + \ell_{\mathcal{D}}(f^*)\end{aligned}$$


(estimation error  $\rightarrow$  overfitting)

(approximation error  $\rightarrow$  underfitting)

(Bayes risk)

## Trade-offs

- **Underfitting control:** Let  $\mathcal{H}$  be as large as possible
- **Overfitting control:**






# The bias-variance decomposition

Suppose  $h_S \in \mathcal{H}$  is the predictor output by a learning algorithm  $A$  with training set  $S$   
( $h_S \in \mathcal{H}$  is a random variable)

$$\begin{aligned}\ell_{\mathcal{D}}(h_S) &= \ell_{\mathcal{D}}(h_S) - \inf_{h \in \mathcal{H}} \ell_{\mathcal{D}}(h) && \text{(estimation error} \rightarrow \text{overfitting)} \\ &+ \inf_{h \in \mathcal{H}} \ell_{\mathcal{D}}(h) - \ell_{\mathcal{D}}(f^*) && \text{(approximation error} \rightarrow \text{underfitting)} \\ &+ \ell_{\mathcal{D}}(f^*) && \text{(Bayes risk)}\end{aligned}$$

## Trade-offs

- ▶ **Underfitting control:** Let  $\mathcal{H}$  be as large as possible
- ▶ **Overfitting control:**
  - ▶ Ensure that training error of  $h$  is close to  $\ell_{\mathcal{D}}(h)$  for all  $h \in \mathcal{H}$  (uniform convergence)




# The bias-variance decomposition

Suppose  $h_S \in \mathcal{H}$  is the predictor output by a learning algorithm  $A$  with training set  $S$   
( $h_S \in \mathcal{H}$  is a random variable)

$$\begin{aligned}\ell_{\mathcal{D}}(h_S) &= \ell_{\mathcal{D}}(h_S) - \inf_{h \in \mathcal{H}} \ell_{\mathcal{D}}(h) && \text{(estimation error} \rightarrow \text{overfitting)} \\ &+ \inf_{h \in \mathcal{H}} \ell_{\mathcal{D}}(h) - \ell_{\mathcal{D}}(f^*) && \text{(approximation error} \rightarrow \text{underfitting)} \\ &+ \ell_{\mathcal{D}}(f^*) && \text{(Bayes risk)}\end{aligned}$$

## Trade-offs

- ▶ **Underfitting control:** Let  $\mathcal{H}$  be as large as possible
- ▶ **Overfitting control:**
  - ▶ Ensure that training error of  $h$  is close to  $\ell_{\mathcal{D}}(h)$  for all  $h \in \mathcal{H}$  (uniform convergence)
  - ▶ Minimize regularized training error (stability)



# The bias-variance decomposition

Suppose  $h_S \in \mathcal{H}$  is the predictor output by a learning algorithm  $A$  with training set  $S$   
( $h_S \in \mathcal{H}$  is a random variable)

$$\begin{aligned}\ell_{\mathcal{D}}(h_S) &= \ell_{\mathcal{D}}(h_S) - \inf_{h \in \mathcal{H}} \ell_{\mathcal{D}}(h) && \text{(estimation error} \rightarrow \text{overfitting)} \\ &+ \inf_{h \in \mathcal{H}} \ell_{\mathcal{D}}(h) - \ell_{\mathcal{D}}(f^*) && \text{(approximation error} \rightarrow \text{underfitting)} \\ &+ \ell_{\mathcal{D}}(f^*) && \text{(Bayes risk)}\end{aligned}$$

## Trade-offs

- ▶ **Underfitting control:** Let  $\mathcal{H}$  be as large as possible
- ▶ **Overfitting control:**
  - ▶ Ensure that training error of  $h$  is close to  $\ell_{\mathcal{D}}(h)$  for all  $h \in \mathcal{H}$  (uniform convergence)
  - ▶ Minimize regularized training error (stability)
  - ▶ Show that  $A$  can compress the training set (compression implies learning)

## Success stories: Characterization of sample complexity

What is the training set size  $m_{\mathcal{H}}$  necessary and sufficient to ensure

$$\ell_{\mathcal{D}}(h_S) - \inf_{h \in \mathcal{H}} \ell_{\mathcal{D}}(h) \leq \varepsilon$$

with probability at least  $1 - \delta$  w.r.t. the random draw of  $S$  and irrespective to  $\mathcal{D}$ ?



## Success stories: Characterization of sample complexity

What is the training set size  $m_{\mathcal{H}}$  necessary and sufficient to ensure

$$\ell_{\mathcal{D}}(h_S) - \inf_{h \in \mathcal{H}} \ell_{\mathcal{D}}(h) \leq \varepsilon$$

with probability at least  $1 - \delta$  w.r.t. the random draw of  $S$  and irrespective to  $\mathcal{D}$ ?

Binary classification with zero-one loss



## Success stories: Characterization of sample complexity


What is the training set size  $m_{\mathcal{H}}$  necessary and sufficient to ensure

$$\ell_{\mathcal{D}}(h_S) - \inf_{h \in \mathcal{H}} \ell_{\mathcal{D}}(h) \leq \varepsilon$$

with probability at least  $1 - \delta$  w.r.t. the random draw of  $S$  and irrespective to  $\mathcal{D}$ ?

Binary classification with zero-one loss

- $m_{\mathcal{H}}$  is determined by a simple combinatorial parameter, the VC-dimension  $d_{\mathcal{H}}$



## Success stories: Characterization of sample complexity


What is the training set size  $m_{\mathcal{H}}$  necessary and sufficient to ensure

$$\ell_{\mathcal{D}}(h_S) - \inf_{h \in \mathcal{H}} \ell_{\mathcal{D}}(h) \leq \varepsilon$$

with probability at least  $1 - \delta$  w.r.t. the random draw of  $S$  and irrespective to  $\mathcal{D}$ ?

Binary classification with zero-one loss

- ▶  $m_{\mathcal{H}}$  is determined by a simple combinatorial parameter, the VC-dimension  $d_{\mathcal{H}}$
- ▶ **Agnostic case:**  $m_{\mathcal{H}} = \Theta\left(\frac{d_{\mathcal{H}} + \ln(1/\delta)}{\varepsilon^2}\right)$



## Success stories: Characterization of sample complexity


What is the training set size  $m_{\mathcal{H}}$  necessary and sufficient to ensure

$$\ell_{\mathcal{D}}(h_S) - \inf_{h \in \mathcal{H}} \ell_{\mathcal{D}}(h) \leq \varepsilon$$

with probability at least  $1 - \delta$  w.r.t. the random draw of  $S$  and irrespective to  $\mathcal{D}$ ?

Binary classification with zero-one loss

- ▶  $m_{\mathcal{H}}$  is determined by a simple combinatorial parameter, the VC-dimension  $d_{\mathcal{H}}$
- ▶ **Agnostic case:**  $m_{\mathcal{H}} = \Theta\left(\frac{d_{\mathcal{H}} + \ln(1/\delta)}{\varepsilon^2}\right)$
- ▶ **Realizable case:** ( $f^* \in \mathcal{H}$  and  $\ell_{\mathcal{D}}(f^*) = 0$ )  $m_{\mathcal{H}} = \Theta\left(\frac{d_{\mathcal{H}} + \ln(1/\delta)}{\varepsilon}\right)$





## Success stories: Characterization of sample complexity


What is the training set size  $m_{\mathcal{H}}$  necessary and sufficient to ensure

$$\ell_{\mathcal{D}}(h_S) - \inf_{h \in \mathcal{H}} \ell_{\mathcal{D}}(h) \leq \varepsilon$$

with probability at least  $1 - \delta$  w.r.t. the random draw of  $S$  and irrespective to  $\mathcal{D}$ ?

Binary classification with zero-one loss

- ▶  $m_{\mathcal{H}}$  is determined by a simple combinatorial parameter, the VC-dimension  $d_{\mathcal{H}}$
- ▶ **Agnostic case:**  $m_{\mathcal{H}} = \Theta\left(\frac{d_{\mathcal{H}} + \ln(1/\delta)}{\varepsilon^2}\right)$
- ▶ **Realizable case:** ( $f^* \in \mathcal{H}$  and  $\ell_{\mathcal{D}}(f^*) = 0$ )  $m_{\mathcal{H}} = \Theta\left(\frac{d_{\mathcal{H}} + \ln(1/\delta)}{\varepsilon}\right)$
- ▶  $d_{\mathcal{H}}$  can be infinite, implying  $\mathcal{H}$  is not learnable



## Success stories: Characterization of sample complexity


What is the training set size  $m_{\mathcal{H}}$  necessary and sufficient to ensure

$$\ell_{\mathcal{D}}(h_S) - \inf_{h \in \mathcal{H}} \ell_{\mathcal{D}}(h) \leq \varepsilon$$

with probability at least  $1 - \delta$  w.r.t. the random draw of  $S$  and irrespective to  $\mathcal{D}$ ?

Binary classification with zero-one loss

- ▶  $m_{\mathcal{H}}$  is determined by a simple combinatorial parameter, the VC-dimension  $d_{\mathcal{H}}$
- ▶ **Agnostic case:**  $m_{\mathcal{H}} = \Theta\left(\frac{d_{\mathcal{H}} + \ln(1/\delta)}{\varepsilon^2}\right)$
- ▶ **Realizable case:** ( $f^* \in \mathcal{H}$  and  $\ell_{\mathcal{D}}(f^*) = 0$ )  $m_{\mathcal{H}} = \Theta\left(\frac{d_{\mathcal{H}} + \ln(1/\delta)}{\varepsilon}\right)$
- ▶  $d_{\mathcal{H}}$  can be infinite, implying  $\mathcal{H}$  is not learnable
- ▶ Minimizing training error in  $\mathcal{H}$  achieves upper bound in the agnostic case



## Success stories: Characterization of sample complexity

What is the training set size  $m_{\mathcal{H}}$  necessary and sufficient to ensure

$$\ell_{\mathcal{D}}(h_S) - \inf_{h \in \mathcal{H}} \ell_{\mathcal{D}}(h) \leq \varepsilon$$

with probability at least  $1 - \delta$  w.r.t. the random draw of  $S$  and irrespective to  $\mathcal{D}$ ?

### Binary classification with zero-one loss

- ▶  $m_{\mathcal{H}}$  is determined by a simple combinatorial parameter, the VC-dimension  $d_{\mathcal{H}}$
- ▶ **Agnostic case:**  $m_{\mathcal{H}} = \Theta\left(\frac{d_{\mathcal{H}} + \ln(1/\delta)}{\varepsilon^2}\right)$
- ▶ **Realizable case:** ( $f^* \in \mathcal{H}$  and  $\ell_{\mathcal{D}}(f^*) = 0$ )  $m_{\mathcal{H}} = \Theta\left(\frac{d_{\mathcal{H}} + \ln(1/\delta)}{\varepsilon}\right)$
- ▶  $d_{\mathcal{H}}$  can be infinite, implying  $\mathcal{H}$  is not learnable
- ▶ Minimizing training error in  $\mathcal{H}$  achieves upper bound in the agnostic case
- ▶ Majority vote over a set of consistent predictors achieves upper bound in the realizable case

## Statistical consistency

►  $A$  is statistically consistent if  $\lim_{m \rightarrow \infty} \mathbb{E}[\ell_{\mathcal{D}}(A(S_m))] = \ell_{\mathcal{D}}(f^*)$



# Statistical consistency

- ▶  $A$  is **statistically consistent** if  $\lim_{m \rightarrow \infty} \mathbb{E}[\ell_{\mathcal{D}}(A(S_m))] = \ell_{\mathcal{D}}(f^*)$
- ▶ In order to achieve distribution-free consistency,  $A$  has to be **nonparametric** (e.g.,  $k$ -NN, tree classifiers, SVMs with Gaussian kernels)




# Statistical consistency

- ▶  $A$  is **statistically consistent** if  $\lim_{m \rightarrow \infty} \mathbb{E}[\ell_{\mathcal{D}}(A(S_m))] = \ell_{\mathcal{D}}(f^*)$
- ▶ In order to achieve distribution-free consistency,  $A$  has to be **nonparametric** (e.g.,  $k$ -NN, tree classifiers, SVMs with Gaussian kernels)

## No Free Lunch Theorem

Let  $a_1, a_2, \dots > 0$  be any sequence of numbers slowly converging to zero.

For all binary classification algorithms  $A$  there exists  $\mathcal{D}$  such that the Bayes risk is zero and, simultaneously,  $\mathbb{E}[\ell_{\mathcal{D}}(A(S_m))] \geq a_m$  for all  $m \geq 1$ .



# Statistical consistency

- ▶  $A$  is **statistically consistent** if  $\lim_{m \rightarrow \infty} \mathbb{E}[\ell_{\mathcal{D}}(A(S_m))] = \ell_{\mathcal{D}}(f^*)$
- ▶ In order to achieve distribution-free consistency,  $A$  has to be **nonparametric** (e.g.,  $k$ -NN, tree classifiers, SVMs with Gaussian kernels)

## No Free Lunch Theorem

Let  $a_1, a_2, \dots > 0$  be any sequence of numbers slowly converging to zero.

For all binary classification algorithms  $A$  there exists  $\mathcal{D}$  such that the Bayes risk is zero and, simultaneously,  $\mathbb{E}[\ell_{\mathcal{D}}(A(S_m))] \geq a_m$  for all  $m \geq 1$ .


## Curse of dimensionality

- ▶ Typical parametric rates for convergence to  $\ell_{\mathcal{D}}(h^*)$ :  $m^{-1/2}$
- ▶ Typical nonparametric rates for convergence to Bayes risk:  $m^{-1/d}$  for  $d \geq 2$  (under assumptions on  $\mathcal{D}$ )

# Online learning



- **Data streams** are ubiquitous: sensors, markets, user interactions






# Online learning




- ▶ **Data streams** are ubiquitous: sensors, markets, user interactions
- ▶ New data is being generated all the time



# Online learning



- ▶ **Data streams** are ubiquitous: sensors, markets, user interactions
- ▶ New data is being generated all the time
- ▶ The train-test model of statistical learning is ill-suited for learning on data streams



# Online learning




- ▶ **Data streams** are ubiquitous: sensors, markets, user interactions
- ▶ New data is being generated all the time
- ▶ The train-test model of statistical learning is ill-suited for learning on data streams
- ▶ After observing a new data point, predictors should be **incrementally adjusted** at a constant cost


## History bits




- ▶ Online learning model formalized by Nick Littlestone and Manfred Warmuth (Mistake bounds and logarithmic linear-threshold learning algorithms, 1989)




## History bits




- ▶ Online learning model formalized by Nick Littlestone and Manfred Warmuth (Mistake bounds and logarithmic linear-threshold learning algorithms, 1989)
- ▶ Volodya Vovk independently develops a related framework (Aggregating strategies, 1990)



## History bits



- ▶ Online learning model formalized by Nick Littlestone and Manfred Warmuth (Mistake bounds and logarithmic linear-threshold learning algorithms, 1989)
- ▶ Volodya Vovk independently develops a related framework (Aggregating strategies, 1990)
- ▶ Similar ideas also independently emerged in game theory and information theory



# The online learning protocol

The algorithm starts with a default model  $h_1 \in \mathcal{H}$

For  $t = 1, 2, \dots$



# The online learning protocol

The algorithm starts with a default model  $h_1 \in \mathcal{H}$

For  $t = 1, 2, \dots$

1. The current model  $h_t \in \mathcal{H}$  is tested on the next data point  $(\mathbf{x}_t, y_t)$  in the stream





# The online learning protocol

The algorithm starts with a default model  $h_1 \in \mathcal{H}$

For  $t = 1, 2, \dots$

1. The current model  $h_t \in \mathcal{H}$  is tested on the next data point  $(\mathbf{x}_t, y_t)$  in the stream
2.  $A$  is charged with loss  $\ell(y_t, h_t(\mathbf{x}_t))$



# The online learning protocol

The algorithm starts with a default model  $h_1 \in \mathcal{H}$

For  $t = 1, 2, \dots$

1. The current model  $h_t \in \mathcal{H}$  is tested on the next data point  $(\mathbf{x}_t, y_t)$  in the stream
2.  $A$  is charged with loss  $\ell(y_t, h_t(\mathbf{x}_t))$
3.  $h_{t+1} \in \mathcal{H}$  is computed based on  $h_t$  and  $(\mathbf{x}_t, y_t)$



# The online learning protocol

The algorithm starts with a default model  $h_1 \in \mathcal{H}$

For  $t = 1, 2, \dots$

1. The current model  $h_t \in \mathcal{H}$  is tested on the next data point  $(\mathbf{x}_t, y_t)$  in the stream
  2.  $A$  is charged with loss  $\ell(y_t, h_t(\mathbf{x}_t))$
  3.  $h_{t+1} \in \mathcal{H}$  is computed based on  $h_t$  and  $(\mathbf{x}_t, y_t)$
- Computation of  $h_{t+1}$  relies on local information



# The online learning protocol

The algorithm starts with a default model  $h_1 \in \mathcal{H}$

For  $t = 1, 2, \dots$

1. The current model  $h_t \in \mathcal{H}$  is tested on the next data point  $(\mathbf{x}_t, y_t)$  in the stream
  2.  $A$  is charged with loss  $\ell(y_t, h_t(\mathbf{x}_t))$
  3.  $h_{t+1} \in \mathcal{H}$  is computed based on  $h_t$  and  $(\mathbf{x}_t, y_t)$
- Computation of  $h_{t+1}$  relies on local information
  - No stochastic assumptions on the stream



# Regret

## Sequential risk

Given a convex loss  $\ell$  and a stream  $(\mathbf{x}_1, y_1), (\mathbf{x}_2, y_2), \dots$ , the **sequential risk** of  $A$  is

$$\sum_{t=1}^T \ell(y_t, h_t(\mathbf{x}_t))$$



# Regret


## Sequential risk

Given a convex loss  $\ell$  and a stream  $(\mathbf{x}_1, y_1), (\mathbf{x}_2, y_2), \dots$ , the **sequential risk** of  $A$  is

$$\sum_{t=1}^T \ell(y_t, h_t(\mathbf{x}_t))$$

## Regret

$$R_T = \sum_{t=1}^T \ell(y_t, h_t(\mathbf{x}_t)) - \inf_{h \in \mathcal{H}} \sum_{t=1}^T \ell(y_t, h(\mathbf{x}_t))$$



# Regret

## Sequential risk


Given a convex loss  $\ell$  and a stream  $(\mathbf{x}_1, y_1), (\mathbf{x}_2, y_2), \dots$ , the **sequential risk** of  $A$  is

$$\sum_{t=1}^T \ell(y_t, h_t(\mathbf{x}_t))$$

## Regret

$$R_T = \sum_{t=1}^T \ell(y_t, h_t(\mathbf{x}_t)) - \inf_{h \in \mathcal{H}} \sum_{t=1}^T \ell(y_t, h(\mathbf{x}_t))$$

- A sequential counterpart to the **variance error** in statistical learning



# Regret

## Sequential risk


Given a convex loss  $\ell$  and a stream  $(\mathbf{x}_1, y_1), (\mathbf{x}_2, y_2), \dots$ , the **sequential risk** of  $A$  is

$$\sum_{t=1}^T \ell(y_t, h_t(\mathbf{x}_t))$$

## Regret

$$R_T = \sum_{t=1}^T \ell(y_t, h_t(\mathbf{x}_t)) - \inf_{h \in \mathcal{H}} \sum_{t=1}^T \ell(y_t, h(\mathbf{x}_t))$$

- ▶ A sequential counterpart to the **variance error** in statistical learning
- ▶ Can we ensure  $\frac{R_T}{T} \rightarrow 0$  as  $T \rightarrow \infty$  for all streams?





# Online learning as a repeated game

## Learning to play a game (1956)

- ▶ Theory of repeated games pioneered by James Hannan and David Blackwell



# Online learning as a repeated game

## Learning to play a game (1956)

- ▶ Theory of repeated games pioneered by James Hannan and David Blackwell
- ▶ Play a game repeatedly against a possibly suboptimal opponent (a.k.a. the data stream)




# Online learning as a repeated game



## Learning to play a game (1956)

- ▶ Theory of repeated games pioneered by James Hannan and David Blackwell
- ▶ Play a game repeatedly against a possibly suboptimal opponent (a.k.a. the data stream)
- ▶ Replace data stream with sequence of **loss functions**, e.g.,  $\ell_t(h_t) = \ell(y_t, h_t(\mathbf{x}_t))$



# Online learning as a repeated game




## Learning to play a game (1956)

- ▶ Theory of repeated games pioneered by James Hannan and David Blackwell
- ▶ Play a game repeatedly against a possibly suboptimal opponent (a.k.a. the data stream)
- ▶ Replace data stream with sequence of **loss functions**, e.g.,  $\ell_t(h_t) = \ell(y_t, h_t(\mathbf{x}_t))$

## Online learning in the simplex

- ▶ Let  $\mathcal{H}$  be the  $d$ -dimensional simplex  $\Delta_d$



# Online learning as a repeated game




## Learning to play a game (1956)

- ▶ Theory of repeated games pioneered by James Hannan and David Blackwell
- ▶ Play a game repeatedly against a possibly suboptimal opponent (a.k.a. the data stream)
- ▶ Replace data stream with sequence of **loss functions**, e.g.,  $\ell_t(h_t) = \ell(y_t, h_t(\mathbf{x}_t))$

## Online learning in the simplex

- ▶ Let  $\mathcal{H}$  be the  $d$ -dimensional simplex  $\Delta_d$
- ▶ The loss at time  $t$  of  $\mathbf{p}_t \in \Delta_d$  is  $\ell_t^\top \mathbf{p}_t = \mathbb{E}[I_t]$  for  $I_t \sim \mathbf{p}_t$



# Online learning as a repeated game




## Learning to play a game (1956)

- ▶ Theory of repeated games pioneered by James Hannan and David Blackwell
- ▶ Play a game repeatedly against a possibly suboptimal opponent (a.k.a. the data stream)
- ▶ Replace data stream with sequence of **loss functions**, e.g.,  $\ell_t(h_t) = \ell(y_t, h_t(\mathbf{x}_t))$

## Online learning in the simplex

- ▶ Let  $\mathcal{H}$  be the  $d$ -dimensional simplex  $\Delta_d$
- ▶ The loss at time  $t$  of  $\mathbf{p}_t \in \Delta_d$  is  $\ell_t^\top \mathbf{p}_t = \mathbb{E}[I_t]$  for  $I_t \sim \mathbf{p}_t$
- ▶ This is a **linear loss** with bounded coefficients  $\ell_t(i) \in [0, 1]$




# Prediction with expert advice

## A sequential decision problem

- ▶  $d$  actions
- ▶ Unknown deterministic assignment of losses to actions  $\ell_t = (\ell_t(1), \dots, \ell_t(d)) \in [0, 1]^d$  for each time step  $t$



For  $t = 1, 2, \dots$



# Prediction with expert advice


## A sequential decision problem

- ▶  $d$  actions
- ▶ Unknown deterministic assignment of losses to actions  $\ell_t = (\ell_t(1), \dots, \ell_t(d)) \in [0, 1]^d$  for each time step  $t$



For  $t = 1, 2, \dots$

1. Player picks an action  $I_t$  (possibly using randomization) and incurs loss  $\ell_t(I_t)$





# Prediction with expert advice

## A sequential decision problem

- ▶  $d$  actions
- ▶ Unknown deterministic assignment of losses to actions  $\ell_t = (\ell_t(1), \dots, \ell_t(d)) \in [0, 1]^d$  for each time step  $t$



For  $t = 1, 2, \dots$

1. Player picks an action  $I_t$  (possibly using randomization) and incurs loss  $\ell_t(I_t)$
2. Player gets **feedback information**:  $\ell_t(1), \dots, \ell_t(d)$

# Regret

$$R_T = \sum_{t=1}^T \ell_t^\top \mathbf{p}_t - \min_{\mathbf{p} \in \Delta_d} \sum_{t=1}^T \ell_t^\top \mathbf{p}$$



# Regret

$$R_T = \sum_{t=1}^T \ell_t^\top \mathbf{p}_t - \min_{\mathbf{p} \in \Delta_d} \sum_{t=1}^T \ell_t^\top \mathbf{p} = \mathbb{E} \left[ \sum_{t=1}^T \ell_t(I_t) \right] - \min_{i=1, \dots, d} \sum_{t=1}^T \ell_t(i)$$



## Regret

$$R_T = \sum_{t=1}^T \ell_t^\top \mathbf{p}_t - \min_{\mathbf{p} \in \Delta_d} \sum_{t=1}^T \ell_t^\top \mathbf{p} = \mathbb{E} \left[ \sum_{t=1}^T \ell_t(I_t) \right] - \min_{i=1, \dots, d} \sum_{t=1}^T \ell_t(i)$$

Lower bound using a statistical learning argument



# Regret

$$R_T = \sum_{t=1}^T \ell_t^\top \mathbf{p}_t - \min_{\mathbf{p} \in \Delta_d} \sum_{t=1}^T \ell_t^\top \mathbf{p} = \mathbb{E} \left[ \sum_{t=1}^T \ell_t(I_t) \right] - \min_{i=1, \dots, d} \sum_{t=1}^T \ell_t(i)$$

Lower bound using a statistical learning argument

- $\ell_t(i) \rightarrow L_t(i) \in \{0, 1\}$  independent random coin flip



# Regret

$$R_T = \sum_{t=1}^T \ell_t^\top \mathbf{p}_t - \min_{\mathbf{p} \in \Delta_d} \sum_{t=1}^T \ell_t^\top \mathbf{p} = \mathbb{E} \left[ \sum_{t=1}^T \ell_t(I_t) \right] - \min_{i=1, \dots, d} \sum_{t=1}^T \ell_t(i)$$

Lower bound using a statistical learning argument

- ▶  $\ell_t(i) \rightarrow L_t(i) \in \{0, 1\}$  independent random coin flip
- ▶ For any player strategy  $\mathbb{E} \left[ \sum_{t=1}^T L_t(I_t) \right] = \frac{T}{2}$



# Regret

$$R_T = \sum_{t=1}^T \ell_t^\top \mathbf{p}_t - \min_{\mathbf{p} \in \Delta_d} \sum_{t=1}^T \ell_t^\top \mathbf{p} = \mathbb{E} \left[ \sum_{t=1}^T \ell_t(I_t) \right] - \min_{i=1, \dots, d} \sum_{t=1}^T \ell_t(i)$$

Lower bound using a statistical learning argument

- ▶  $\ell_t(i) \rightarrow L_t(i) \in \{0, 1\}$  independent random coin flip
- ▶ For any player strategy  $\mathbb{E} \left[ \sum_{t=1}^T L_t(I_t) \right] = \frac{T}{2}$
- ▶ Then the expected regret is

$$\mathbb{E} \left[ \max_{i=1, \dots, d} \sum_{t=1}^T \left( \frac{1}{2} - L_t(i) \right) \right] = (1 - o(1)) \sqrt{\frac{T \ln d}{2}}$$

for  $d, T \rightarrow \infty$

## Exponentially weighted forecaster (Hedge)

At time  $t$  pick action  $I_t = i$  with probability proportional to

$$\exp \left( -\eta \sum_{s=1}^{t-1} \ell_s(i) \right)$$

the sum at the exponent is the **total loss** of action  $i$  up to the previous time step





## Exponentially weighted forecaster (Hedge)

At time  $t$  pick action  $I_t = i$  with probability proportional to

$$\exp \left( -\eta \sum_{s=1}^{t-1} \ell_s(i) \right)$$

the sum at the exponent is the **total loss** of action  $i$  up to the previous time step

Regret bound



## Exponentially weighted forecaster (Hedge)

At time  $t$  pick action  $I_t = i$  with probability proportional to

$$\exp \left( -\eta \sum_{s=1}^{t-1} \ell_s(i) \right)$$

the sum at the exponent is the **total loss** of action  $i$  up to the previous time step

Regret bound

► If  $\eta = \sqrt{\frac{\ln d}{8T}}$  then

$$R_T \leq \sqrt{\frac{T \ln d}{2}}$$



## Exponentially weighted forecaster (Hedge)

At time  $t$  pick action  $I_t = i$  with probability proportional to

$$\exp \left( -\eta \sum_{s=1}^{t-1} \ell_s(i) \right)$$

the sum at the exponent is the **total loss** of action  $i$  up to the previous time step

### Regret bound

► If  $\eta = \sqrt{\frac{\ln d}{8T}}$  then

$$R_T \leq \sqrt{\frac{T \ln d}{2}}$$

► This matches the asymptotic lower bound, **including constants**



## Exponentially weighted forecaster (Hedge)

At time  $t$  pick action  $I_t = i$  with probability proportional to

$$\exp \left( -\eta \sum_{s=1}^{t-1} \ell_s(i) \right)$$

the sum at the exponent is the **total loss** of action  $i$  up to the previous time step

### Regret bound

- ▶ If  $\eta = \sqrt{\frac{\ln d}{8T}}$  then  $R_T \leq \sqrt{\frac{T \ln d}{2}}$
- ▶ This matches the asymptotic lower bound, **including constants**
- ▶ We prove this later in a more general setting




# The bandit problem: playing an unknown game



- ▶  $d$  actions
- ▶ Unknown deterministic assignment of losses to actions  $\ell_t = (\ell_t(1), \dots, \ell_t(d)) \in [0, 1]^d$  for each time step  $t$



For  $t = 1, 2, \dots$



# The bandit problem: playing an unknown game



- ▶  $d$  actions
- ▶ Unknown deterministic assignment of losses to actions  $\ell_t = (\ell_t(1), \dots, \ell_t(d)) \in [0, 1]^d$  for each time step  $t$



For  $t = 1, 2, \dots$

1. Player picks an action  $I_t$  (possibly using randomization) and incurs loss  $\ell_t(I_t)$

# The bandit problem: playing an unknown game



- ▶  $d$  actions
- ▶ Unknown deterministic assignment of losses to actions  $\ell_t = (\ell_t(1), \dots, \ell_t(d)) \in [0, 1]^d$  for each time step  $t$



For  $t = 1, 2, \dots$

1. Player picks an action  $I_t$  (possibly using randomization) and incurs loss  $\ell_t(I_t)$
2. Player gets **feedback information**: Only  $\ell_t(I_t)$  is revealed

# A growing range of applications

- ▶ Ad placement





## A growing range of applications

- ▶ Ad placement
- ▶ Dynamic content/layout optimization



## A growing range of applications

- ▶ Ad placement
- ▶ Dynamic content/layout optimization
- ▶ Real time bidding



## A growing range of applications

- ▶ Ad placement
- ▶ Dynamic content/layout optimization
- ▶ Real time bidding
- ▶ Recommender systems



## A growing range of applications

- ▶ Ad placement
- ▶ Dynamic content/layout optimization
- ▶ Real time bidding
- ▶ Recommender systems
- ▶ Clinical trials





## A growing range of applications



- ▶ Ad placement
- ▶ Dynamic content/layout optimization
- ▶ Real time bidding
- ▶ Recommender systems
- ▶ Clinical trials
- ▶ Network protocol optimization




## An observability graph over actions



## An observability graph over actions




## An observability graph over actions


$$\ell_t(i) \text{ is observed iff } I_t \in \{i\} \cup \mathcal{N}_G(i)$$




## Recovering expert and bandit settings



Experts: clique



Bandits: edgeless graph



## Relationships between actions



## Hedge revisited on an observability graph $G$

Player's strategy must use loss estimates

$$\blacktriangleright p_t(i) \propto \exp \left( -\eta \sum_{s=1}^{t-1} \widehat{\ell}_s(i) \right) \quad i = 1, \dots, d$$



## Hedge revisited on an observability graph $G$

Player's strategy must use loss estimates

- ▶  $p_t(i) \propto \exp \left( -\eta \sum_{s=1}^{t-1} \widehat{\ell}_s(i) \right) \quad i = 1, \dots, d$
- ▶  $\widehat{\ell}_t(i) = \begin{cases} \frac{\ell_t(i)}{\mathbb{P}_t(\ell_t(i) \text{ observed})} & \text{if } \ell_t(i) \text{ is observed because } I_t \in \{i\} \cup \mathcal{N}_G(i) \\ 0 & \text{otherwise} \end{cases}$



## Hedge revisited on an observability graph $G$

Player's strategy must use loss estimates

- ▶  $p_t(i) \propto \exp \left( -\eta \sum_{s=1}^{t-1} \widehat{\ell}_s(i) \right) \quad i = 1, \dots, d$
- ▶  $\widehat{\ell}_t(i) = \begin{cases} \frac{\ell_t(i)}{\mathbb{P}_t(\ell_t(i) \text{ observed})} & \text{if } \ell_t(i) \text{ is observed because } I_t \in \{i\} \cup \mathcal{N}_G(i) \\ 0 & \text{otherwise} \end{cases}$

Importance sampling estimator



## Hedge revisited on an observability graph $G$

Player's strategy must use loss estimates

- ▶  $p_t(i) \propto \exp \left( -\eta \sum_{s=1}^{t-1} \widehat{\ell}_s(i) \right) \quad i = 1, \dots, d$
- ▶  $\widehat{\ell}_t(i) = \begin{cases} \frac{\ell_t(i)}{\mathbb{P}_t(\ell_t(i) \text{ observed})} & \text{if } \ell_t(i) \text{ is observed because } I_t \in \{i\} \cup \mathcal{N}_G(i) \\ 0 & \text{otherwise} \end{cases}$

Importance sampling estimator

$$\mathbb{E}_t[\widehat{\ell}_t(i)] = \frac{\ell_t(i)}{\mathbb{P}_t(\ell_t(i) \text{ observed})} \times \mathbb{P}_t(\ell_t(i) \text{ observed}) + 0 = \ell_t(i)$$
$$\mathbb{E}_t[\widehat{\ell}_t(i)^2] = \frac{\ell_t(i)^2}{\mathbb{P}_t(\ell_t(i) \text{ observed})^2} \times \mathbb{P}_t(\ell_t(i) \text{ observed}) + 0 = \frac{\ell_t(i)^2}{\mathbb{P}_t(\ell_t(i) \text{ observed})}$$

## Hedge revisited on an observability graph $G$

Player's strategy must use loss estimates

- ▶  $p_t(i) \propto \exp \left( -\eta \sum_{s=1}^{t-1} \widehat{\ell}_s(i) \right) \quad i = 1, \dots, d$
- ▶  $\widehat{\ell}_t(i) = \begin{cases} \frac{\ell_t(i)}{\mathbb{P}_t(\ell_t(i) \text{ observed})} & \text{if } \ell_t(i) \text{ is observed because } I_t \in \{i\} \cup \mathcal{N}_G(i) \\ 0 & \text{otherwise} \end{cases}$

Importance sampling estimator

$$\mathbb{E}_t[\widehat{\ell}_t(i)] = \frac{\ell_t(i)}{\mathbb{P}_t(\ell_t(i) \text{ observed})} \times \mathbb{P}_t(\ell_t(i) \text{ observed}) + 0 = \ell_t(i)$$
$$\mathbb{E}_t[\widehat{\ell}_t(i)^2] = \frac{\ell_t(i)^2}{\mathbb{P}_t(\ell_t(i) \text{ observed})^2} \times \mathbb{P}_t(\ell_t(i) \text{ observed}) + 0 \leq \frac{1}{\mathbb{P}_t(\ell_t(i) \text{ observed})}$$

## Regret analysis

$$\frac{W_{t+1}}{W_t} = \sum_{i=1}^d \frac{w_{t+1}(i)}{W_t} \quad p_t(i) = \frac{1}{W_t} \exp \left( -\eta \sum_{s=1}^{t-1} \hat{\ell}_s(i) \right) = \frac{w_t(i)}{W_t} \quad \text{is a r.v.!}$$





## Regret analysis

$$\begin{aligned}\frac{W_{t+1}}{W_t} &= \sum_{i=1}^d \frac{w_{t+1}(i)}{W_t} & p_t(i) &= \frac{1}{W_t} \exp \left( -\eta \sum_{s=1}^{t-1} \hat{\ell}_s(i) \right) = \frac{w_t(i)}{W_t} \quad \text{is a r.v.!} \\ &= \sum_{i=1}^d \frac{w_t(i)}{W_t} \exp(-\eta \hat{\ell}_t(i)) & & \quad \text{(because } w_{t+1}(i) = e^{-\eta \sum_{s=1}^{t-1} \hat{\ell}_s(i) - \eta \hat{\ell}_t(i)} \text{)}\end{aligned}$$




## Regret analysis

$$\begin{aligned}\frac{W_{t+1}}{W_t} &= \sum_{i=1}^d \frac{w_{t+1}(i)}{W_t} & p_t(i) &= \frac{1}{W_t} \exp \left( -\eta \sum_{s=1}^{t-1} \hat{\ell}_s(i) \right) = \frac{w_t(i)}{W_t} \quad \text{is a r.v.!} \\ &= \sum_{i=1}^d \frac{w_t(i)}{W_t} \exp(-\eta \hat{\ell}_t(i)) & & \text{(because } w_{t+1}(i) = e^{-\eta \sum_{s=1}^{t-1} \hat{\ell}_s(i) - \eta \hat{\ell}_t(i)} \text{)} \\ &= \sum_{i=1}^d p_t(i) \exp(-\eta \hat{\ell}_t(i))\end{aligned}$$




## Regret analysis

$$\begin{aligned}\frac{W_{t+1}}{W_t} &= \sum_{i=1}^d \frac{w_{t+1}(i)}{W_t} & p_t(i) &= \frac{1}{W_t} \exp \left( -\eta \sum_{s=1}^{t-1} \hat{\ell}_s(i) \right) = \frac{w_t(i)}{W_t} \quad \text{is a r.v.!} \\ &= \sum_{i=1}^d \frac{w_t(i)}{W_t} \exp(-\eta \hat{\ell}_t(i)) & & \text{(because } w_{t+1}(i) = e^{-\eta \sum_{s=1}^{t-1} \hat{\ell}_s(i) - \eta \hat{\ell}_t(i)} \text{)} \\ &= \sum_{i=1}^d p_t(i) \exp(-\eta \hat{\ell}_t(i)) \\ &\leq \sum_{i=1}^d p_t(i) \left( 1 - \eta \hat{\ell}_t(i) + \frac{(\eta \hat{\ell}_t(i))^2}{2} \right) & & \text{(using } e^{-x} \leq 1 - x + x^2/2 \text{ for all } x \geq 0 \text{)}\end{aligned}$$



## Regret analysis

$$\begin{aligned}\frac{W_{t+1}}{W_t} &= \sum_{i=1}^d \frac{w_{t+1}(i)}{W_t} & p_t(i) &= \frac{1}{W_t} \exp \left( -\eta \sum_{s=1}^{t-1} \hat{\ell}_s(i) \right) = \frac{w_t(i)}{W_t} \quad \text{is a r.v.!} \\ &= \sum_{i=1}^d \frac{w_t(i)}{W_t} \exp(-\eta \hat{\ell}_t(i)) & & \quad \text{(because } w_{t+1}(i) = e^{-\eta \sum_{s=1}^{t-1} \hat{\ell}_s(i) - \eta \hat{\ell}_t(i)}) \\ &= \sum_{i=1}^d p_t(i) \exp(-\eta \hat{\ell}_t(i)) \\ &\leq \sum_{i=1}^d p_t(i) \left( 1 - \eta \hat{\ell}_t(i) + \frac{(\eta \hat{\ell}_t(i))^2}{2} \right) & & \quad \text{(using } e^{-x} \leq 1 - x + x^2/2 \text{ for all } x \geq 0) \\ &\leq 1 - \eta \sum_{i=1}^d p_t(i) \hat{\ell}_t(i) + \frac{\eta^2}{2} \sum_{i=1}^d p_t(i) \hat{\ell}_t(i)^2\end{aligned}$$



## Regret analysis (cont.)

Taking logs, using  $\ln(1+x) \leq x$ , and summing over  $t = 1, \dots, T$  yields

$$\ln \frac{W_{T+1}}{W_1} \leq -\eta \sum_{t=1}^T \sum_{i=1}^d p_t(i) \hat{\ell}_t(i) + \frac{\eta^2}{2} \sum_{t=1}^T \sum_{i=1}^d p_t(i) \hat{\ell}_t(i)^2$$



## Regret analysis (cont.)

Taking logs, using  $\ln(1+x) \leq x$ , and summing over  $t = 1, \dots, T$  yields

$$\ln \frac{W_{T+1}}{W_1} \leq -\eta \sum_{t=1}^T \sum_{i=1}^d p_t(i) \hat{\ell}_t(i) + \frac{\eta^2}{2} \sum_{t=1}^T \sum_{i=1}^d p_t(i) \hat{\ell}_t(i)^2$$

Moreover, for any fixed action  $k$ , we also have

$$\ln \frac{W_{T+1}}{W_1} \geq \ln \frac{w_{T+1}(k)}{W_1} = -\eta \sum_{t=1}^T \hat{\ell}_t(k) - \ln d$$



## Regret analysis (cont.)

Taking logs, using  $\ln(1+x) \leq x$ , and summing over  $t = 1, \dots, T$  yields


$$\ln \frac{W_{T+1}}{W_1} \leq -\eta \sum_{t=1}^T \sum_{i=1}^d p_t(i) \hat{\ell}_t(i) + \frac{\eta^2}{2} \sum_{t=1}^T \sum_{i=1}^d p_t(i) \hat{\ell}_t(i)^2$$

Moreover, for any fixed action  $k$ , we also have

$$\ln \frac{W_{T+1}}{W_1} \geq \ln \frac{w_{T+1}(k)}{W_1} = -\eta \sum_{t=1}^T \hat{\ell}_t(k) - \ln d$$

Putting together and dividing both sides by  $\eta > 0$  gives

$$\sum_{t=1}^T \sum_{i=1}^d p_t(i) \hat{\ell}_t(i) - \sum_{t=1}^T \hat{\ell}_t(k) \leq \frac{\ln d}{\eta} + \frac{\eta}{2} \sum_{t=1}^T \sum_{i=1}^d p_t(i) \hat{\ell}_t(i)^2$$



## Regret analysis (cont.)

Recall where we were:

$$\sum_{t=1}^T \sum_{i=1}^d p_t(i) \hat{\ell}_t(i) - \sum_{t=1}^T \hat{\ell}_t(k) \leq \frac{\ln d}{\eta} + \frac{\eta}{2} \sum_{t=1}^T \sum_{i=1}^d p_t(i) \hat{\ell}_t(i)^2$$






## Regret analysis (cont.)

Recall where we were:

$$\sum_{t=1}^T \sum_{i=1}^d p_t(i) \hat{\ell}_t(i) - \sum_{t=1}^T \hat{\ell}_t(k) \leq \frac{\ln d}{\eta} + \frac{\eta}{2} \sum_{t=1}^T \sum_{i=1}^d p_t(i) \hat{\ell}_t(i)^2$$

Take expectation w.r.t.  $I_1, \dots, I_T$

$$\mathbb{E} \left[ \sum_{t=1}^T \sum_{i=1}^d p_t(i) \mathbb{E}_t[\hat{\ell}_t(i)] - \sum_{t=1}^T \mathbb{E}_t[\hat{\ell}_t(k)] \right] \leq \frac{\ln d}{\eta} + \frac{\eta}{2} \mathbb{E} \left[ \sum_{t=1}^T \sum_{i=1}^d p_t(i) \mathbb{E}_t[\hat{\ell}_t(i)^2] \right]$$



## Regret analysis (cont.)

Recall where we were:

$$\sum_{t=1}^T \sum_{i=1}^d p_t(i) \hat{\ell}_t(i) - \sum_{t=1}^T \hat{\ell}_t(k) \leq \frac{\ln d}{\eta} + \frac{\eta}{2} \sum_{t=1}^T \sum_{i=1}^d p_t(i) \hat{\ell}_t(i)^2$$

Take expectation w.r.t.  $I_1, \dots, I_T$

$$\mathbb{E} \left[ \sum_{t=1}^T \sum_{i=1}^d p_t(i) \mathbb{E}_t[\hat{\ell}_t(i)] - \sum_{t=1}^T \mathbb{E}_t[\hat{\ell}_t(k)] \right] \leq \frac{\ln d}{\eta} + \frac{\eta}{2} \mathbb{E} \left[ \sum_{t=1}^T \sum_{i=1}^d p_t(i) \mathbb{E}_t[\hat{\ell}_t(i)^2] \right]$$

Loss estimates are unbiased:

$$\mathbb{E} \left[ \sum_{t=1}^T \sum_{i=1}^d p_t(i) \ell_t(i) - \sum_{t=1}^T \ell_t(k) \right] \leq \frac{\ln d}{\eta} + \frac{\eta}{2} \mathbb{E} \left[ \sum_{t=1}^T \sum_{i=1}^d p_t(i) \mathbb{E}_t[\hat{\ell}_t(i)^2] \right]$$

## Regret analysis (cont.)

Recall where we were:

$$\sum_{t=1}^T \sum_{i=1}^d p_t(i) \hat{\ell}_t(i) - \sum_{t=1}^T \hat{\ell}_t(k) \leq \frac{\ln d}{\eta} + \frac{\eta}{2} \sum_{t=1}^T \sum_{i=1}^d p_t(i) \hat{\ell}_t(i)^2$$

Take expectation w.r.t.  $I_1, \dots, I_T$

$$\mathbb{E} \left[ \sum_{t=1}^T \sum_{i=1}^d p_t(i) \mathbb{E}_t[\hat{\ell}_t(i)] - \sum_{t=1}^T \mathbb{E}_t[\hat{\ell}_t(k)] \right] \leq \frac{\ln d}{\eta} + \frac{\eta}{2} \mathbb{E} \left[ \sum_{t=1}^T \sum_{i=1}^d p_t(i) \mathbb{E}_t[\hat{\ell}_t(i)^2] \right]$$

This is just the regret

$$R_T = \mathbb{E} \left[ \sum_{t=1}^T \sum_{i=1}^d p_t(i) \ell_t(i) - \sum_{t=1}^T \ell_t(k) \right] \leq \frac{\ln d}{\eta} + \frac{\eta}{2} \mathbb{E} \left[ \sum_{t=1}^T \sum_{i=1}^d p_t(i) \mathbb{E}_t[\hat{\ell}_t(i)^2] \right]$$

## Regret analysis (cont.)


$$R_T \leq \frac{\ln d}{\eta} + \frac{\eta}{2} \mathbb{E} \left[ \sum_{t=1}^T \sum_{i=1}^d p_t(i) \mathbb{E}_t \left[ \widehat{\ell}_t(i)^2 \right] \right]$$



## Regret analysis (cont.)

$$\begin{aligned} R_T &\leq \frac{\ln d}{\eta} + \frac{\eta}{2} \mathbb{E} \left[ \sum_{t=1}^T \sum_{i=1}^d p_t(i) \mathbb{E}_t \left[ \widehat{\ell}_t(i)^2 \right] \right] \\ &\leq \frac{\ln d}{\eta} + \frac{\eta}{2} \mathbb{E} \left[ \sum_{t=1}^T \sum_{i=1}^d \frac{p_t(i)}{\mathbb{P}_t(\ell_t(i) \text{ is observed})} \right] \end{aligned}$$

(variance bound)




## Regret analysis (cont.)

$$\begin{aligned} R_T &\leq \frac{\ln d}{\eta} + \frac{\eta}{2} \mathbb{E} \left[ \sum_{t=1}^T \sum_{i=1}^d p_t(i) \mathbb{E}_t \left[ \widehat{\ell}_t(i)^2 \right] \right] \\ &\leq \frac{\ln d}{\eta} + \frac{\eta}{2} \mathbb{E} \left[ \sum_{t=1}^T \sum_{i=1}^d \frac{p_t(i)}{\mathbb{P}_t(\ell_t(i) \text{ is observed})} \right] \\ &= \frac{\ln d}{\eta} + \frac{\eta}{2} \mathbb{E} \left[ \sum_{t=1}^T \sum_{i=1}^d \frac{p_t(i)}{p_t(i) + \sum_{j \in \mathcal{N}_G(i)} p_t(j)} \right] \end{aligned}$$

(variance bound)

(observability condition)



## Regret analysis (cont.)

$$\begin{aligned} R_T &\leq \frac{\ln d}{\eta} + \frac{\eta}{2} \mathbb{E} \left[ \sum_{t=1}^T \sum_{i=1}^d p_t(i) \mathbb{E}_t [\widehat{\ell}_t(i)^2] \right] \\ &\leq \frac{\ln d}{\eta} + \frac{\eta}{2} \mathbb{E} \left[ \sum_{t=1}^T \sum_{i=1}^d \frac{p_t(i)}{\mathbb{P}_t(\ell_t(i) \text{ is observed})} \right] \\ &= \frac{\ln d}{\eta} + \frac{\eta}{2} \mathbb{E} \left[ \sum_{t=1}^T \sum_{i=1}^d \frac{p_t(i)}{p_t(i) + \sum_{j \in \mathcal{N}_G(i)} p_t(j)} \right] \\ &\leq \frac{\ln d}{\eta} + \frac{\eta}{2} T \alpha(G) \end{aligned}$$

(variance bound)



(observability condition)

(cool graph-theoretic fact)

$\alpha(G)$  is the independence number of  $G$

## Independence number $\alpha(G)$



The size of the largest **independent set** in  $G$





## Independence number $\alpha(G)$

The size of the largest **independent set** in  $G$



## Regret bound

$$R_T \leq \frac{\ln d}{\eta} + \frac{\eta}{2} T \alpha(G)$$



## Regret bound

$$R_T \leq \frac{\ln d}{\eta} + \frac{\eta}{2} T \alpha(G) = \sqrt{T \alpha(G) \ln d}$$



## Regret bound

$$R_T \leq \frac{\ln d}{\eta} + \frac{\eta}{2} T \alpha(G) = \sqrt{T \alpha(G) \ln d}$$

**Note:** This bound is tight for all  $G$  (up to logarithmic factors)



## Regret bound

$$R_T \leq \frac{\ln d}{\eta} + \frac{\eta}{2} T \alpha(G) = \sqrt{T \alpha(G) \ln d}$$

**Note:** This bound is tight for all  $G$  (up to logarithmic factors)

### Special cases

**Experts** (clique):

$$\alpha(G) = 1$$

$$R_T \leq \sqrt{T \ln d}$$

Hedge algorithm


**Bandits** (edgeless graph):

$$\alpha(G) = d$$


$$R_T \leq \sqrt{T d \ln d}$$

Exp3 algorithm


## More general feedback models




Experts



Bandits



Cops & Robbers



Revealing Action



## Partial monitoring: not observing your own loss

Dynamic pricing: Perform as the best fixed price

1. Post a T-shirt price
2. Observe if next customer buys or not
3. Adjust price



Feedback does not reveal the player's loss

	1	2	3	4	5
1	0	1	2	3	4
2	$c$	0	1	2	3
3	$c$	$c$	0	1	2
4	$c$	$c$	$c$	0	1
5	$c$	$c$	$c$	$c$	0

Loss

	1	2	3	4	5
1	1	1	1	1	1
2	0	1	1	1	1
3	0	0	1	1	1
4	0	0	0	1	1
5	0	0	0	0	1

Feedback

## A general gap theorem

- ▶ A constructive characterization of the minimax regret for any partial monitoring game





## A general gap theorem

- ▶ A constructive characterization of the minimax regret for any partial monitoring game
- ▶ Only three possible rates for nontrivial games:



## A general gap theorem

- ▶ A constructive characterization of the minimax regret for any partial monitoring game
- ▶ Only three possible rates for nontrivial games:
  1. Easy games (e.g., experts, bandits, cops & robbers):  $\Theta(\sqrt{T})$




## A general gap theorem

- ▶ A constructive characterization of the minimax regret for any partial monitoring game
- ▶ Only three possible rates for nontrivial games:
  1. Easy games (e.g., experts, bandits, cops & robbers):  $\Theta(\sqrt{T})$
  2. Hard games (e.g., revealing action, dynamic pricing):  $\Theta(T^{2/3})$



## A general gap theorem

- ▶ A constructive characterization of the minimax regret for any partial monitoring game
- ▶ Only three possible rates for nontrivial games:
  1. Easy games (e.g., experts, bandits, cops & robbers):  $\Theta(\sqrt{T})$
  2. Hard games (e.g., revealing action, dynamic pricing):  $\Theta(T^{2/3})$
  3. Impossible games:  $\Theta(T)$



## Contextual bandits

- ▶ A policy  $\pi$  maps side information (e.g., feature vectors  $\mathbf{x}_t$ ) to probabilistic decisions  $\pi(\mathbf{x}_t) \in \Delta_d$




# Contextual bandits

- ▶ A policy  $\pi$  maps side information (e.g., feature vectors  $\mathbf{x}_t$ ) to probabilistic decisions  $\pi(\mathbf{x}_t) \in \Delta_d$
- ▶ Consider a finite set  $\Pi$  of such policies




# Contextual bandits

- ▶ A policy  $\pi$  maps side information (e.g., feature vectors  $\mathbf{x}_t$ ) to probabilistic decisions  $\pi(\mathbf{x}_t) \in \Delta_d$
- ▶ Consider a finite set  $\Pi$  of such policies
- ▶ Regret against best policy:  $R_T^{\text{pol}} = \mathbb{E} \left[ \sum_{t=1}^T \ell_t(I_t) \right] - \min_{\pi \in \Pi} \sum_{t=1}^T \ell_t(\pi(\mathbf{x}_t))$



## Contextual bandits


- ▶ A policy  $\pi$  maps side information (e.g., feature vectors  $\mathbf{x}_t$ ) to probabilistic decisions  $\pi(\mathbf{x}_t) \in \Delta_d$
- ▶ Consider a finite set  $\Pi$  of such policies
- ▶ Regret against best policy:  $R_T^{\text{pol}} = \mathbb{E} \left[ \sum_{t=1}^T \ell_t(I_t) \right] - \min_{\pi \in \Pi} \sum_{t=1}^T \ell_t(\pi(\mathbf{x}_t))$
- ▶ Exp4 (a variant of Exp3) selects actions  $I_t$  based on  $\{\pi(\mathbf{x}_t) : \pi \in \Pi\}$






## Contextual bandits

- ▶ A policy  $\pi$  maps side information (e.g., feature vectors  $\mathbf{x}_t$ ) to probabilistic decisions  $\pi(\mathbf{x}_t) \in \Delta_d$
- ▶ Consider a finite set  $\Pi$  of such policies
- ▶ Regret against best policy:  $R_T^{\text{pol}} = \mathbb{E} \left[ \sum_{t=1}^T \ell_t(I_t) \right] - \min_{\pi \in \Pi} \sum_{t=1}^T \ell_t(\pi(\mathbf{x}_t))$
- ▶ Exp4 (a variant of Exp3) selects actions  $I_t$  based on  $\{\pi(\mathbf{x}_t) : \pi \in \Pi\}$
- ▶ Regret bound:  $R_T^{\text{pol}} \leq \sqrt{Td \ln |\Pi|}$  (with bandit feedback)




## Contextual bandits

- ▶ A policy  $\pi$  maps side information (e.g., feature vectors  $\mathbf{x}_t$ ) to probabilistic decisions  $\pi(\mathbf{x}_t) \in \Delta_d$
- ▶ Consider a finite set  $\Pi$  of such policies
- ▶ Regret against best policy:  $R_T^{\text{pol}} = \mathbb{E} \left[ \sum_{t=1}^T \ell_t(I_t) \right] - \min_{\pi \in \Pi} \sum_{t=1}^T \ell_t(\pi(\mathbf{x}_t))$
- ▶ Exp4 (a variant of Exp3) selects actions  $I_t$  based on  $\{\pi(\mathbf{x}_t) : \pi \in \Pi\}$
- ▶ Regret bound:  $R_T^{\text{pol}} \leq \sqrt{Td \ln |\Pi|}$  (with bandit feedback)
- ▶ This holds for all loss sequences, sets of policies, and side information sequences



## Contextual bandits

- ▶ A policy  $\pi$  maps side information (e.g., feature vectors  $\mathbf{x}_t$ ) to probabilistic decisions  $\pi(\mathbf{x}_t) \in \Delta_d$
- ▶ Consider a finite set  $\Pi$  of such policies
- ▶ Regret against best policy:  $R_T^{\text{pol}} = \mathbb{E} \left[ \sum_{t=1}^T \ell_t(I_t) \right] - \min_{\pi \in \Pi} \sum_{t=1}^T \ell_t(\pi(\mathbf{x}_t))$
- ▶ Exp4 (a variant of Exp3) selects actions  $I_t$  based on  $\{\pi(\mathbf{x}_t) : \pi \in \Pi\}$
- ▶ Regret bound:  $R_T^{\text{pol}} \leq \sqrt{Td \ln |\Pi|}$  (with bandit feedback)
- ▶ This holds for all loss sequences, sets of policies, and side information sequences
- ▶ Need time linear in  $|\Pi|$  at each step



# Online convex optimization

Model space  $\mathbb{V} \subseteq \mathbb{R}^d$  convex, closed, and nonempty

For  $t = 1, 2, \dots$

1. The current  $h_t \in \mathcal{H}$  is tested on the next data point  $(\mathbf{x}_t, y_t)$  in the stream
2.  $A$  is charged with loss  $\ell(y_t, h_t(\mathbf{x}_t))$
3.  $h_{t+1}$  is computed based on  $h_t$  and  $(\mathbf{x}_t, y_t)$



# Online convex optimization

Model space  $\mathbb{V} \subseteq \mathbb{R}^d$  convex, closed, and nonempty

For  $t = 1, 2, \dots$

1. The current  $\mathbf{w} \in \mathbb{V}$  is tested on the next convex loss function  $\ell_t$  in the stream
2.  $A$  is charged with loss  $\ell(y_t, h_t(\mathbf{x}_t))$
3.  $h_{t+1}$  is computed based on  $h_t$  and  $(\mathbf{x}_t, y_t)$



# Online convex optimization

Model space  $\mathbb{V} \subseteq \mathbb{R}^d$  convex, closed, and nonempty

For  $t = 1, 2, \dots$

1. The current  $\mathbf{w} \in \mathbb{V}$  is tested on the next convex loss function  $\ell_t$  in the stream
2.  $A$  is charged loss  $\ell_t(\mathbf{w}_t)$
3.  $h_{t+1}$  is computed based on  $h_t$  and  $(\mathbf{x}_t, y_t)$




# Online convex optimization

Model space  $\mathbb{V} \subseteq \mathbb{R}^d$  convex, closed, and nonempty

For  $t = 1, 2, \dots$

1. The current  $\mathbf{w} \in \mathbb{V}$  is tested on the next convex loss function  $\ell_t$  in the stream
2.  $A$  is charged loss  $\ell_t(\mathbf{w}_t)$
3.  $\mathbf{w}_{t+1}$  is computed based on  $\mathbf{w}_t$  and  $\nabla \ell_t(\mathbf{w}_t)$  (first-order oracle)



# Online convex optimization


Model space  $\mathbb{V} \subseteq \mathbb{R}^d$  convex, closed, and nonempty

For  $t = 1, 2, \dots$

1. The current  $\mathbf{w} \in \mathbb{V}$  is tested on the next convex loss function  $\ell_t$  in the stream
2.  $A$  is charged loss  $\ell_t(\mathbf{w}_t)$
3.  $\mathbf{w}_{t+1}$  is computed based on  $\mathbf{w}_t$  and  $\nabla \ell_t(\mathbf{w}_t)$  (first-order oracle)

Regret

$$R_T(\mathbf{u}) = \sum_{t=1}^T \ell_t(\mathbf{w}_t) - \sum_{t=1}^T \ell_t(\mathbf{u}) \quad \mathbf{u} \in \mathbb{V}$$





# Online convex optimization


Model space  $\mathbb{V} \subseteq \mathbb{R}^d$  convex, closed, and nonempty

For  $t = 1, 2, \dots$


1. The current  $\mathbf{w} \in \mathbb{V}$  is tested on the next convex loss function  $\ell_t$  in the stream
2.  $A$  is charged loss  $\ell_t(\mathbf{w}_t)$
3.  $\mathbf{w}_{t+1}$  is computed based on  $\mathbf{w}_t$  and  $\nabla \ell_t(\mathbf{w}_t)$  (first-order oracle)

Regret

$$R_T = \sum_{t=1}^T \ell_t(\mathbf{w}_t) - \inf_{\mathbf{u} \in \mathbb{V}} \sum_{t=1}^T \ell_t(\mathbf{u})$$




# Stochastic gradient descent




Minimization of training error

$$\min_{\mathbf{w} \in \mathbb{V}} \sum_{i=1}^m \ell(\mathbf{w}, (\mathbf{x}_i, y_i))$$

$\ell(\mathbf{w}, (\mathbf{x}_i, y_i))$  measures the (convex) loss of  $\mathbf{w}$  on the training example  $(\mathbf{x}_i, y_i)$



# Stochastic gradient descent




Minimization of training error


$$\min_{\mathbf{w} \in \mathbb{V}} \sum_{i=1}^m \ell(\mathbf{w}, (\mathbf{x}_i, y_i))$$

$\ell(\mathbf{w}, (\mathbf{x}_i, y_i))$  measures the (convex) loss of  $\mathbf{w}$  on the training example  $(\mathbf{x}_i, y_i)$

- ▶ When  $m$  is large we cannot afford to spend more than **constant time** on each data point



# Stochastic gradient descent




## Minimization of training error


$$\min_{\mathbf{w} \in \mathbb{V}} \sum_{i=1}^m \ell(\mathbf{w}, (\mathbf{x}_i, y_i))$$

$\ell(\mathbf{w}, (\mathbf{x}_i, y_i))$  measures the (convex) loss of  $\mathbf{w}$  on the training example  $(\mathbf{x}_i, y_i)$

- ▶ When  $m$  is large we cannot afford to spend more than **constant time** on each data point
- ▶ Online convex optimization can be used for **stochastic optimization**



# Stochastic gradient descent




## Minimization of training error


$$\min_{\mathbf{w} \in \mathbb{V}} \sum_{i=1}^m \ell(\mathbf{w}, (\mathbf{x}_i, y_i))$$

$\ell(\mathbf{w}, (\mathbf{x}_i, y_i))$  measures the (convex) loss of  $\mathbf{w}$  on the training example  $(\mathbf{x}_i, y_i)$

- ▶ When  $m$  is large we cannot afford to spend more than **constant time** on each data point
- ▶ Online convex optimization can be used for **stochastic optimization**
- ▶ Draw  $(\mathbf{X}_1, Y_1), (\mathbf{X}_2, Y_2) \dots$  uniformly i.i.d. from the training set



# Stochastic gradient descent



## Minimization of training error

$$\min_{\mathbf{w} \in \mathbb{V}} \sum_{i=1}^m \ell(\mathbf{w}, (\mathbf{x}_i, y_i))$$

$\ell(\mathbf{w}, (\mathbf{x}_i, y_i))$  measures the (convex) loss of  $\mathbf{w}$  on the training example  $(\mathbf{x}_i, y_i)$

- ▶ When  $m$  is large we cannot afford to spend more than **constant time** on each data point
- ▶ Online convex optimization can be used for **stochastic optimization**
- ▶ Draw  $(\mathbf{X}_1, Y_1), (\mathbf{X}_2, Y_2) \dots$  uniformly i.i.d. from the training set
- ▶ Run online algorithm on the sequence of loss functions  $\ell_t = \ell_t(\cdot, (\mathbf{X}_t, Y_t))$

## Lower bounds

- $\mathbb{V}$  is a bounded set of diameter  $D$  and all  $\ell_t$  are Lipschitz with constant  $L$



## Lower bounds


- ▶  $\mathbb{V}$  is a bounded set of diameter  $D$  and all  $\ell_t$  are Lipschitz with constant  $L$
- ▶ Take  $\mathbf{v}_1, \mathbf{v}_2 \in \mathbb{V}$  such that  $\|\mathbf{v}_1 - \mathbf{v}_2\|_2 = D$  and set  $\mathbf{z}_0 = (\mathbf{v}_1 - \mathbf{v}_2) / \|\mathbf{v}_1 - \mathbf{v}_2\|_2$





## Lower bounds

- ▶  $\mathbb{V}$  is a bounded set of diameter  $D$  and all  $\ell_t$  are Lipschitz with constant  $L$
- ▶ Take  $\mathbf{v}_1, \mathbf{v}_2 \in \mathbb{V}$  such that  $\|\mathbf{v}_1 - \mathbf{v}_2\|_2 = D$  and set  $\mathbf{z}_0 = (\mathbf{v}_1 - \mathbf{v}_2) / \|\mathbf{v}_1 - \mathbf{v}_2\|_2$
- ▶ Stochastic **linear losses**  $L_t(\mathbf{w}) = \varepsilon_t L \mathbf{w}^\top \mathbf{z}_0$  where  $\varepsilon_t \in \{-1, 1\}$  are uniform



## Lower bounds

- ▶  $\mathbb{V}$  is a bounded set of diameter  $D$  and all  $\ell_t$  are Lipschitz with constant  $L$
- ▶ Take  $\mathbf{v}_1, \mathbf{v}_2 \in \mathbb{V}$  such that  $\|\mathbf{v}_1 - \mathbf{v}_2\|_2 = D$  and set  $\mathbf{z}_0 = (\mathbf{v}_1 - \mathbf{v}_2) / \|\mathbf{v}_1 - \mathbf{v}_2\|_2$
- ▶ Stochastic **linear losses**  $L_t(\mathbf{w}) = \varepsilon_t L \mathbf{w}^\top \mathbf{z}_0$  where  $\varepsilon_t \in \{-1, 1\}$  are uniform

$$\mathbb{E} \left[ \max_{\mathbf{u} \in \{\mathbf{v}_1, \mathbf{v}_2\}} R_T(\mathbf{u}) \right]$$



## Lower bounds

- ▶  $\mathbb{V}$  is a bounded set of diameter  $D$  and all  $\ell_t$  are Lipschitz with constant  $L$
- ▶ Take  $\mathbf{v}_1, \mathbf{v}_2 \in \mathbb{V}$  such that  $\|\mathbf{v}_1 - \mathbf{v}_2\|_2 = D$  and set  $\mathbf{z}_0 = (\mathbf{v}_1 - \mathbf{v}_2) / \|\mathbf{v}_1 - \mathbf{v}_2\|_2$
- ▶ Stochastic **linear losses**  $L_t(\mathbf{w}) = \varepsilon_t L \mathbf{w}^\top \mathbf{z}_0$  where  $\varepsilon_t \in \{-1, 1\}$  are uniform


$$\mathbb{E} \left[ \max_{\mathbf{u} \in \{\mathbf{v}_1, \mathbf{v}_2\}} R_T(\mathbf{u}) \right] = \mathbb{E} \left[ \max_{\mathbf{u} \in \{\mathbf{v}_1, \mathbf{v}_2\}} \sum_{t=1}^T L_t(\mathbf{u}) \right] \quad (\text{since } \mathbb{E}[L_t(\mathbf{w})] = 0)$$



## Lower bounds

- ▶  $\mathbb{V}$  is a bounded set of diameter  $D$  and all  $\ell_t$  are Lipschitz with constant  $L$
- ▶ Take  $\mathbf{v}_1, \mathbf{v}_2 \in \mathbb{V}$  such that  $\|\mathbf{v}_1 - \mathbf{v}_2\|_2 = D$  and set  $\mathbf{z}_0 = (\mathbf{v}_1 - \mathbf{v}_2) / \|\mathbf{v}_1 - \mathbf{v}_2\|_2$
- ▶ Stochastic **linear losses**  $L_t(\mathbf{w}) = \varepsilon_t L \mathbf{w}^\top \mathbf{z}_0$  where  $\varepsilon_t \in \{-1, 1\}$  are uniform

$$\begin{aligned} \mathbb{E} \left[ \max_{\mathbf{u} \in \{\mathbf{v}_1, \mathbf{v}_2\}} R_T(\mathbf{u}) \right] &= \mathbb{E} \left[ \max_{\mathbf{u} \in \{\mathbf{v}_1, \mathbf{v}_2\}} \sum_{t=1}^T L_t(\mathbf{u}) \right] && \text{(since } \mathbb{E}[L_t(\mathbf{w})] = 0\text{)} \\ &= \frac{L}{2} \mathbb{E} \left[ \left| \sum_{t=1}^T \varepsilon_t \mathbf{z}_0^\top (\mathbf{v}_1 - \mathbf{v}_2) \right| \right] && \text{(using } \max\{a, b\} = \frac{1}{2}(a + b + |a - b|)\text{)} \end{aligned}$$



## Lower bounds

- ▶  $\mathbb{V}$  is a bounded set of diameter  $D$  and all  $\ell_t$  are Lipschitz with constant  $L$
- ▶ Take  $\mathbf{v}_1, \mathbf{v}_2 \in \mathbb{V}$  such that  $\|\mathbf{v}_1 - \mathbf{v}_2\|_2 = D$  and set  $\mathbf{z}_0 = (\mathbf{v}_1 - \mathbf{v}_2) / \|\mathbf{v}_1 - \mathbf{v}_2\|_2$
- ▶ Stochastic **linear losses**  $L_t(\mathbf{w}) = \varepsilon_t L \mathbf{w}^\top \mathbf{z}_0$  where  $\varepsilon_t \in \{-1, 1\}$  are uniform

$$\begin{aligned}\mathbb{E} \left[ \max_{\mathbf{u} \in \{\mathbf{v}_1, \mathbf{v}_2\}} R_T(\mathbf{u}) \right] &= \mathbb{E} \left[ \max_{\mathbf{u} \in \{\mathbf{v}_1, \mathbf{v}_2\}} \sum_{t=1}^T L_t(\mathbf{u}) \right] && \text{(since } \mathbb{E}[L_t(\mathbf{w})] = 0\text{)} \\ &= \frac{L}{2} \mathbb{E} \left[ \left| \sum_{t=1}^T \varepsilon_t \mathbf{z}_0^\top (\mathbf{v}_1 - \mathbf{v}_2) \right| \right] && \text{(using } \max\{a, b\} = \frac{1}{2}(a + b + |a - b|)\text{)} \\ &= \frac{LD}{2} \mathbb{E} \left[ \left| \sum_{t=1}^T \varepsilon_t \right| \right] && \text{(because } \mathbf{z}_0^\top (\mathbf{v}_1 - \mathbf{v}_2) = D\text{)}\end{aligned}$$

## Lower bounds

- ▶  $\mathbb{V}$  is a bounded set of diameter  $D$  and all  $\ell_t$  are Lipschitz with constant  $L$
- ▶ Take  $\mathbf{v}_1, \mathbf{v}_2 \in \mathbb{V}$  such that  $\|\mathbf{v}_1 - \mathbf{v}_2\|_2 = D$  and set  $\mathbf{z}_0 = (\mathbf{v}_1 - \mathbf{v}_2) / \|\mathbf{v}_1 - \mathbf{v}_2\|_2$
- ▶ Stochastic **linear losses**  $L_t(\mathbf{w}) = \varepsilon_t L \mathbf{w}^\top \mathbf{z}_0$  where  $\varepsilon_t \in \{-1, 1\}$  are uniform

$$\begin{aligned}\mathbb{E} \left[ \max_{\mathbf{u} \in \{\mathbf{v}_1, \mathbf{v}_2\}} R_T(\mathbf{u}) \right] &= \mathbb{E} \left[ \max_{\mathbf{u} \in \{\mathbf{v}_1, \mathbf{v}_2\}} \sum_{t=1}^T L_t(\mathbf{u}) \right] && \text{(since } \mathbb{E}[L_t(\mathbf{w})] = 0\text{)} \\ &= \frac{L}{2} \mathbb{E} \left[ \left| \sum_{t=1}^T \varepsilon_t \mathbf{z}_0^\top (\mathbf{v}_1 - \mathbf{v}_2) \right| \right] && \text{(using } \max\{a, b\} = \frac{1}{2}(a + b + |a - b|)\text{)} \\ &= \frac{LD}{2} \mathbb{E} \left[ \left| \sum_{t=1}^T \varepsilon_t \right| \right] && \text{(because } \mathbf{z}_0^\top (\mathbf{v}_1 - \mathbf{v}_2) = D\text{)} \\ &\geq LD \sqrt{\frac{T}{8}} && \text{(Khinchine inequality)}\end{aligned}$$

## Some remarks

- Let  $\mathbb{V}$  be the unit Euclidean ball and assume  $\ell_t$  is such that  $\|\nabla \ell_t\|_\infty = \Omega(1)$



## Some remarks


- ▶ Let  $\mathbb{V}$  be the unit Euclidean ball and assume  $\ell_t$  is such that  $\|\nabla \ell_t\|_\infty = \Omega(1)$
- ▶ The previous lower bound suggests  $R_T(\mathbf{u}) = \Omega(\sqrt{dT})$  for  $\|\mathbf{u}\| \leq 1$






## Some remarks

- ▶ Let  $\mathbb{V}$  be the unit Euclidean ball and assume  $\ell_t$  is such that  $\|\nabla \ell_t\|_\infty = \Omega(1)$
- ▶ The previous lower bound suggests  $R_T(\mathbf{u}) = \Omega(\sqrt{dT})$  for  $\|\mathbf{u}\| \leq 1$
- ▶  $\mathbb{V}$  is the simplex  $\Delta_d$  and  $\ell_t$  is linear with coefficients  $\|\ell\|_\infty = \Theta(1)$



## Some remarks


- ▶ Let  $\mathbb{V}$  be the unit Euclidean ball and assume  $\ell_t$  is such that  $\|\nabla \ell_t\|_\infty = \Omega(1)$
- ▶ The previous lower bound suggests  $R_T(\mathbf{u}) = \Omega(\sqrt{dT})$  for  $\|\mathbf{u}\| \leq 1$
- ▶  $\mathbb{V}$  is the simplex  $\Delta_d$  and  $\ell_t$  is linear with coefficients  $\|\ell\|_\infty = \Theta(1)$
- ▶ Hedge (exponential weights) achieves  $R_T(\mathbf{p}) = \mathcal{O}(\sqrt{T \ln d})$  for  $\mathbf{p} \in \Delta_d$



## Some remarks

- ▶ Let  $\mathbb{V}$  be the unit Euclidean ball and assume  $\ell_t$  is such that  $\|\nabla \ell_t\|_\infty = \Omega(1)$
- ▶ The previous lower bound suggests  $R_T(\mathbf{u}) = \Omega(\sqrt{dT})$  for  $\|\mathbf{u}\| \leq 1$
- ▶  $\mathbb{V}$  is the simplex  $\Delta_d$  and  $\ell_t$  is linear with coefficients  $\|\ell\|_\infty = \Theta(1)$
- ▶ Hedge (exponential weights) achieves  $R_T(\mathbf{p}) = \mathcal{O}(\sqrt{T \ln d})$  for  $\mathbf{p} \in \Delta_d$

The geometry of  $\mathbb{V}$  matters



## Gradient descent: from online to offline

- Projected gradient descent:  $\mathbf{w}_{t+1} = \Pi_{\mathbb{V}}(\mathbf{w}_t - \eta_t \nabla F(\mathbf{w}_t))$




## Gradient descent: from online to offline

- ▶ Projected gradient descent:  $\mathbf{w}_{t+1} = \Pi_{\mathbb{V}}(\mathbf{w}_t - \eta_t \nabla F(\mathbf{w}_t))$
- ▶ Projected GD, optimization form:  $\mathbf{w}_{t+1} = \operatorname{argmin}_{\mathbf{w} \in \mathbb{V}} \frac{1}{2\eta_t} \|\mathbf{w} - \mathbf{w}_t\|_2^2 + \mathbf{w}^\top \nabla F(\mathbf{w}_t)$




## Gradient descent: from online to offline

- ▶ Projected gradient descent:  $\mathbf{w}_{t+1} = \Pi_{\mathbb{V}}(\mathbf{w}_t - \eta_t \nabla F(\mathbf{w}_t))$
- ▶ Projected GD, optimization form:  $\mathbf{w}_{t+1} = \operatorname{argmin}_{\mathbf{w} \in \mathbb{V}} \frac{1}{2\eta_t} \|\mathbf{w} - \mathbf{w}_t\|_2^2 + \mathbf{w}^\top \nabla F(\mathbf{w}_t)$
- ▶ Projecte **online** GD (OGD):  $\mathbf{w}_{t+1} = \operatorname{argmin}_{\mathbf{w} \in \mathbb{V}} \frac{1}{2\eta_t} \|\mathbf{w} - \mathbf{w}_t\|_2^2 + \mathbf{w}^\top \nabla \ell_t(\mathbf{w}_t)$



## Gradient descent: from online to offline

- ▶ Projected gradient descent:  $\mathbf{w}_{t+1} = \Pi_{\mathbb{V}}(\mathbf{w}_t - \eta_t \nabla F(\mathbf{w}_t))$
- ▶ Projected GD, optimization form:  $\mathbf{w}_{t+1} = \operatorname{argmin}_{\mathbf{w} \in \mathbb{V}} \frac{1}{2\eta_t} \|\mathbf{w} - \mathbf{w}_t\|_2^2 + \mathbf{w}^\top \nabla F(\mathbf{w}_t)$
- ▶ Projected **online** GD (OGD):  $\mathbf{w}_{t+1} = \operatorname{argmin}_{\mathbf{w} \in \mathbb{V}} \frac{1}{2\eta_t} \|\mathbf{w} - \mathbf{w}_t\|_2^2 + \mathbf{w}^\top \nabla \ell_t(\mathbf{w}_t)$
- ▶ Online Mirror Descent (OMD):  $\mathbf{w}_{t+1} = \operatorname{argmin}_{\mathbf{w} \in \mathbb{V}} \frac{1}{2\eta_t} B_\psi(\mathbf{w}, \mathbf{w}_t) + \mathbf{w}^\top \nabla \ell_t(\mathbf{w}_t)$



## Gradient descent: from online to offline

- ▶ Projected gradient descent:  $\mathbf{w}_{t+1} = \Pi_{\mathbb{V}}(\mathbf{w}_t - \eta_t \nabla F(\mathbf{w}_t))$
- ▶ Projected GD, optimization form:  $\mathbf{w}_{t+1} = \operatorname{argmin}_{\mathbf{w} \in \mathbb{V}} \frac{1}{2\eta_t} \|\mathbf{w} - \mathbf{w}_t\|_2^2 + \mathbf{w}^\top \nabla F(\mathbf{w}_t)$
- ▶ Projected **online** GD (OGD):  $\mathbf{w}_{t+1} = \operatorname{argmin}_{\mathbf{w} \in \mathbb{V}} \frac{1}{2\eta_t} \|\mathbf{w} - \mathbf{w}_t\|_2^2 + \mathbf{w}^\top \nabla \ell_t(\mathbf{w}_t)$
- ▶ Online Mirror Descent (OMD):  $\mathbf{w}_{t+1} = \operatorname{argmin}_{\mathbf{w} \in \mathbb{V}} \frac{1}{2\eta_t} B_\psi(\mathbf{w}, \mathbf{w}_t) + \mathbf{w}^\top \nabla \ell_t(\mathbf{w}_t)$

The Bregman divergence  $B_\psi$  measures a **generalized squared distance** between  $\mathbf{w}, \mathbf{w}_t \in \mathbb{V}$



## Bregman divergences

- ▶ Parameterized by strictly convex and differentiable **mirror map** functions  $\psi : \mathbb{R}^d \rightarrow \mathbb{R}$



## Bregman divergences

- ▶ Parameterized by strictly convex and differentiable **mirror map** functions  $\psi : \mathbb{R}^d \rightarrow \mathbb{R}$
- ▶  $B_\psi(\mathbf{u}, \mathbf{w}) = \psi(\mathbf{u}) - \psi(\mathbf{w}) - \nabla\psi(\mathbf{w})^\top(\mathbf{u} - \mathbf{w})$



## Bregman divergences

- ▶ Parameterized by strictly convex and differentiable **mirror map** functions  $\psi : \mathbb{R}^d \rightarrow \mathbb{R}$
- ▶  $B_\psi(\mathbf{u}, \mathbf{w}) = \psi(\mathbf{u}) - \psi(\mathbf{w}) - \nabla\psi(\mathbf{w})^\top(\mathbf{u} - \mathbf{w})$
- ▶ Error in first-order Taylor expansion of  $\psi$  around  $\mathbf{w}$




## Bregman divergences

- ▶ Parameterized by strictly convex and differentiable **mirror map** functions  $\psi : \mathbb{R}^d \rightarrow \mathbb{R}$
- ▶  $B_\psi(\mathbf{u}, \mathbf{w}) = \psi(\mathbf{u}) - \psi(\mathbf{w}) - \nabla\psi(\mathbf{w})^\top(\mathbf{u} - \mathbf{w})$
- ▶ Error in first-order Taylor expansion of  $\psi$  around  $\mathbf{w}$
- ▶ If  $\psi = \frac{1}{2} \|\cdot\|_2^2$ , then  $B_\psi(\mathbf{u}, \mathbf{w}) = \frac{1}{2} \|\mathbf{u} - \mathbf{w}\|_2^2$




## Bregman divergences

- ▶ Parameterized by strictly convex and differentiable **mirror map** functions  $\psi : \mathbb{R}^d \rightarrow \mathbb{R}$
- ▶  $B_\psi(\mathbf{u}, \mathbf{w}) = \psi(\mathbf{u}) - \psi(\mathbf{w}) - \nabla\psi(\mathbf{w})^\top(\mathbf{u} - \mathbf{w})$
- ▶ Error in first-order Taylor expansion of  $\psi$  around  $\mathbf{w}$
- ▶ If  $\psi = \frac{1}{2} \|\cdot\|_2^2$ , then  $B_\psi(\mathbf{u}, \mathbf{w}) = \frac{1}{2} \|\mathbf{u} - \mathbf{w}\|_2^2$
- ▶ OMD becomes online gradient descent (OGD) with Euclidean projection



## Bregman divergences

- ▶ Parameterized by strictly convex and differentiable **mirror map** functions  $\psi : \mathbb{R}^d \rightarrow \mathbb{R}$
- ▶  $B_\psi(\mathbf{u}, \mathbf{w}) = \psi(\mathbf{u}) - \psi(\mathbf{w}) - \nabla\psi(\mathbf{w})^\top(\mathbf{u} - \mathbf{w})$
- ▶ Error in first-order Taylor expansion of  $\psi$  around  $\mathbf{w}$
- ▶ If  $\psi = \frac{1}{2} \|\cdot\|_2^2$ , then  $B_\psi(\mathbf{u}, \mathbf{w}) = \frac{1}{2} \|\mathbf{u} - \mathbf{w}\|_2^2$
- ▶ OMD becomes online gradient descent (OGD) with Euclidean projection
- ▶ If  $\mathbb{V} = \Delta_d$  and  $\psi(\mathbf{w}) = \sum_i w_i \ln w_i$ , then  $B_\psi(\mathbf{u}, \mathbf{w}) = \sum_i u_i \ln \frac{u_i}{w_i}$   
(Kullback-Leibler divergence)



## Bregman divergences

- ▶ Parameterized by strictly convex and differentiable **mirror map** functions  $\psi : \mathbb{R}^d \rightarrow \mathbb{R}$
- ▶  $B_\psi(\mathbf{u}, \mathbf{w}) = \psi(\mathbf{u}) - \psi(\mathbf{w}) - \nabla\psi(\mathbf{w})^\top(\mathbf{u} - \mathbf{w})$
- ▶ Error in first-order Taylor expansion of  $\psi$  around  $\mathbf{w}$
- ▶ If  $\psi = \frac{1}{2} \|\cdot\|_2^2$ , then  $B_\psi(\mathbf{u}, \mathbf{w}) = \frac{1}{2} \|\mathbf{u} - \mathbf{w}\|_2^2$
- ▶ OMD becomes online gradient descent (OGD) with Euclidean projection
- ▶ If  $\mathbb{V} = \Delta_d$  and  $\psi(\mathbf{w}) = \sum_i w_i \ln w_i$ , then  $B_\psi(\mathbf{u}, \mathbf{w}) = \sum_i u_i \ln \frac{u_i}{w_i}$   
(Kullback-Leibler divergence)
- ▶ OMD becomes the **Exponentiated Gradient** (EG) algorithm  
(Hedge for general convex losses)

$$w_{t+1,i} \propto \exp \left( -\eta \sum_{s=1}^t \nabla \ell_s(\mathbf{w}_s)_i \right) \quad i = 1, \dots, d$$

## Bregman divergences

- ▶ Parameterized by strictly convex and differentiable **mirror map** functions  $\psi : \mathbb{R}^d \rightarrow \mathbb{R}$
- ▶  $B_\psi(\mathbf{u}, \mathbf{w}) = \psi(\mathbf{u}) - \psi(\mathbf{w}) - \nabla\psi(\mathbf{w})^\top(\mathbf{u} - \mathbf{w})$
- ▶ Error in first-order Taylor expansion of  $\psi$  around  $\mathbf{w}$
- ▶ If  $\psi = \frac{1}{2} \|\cdot\|_2^2$ , then  $B_\psi(\mathbf{u}, \mathbf{w}) = \frac{1}{2} \|\mathbf{u} - \mathbf{w}\|_2^2$
- ▶ OMD becomes online gradient descent (OGD) with Euclidean projection
- ▶ If  $\mathbb{V} = \Delta_d$  and  $\psi(\mathbf{w}) = \sum_i w_i \ln w_i$ , then  $B_\psi(\mathbf{u}, \mathbf{w}) = \sum_i u_i \ln \frac{u_i}{w_i}$   
(Kullback-Leibler divergence)
- ▶ OMD becomes the **Exponentiated Gradient** (EG) algorithm  
(Hedge for general convex losses)

$$p_{t+1}(i) \propto \exp \left( -\eta \sum_{s=1}^t \ell_s(i) \right) \quad i = 1, \dots, d$$



## Strongly convex mirror maps

A differentiable  $\psi : \mathbb{R}^d \rightarrow \mathbb{R}$  is  $\mu$ -strongly convex on  $\mathbb{V}$  with respect to  $\|\cdot\|$  if

$$\psi(\mathbf{u}) \geq \psi(\mathbf{v}) + \nabla\psi(\mathbf{v})^\top (\mathbf{u} - \mathbf{v}) + \frac{\mu}{2} \|\mathbf{u} - \mathbf{v}\|^2 \quad \mathbf{u}, \mathbf{v} \in \mathbb{V}$$



## Strongly convex mirror maps

A differentiable  $\psi : \mathbb{R}^d \rightarrow \mathbb{R}$  is  $\mu$ -strongly convex on  $\mathbb{V}$  with respect to  $\|\cdot\|$  if

$$\psi(\mathbf{u}) \geq \psi(\mathbf{v}) + \nabla\psi(\mathbf{v})^\top (\mathbf{u} - \mathbf{v}) + \frac{\mu}{2} \|\mathbf{u} - \mathbf{v}\|^2 \quad \mathbf{u}, \mathbf{v} \in \mathbb{V}$$

Properties of strongly convex mirror maps (helpful picture on next slide)



## Strongly convex mirror maps

A differentiable  $\psi : \mathbb{R}^d \rightarrow \mathbb{R}$  is  $\mu$ -strongly convex on  $\mathbb{V}$  with respect to  $\|\cdot\|$  if

$$\psi(\mathbf{u}) \geq \psi(\mathbf{v}) + \nabla\psi(\mathbf{v})^\top (\mathbf{u} - \mathbf{v}) + \frac{\mu}{2} \|\mathbf{u} - \mathbf{v}\|^2 \quad \mathbf{u}, \mathbf{v} \in \mathbb{V}$$

Properties of strongly convex mirror maps (helpful picture on next slide)

►  $B_\psi(\mathbf{u}, \mathbf{w}) \geq \frac{\mu}{2} \|\mathbf{u} - \mathbf{w}\|^2$




## Strongly convex mirror maps

A differentiable  $\psi : \mathbb{R}^d \rightarrow \mathbb{R}$  is  $\mu$ -strongly convex on  $\mathbb{V}$  with respect to  $\|\cdot\|$  if

$$\psi(\mathbf{u}) \geq \psi(\mathbf{v}) + \nabla\psi(\mathbf{v})^\top (\mathbf{u} - \mathbf{v}) + \frac{\mu}{2} \|\mathbf{u} - \mathbf{v}\|^2 \quad \mathbf{u}, \mathbf{v} \in \mathbb{V}$$

Properties of strongly convex mirror maps (helpful picture on next slide)

- ▶  $B_\psi(\mathbf{u}, \mathbf{w}) \geq \frac{\mu}{2} \|\mathbf{u} - \mathbf{w}\|^2$
- ▶ OMD becomes  $\mathbf{w}_{t+1} = \nabla\psi_{\mathbb{V}}^* \left( \nabla\psi_{\mathbb{V}}(\mathbf{w}_t) - \eta_t \nabla\ell_t(\mathbf{w}_t) \right)$  ( $\psi_{\mathbb{V}}$  is the restriction of  $\psi$  to  $\mathbb{V}$ )



## Strongly convex mirror maps


A differentiable  $\psi : \mathbb{R}^d \rightarrow \mathbb{R}$  is  $\mu$ -strongly convex on  $\mathbb{V}$  with respect to  $\|\cdot\|$  if

$$\psi(\mathbf{u}) \geq \psi(\mathbf{v}) + \nabla\psi(\mathbf{v})^\top (\mathbf{u} - \mathbf{v}) + \frac{\mu}{2} \|\mathbf{u} - \mathbf{v}\|^2 \quad \mathbf{u}, \mathbf{v} \in \mathbb{V}$$

Properties of strongly convex mirror maps (helpful picture on next slide)

- ▶  $B_\psi(\mathbf{u}, \mathbf{w}) \geq \frac{\mu}{2} \|\mathbf{u} - \mathbf{w}\|^2$
- ▶ OMD becomes  $\mathbf{w}_{t+1} = \nabla\psi_\mathbb{V}^* \left( \nabla\psi_\mathbb{V}(\mathbf{w}_t) - \eta_t \nabla\ell_t(\mathbf{w}_t) \right)$  ( $\psi_\mathbb{V}$  is the restriction of  $\psi$  to  $\mathbb{V}$ )
- ▶ The function  $\psi_\mathbb{V}^* : \mathbb{R}^d \rightarrow \mathbb{R}$  is the Fenchel conjugate of  $\psi_\mathbb{V}$

$$\psi_\mathbb{V}^*(\boldsymbol{\theta}) = \max_{\mathbf{w} \in \mathbb{R}^d} \left( \mathbf{w}^\top \boldsymbol{\theta} - \psi_\mathbb{V}(\mathbf{w}) \right)$$




## Strongly convex mirror maps

A differentiable  $\psi : \mathbb{R}^d \rightarrow \mathbb{R}$  is  $\mu$ -strongly convex on  $\mathbb{V}$  with respect to  $\|\cdot\|$  if

$$\psi(\mathbf{u}) \geq \psi(\mathbf{v}) + \nabla \psi(\mathbf{v})^\top (\mathbf{u} - \mathbf{v}) + \frac{\mu}{2} \|\mathbf{u} - \mathbf{v}\|^2 \quad \mathbf{u}, \mathbf{v} \in \mathbb{V}$$

Properties of strongly convex mirror maps (helpful picture on next slide)

- ▶  $B_\psi(\mathbf{u}, \mathbf{w}) \geq \frac{\mu}{2} \|\mathbf{u} - \mathbf{w}\|^2$
- ▶ OMD becomes  $\mathbf{w}_{t+1} = \nabla \psi_\mathbb{V}^* \left( \nabla \psi_\mathbb{V}(\mathbf{w}_t) - \eta_t \nabla \ell_t(\mathbf{w}_t) \right)$  ( $\psi_\mathbb{V}$  is the restriction of  $\psi$  to  $\mathbb{V}$ )
- ▶ The function  $\psi_\mathbb{V}^* : \mathbb{R}^d \rightarrow \mathbb{R}$  is the Fenchel conjugate of  $\psi_\mathbb{V}$ 
$$\psi_\mathbb{V}^*(\boldsymbol{\theta}) = \max_{\mathbf{w} \in \mathbb{R}^d} \left( \mathbf{w}^\top \boldsymbol{\theta} - \psi_\mathbb{V}(\mathbf{w}) \right)$$
- ▶  $\psi_\mathbb{V}^*$  is differentiable




## Strongly convex mirror maps

A differentiable  $\psi : \mathbb{R}^d \rightarrow \mathbb{R}$  is  $\mu$ -strongly convex on  $\mathbb{V}$  with respect to  $\|\cdot\|$  if


$$\psi(\mathbf{u}) \geq \psi(\mathbf{v}) + \nabla\psi(\mathbf{v})^\top (\mathbf{u} - \mathbf{v}) + \frac{\mu}{2} \|\mathbf{u} - \mathbf{v}\|^2 \quad \mathbf{u}, \mathbf{v} \in \mathbb{V}$$

Properties of strongly convex mirror maps (helpful picture on next slide)

- ▶  $B_\psi(\mathbf{u}, \mathbf{w}) \geq \frac{\mu}{2} \|\mathbf{u} - \mathbf{w}\|^2$
- ▶ OMD becomes  $\mathbf{w}_{t+1} = \nabla\psi_\mathbb{V}^* \left( \nabla\psi_\mathbb{V}(\mathbf{w}_t) - \eta_t \nabla\ell_t(\mathbf{w}_t) \right)$  ( $\psi_\mathbb{V}$  is the restriction of  $\psi$  to  $\mathbb{V}$ )
- ▶ The function  $\psi_\mathbb{V}^* : \mathbb{R}^d \rightarrow \mathbb{R}$  is the Fenchel conjugate of  $\psi_\mathbb{V}$ 
$$\psi_\mathbb{V}^*(\boldsymbol{\theta}) = \max_{\mathbf{w} \in \mathbb{R}^d} \left( \mathbf{w}^\top \boldsymbol{\theta} - \psi_\mathbb{V}(\mathbf{w}) \right)$$
- ▶  $\psi_\mathbb{V}^*$  is differentiable
- ▶  $\nabla\psi_\mathbb{V}^*$  is the functional inverse of  $\nabla\psi_\mathbb{V}$



## The mirror step



$$w_{t+1} = \nabla\psi_{\mathbb{V}}^*\left(\nabla\psi_{\mathbb{V}}(w_t) - \eta_t \underbrace{\nabla\ell_t(w_t)}_{g_t}\right)$$



# Regret analysis

## Two basic inequalities

$$\mathbf{g}_t = \nabla \ell_t(\mathbf{w}_t)$$

- ▶ Linearized regret:  $\ell_t(\mathbf{w}_t) - \ell_t(\mathbf{u}) \leq \mathbf{g}_t^\top (\mathbf{w}_t - \mathbf{u})$



# Regret analysis

## Two basic inequalities

$$\mathbf{g}_t = \nabla \ell_t(\mathbf{w}_t)$$

- ▶ Linearized regret:  $\ell_t(\mathbf{w}_t) - \ell_t(\mathbf{u}) \leq \mathbf{g}_t^\top (\mathbf{w}_t - \mathbf{u})$
- ▶ Bregman's progress:  $\eta \mathbf{g}_t^\top (\mathbf{w}_t - \mathbf{u}) \leq B_\psi(\mathbf{u}, \mathbf{w}_t) - B_\psi(\mathbf{u}, \mathbf{w}_{t+1}) + \frac{\eta^2}{2\mu} \|\mathbf{g}_t\|_\star^2$



# Regret analysis

## Two basic inequalities

$$\mathbf{g}_t = \nabla \ell_t(\mathbf{w}_t)$$

- ▶ Linearized regret:  $\ell_t(\mathbf{w}_t) - \ell_t(\mathbf{u}) \leq \mathbf{g}_t^\top (\mathbf{w}_t - \mathbf{u})$
- ▶ Bregman's progress:  $\eta \mathbf{g}_t^\top (\mathbf{w}_t - \mathbf{u}) \leq B_\psi(\mathbf{u}, \mathbf{w}_t) - B_\psi(\mathbf{u}, \mathbf{w}_{t+1}) + \frac{\eta^2}{2\mu} \|\mathbf{g}_t\|_\star^2$

$$R_T(\mathbf{u}) = \sum_{t=1}^T (\ell_t(\mathbf{w}_t) - \ell_t(\mathbf{u}))$$



# Regret analysis


## Two basic inequalities

$$\mathbf{g}_t = \nabla \ell_t(\mathbf{w}_t)$$

- ▶ Linearized regret:  $\ell_t(\mathbf{w}_t) - \ell_t(\mathbf{u}) \leq \mathbf{g}_t^\top (\mathbf{w}_t - \mathbf{u})$
- ▶ Bregman's progress:  $\eta \mathbf{g}_t^\top (\mathbf{w}_t - \mathbf{u}) \leq B_\psi(\mathbf{u}, \mathbf{w}_t) - B_\psi(\mathbf{u}, \mathbf{w}_{t+1}) + \frac{\eta^2}{2\mu} \|\mathbf{g}_t\|_\star^2$

$$\begin{aligned} R_T(\mathbf{u}) &= \sum_{t=1}^T (\ell_t(\mathbf{w}_t) - \ell_t(\mathbf{u})) \\ &\leq \sum_{t=1}^T \mathbf{g}_t^\top (\mathbf{w}_t - \mathbf{u}) \end{aligned}$$

(linearized regret)



# Regret analysis

## Two basic inequalities

$$\mathbf{g}_t = \nabla \ell_t(\mathbf{w}_t)$$

- ▶ Linearized regret:  $\ell_t(\mathbf{w}_t) - \ell_t(\mathbf{u}) \leq \mathbf{g}_t^\top (\mathbf{w}_t - \mathbf{u})$
- ▶ Bregman's progress:  $\eta \mathbf{g}_t^\top (\mathbf{w}_t - \mathbf{u}) \leq B_\psi(\mathbf{u}, \mathbf{w}_t) - B_\psi(\mathbf{u}, \mathbf{w}_{t+1}) + \frac{\eta^2}{2\mu} \|\mathbf{g}_t\|_\star^2$

$$\begin{aligned} R_T(\mathbf{u}) &= \sum_{t=1}^T (\ell_t(\mathbf{w}_t) - \ell_t(\mathbf{u})) \\ &\leq \sum_{t=1}^T \mathbf{g}_t^\top (\mathbf{w}_t - \mathbf{u}) \\ &\leq \sum_{t=1}^T \left( \frac{B_\psi(\mathbf{u}, \mathbf{w}_t)}{\eta_t} - \frac{B_\psi(\mathbf{u}, \mathbf{w}_{t+1})}{\eta_t} \right) + \frac{1}{2\mu} \sum_{t=1}^T \eta_t \|\mathbf{g}_t\|_\star^2 \end{aligned}$$

(linearized regret)

(Bregman's progress)

## Regret analysis (cont.)

$$\sum_{t=1}^T \left( \frac{B_\psi(\mathbf{u}, \mathbf{w}_t)}{\eta_t} - \frac{B_\psi(\mathbf{u}, \mathbf{w}_{t+1})}{\eta_t} \right) + \frac{1}{2\mu} \sum_{t=1}^T \eta_t \|\mathbf{g}_t\|_\star^2$$




## Regret analysis (cont.)

$$\sum_{t=1}^T \left( \frac{B_{\psi}(\mathbf{u}, \mathbf{w}_t)}{\eta_t} - \frac{B_{\psi}(\mathbf{u}, \mathbf{w}_{t+1})}{\eta_t} \right) + \square$$



## Regret analysis (cont.)

$$\begin{aligned} & \sum_{t=1}^T \left( \frac{B_\psi(\mathbf{u}, \mathbf{w}_t)}{\eta_t} - \frac{B_\psi(\mathbf{u}, \mathbf{w}_{t+1})}{\eta_t} \right) + \square \\ &= \frac{B_\psi(\mathbf{u}, \mathbf{w}_1)}{\eta_1} - \frac{B_\psi(\mathbf{u}, \mathbf{w}_{T+1})}{\eta_{T+1}} + \sum_{t=1}^{T-1} \left( \frac{1}{\eta_{t+1}} - \frac{1}{\eta_t} \right) B_\psi(\mathbf{u}, \mathbf{w}_{t+1}) + \square \quad (\text{fix telescoping}) \end{aligned}$$





## Regret analysis (cont.)

$$\begin{aligned} & \sum_{t=1}^T \left( \frac{B_\psi(\mathbf{u}, \mathbf{w}_t)}{\eta_t} - \frac{B_\psi(\mathbf{u}, \mathbf{w}_{t+1})}{\eta_t} \right) + \square \\ &= \frac{B_\psi(\mathbf{u}, \mathbf{w}_1)}{\eta_1} - \frac{B_\psi(\mathbf{u}, \mathbf{w}_{T+1})}{\eta_{T+1}} + \sum_{t=1}^{T-1} \left( \frac{1}{\eta_{t+1}} - \frac{1}{\eta_t} \right) B_\psi(\mathbf{u}, \mathbf{w}_{t+1}) + \square \quad (\text{fix telescoping}) \\ &\leq \frac{D^2}{\eta_1} + \left( \frac{1}{\eta_T} - \frac{1}{\eta_1} \right) D^2 + \square \end{aligned}$$

(where  $D^2 = \max_{\mathbf{u}, \mathbf{w} \in \mathbb{V}} B_\psi(\mathbf{u}, \mathbf{w})$ )


## Regret analysis (cont.)

$$\begin{aligned} & \sum_{t=1}^T \left( \frac{B_\psi(\mathbf{u}, \mathbf{w}_t)}{\eta_t} - \frac{B_\psi(\mathbf{u}, \mathbf{w}_{t+1})}{\eta_t} \right) + \square \\ &= \frac{B_\psi(\mathbf{u}, \mathbf{w}_1)}{\eta_1} - \frac{B_\psi(\mathbf{u}, \mathbf{w}_{T+1})}{\eta_{T+1}} + \sum_{t=1}^{T-1} \left( \frac{1}{\eta_{t+1}} - \frac{1}{\eta_t} \right) B_\psi(\mathbf{u}, \mathbf{w}_{t+1}) + \square \quad (\text{fix telescoping}) \\ &\leq \frac{D^2}{\eta_1} + \left( \frac{1}{\eta_T} - \frac{1}{\eta_1} \right) D^2 + \square \\ &= \frac{D^2}{\eta_T} + \square \end{aligned}$$

(where  $D^2 = \max_{\mathbf{u}, \mathbf{w} \in \mathbb{V}} B_\psi(\mathbf{u}, \mathbf{w})$ )

## The final bound

► We proved 
$$R_T(\mathbf{u}) \leq \frac{D^2}{\eta_T} + \frac{1}{2\mu} \sum_{t=1}^T \eta_t \|\mathbf{g}_t\|_{\star}^2$$



## The final bound

- ▶ We proved  $R_T(\mathbf{u}) \leq \frac{D^2}{\eta_T} + \frac{1}{2\mu} \sum_{t=1}^T \eta_t \|\mathbf{g}_t\|_\star^2$
- ▶ Setting  $\eta_t = D \sqrt{\frac{\mu}{\sum_{s=1}^t \|\mathbf{g}_s\|_\star^2}}$



## The final bound

- ▶ We proved  $R_T(\mathbf{u}) \leq \frac{D^2}{\eta_T} + \frac{1}{2\mu} \sum_{t=1}^T \eta_t \|\mathbf{g}_t\|_\star^2$
- ▶ Setting  $\eta_t = D \sqrt{\frac{\mu}{\sum_{s=1}^t \|\mathbf{g}_s\|_\star^2}}$
- ▶ We get  $R_T(\mathbf{u}) \leq 2D \sqrt{\frac{1}{\mu} \sum_{t=1}^T \|\mathbf{g}_t\|_\star^2}$



## Matching the mirror map to the geometry of the model space



# Matching the mirror map to the geometry of the model space


OGD



# Matching the mirror map to the geometry of the model space

OGD

- ▶  $\mathbb{V}$  is the closed Euclidean ball of radius  $\frac{D}{2}$





# Matching the mirror map to the geometry of the model space

## OGD

- ▶  $\mathbb{V}$  is the closed Euclidean ball of radius  $\frac{D}{2}$
- ▶  $\psi = \frac{1}{2} \|\cdot\|_2^2$  is 1-strongly convex with respect to  $\|\cdot\|_2$



# Matching the mirror map to the geometry of the model space

## OGD

- ▶  $\mathbb{V}$  is the closed Euclidean ball of radius  $\frac{D}{2}$
- ▶  $\psi = \frac{1}{2} \|\cdot\|_2^2$  is 1-strongly convex with respect to  $\|\cdot\|_2$
- ▶ Bregman divergence:  $B_\psi(\mathbf{u}, \mathbf{w}) = \frac{1}{2} \|\mathbf{u} - \mathbf{w}\|_2^2$



# Matching the mirror map to the geometry of the model space

## OGD

- ▶  $\mathbb{V}$  is the closed Euclidean ball of radius  $\frac{D}{2}$
- ▶  $\psi = \frac{1}{2} \|\cdot\|_2^2$  is 1-strongly convex with respect to  $\|\cdot\|_2$
- ▶ Bregman divergence:  $B_\psi(\mathbf{u}, \mathbf{w}) = \frac{1}{2} \|\mathbf{u} - \mathbf{w}\|_2^2$
- ▶ Assume  $\|\mathbf{g}_t\|_\star^2 = \|\mathbf{g}_t\|_2^2 = \mathcal{O}(d)$



# Matching the mirror map to the geometry of the model space

## OGD

- ▶  $\mathbb{V}$  is the closed Euclidean ball of radius  $\frac{D}{2}$
- ▶  $\psi = \frac{1}{2} \|\cdot\|_2^2$  is 1-strongly convex with respect to  $\|\cdot\|_2$
- ▶ Bregman divergence:  $B_\psi(\mathbf{u}, \mathbf{w}) = \frac{1}{2} \|\mathbf{u} - \mathbf{w}\|_2^2$
- ▶ Assume  $\|\mathbf{g}_t\|_\star^2 = \|\mathbf{g}_t\|_2^2 = \mathcal{O}(d)$
- ▶  $R_T = \mathcal{O}(D\sqrt{dT})$



# Matching the mirror map to the geometry of the model space

EG (with constant stepsize  $\eta = \sqrt{(\ln d)/T}$ )



# Matching the mirror map to the geometry of the model space

EG (with constant stepsize  $\eta = \sqrt{(\ln d)/T}$ )

- $\mathbb{V}$  is the probability simplex



# Matching the mirror map to the geometry of the model space

EG (with constant stepsize  $\eta = \sqrt{(\ln d)/T}$ )

- ▶  $\mathbb{V}$  is the probability simplex
- ▶  $\psi(\mathbf{p}) = \sum_i p_i \ln p_i$  is 1-strongly convex with respect to  $\|\cdot\|_1$



# Matching the mirror map to the geometry of the model space

EG (with constant stepsize  $\eta = \sqrt{(\ln d)/T}$ )

- ▶  $\mathbb{V}$  is the probability simplex
- ▶  $\psi(\mathbf{p}) = \sum_i p_i \ln p_i$  is 1-strongly convex with respect to  $\|\cdot\|_1$
- ▶ Bregman divergence:  $B_\psi(\mathbf{q}, \mathbf{p}) = \sum_{i=1}^d q_i \ln \frac{q_i}{p_i}$





# Matching the mirror map to the geometry of the model space

EG (with constant stepsize  $\eta = \sqrt{(\ln d)/T}$ )


- ▶  $\mathbb{V}$  is the probability simplex
- ▶  $\psi(\mathbf{p}) = \sum_i p_i \ln p_i$  is 1-strongly convex with respect to  $\|\cdot\|_1$
- ▶ Bregman divergence:  $B_\psi(\mathbf{q}, \mathbf{p}) = \sum_{i=1}^d q_i \ln \frac{q_i}{p_i}$
- ▶ Problem:  $D^2 = \max_{\mathbf{p}, \mathbf{q} \in \Delta_d} B_\psi(\mathbf{q}, \mathbf{p}) = \infty$



# Matching the mirror map to the geometry of the model space

EG (with constant stepsize  $\eta = \sqrt{(\ln d)/T}$ )


- ▶  $\mathbb{V}$  is the probability simplex
- ▶  $\psi(\mathbf{p}) = \sum_i p_i \ln p_i$  is 1-strongly convex with respect to  $\|\cdot\|_1$
- ▶ Bregman divergence:  $B_\psi(\mathbf{q}, \mathbf{p}) = \sum_{i=1}^d q_i \ln \frac{q_i}{p_i}$
- ▶ Problem:  $D^2 = \max_{\mathbf{p}, \mathbf{q} \in \Delta_d} B_\psi(\mathbf{q}, \mathbf{p}) = \infty$
- ▶ OMD analysis for **constant learning rate**:  $R_T(\mathbf{q}) \leq \frac{B_\psi(\mathbf{q}, \mathbf{p}_1)}{\eta} + \frac{\eta}{2} \sum_{t=1}^T \|\mathbf{g}_t\|_\star^2$



# Matching the mirror map to the geometry of the model space

EG (with constant stepsize  $\eta = \sqrt{(\ln d)/T}$ )


- ▶  $\mathbb{V}$  is the probability simplex
- ▶  $\psi(\mathbf{p}) = \sum_i p_i \ln p_i$  is 1-strongly convex with respect to  $\|\cdot\|_1$
- ▶ Bregman divergence:  $B_\psi(\mathbf{q}, \mathbf{p}) = \sum_{i=1}^d q_i \ln \frac{q_i}{p_i}$
- ▶ Problem:  $D^2 = \max_{\mathbf{p}, \mathbf{q} \in \Delta_d} B_\psi(\mathbf{q}, \mathbf{p}) = \infty$
- ▶ OMD analysis for **constant learning rate**:  $R_T(\mathbf{q}) \leq \frac{B_\psi(\mathbf{q}, \mathbf{p}_1)}{\eta} + \frac{\eta}{2} \sum_{t=1}^T \|\mathbf{g}_t\|_\star^2$
- ▶ Choosing  $\mathbf{p}_1 = (\frac{1}{d}, \dots, \frac{1}{d})$  we get  $B_\psi(\mathbf{q}, \mathbf{p}_1) \leq \ln d$



# Matching the mirror map to the geometry of the model space

EG (with constant stepsize  $\eta = \sqrt{(\ln d)/T}$ )


- ▶  $\mathbb{V}$  is the probability simplex
- ▶  $\psi(\mathbf{p}) = \sum_i p_i \ln p_i$  is 1-strongly convex with respect to  $\|\cdot\|_1$
- ▶ Bregman divergence:  $B_\psi(\mathbf{q}, \mathbf{p}) = \sum_{i=1}^d q_i \ln \frac{q_i}{p_i}$
- ▶ Problem:  $D^2 = \max_{\mathbf{p}, \mathbf{q} \in \Delta_d} B_\psi(\mathbf{q}, \mathbf{p}) = \infty$
- ▶ OMD analysis for **constant learning rate**:  $R_T(\mathbf{q}) \leq \frac{B_\psi(\mathbf{q}, \mathbf{p}_1)}{\eta} + \frac{\eta}{2} \sum_{t=1}^T \|\mathbf{g}_t\|_\star^2$
- ▶ Choosing  $\mathbf{p}_1 = (\frac{1}{d}, \dots, \frac{1}{d})$  we get  $B_\psi(\mathbf{q}, \mathbf{p}_1) \leq \ln d$
- ▶ Assume  $\|\mathbf{g}_t\|_\star^2 = \|\mathbf{g}_t\|_\infty^2 = \mathcal{O}(1)$



# Matching the mirror map to the geometry of the model space

EG (with constant stepsize  $\eta = \sqrt{(\ln d)/T}$ )

- ▶  $\mathbb{V}$  is the probability simplex
- ▶  $\psi(\mathbf{p}) = \sum_i p_i \ln p_i$  is 1-strongly convex with respect to  $\|\cdot\|_1$
- ▶ Bregman divergence:  $B_\psi(\mathbf{q}, \mathbf{p}) = \sum_{i=1}^d q_i \ln \frac{q_i}{p_i}$
- ▶ Problem:  $D^2 = \max_{\mathbf{p}, \mathbf{q} \in \Delta_d} B_\psi(\mathbf{q}, \mathbf{p}) = \infty$
- ▶ OMD analysis for **constant learning rate**:  $R_T(\mathbf{q}) \leq \frac{B_\psi(\mathbf{q}, \mathbf{p}_1)}{\eta} + \frac{\eta}{2} \sum_{t=1}^T \|\mathbf{g}_t\|_\star^2$
- ▶ Choosing  $\mathbf{p}_1 = (\frac{1}{d}, \dots, \frac{1}{d})$  we get  $B_\psi(\mathbf{q}, \mathbf{p}_1) \leq \ln d$
- ▶ Assume  $\|\mathbf{g}_t\|_\star^2 = \|\mathbf{g}_t\|_\infty^2 = \mathcal{O}(1)$
- ▶  $R_T = \mathcal{O}(\sqrt{T \ln d})$



## Some remarks

- We can interpolate between OGD and EG using a  $p$ -norm as a mirror map:

$$\psi(\mathbf{w}) = \frac{1}{2} \left( \sum_{i=1}^d |w_i|^p \right)^{2/p} \quad \text{for } 1 < p \leq 2$$




## Some remarks

- ▶ We can interpolate between OGD and EG using a  $p$ -norm as a mirror map:

$$\psi(\mathbf{w}) = \frac{1}{2} \left( \sum_{i=1}^d |w_i|^p \right)^{2/p} \quad \text{for } 1 < p \leq 2$$

- ▶ Choosing  $p = \frac{2 \ln d}{2 \ln d - 1}$  gives bound similar to EG without the tuning problem



## AdaGrad (diagonal version)





## AdaGrad (diagonal version)

- Independence w.r.t. rescaling of the coordinates



## AdaGrad (diagonal version)

- ▶ Independence w.r.t. rescaling of the coordinates
- ▶ Useful in neural network training where range of gradient components varies across layers



## AdaGrad (diagonal version)


- ▶ Independence w.r.t. rescaling of the coordinates
- ▶ Useful in neural network training where range of gradient components varies across layers
- ▶  $\mathbb{V}$  is the hyperrectangle  $[a_1, b_1] \times \cdots \times [a_d, b_d] \in \mathbb{R}^d$



## AdaGrad (diagonal version)

- ▶ Independence w.r.t. rescaling of the coordinates
- ▶ Useful in neural network training where range of gradient components varies across layers
- ▶  $\mathbb{V}$  is the **hyperrectangle**  $[a_1, b_1] \times \cdots \times [a_d, b_d] \in \mathbb{R}^d$
- ▶ Run OMD with Euclidean mirror map independently on each coordinate:

$$w_{t+1,i} = \max \{ \min \{ w_{t,i} - \eta_{t,i} g_{t,i} \}, a_i \} \quad i = 1, \dots, d$$




## AdaGrad (diagonal version)

- ▶ Independence w.r.t. rescaling of the coordinates
- ▶ Useful in neural network training where range of gradient components varies across layers
- ▶  $\mathbb{V}$  is the **hyperrectangle**  $[a_1, b_1] \times \cdots \times [a_d, b_d] \in \mathbb{R}^d$
- ▶ Run OMD with Euclidean mirror map independently on each coordinate:

$$w_{t+1,i} = \max \{ \min \{ w_{t,i} - \eta_{t,i} g_{t,i} \}, a_i \} \quad i = 1, \dots, d$$

- ▶ With learning rate

$$\eta_{t,i} = \frac{b_i - a_i}{\sqrt{2 \sum_{s=1}^t g_{s,i}^2}} \quad i = 1, \dots, d$$



# AdaGrad analysis



## AdaGrad analysis

By applying OMD analysis on each coordinate

$$R_T \leq \sum_{i=1}^d (b_i - a_i) \sqrt{2 \sum_{t=1}^T g_{t,i}^2}$$



## AdaGrad analysis

By applying OMD analysis on each coordinate

$$R_T \leq \sum_{i=1}^d (b_i - a_i) \sqrt{2 \sum_{t=1}^T g_{t,i}^2}$$

Comparing with OGD bound





## AdaGrad analysis

By applying OMD analysis on each coordinate

$$R_T \leq \sum_{i=1}^d (b_i - a_i) \sqrt{2 \sum_{t=1}^T g_{t,i}^2}$$

Comparing with OGD bound

- For simplicity, take  $b_i - a_i = 1$  for  $i = 1, \dots, d$



## AdaGrad analysis

By applying OMD analysis on each coordinate

$$R_T \leq \sum_{i=1}^d (b_i - a_i) \sqrt{2 \sum_{t=1}^T g_{t,i}^2}$$

Comparing with OGD bound

- ▶ For simplicity, take  $b_i - a_i = 1$  for  $i = 1, \dots, d$
- ▶ The diameter of  $\mathbb{V}$  is then  $D = \sqrt{d}$




## AdaGrad analysis

By applying OMD analysis on each coordinate

$$R_T \leq \sum_{i=1}^d (b_i - a_i) \sqrt{2 \sum_{t=1}^T g_{t,i}^2}$$

### Comparing with OGD bound

- ▶ For simplicity, take  $b_i - a_i = 1$  for  $i = 1, \dots, d$
- ▶ The diameter of  $\mathbb{V}$  is then  $D = \sqrt{d}$
- ▶ OGD update:  $\mathbf{w}_{t+1} = \mathbf{w}_t - \eta_t \mathbf{g}_t$  followed by projection onto  $\mathbb{V}$




## AdaGrad analysis

By applying OMD analysis on each coordinate

$$R_T \leq \sum_{i=1}^d (b_i - a_i) \sqrt{2 \sum_{t=1}^T g_{t,i}^2}$$

### Comparing with OGD bound

- ▶ For simplicity, take  $b_i - a_i = 1$  for  $i = 1, \dots, d$
- ▶ The diameter of  $\mathbb{V}$  is then  $D = \sqrt{d}$
- ▶ OGD update:  $\mathbf{w}_{t+1} = \mathbf{w}_t - \eta_t \mathbf{g}_t$  followed by projection onto  $\mathbb{V}$
- ▶ OGD learning rate:  $\eta_t = \sqrt{\frac{d}{\sum_{s=1}^t \|\mathbf{g}_s\|^2}}$



## AdaGrad analysis


By applying OMD analysis on each coordinate  $R_T \leq \sum_{i=1}^d (b_i - a_i) \sqrt{2 \sum_{t=1}^T g_{t,i}^2}$

### Comparing with OGD bound

- For simplicity, take  $b_i - a_i = 1$  for  $i = 1, \dots, d$
- The diameter of  $\mathbb{V}$  is then  $D = \sqrt{d}$
- OGD update:  $\mathbf{w}_{t+1} = \mathbf{w}_t - \eta_t \mathbf{g}_t$  followed by projection onto  $\mathbb{V}$

- OGD learning rate:  $\eta_t = \sqrt{\frac{d}{\sum_{s=1}^t \|\mathbf{g}_s\|^2}}$

- By Jensen's inequality  $\underbrace{\sum_{i=1}^d \sqrt{\sum_{t=1}^T g_{t,i}^2}}_{\text{AdaGrad}} \leq \underbrace{\sqrt{d} \sqrt{\sum_{t=1}^T \|\mathbf{g}_t\|_2^2}}_{\text{OGD}}$



## Exploiting curvature of the losses



## Exploiting curvature of the losses

- Convex losses: OGD with  $\eta_t \approx \frac{1}{\sqrt{t}}$  achieves  $R_T = \mathcal{O}(\sqrt{dT})$



## Exploiting curvature of the losses

- ▶ Convex losses: OGD with  $\eta_t \approx \frac{1}{\sqrt{t}}$  achieves  $R_T = \mathcal{O}(\sqrt{dT})$
- ▶ Strongly convex losses: OGD with  $\eta_t \approx \frac{1}{t}$  achieves  $R_T = \mathcal{O}(d \ln T)$  (unconstrained!)






## Exploiting curvature of the losses

- ▶ Convex losses: OGD with  $\eta_t \approx \frac{1}{\sqrt{t}}$  achieves  $R_T = \mathcal{O}(\sqrt{dT})$
- ▶ Strongly convex losses: OGD with  $\eta_t \approx \frac{1}{t}$  achieves  $R_T = \mathcal{O}(d \ln T)$  (unconstrained!)

Strong convexity in the direction of the gradient

$$\ell_t(\mathbf{u}) \geq \ell_t(\mathbf{w}) + \mathbf{g}^\top (\mathbf{u} - \mathbf{w}) + \frac{\lambda}{2} \|\mathbf{u} - \mathbf{w}\|_{\mathbf{g}\mathbf{g}^\top}^2 \quad \mathbf{u}, \mathbf{w} \in \mathbb{V}$$

where  $\mathbf{g} = \nabla \ell_t(\mathbf{w})$  and  $\|\mathbf{w}\|_M^2 = \mathbf{w}^\top M \mathbf{w}$



## Exploiting curvature of the losses

- ▶ Convex losses: OGD with  $\eta_t \approx \frac{1}{\sqrt{t}}$  achieves  $R_T = \mathcal{O}(\sqrt{dT})$
- ▶ Strongly convex losses: OGD with  $\eta_t \approx \frac{1}{t}$  achieves  $R_T = \mathcal{O}(d \ln T)$  (unconstrained!)


Strong convexity in the direction of the gradient

$$\ell_t(\mathbf{u}) \geq \ell_t(\mathbf{w}) + \mathbf{g}^\top (\mathbf{u} - \mathbf{w}) + \frac{\lambda}{2} \|\mathbf{u} - \mathbf{w}\|_{\mathbf{g}\mathbf{g}^\top}^2 \quad \mathbf{u}, \mathbf{w} \in \mathbb{V}$$

where  $\mathbf{g} = \nabla \ell_t(\mathbf{w})$  and  $\|\mathbf{w}\|_M^2 = \mathbf{w}^\top M \mathbf{w}$

Some losses satisfying the condition

- ▶ Square loss  $\ell(\mathbf{w}) = \frac{1}{2}(\mathbf{w}^\top \mathbf{x} - y)^2$  for bounded  $|\mathbf{w}^\top \mathbf{x}|, |y|$



## Exploiting curvature of the losses

- ▶ Convex losses: OGD with  $\eta_t \approx \frac{1}{\sqrt{t}}$  achieves  $R_T = \mathcal{O}(\sqrt{dT})$
- ▶ Strongly convex losses: OGD with  $\eta_t \approx \frac{1}{t}$  achieves  $R_T = \mathcal{O}(d \ln T)$  (unconstrained!)


Strong convexity in the direction of the gradient

$$\ell_t(\mathbf{u}) \geq \ell_t(\mathbf{w}) + \mathbf{g}^\top (\mathbf{u} - \mathbf{w}) + \frac{\lambda}{2} \|\mathbf{u} - \mathbf{w}\|_{\mathbf{g}\mathbf{g}^\top}^2 \quad \mathbf{u}, \mathbf{w} \in \mathbb{V}$$

where  $\mathbf{g} = \nabla \ell_t(\mathbf{w})$  and  $\|\mathbf{w}\|_M^2 = \mathbf{w}^\top M \mathbf{w}$

Some losses satisfying the condition

- ▶ Square loss  $\ell(\mathbf{w}) = \frac{1}{2} (\mathbf{w}^\top \mathbf{x} - y)^2$  for bounded  $|\mathbf{w}^\top \mathbf{x}|, |y|$
- ▶ Logistic loss  $\ell_t(\mathbf{w}) = \ln(1 + \exp(-\mathbf{w}^\top \mathbf{x}_t))$  for bounded  $\|\mathbf{w}\|$



## Follow the Regularized Leader

- ▶ FTRL is not formulated as gradient descent, but as **regularized error minimization**



## Follow the Regularized Leader

- ▶ FTRL is not formulated as gradient descent, but as **regularized error minimization**
- ▶ OMD learning rates  $\eta_t$  are replaced by **time-dependent regularizers** (mirror maps)  $\psi_t$



## Follow the Regularized Leader

- ▶ FTRL is not formulated as gradient descent, but as **regularized error minimization**
- ▶ OMD learning rates  $\eta_t$  are replaced by **time-dependent regularizers** (mirror maps)  $\psi_t$
- ▶  $\mathbf{w}_{t+1} = \operatorname{argmin}_{\mathbf{w} \in \mathbb{V}} \psi_{t+1}(\mathbf{w}) + \sum_{s=1}^t \ell_s(\mathbf{w})$




## Follow the Regularized Leader

- ▶ FTRL is not formulated as gradient descent, but as **regularized error minimization**
- ▶ OMD learning rates  $\eta_t$  are replaced by **time-dependent regularizers** (mirror maps)  $\psi_t$
- ▶ 
$$\mathbf{w}_{t+1} = \operatorname{argmin}_{\mathbf{w} \in \mathbb{V}} \psi_{t+1}(\mathbf{w}) + \sum_{s=1}^t \nabla \ell_s(\mathbf{w}_s)^\top \mathbf{w}$$



# Follow the Regularized Leader


- ▶ FTRL is not formulated as gradient descent, but as **regularized error minimization**
- ▶ OMD learning rates  $\eta_t$  are replaced by **time-dependent regularizers** (mirror maps)  $\psi_t$
- ▶  $\mathbf{w}_{t+1} = \operatorname{argmin}_{\mathbf{w} \in \mathbb{V}} \psi_{t+1}(\mathbf{w}) + \sum_{s=1}^t \nabla \ell_s(\mathbf{w}_s)^\top \mathbf{w}$
- ▶ If  $\psi_{\mathbb{V},t}$  are all strongly convex, then  $\mathbf{w}_{t+1} = \nabla \psi_{\mathbb{V},t+1}^* \left( - \sum_{s=1}^t \nabla \ell_s(\mathbf{w}_s) \right)$





# Follow the Regularized Leader

- ▶ FTRL is not formulated as gradient descent, but as **regularized error minimization**
- ▶ OMD learning rates  $\eta_t$  are replaced by **time-dependent regularizers** (mirror maps)  $\psi_t$
- ▶  $\mathbf{w}_{t+1} = \operatorname{argmin}_{\mathbf{w} \in \mathbb{V}} \psi_{t+1}(\mathbf{w}) + \sum_{s=1}^t \nabla \ell_s(\mathbf{w}_s)^\top \mathbf{w}$
- ▶ If  $\psi_{\mathbb{V},t}$  are all strongly convex, then  $\mathbf{w}_{t+1} = \nabla \psi_{\mathbb{V},t+1}^* \left( - \sum_{s=1}^t \nabla \ell_s(\mathbf{w}_s) \right)$
- ▶ Recall OMD:  $\mathbf{w}_{t+1} = \nabla \psi_{\mathbb{V}}^*(\boldsymbol{\theta}'_{t+1})$  where  $\boldsymbol{\theta}'_{t+1} = \nabla \psi_{\mathbb{V}}(\mathbf{w}_t) - \eta_t \nabla \ell_t(\mathbf{w}_t)$



# Follow the Regularized Leader

- ▶ FTRL is not formulated as gradient descent, but as **regularized error minimization**
- ▶ OMD learning rates  $\eta_t$  are replaced by **time-dependent regularizers** (mirror maps)  $\psi_t$
- ▶  $\mathbf{w}_{t+1} = \operatorname{argmin}_{\mathbf{w} \in \mathbb{V}} \psi_{t+1}(\mathbf{w}) + \sum_{s=1}^t \nabla \ell_s(\mathbf{w}_s)^\top \mathbf{w}$
- ▶ If  $\psi_{\mathbb{V},t}$  are all strongly convex, then  $\mathbf{w}_{t+1} = \nabla \psi_{\mathbb{V},t+1}^* \left( - \sum_{s=1}^t \nabla \ell_s(\mathbf{w}_s) \right)$
- ▶ Recall OMD:  $\mathbf{w}_{t+1} = \nabla \psi_{\mathbb{V}}^*(\boldsymbol{\theta}'_{t+1})$  where  $\boldsymbol{\theta}'_{t+1} = \nabla \psi_{\mathbb{V}}(\mathbf{w}_t) - \eta_t \nabla \ell_t(\mathbf{w}_t)$
- ▶ OMD throws away information by projecting after each update

## Some differences between OMD and FTRL

- ▶ FTRL keeps a state variable  $\theta_t$  in the dual space of gradients



## Some differences between OMD and FTRL

- ▶ FTRL keeps a state variable  $\theta_t$  in the dual space of gradients
- ▶ This is then mapped to the primal space of iterates everytime a prediction is needed




## Some differences between OMD and FTRL

- ▶ FTRL keeps a state variable  $\theta_t$  in the dual space of gradients
- ▶ This is then mapped to the primal space of iterates everytime a prediction is needed
- ▶ OMD keeps its state  $w_t$  in the primal space of iterates




## Some differences between OMD and FTRL

- ▶ FTRL keeps a state variable  $\theta_t$  in the dual space of gradients
- ▶ This is then mapped to the primal space of iterates everytime a prediction is needed
- ▶ OMD keeps its state  $w_t$  in the primal space of iterates
- ▶ This is then mapped to the dual space of gradients everytime an update must be computed




## Some differences between OMD and FTRL

- ▶ FTRL keeps a state variable  $\theta_t$  in the dual space of gradients
- ▶ This is then mapped to the primal space of iterates everytime a prediction is needed
- ▶ OMD keeps its state  $w_t$  in the primal space of iterates
- ▶ This is then mapped to the dual space of gradients everytime an update must be computed
- ▶ OMD and FTRL have similar regret bounds and become identical in certain cases



## Some differences between OMD and FTRL

- ▶ FTRL keeps a state variable  $\theta_t$  in the dual space of gradients
- ▶ This is then mapped to the primal space of iterates everytime a prediction is needed
- ▶ OMD keeps its state  $w_t$  in the primal space of iterates
- ▶ This is then mapped to the dual space of gradients everytime an update must be computed
- ▶ OMD and FTRL have similar regret bounds and become identical in certain cases
- ▶ Time-dependent regularizers are generally more flexible than time-dependent learning rates





## Online Newton Step

Choose the model minimizing a second-order approximation of the true loss:

$$\mathbf{w}_{t+1} = \operatorname{argmin}_{\mathbf{w} \in \mathbb{V}} \sum_{s=1}^t \hat{\ell}_s(\mathbf{w})$$

(Follow-the-Leader approach)

$$\hat{\ell}_t(\mathbf{w}) = \ell_t(\mathbf{w}_t) + \mathbf{g}_t^\top (\mathbf{w} - \mathbf{w}_t) + \frac{\lambda}{2} \|\mathbf{w} - \mathbf{w}_t\|_{\mathbf{g}_t \mathbf{g}_t^\top}^2 \quad \mathbf{g}_t = \nabla \ell_t(\mathbf{w}_t)$$



## Online Newton Step


Choose the model minimizing a second-order approximation of the true loss:

$$\mathbf{w}_{t+1} = \operatorname{argmin}_{\mathbf{w} \in \mathbb{V}} \sum_{s=1}^t \hat{\ell}_s(\mathbf{w})$$

(Follow-the-Leader approach)

$$\hat{\ell}_t(\mathbf{w}) = \ell_t(\mathbf{w}_t) + \mathbf{g}_t^\top (\mathbf{w} - \mathbf{w}_t) + \frac{\lambda}{2} \|\mathbf{w} - \mathbf{w}_t\|_{\mathbf{g}_t \mathbf{g}_t^\top}^2 \quad \mathbf{g}_t = \nabla \ell_t(\mathbf{w}_t)$$

Regret analysis:



## Online Newton Step

Choose the model minimizing a second-order approximation of the true loss:

$$\mathbf{w}_{t+1} = \operatorname{argmin}_{\mathbf{w} \in \mathbb{V}} \sum_{s=1}^t \hat{\ell}_s(\mathbf{w})$$

(Follow-the-Leader approach)

$$\hat{\ell}_t(\mathbf{w}) = \ell_t(\mathbf{w}_t) + \mathbf{g}_t^\top (\mathbf{w} - \mathbf{w}_t) + \frac{\lambda}{2} \|\mathbf{w} - \mathbf{w}_t\|_{\mathbf{g}_t \mathbf{g}_t^\top}^2 \quad \mathbf{g}_t = \nabla \ell_t(\mathbf{w}_t)$$

Regret analysis:

►  $\hat{\ell}_t(\mathbf{w}_t) = \ell_t(\mathbf{w}_t)$



## Online Newton Step

Choose the model minimizing a second-order approximation of the true loss:

$$\mathbf{w}_{t+1} = \operatorname{argmin}_{\mathbf{w} \in \mathbb{V}} \sum_{s=1}^t \hat{\ell}_s(\mathbf{w})$$

(Follow-the-Leader approach)

$$\hat{\ell}_t(\mathbf{w}) = \ell_t(\mathbf{w}_t) + \mathbf{g}_t^\top (\mathbf{w} - \mathbf{w}_t) + \frac{\lambda}{2} \|\mathbf{w} - \mathbf{w}_t\|_{\mathbf{g}_t \mathbf{g}_t^\top}^2 \quad \mathbf{g}_t = \nabla \ell_t(\mathbf{w}_t)$$

Regret analysis:

- ▶  $\hat{\ell}_t(\mathbf{w}_t) = \ell_t(\mathbf{w}_t)$
- ▶  $\hat{\ell}_t(\mathbf{u}) \leq \ell_t(\mathbf{u})$  for all  $\mathbf{u} \in \mathbb{V}$



## Online Newton Step


Choose the model minimizing a second-order approximation of the true loss:

$$\mathbf{w}_{t+1} = \operatorname{argmin}_{\mathbf{w} \in \mathbb{V}} \sum_{s=1}^t \hat{\ell}_s(\mathbf{w}) \quad (\text{Follow-the-Leader approach})$$

$$\hat{\ell}_t(\mathbf{w}) = \ell_t(\mathbf{w}_t) + \mathbf{g}_t^\top (\mathbf{w} - \mathbf{w}_t) + \frac{\lambda}{2} \|\mathbf{w} - \mathbf{w}_t\|_{\mathbf{g}_t \mathbf{g}_t^\top}^2 \quad \mathbf{g}_t = \nabla \ell_t(\mathbf{w}_t)$$

Regret analysis:

- ▶  $\hat{\ell}_t(\mathbf{w}_t) = \ell_t(\mathbf{w}_t)$
- ▶  $\hat{\ell}_t(\mathbf{u}) \leq \ell_t(\mathbf{u})$  for all  $\mathbf{u} \in \mathbb{V}$
- ▶ Regret bound:  $R_T(\mathbf{u}) \leq \sum_{t=1}^T \hat{\ell}_t(\mathbf{w}_t) - \sum_{t=1}^T \hat{\ell}_t(\mathbf{u}) = \mathcal{O}(d \ln T)$



## Online Newton Step

Choose the model minimizing a second-order approximation of the true loss:

$$\mathbf{w}_{t+1} = \operatorname{argmin}_{\mathbf{w} \in \mathbb{V}} \sum_{s=1}^t \hat{\ell}_s(\mathbf{w}) \quad (\text{Follow-the-Leader approach})$$

$$\hat{\ell}_t(\mathbf{w}) = \ell_t(\mathbf{w}_t) + \mathbf{g}_t^\top (\mathbf{w} - \mathbf{w}_t) + \frac{\lambda}{2} \|\mathbf{w} - \mathbf{w}_t\|_{\mathbf{g}_t \mathbf{g}_t^\top}^2 \quad \mathbf{g}_t = \nabla \ell_t(\mathbf{w}_t)$$

Regret analysis:

- ▶  $\hat{\ell}_t(\mathbf{w}_t) = \ell_t(\mathbf{w}_t)$
- ▶  $\hat{\ell}_t(\mathbf{u}) \leq \ell_t(\mathbf{u})$  for all  $\mathbf{u} \in \mathbb{V}$
- ▶ Regret bound:  $R_T(\mathbf{u}) \leq \sum_{t=1}^T \hat{\ell}_t(\mathbf{w}_t) - \sum_{t=1}^T \hat{\ell}_t(\mathbf{u}) = \mathcal{O}(d \ln T)$
- ▶  $\mathcal{O}(d \ln T)$  matches the bound for strongly convex losses



# Unconstrained online convex optimization

- Model space is unconstrained:  $\mathcal{V} = \mathbb{R}^d$



# Unconstrained online convex optimization

- ▶ Model space is unconstrained:  $\mathcal{V} = \mathbb{R}^d$
- ▶ Run OGD with fixed learning rate  $\eta = \alpha/\sqrt{T}$  for  $\alpha > 0$





# Unconstrained online convex optimization

- ▶ Model space is unconstrained:  $\mathbb{V} = \mathbb{R}^d$
- ▶ Run OGD with fixed learning rate  $\eta = \alpha/\sqrt{T}$  for  $\alpha > 0$
- ▶  $R_T(\mathbf{u}) \leq \frac{1}{2} \left( \frac{\|\mathbf{u}\|_2^2}{\alpha} + \alpha \right) \sqrt{T} \quad \forall \mathbf{u} \in \mathbb{R}^d$




# Unconstrained online convex optimization

- ▶ Model space is unconstrained:  $\mathbb{V} = \mathbb{R}^d$
- ▶ Run OGD with fixed learning rate  $\eta = \alpha/\sqrt{T}$  for  $\alpha > 0$
- ▶  $R_T(\mathbf{u}) \leq \frac{1}{2} \left( \frac{\|\mathbf{u}\|_2^2}{\alpha} + \alpha \right) \sqrt{T} \quad \forall \mathbf{u} \in \mathbb{R}^d$
- ▶  $R_T(\mathbf{u}) \leq \|\mathbf{u}\|_2 \sqrt{T}$  for  $\alpha = \|\mathbf{u}\|_2$




# Unconstrained online convex optimization

- ▶ Model space is unconstrained:  $\mathbb{V} = \mathbb{R}^d$
- ▶ Run OGD with fixed learning rate  $\eta = \alpha/\sqrt{T}$  for  $\alpha > 0$
- ▶  $R_T(\mathbf{u}) \leq \frac{1}{2} \left( \frac{\|\mathbf{u}\|_2^2}{\alpha} + \alpha \right) \sqrt{T} \quad \forall \mathbf{u} \in \mathbb{R}^d$
- ▶  $R_T(\mathbf{u}) \leq \|\mathbf{u}\|_2 \sqrt{T}$  for  $\alpha = \|\mathbf{u}\|_2$
- ▶ Equivalent to running OGD with projection in the Euclidean ball of radius  $\|\mathbf{u}\|_2$



# Unconstrained online convex optimization

- ▶ Model space is unconstrained:  $\mathbb{V} = \mathbb{R}^d$
- ▶ Run OGD with fixed learning rate  $\eta = \alpha/\sqrt{T}$  for  $\alpha > 0$
- ▶  $R_T(\mathbf{u}) \leq \frac{1}{2} \left( \frac{\|\mathbf{u}\|_2^2}{\alpha} + \alpha \right) \sqrt{T} \quad \forall \mathbf{u} \in \mathbb{R}^d$
- ▶  $R_T(\mathbf{u}) \leq \|\mathbf{u}\|_2 \sqrt{T}$  for  $\alpha = \|\mathbf{u}\|_2$
- ▶ Equivalent to running OGD with projection in the Euclidean ball of radius  $\|\mathbf{u}\|_2$
- ▶ This bound cannot be simultaneously achieved for all  $\mathbf{u}$ !



## Main idea

- ▶ Control  $R_T(\mathbf{u})$  by learning length  $w = \|\mathbf{u}\|$  and direction  $\mathbf{v} = \mathbf{u} / \|\mathbf{u}\|$  separately




## Main idea

- ▶ Control  $R_T(\mathbf{u})$  by learning length  $w = \|\mathbf{u}\|$  and direction  $\mathbf{v} = \mathbf{u} / \|\mathbf{u}\|$  separately
- ▶ The **direction** can be learned via OMD run in the unit ball




## Main idea

- ▶ Control  $R_T(\mathbf{u})$  by learning length  $w = \|\mathbf{u}\|$  and direction  $\mathbf{v} = \mathbf{u} / \|\mathbf{u}\|$  separately
- ▶ The **direction** can be learned via OMD run in the unit ball
- ▶ The **length** is learned using a parameterless 1-dimensional online learning algorithm



## Main idea

- ▶ Control  $R_T(\mathbf{u})$  by learning length  $w = \|\mathbf{u}\|$  and direction  $\mathbf{v} = \mathbf{u} / \|\mathbf{u}\|$  separately
- ▶ The **direction** can be learned via OMD run in the unit ball
- ▶ The **length** is learned using a parameterless 1-dimensional online learning algorithm
- ▶ One such algorithm has regret  $R_T(w) = \mathcal{O}(|w|\sqrt{T \ln(T)})$  for all  $w \in R$





# Analysis



# Analysis

$$R_T(\mathbf{u}) = \sum_{t=1}^T \ell_t(w_t \mathbf{v}_t) - \sum_{t=1}^T \ell_t(\mathbf{u})$$



# Analysis


$$\begin{aligned} R_T(\mathbf{u}) &= \sum_{t=1}^T \ell_t(w_t \mathbf{v}_t) - \sum_{t=1}^T \ell_t(\mathbf{u}) \\ &\leq \sum_{t=1}^T \mathbf{g}_t^\top (w_t \mathbf{v}_t - \mathbf{u}) \end{aligned}$$

(linearized regret)



# Analysis

$$\begin{aligned} R_T(\mathbf{u}) &= \sum_{t=1}^T \ell_t(w_t \mathbf{v}_t) - \sum_{t=1}^T \ell_t(\mathbf{u}) \\ &\leq \sum_{t=1}^T \mathbf{g}_t^\top (w_t \mathbf{v}_t - \mathbf{u}) && \text{(linearized regret)} \\ &= \sum_{t=1}^T \left( w_t \mathbf{g}_t^\top \mathbf{v}_t - \|\mathbf{u}\| \mathbf{g}_t^\top \mathbf{v}_t \right) + \|\mathbf{u}\| \sum_{t=1}^T \left( \mathbf{g}_t^\top \mathbf{v}_t - \mathbf{g}_t^\top \frac{\mathbf{u}}{\|\mathbf{u}\|} \right) \end{aligned}$$



# Analysis

$$\begin{aligned} R_T(\mathbf{u}) &= \sum_{t=1}^T \ell_t(w_t \mathbf{v}_t) - \sum_{t=1}^T \ell_t(\mathbf{u}) \\ &\leq \sum_{t=1}^T \mathbf{g}_t^\top (w_t \mathbf{v}_t - \mathbf{u}) \quad \text{(linearized regret)} \\ &= \sum_{t=1}^T \underbrace{(w_t \ell'_t(w_t) - \|\mathbf{u}\| \ell'_t(w_t))}_{\text{parameterless}} + \|\mathbf{u}\| \sum_{t=1}^T \underbrace{\left( \mathbf{g}_t^\top \mathbf{v}_t - \mathbf{g}_t^\top \frac{\mathbf{u}}{\|\mathbf{u}\|} \right)}_{\text{OMD}} \end{aligned}$$

# Analysis

$$\begin{aligned} R_T(\mathbf{u}) &= \sum_{t=1}^T \ell_t(w_t \mathbf{v}_t) - \sum_{t=1}^T \ell_t(\mathbf{u}) \\ &\leq \sum_{t=1}^T \mathbf{g}_t^\top (w_t \mathbf{v}_t - \mathbf{u}) && \text{(linearized regret)} \\ &= \sum_{t=1}^T \underbrace{(w_t \ell'_t(w_t) - \|\mathbf{u}\| \ell'_t(w_t))}_{\text{parameterless}} + \|\mathbf{u}\| \sum_{t=1}^T \underbrace{\left( \mathbf{g}_t^\top \mathbf{v}_t - \mathbf{g}_t^\top \frac{\mathbf{u}}{\|\mathbf{u}\|} \right)}_{\text{OMD}} \end{aligned}$$

$$R_T(\mathbf{u}) = \mathcal{O} \left( \left( \sqrt{\ln(\|\mathbf{u}\|^2 T + 1)} + 1 \right) \|\mathbf{u}\| \sqrt{T} + 1 \right) \quad \forall \mathbf{u} \in \mathbb{R}^d$$

# Analysis

$$\begin{aligned} R_T(\mathbf{u}) &= \sum_{t=1}^T \ell_t(w_t \mathbf{v}_t) - \sum_{t=1}^T \ell_t(\mathbf{u}) \\ &\leq \sum_{t=1}^T \mathbf{g}_t^\top (w_t \mathbf{v}_t - \mathbf{u}) && \text{(linearized regret)} \\ &= \sum_{t=1}^T \underbrace{(w_t \ell'_t(w_t) - \|\mathbf{u}\| \ell'_t(w_t))}_{\text{parameterless}} + \|\mathbf{u}\| \sum_{t=1}^T \underbrace{\left( \mathbf{g}_t^\top \mathbf{v}_t - \mathbf{g}_t^\top \frac{\mathbf{u}}{\|\mathbf{u}\|} \right)}_{\text{OMD}} \end{aligned}$$

$$R_T(\mathbf{u}) = \mathcal{O}\left(\underbrace{\left(\sqrt{\ln(\|\mathbf{u}\|^2 T + 1)} + 1\right)}_{\text{unavoidable}} \|\mathbf{u}\| \sqrt{T} + 1\right) \quad \forall \mathbf{u} \in \mathbb{R}^d$$

# Learning and investing

1-dimensional parameterless online algorithms extracted from investment strategies





# Learning and investing

1-dimensional parameterless online algorithms extracted from investment strategies

The betting game



# Learning and investing

1-dimensional parameterless online algorithms extracted from investment strategies

## The betting game

- ▶ The bettor starts out with an initial wealth of  $C_0 = 1$



# Learning and investing

1-dimensional parameterless online algorithms extracted from investment strategies

## The betting game

- ▶ The bettor starts out with an initial wealth of  $C_0 = 1$
- ▶ In each round  $t = 1, 2, \dots$  of the game



# Learning and investing

1-dimensional parameterless online algorithms extracted from investment strategies

## The betting game

- ▶ The bettor starts out with an initial wealth of  $C_0 = 1$
- ▶ In each round  $t = 1, 2, \dots$  of the game
  1. The bettor bets  $\alpha_t \in [-1, 1]$



# Learning and investing

1-dimensional parameterless online algorithms extracted from investment strategies

## The betting game

- ▶ The bettor starts out with an initial wealth of  $C_0 = 1$
- ▶ In each round  $t = 1, 2, \dots$  of the game
  1. The bettor bets  $\alpha_t \in [-1, 1]$
  2. The market reveals  $x_t \in [-1, 1]$



# Learning and investing

1-dimensional parameterless online algorithms extracted from investment strategies

## The betting game

- ▶ The bettor starts out with an initial wealth of  $C_0 = 1$
- ▶ In each round  $t = 1, 2, \dots$  of the game
  1. The bettor bets  $\alpha_t \in [-1, 1]$
  2. The market reveals  $x_t \in [-1, 1]$
  3. The bettor's wealth is  $C_{t+1} = (1 + \alpha_t x_t) C_t$



# Learning and investing

1-dimensional parameterless online algorithms extracted from investment strategies

## The betting game

- ▶ The bettor starts out with an initial wealth of  $C_0 = 1$
- ▶ In each round  $t = 1, 2, \dots$  of the game
  1. The bettor bets  $\alpha_t \in [-1, 1]$
  2. The market reveals  $x_t \in [-1, 1]$
  3. The bettor's wealth is  $C_{t+1} = (1 + \alpha_t x_t) C_t$

## Reduction to learning



# Learning and investing

1-dimensional parameterless online algorithms extracted from investment strategies

## The betting game

- ▶ The bettor starts out with an initial wealth of  $C_0 = 1$
- ▶ In each round  $t = 1, 2, \dots$  of the game
  1. The bettor bets  $\alpha_t \in [-1, 1]$
  2. The market reveals  $x_t \in [-1, 1]$
  3. The bettor's wealth is  $C_{t+1} = (1 + \alpha_t x_t) C_t$

## Reduction to learning

- ▶  $w_t = \alpha_t C_t$





# Learning and investing

1-dimensional parameterless online algorithms extracted from investment strategies

## The betting game

- ▶ The bettor starts out with an initial wealth of  $C_0 = 1$
- ▶ In each round  $t = 1, 2, \dots$  of the game
  1. The bettor bets  $\alpha_t \in [-1, 1]$
  2. The market reveals  $x_t \in [-1, 1]$
  3. The bettor's wealth is  $C_{t+1} = (1 + \alpha_t x_t) C_t$

## Reduction to learning

- ▶  $w_t = \alpha_t C_t$
- ▶  $x_t = -\ell'_t(w_t)$



# Learning and investing

1-dimensional parameterless online algorithms extracted from investment strategies

## The betting game

- ▶ The bettor starts out with an initial wealth of  $C_0 = 1$
- ▶ In each round  $t = 1, 2, \dots$  of the game
  1. The bettor bets  $\alpha_t \in [-1, 1]$
  2. The market reveals  $x_t \in [-1, 1]$
  3. The bettor's wealth is  $C_{t+1} = (1 + \alpha_t x_t) C_t$

## Reduction to learning

- ▶  $w_t = \alpha_t C_t$
- ▶  $x_t = -\ell'_t(w_t)$
- ▶  $C_T = \prod_{t=1}^T (1 + \alpha_t x_t) = 1 + \sum_{t=1}^T w_t x_t = 1 - \sum_{t=1}^T w_t \ell'_t(w_t)$



# Learning and investing

1-dimensional parameterless online algorithms extracted from investment strategies

## The betting game

- ▶ The bettor starts out with an initial wealth of  $C_0 = 1$
- ▶ In each round  $t = 1, 2, \dots$  of the game
  1. The bettor bets  $\alpha_t \in [-1, 1]$
  2. The market reveals  $x_t \in [-1, 1]$
  3. The bettor's wealth is  $C_{t+1} = (1 + \alpha_t x_t) C_t$

## Reduction to learning

- ▶  $w_t = \alpha_t C_t$
- ▶  $x_t = -\ell'_t(w_t)$
- ▶  $C_T = \prod_{t=1}^T (1 + \alpha_t x_t) = 1 + \sum_{t=1}^T w_t x_t = 1 - \sum_{t=1}^T w_t \ell'_t(w_t)$
- ▶ A lower bound on  $C_T$  implies an upper bound on  $R_T(w)$  for all  $w \in \mathbb{R}$



## Other notions of regret



## Other notions of regret

- If the loss sequence  $\ell_1, \ell_2, \dots$  is such that no  $\mathbf{u} \in \mathbb{V}$  achieves a small cumulative loss  $\ell_1(\mathbf{u}) + \ell_2(\mathbf{u}) + \dots$ , then regret bounds are meaningless



## Other notions of regret

- ▶ If the loss sequence  $\ell_1, \ell_2, \dots$  is such that no  $\mathbf{u} \in \mathbb{V}$  achieves a small cumulative loss  $\ell_1(\mathbf{u}) + \ell_2(\mathbf{u}) + \dots$ , then regret bounds are meaningless
- ▶ Lack of a single good minimizer in  $\mathbb{V}$  caused by a highly nonstationary data sequence



## Other notions of regret


- ▶ If the loss sequence  $\ell_1, \ell_2, \dots$  is such that no  $\mathbf{u} \in \mathbb{V}$  achieves a small cumulative loss  $\ell_1(\mathbf{u}) + \ell_2(\mathbf{u}) + \dots$ , then regret bounds are meaningless
- ▶ Lack of a single good minimizer in  $\mathbb{V}$  caused by a highly nonstationary data sequence
- ▶ In this case, the regret should be replaced by more robust measures



## Other notions of regret

- ▶ If the loss sequence  $\ell_1, \ell_2, \dots$  is such that no  $\mathbf{u} \in \mathbb{V}$  achieves a small cumulative loss  $\ell_1(\mathbf{u}) + \ell_2(\mathbf{u}) + \dots$ , then regret bounds are meaningless
- ▶ Lack of a single good minimizer in  $\mathbb{V}$  caused by a highly nonstationary data sequence
- ▶ In this case, the regret should be replaced by more robust measures

▶ **Dynamic regret**  $R_T^{\text{dyn}}(\mathbf{u}_1, \dots, \mathbf{u}_T) = \sum_{t=1}^T \ell_t(\mathbf{w}_t) - \sum_{t=1}^T \ell_t(\mathbf{u}_t)$  where  $\mathbf{u}_1, \dots, \mathbf{u}_T \in \mathbb{V}$






## Other notions of regret

- ▶ If the loss sequence  $\ell_1, \ell_2, \dots$  is such that no  $\mathbf{u} \in \mathbb{V}$  achieves a small cumulative loss  $\ell_1(\mathbf{u}) + \ell_2(\mathbf{u}) + \dots$ , then regret bounds are meaningless
- ▶ Lack of a single good minimizer in  $\mathbb{V}$  caused by a highly nonstationary data sequence
- ▶ In this case, the regret should be replaced by more robust measures


▶ **Dynamic regret**  $R_T^{\text{dyn}}(\mathbf{u}_1, \dots, \mathbf{u}_T) = \sum_{t=1}^T \ell_t(\mathbf{w}_t) - \sum_{t=1}^T \ell_t(\mathbf{u}_t)$  where  $\mathbf{u}_1, \dots, \mathbf{u}_T \in \mathbb{V}$

▶ Complexity parameter:  $\Pi_T = \sum_{t=1}^{T-1} \|\mathbf{u}_{t+1} - \mathbf{u}_t\|$




## Other notions of regret

- ▶ If the loss sequence  $\ell_1, \ell_2, \dots$  is such that no  $\mathbf{u} \in \mathbb{V}$  achieves a small cumulative loss  $\ell_1(\mathbf{u}) + \ell_2(\mathbf{u}) + \dots$ , then regret bounds are meaningless
- ▶ Lack of a single good minimizer in  $\mathbb{V}$  caused by a highly nonstationary data sequence
- ▶ In this case, the regret should be replaced by more robust measures
- ▶ **Dynamic regret**  $R_T^{\text{dyn}}(\mathbf{u}_1, \dots, \mathbf{u}_T) = \sum_{t=1}^T \ell_t(\mathbf{w}_t) - \sum_{t=1}^T \ell_t(\mathbf{u}_t)$  where  $\mathbf{u}_1, \dots, \mathbf{u}_T \in \mathbb{V}$
- ▶ Complexity parameter:  $\Pi_T = \sum_{t=1}^{T-1} \|\mathbf{u}_{t+1} - \mathbf{u}_t\|$
- ▶ Lower bound:  $\Omega(L\sqrt{(D + \Pi_T)DT})$



## Other notions of regret

- ▶ If the loss sequence  $\ell_1, \ell_2, \dots$  is such that no  $\mathbf{u} \in \mathbb{V}$  achieves a small cumulative loss  $\ell_1(\mathbf{u}) + \ell_2(\mathbf{u}) + \dots$ , then regret bounds are meaningless
- ▶ Lack of a single good minimizer in  $\mathbb{V}$  caused by a highly nonstationary data sequence
- ▶ In this case, the regret should be replaced by more robust measures
- ▶ **Dynamic regret**  $R_T^{\text{dyn}}(\mathbf{u}_1, \dots, \mathbf{u}_T) = \sum_{t=1}^T \ell_t(\mathbf{w}_t) - \sum_{t=1}^T \ell_t(\mathbf{u}_t)$  where  $\mathbf{u}_1, \dots, \mathbf{u}_T \in \mathbb{V}$
- ▶ Complexity parameter:  $\Pi_T = \sum_{t=1}^{T-1} \|\mathbf{u}_{t+1} - \mathbf{u}_t\|$
- ▶ Lower bound:  $\Omega(L\sqrt{(D + \Pi_T)DT})$
- ▶ When  $\Pi_T = 0$  this reduces to the standard lower bound  $\Omega(LD\sqrt{T})$



## Other notions of regret

- ▶ If the loss sequence  $\ell_1, \ell_2, \dots$  is such that no  $\mathbf{u} \in \mathbb{V}$  achieves a small cumulative loss  $\ell_1(\mathbf{u}) + \ell_2(\mathbf{u}) + \dots$ , then regret bounds are meaningless
- ▶ Lack of a single good minimizer in  $\mathbb{V}$  caused by a highly nonstationary data sequence
- ▶ In this case, the regret should be replaced by more robust measures
- ▶ **Dynamic regret**  $R_T^{\text{dyn}}(\mathbf{u}_1, \dots, \mathbf{u}_T) = \sum_{t=1}^T \ell_t(\mathbf{w}_t) - \sum_{t=1}^T \ell_t(\mathbf{u}_t)$  where  $\mathbf{u}_1, \dots, \mathbf{u}_T \in \mathbb{V}$
- ▶ Complexity parameter:  $\Pi_T = \sum_{t=1}^{T-1} \|\mathbf{u}_{t+1} - \mathbf{u}_t\|$
- ▶ Lower bound:  $\Omega(L\sqrt{(D + \Pi_T)DT})$
- ▶ When  $\Pi_T = 0$  this reduces to the standard lower bound  $\Omega(LD\sqrt{T})$
- ▶ Matching upper bound obtained by using Hedge to aggregate  $\mathcal{O}(\ln T)$  instances of OGD each tuned to a different  $\Pi_T$

# Adaptive regret



## Adaptive regret

- Evaluate the performance of the online algorithm against that of the best fixed comparator in any interval of time



## Adaptive regret

- Evaluate the performance of the online algorithm against that of the best fixed comparator in any interval of time

- $R_{\tau,T}^{\text{ada}} = \max_{s=1,\dots,T-\tau+1} \left( \sum_{t=s}^{s+\tau-1} \ell_t(\mathbf{w}_t) - \min_{\mathbf{u} \in \mathbb{V}} \sum_{t=s}^{s+\tau-1} \ell_t(\mathbf{u}) \right)$  where  $\tau \in \{1, \dots, T\}$



## Adaptive regret

- Evaluate the performance of the online algorithm against that of the best fixed comparator in any interval of time

- $R_{\tau,T}^{\text{ada}} = \max_{s=1,\dots,T-\tau+1} \left( \sum_{t=s}^{s+\tau-1} \ell_t(\mathbf{w}_t) - \min_{\mathbf{u} \in \mathbb{V}} \sum_{t=s}^{s+\tau-1} \ell_t(\mathbf{u}) \right)$  where  $\tau \in \{1, \dots, T\}$


- Best known upper bound:  $R_{\tau,T}^{\text{ada}}(\mathbf{u}) = \mathcal{O}(DL\sqrt{\tau} + \sqrt{(\ln T)\tau})$





## Adaptive regret

- ▶ Evaluate the performance of the online algorithm against that of the best fixed comparator in any interval of time
- ▶  $R_{\tau,T}^{\text{ada}} = \max_{s=1,\dots,T-\tau+1} \left( \sum_{t=s}^{s+\tau-1} \ell_t(\mathbf{w}_t) - \min_{\mathbf{u} \in \mathbb{V}} \sum_{t=s}^{s+\tau-1} \ell_t(\mathbf{u}) \right)$  where  $\tau \in \{1, \dots, T\}$
- ▶ Best known upper bound:  $R_{\tau,T}^{\text{ada}}(\mathbf{u}) = \mathcal{O}(DL\sqrt{\tau} + \sqrt{(\ln T)\tau})$
- ▶ Obtained by combining several instances of a standard online algorithm each run in a specific interval of time



## Adaptive regret

- ▶ Evaluate the performance of the online algorithm against that of the best fixed comparator in any interval of time
- ▶  $R_{\tau,T}^{\text{ada}} = \max_{s=1,\dots,T-\tau+1} \left( \sum_{t=s}^{s+\tau-1} \ell_t(\mathbf{w}_t) - \min_{\mathbf{u} \in \mathbb{V}} \sum_{t=s}^{s+\tau-1} \ell_t(\mathbf{u}) \right)$  where  $\tau \in \{1, \dots, T\}$
- ▶ Best known upper bound:  $R_{\tau,T}^{\text{ada}}(\mathbf{u}) = \mathcal{O}(DL\sqrt{\tau} + \sqrt{(\ln T)\tau})$
- ▶ Obtained by combining several instances of a standard online algorithm each run in a specific interval of time
- ▶ The set of intervals is carefully designed so that the overall number of instances to be run is  $\mathcal{O}(\ln T)$

## From sequential to statistical learning

- Assume  $(\mathbf{x}_1, y_1), (\mathbf{x}_2, y_2), \dots$  is the realization of i.i.d. draws from  $\mathcal{D}$



## From sequential to statistical learning

- ▶ Assume  $(\mathbf{x}_1, y_1), (\mathbf{x}_2, y_2), \dots$  is the realization of i.i.d. draws from  $\mathcal{D}$
- ▶ Let  $\bar{\mathbf{w}} = \frac{1}{T} \sum_{t=1}^T \mathbf{w}_t$




## From sequential to statistical learning

► Assume  $(\mathbf{x}_1, y_1), (\mathbf{x}_2, y_2), \dots$  is the realization of i.i.d. draws from  $\mathcal{D}$

► Let  $\bar{\mathbf{w}} = \frac{1}{T} \sum_{t=1}^T \mathbf{w}_t$

► Linear prediction with convex loss  $\ell(\mathbf{w}^\top \mathbf{x}, y_t)$

$$\ell_{\mathcal{D}}(\bar{\mathbf{w}}) = \mathbb{E}[\ell(\bar{\mathbf{w}}^\top \mathbf{X}, Y)] \leq \mathbb{E}\left[\frac{1}{T} \sum_{t=1}^T \ell_t(\mathbf{w}_t^\top \mathbf{X}, Y)\right] = \frac{1}{T} \sum_{t=1}^T \ell_{\mathcal{D}}(\mathbf{w}_t)$$



## From sequential to statistical learning


- ▶ Assume  $(\mathbf{x}_1, y_1), (\mathbf{x}_2, y_2), \dots$  is the realization of i.i.d. draws from  $\mathcal{D}$

- ▶ Let  $\bar{\mathbf{w}} = \frac{1}{T} \sum_{t=1}^T \mathbf{w}_t$

- ▶ Linear prediction with convex loss  $\ell(\mathbf{w}^\top \mathbf{x}, y_t)$

$$\ell_{\mathcal{D}}(\bar{\mathbf{w}}) = \mathbb{E}[\ell(\bar{\mathbf{w}}^\top \mathbf{X}, Y)] \leq \mathbb{E}\left[\frac{1}{T} \sum_{t=1}^T \ell_t(\mathbf{w}_t^\top \mathbf{X}, Y)\right] = \frac{1}{T} \sum_{t=1}^T \ell_{\mathcal{D}}(\mathbf{w}_t)$$

- ▶ Note also that  $\mathbb{E}[\ell_{\mathcal{D}}(\mathbf{w}_t) - \ell(\mathbf{w}_t^\top \mathbf{X}_t, Y_t) \mid (\mathbf{X}_1, Y_1), \dots, (\mathbf{X}_{t-1}, Y_{t-1})] = 0$



## From sequential to statistical learning

- ▶ Assume  $(\mathbf{x}_1, y_1), (\mathbf{x}_2, y_2), \dots$  is the realization of i.i.d. draws from  $\mathcal{D}$

- ▶ Let  $\bar{\mathbf{w}} = \frac{1}{T} \sum_{t=1}^T \mathbf{w}_t$

- ▶ Linear prediction with convex loss  $\ell(\mathbf{w}^\top \mathbf{x}, y_t)$

$$\ell_{\mathcal{D}}(\bar{\mathbf{w}}) = \mathbb{E}[\ell(\bar{\mathbf{w}}^\top \mathbf{X}, Y)] \leq \mathbb{E}\left[\frac{1}{T} \sum_{t=1}^T \ell_t(\mathbf{w}_t^\top \mathbf{X}, Y)\right] = \frac{1}{T} \sum_{t=1}^T \ell_{\mathcal{D}}(\mathbf{w}_t)$$

- ▶ Note also that  $\mathbb{E}[\ell_{\mathcal{D}}(\mathbf{w}_t) - \ell(\mathbf{w}_t^\top \mathbf{X}_t, Y_t) \mid (\mathbf{X}_1, Y_1), \dots, (\mathbf{X}_{t-1}, Y_{t-1})] = 0$

- ▶ Then, by the bounded martingale concentration law,

$$\frac{1}{T} \sum_{t=1}^T \ell_{\mathcal{D}}(\mathbf{w}_t) \leq \frac{1}{T} \sum_{t=1}^T \ell(\mathbf{w}_t^\top \mathbf{X}_t, Y_t) + \mathcal{O}\left(\frac{1}{\sqrt{T}}\right) \quad \text{w.h.p.}$$

## Contextual bandits (reloaded)

In practice, actions in bandit problems have **features** (ads, items on sale, etc.)





## Contextual bandits (reloaded)

In practice, actions in bandit problems have **features** (ads, items on sale, etc.)

For  $t = 1, 2, \dots$

1. Observe finite set  $C_t \subset \mathbb{R}^d$  of contexts (feature vectors)



## Contextual bandits (reloaded)

In practice, actions in bandit problems have **features** (ads, items on sale, etc.)

For  $t = 1, 2, \dots$

1. Observe finite set  $C_t \subset \mathbb{R}^d$  of contexts (feature vectors)
2. Choose  $\mathbf{x}_t \in C_t$



## Contextual bandits (reloaded)

In practice, actions in bandit problems have **features** (ads, items on sale, etc.)

For  $t = 1, 2, \dots$

1. Observe finite set  $C_t \subset \mathbb{R}^d$  of contexts (feature vectors)
2. Choose  $\mathbf{x}_t \in C_t$
3. Get reward  $Y_t$



## Contextual bandits (reloaded)

In practice, actions in bandit problems have **features** (ads, items on sale, etc.)

For  $t = 1, 2, \dots$

1. Observe finite set  $C_t \subset \mathbb{R}^d$  of contexts (feature vectors)
2. Choose  $\mathbf{x}_t \in C_t$
3. Get reward  $Y_t$

We assume a linear model:  $Y_t = \mathbf{w}^\top \mathbf{x}_t + Z_t$



## Contextual bandits (reloaded)

In practice, actions in bandit problems have **features** (ads, items on sale, etc.)

For  $t = 1, 2, \dots$

1. Observe finite set  $C_t \subset \mathbb{R}^d$  of contexts (feature vectors)
2. Choose  $\mathbf{x}_t \in C_t$
3. Get reward  $Y_t$

We assume a linear model:  $Y_t = \mathbf{w}^\top \mathbf{x}_t + Z_t$

- $\mathbf{w} \in \mathbb{R}^d$  is fixed and unknown, but  $\|\mathbf{w}\| \leq D$  with  $D$  known



## Contextual bandits (reloaded)

In practice, actions in bandit problems have **features** (ads, items on sale, etc.)

For  $t = 1, 2, \dots$

1. Observe finite set  $C_t \subset \mathbb{R}^d$  of contexts (feature vectors)
2. Choose  $\mathbf{x}_t \in C_t$
3. Get reward  $Y_t$

We assume a linear model:  $Y_t = \mathbf{w}^\top \mathbf{x}_t + Z_t$

- ▶  $\mathbf{w} \in \mathbb{R}^d$  is fixed and unknown, but  $\|\mathbf{w}\| \leq D$  with  $D$  known
- ▶  $Z_t$  are zero-mean with a known bound  $R$  on the variance



## Contextual bandits (reloaded)

In practice, actions in bandit problems have **features** (ads, items on sale, etc.)

For  $t = 1, 2, \dots$

1. Observe finite set  $C_t \subset \mathbb{R}^d$  of contexts (feature vectors)
2. Choose  $\mathbf{x}_t \in C_t$
3. Get reward  $Y_t$

We assume a linear model:  $Y_t = \mathbf{w}^\top \mathbf{x}_t + Z_t$

- ▶  $\mathbf{w} \in \mathbb{R}^d$  is fixed and unknown, but  $\|\mathbf{w}\| \leq D$  with  $D$  known
- ▶  $Z_t$  are zero-mean with a known bound  $R$  on the variance

Regret: 
$$R_T^{\text{cont}} = \sum_{t=1}^T \max_{\mathbf{x} \in C_t} \mathbf{w}^\top \mathbf{x} - \sum_{t=1}^T \mathbf{w}^\top \mathbf{x}_t$$



# The confidence ellipsoid

Fix a sequence of contexts  $C_1, \dots, C_t$  and choices  $\mathbf{x}_s \in C_s$ ,  $s = 1, \dots, t$

RLS estimate

$$\hat{\mathbf{w}}_t = V_t^{-1} \sum_{s=1}^t Y_s \mathbf{x}_s \quad V_t = \lambda I_d + \underbrace{[\mathbf{x}_1, \dots, \mathbf{x}_t]}_{d \times t} [\mathbf{x}_1, \dots, \mathbf{x}_t]^\top$$

With high probability,  $\mathbf{w} \in \mathcal{E}_t \equiv \left\{ \mathbf{u} \in \mathbb{R}^d : \|\mathbf{u} - \hat{\mathbf{w}}\|_{V_t} \leq \beta_t \right\}$


$\beta_t$  of order  $D + R \sqrt{1 + d \ln \left( 1 + \frac{t}{d} \right)}$

Think of  $\mathcal{E}_t$  as a  $d$ -dimensional confidence interval





# The LinUCB/OFUL algorithm



Optimism in the face of uncertainty

$$\mathbf{x}_{t+1} = \underset{\mathbf{x} \in C_{t+1}}{\operatorname{argmax}} \max_{\mathbf{u} \in \mathcal{E}_t} \mathbf{u}^\top \mathbf{x} = \underset{\mathbf{x} \in C_t}{\operatorname{argmax}} \left( \hat{\mathbf{w}}_t^\top \mathbf{x} + \beta_t \|\mathbf{x}\|_{V_t^{-1}} \right)$$

# Regret

►  $R_T^{\text{cont}} = \mathcal{O}\left((d \ln T) \sqrt{T}\right)$



# Regret

- ▶  $R_T^{\text{cont}} = \mathcal{O}\left((d \ln T) \sqrt{T}\right)$
- ▶ Update time:  $\Theta(d^2)$




# Regret

- ▶  $R_T^{\text{cont}} = \mathcal{O}\left((d \ln T) \sqrt{T}\right)$
- ▶ Update time:  $\Theta(d^2)$
- ▶ This can be reduced to  $\Theta(md)$  by **sketching**  $[x_1, \dots, x_t]$  with a  $d \times m$  matrix




# Regret

- ▶  $R_T^{\text{cont}} = \mathcal{O}\left((d \ln T) \sqrt{T}\right)$
- ▶ Update time:  $\Theta(d^2)$
- ▶ This can be reduced to  $\Theta(md)$  by **sketching**  $[x_1, \dots, x_t]$  with a  $d \times m$  matrix
- ▶ The **spectral error**  $\varepsilon_m$  is bounded by the sum of the last  $d - m + 1$  eigenvalues of  $V_T$




# Regret

- ▶  $R_T^{\text{cont}} = \mathcal{O}\left((d \ln T) \sqrt{T}\right)$
- ▶ Update time:  $\Theta(d^2)$
- ▶ This can be reduced to  $\Theta(md)$  by **sketching**  $[x_1, \dots, x_t]$  with a  $d \times m$  matrix
- ▶ The **spectral error**  $\varepsilon_m$  is bounded by the sum of the last  $d - m + 1$  eigenvalues of  $V_T$
- ▶ The regret becomes  $R_T^{\text{cont}} = \tilde{\mathcal{O}}\left((1 + \varepsilon_m)^{3/2}(m + d \ln(1 + \varepsilon_m)) \sqrt{T}\right)$




# Regret

- ▶  $R_T^{\text{cont}} = \mathcal{O}\left((d \ln T) \sqrt{T}\right)$
- ▶ Update time:  $\Theta(d^2)$
- ▶ This can be reduced to  $\Theta(md)$  by **sketching**  $[\mathbf{x}_1, \dots, \mathbf{x}_t]$  with a  $d \times m$  matrix
- ▶ The **spectral error**  $\varepsilon_m$  is bounded by the sum of the last  $d - m + 1$  eigenvalues of  $V_T$
- ▶ The regret becomes  $R_T^{\text{cont}} = \tilde{\mathcal{O}}\left((1 + \varepsilon_m)^{3/2}(m + d \ln(1 + \varepsilon_m)) \sqrt{T}\right)$
- ▶ If the span of  $\mathbf{x}_1, \dots, \mathbf{x}_T$  has dimension  $m$ , then  $\varepsilon_m = 0$



# Regret

- ▶  $R_T^{\text{cont}} = \mathcal{O}\left((d \ln T) \sqrt{T}\right)$
- ▶ Update time:  $\Theta(d^2)$
- ▶ This can be reduced to  $\Theta(md)$  by **sketching**  $[\mathbf{x}_1, \dots, \mathbf{x}_t]$  with a  $d \times m$  matrix
- ▶ The **spectral error**  $\varepsilon_m$  is bounded by the sum of the last  $d - m + 1$  eigenvalues of  $V_T$
- ▶ The regret becomes  $R_T^{\text{cont}} = \tilde{\mathcal{O}}\left((1 + \varepsilon_m)^{3/2}(m + d \ln(1 + \varepsilon_m)) \sqrt{T}\right)$
- ▶ If the span of  $\mathbf{x}_1, \dots, \mathbf{x}_T$  has dimension  $m$ , then  $\varepsilon_m = 0$
- ▶ In this case,  $R_T^{\text{cont}} = \mathcal{O}\left((m \ln T) \sqrt{T}\right)$  for both algorithms





## Some references

List of wonderful references goes here

