


Predicting depression based on big five personality scales

Load dataset and select training data:

```
library(foreign)
cardata <- read.spss("data Carillo et al.sav", to.data.frame = TRUE)
set.seed(42)
train <- sample(1:112, 80)
```

Regression tree for predicting depression

```
library(tree)
car.tree <- tree(bdi ~ ., data = cardata[train,])
plot(car.tree)
text(car.tree, pretty = 0)
```



```
car.pred <- predict(car.tree, cardata[-train,])
mean((cardata$bdi[-train] - car.pred)^2)
```


```
## [1] 87.56231
```

```
cor(cardata$bdi[-train], car.pred)
```

```
## [1] 0.4378805
```

Classification tree for predicting depression

```
cardata2 <- cardata
cardata2$bdi <- factor(ifelse(cardata2$bdi > 16, 1, 0))
car.tree2 <- tree(bdi ~ ., data = cardata2[train,])
plot(car.tree2)
text(car.tree2, pretty = 0)
```





```
car.pred2 <- predict(car.tree2, cardata2[-train,])
prop.table(table(cardata2$bdi[-train], round(car.pred2[,2])))
```

```
##
##           0           1
##  0 0.75000 0.03125
##  1 0.09375 0.12500
```

Pruning


We are going to prune the regression tree. First, we determine the optimal tree size by 10-fold cross validation:

```
set.seed(3)
cv.cartree <- cv.tree(car.tree)
par(mfrow = c(1,2))
plot(cv.cartree$size, cv.cartree$dev, type = "b")
plot(cv.cartree$k, cv.cartree$dev, type = "b")
```



Optimal tree size is 6. Now we prune the tree:

```
cartree.pruned <- prune.tree(car.tree, best = 6)
plot(cartree.pruned)
text(cartree.pruned, pretty = 0)
```



```
car.pruned.pred <- predict(cartree.pruned, cardata[-train,])
mean((cardata$bdi[-train] - car.pruned.pred)^2)
```

```
## [1] 88.03171
```


```
cor(cardata$bdi[-train], car.pruned.pred)
```

```
## [1] 0.4253286
```

We got a smaller tree, but in this case, pruning did not improve predictive accuracy on test data.

We also determine the optimal size for the classification tree:

```
cv.cartree2 <- cv.tree(car.tree2, FUN = prune.misclass)
plot(cv.cartree2$size, cv.cartree2$dev, type = "b")
```




The classification tree does not need pruning.

Tree instability

We grow a regression tree on a different sample of the same size, from the same data:

```
set.seed(46383)
train2 <- sample(1:112, 80)
car.tree3 <- tree(bdi ~ ., data = cardata[train2,])
plot(car.tree3)
text(car.tree3, pretty = 0)
```



```
car.pred3 <- predict(car.tree3, cardata[-train2,])
mean((cardata$bdi[-train2] - car.pred3)^2)
```


```
## [1] 69.03054
```

```
cor(cardata$bdi[-train2], car.pred3)
```


```
## [1] 0.5435759
```

In this sample, we find a different tree structure: only the first split in the tree is the same. Also, predictive accuracy in test data is different from that in the earlier sample, also indicating instability. Let's prune the tree to see if that yields a more stable tree:

```
set.seed(343545)
cv.cartree3 <- cv.tree(car.tree3)
plot(cv.cartree3$size, cv.cartree3$dev, type = "b")
```



```
cartree3.pruned <- prune.tree(car.tree3, best = 2)
plot(cartree3.pruned)
text(cartree3.pruned, pretty = 0)
```



```
car.pruned.pred3 <- predict(cartree3.pruned, cardata[-train2,])
mean((cardata$bdi[-train2] - car.pruned.pred3)^2)
```

```
## [1] 70.37825
```

```
cor(cardata$bdi[-train2], car.pruned.pred3)
```

```
## [1] 0.4812077
```


Pruning does not completely eliminate the instability problem, although we do get a smaller tree and more similar predictive accuracy as with the full tree.

Tree ensembles


Bagging

```
library(randomForest)
set.seed(45823)
bag.ens <- randomForest(bdi ~ ., mtry = ncol(cardata) - 1,
                        data = cardata[-train,])
plot(bag.ens, main = "OOB error estimates")
```


OOB error estimates




```
varImpPlot(bag.ens)
```




```
partialPlot(bag.ens, pred.data = cardata[train,], x.var = "n3")
```

Partial Dependence on "n3"



```
partialPlot(bag.ens, pred.data = cardata[train,], x.var = "open6")
```

Partial Dependence on "open6"




```
yhat.bag <- predict(bag.ens, newdata = cardata[-train,])  
mean((yhat.bag - cardata$bdi[-train])^2)
```

```
## [1] 12.87469
```


Random forest

```
set.seed(45823)  
rf.ens <- randomForest(bdi ~ ., mtry = sqrt(ncol(cardata) - 1),  
                        data = cardata[-train,])  
plot(rf.ens, main = "OOB error estimates")
```

OOB error estimates




```
varImpPlot(rf.ens)
```




```
partialPlot(rf.ens, pred.data = cardata[train,], x.var = "n3")
```

Partial Dependence on "n3"



```
partialPlot(rf.ens, pred.data = cardata[train,], x.var = "open6")
```

Partial Dependence on "open6"




```
yhat.rf <- predict(rf.ens, newdata = cardata[-train,])  
mean((yhat.rf - cardata$bdi[-train])^2)
```

```
## [1] 12.50123
```


Boosting

```
library(gbm)  
set.seed(47895321)  
boost.ens <- gbm(bdi ~ ., data = cardata[train,], distribution = "gaussian",  
                 n.trees = 500, shrinkage = .01, interaction.depth = 4)  
summary(boost.ens)
```





##	var	rel.inf
## n3	n3	16.0541454
## n4	n4	12.6355765
## open4	open4	7.6476624
## n6	n6	7.2831647
## open3	open3	6.9522351
## n2	n2	6.2984536
## e2	e2	5.7735845
## n1	n1	5.0132382
## e6	e6	4.3465808
## ntot	ntot	4.1149076
## opentot	opentot	2.6137953
## etot	etot	2.5589454
## edad	edad	2.4897261
## n5	n5	2.3205583
## open5	open5	2.0987289
## open1	open1	1.8464558
## altot	altot	1.7182326
## e5	e5	1.5898183
## contot	contot	1.4239046
## open6	open6	1.3221283
## open2	open2	1.0278423
## sexo	sexo	0.8591599
## e4	e4	0.7841236
## e3	e3	0.7386340
## e1	e1	0.4883978


```
plot(boost.ens, i = "n3")
```



```
plot(boost.ens, i = "open4")
```



```
plot(boost.ens$oobag.improve)
```



```
yhat.boost <- predict(boost.ens, newdata = cardata[-train,], n.trees = 500)
mean((yhat.boost - cardata$bdi[-train])^2)
```

```
## [1] 65.23001
```

Note that I selected the parameter values above, after performing a cross validation using the `train()` function from package `caret`:

```
library(caret)
set.seed(4349493)
tuneGrid <- expand.grid(n.trees = c(500, 1000),
                      shrinkage = c(.001, .01, .1),
                      interaction.depth = 3:4,
                      n.minobsinnode = 10)
bdi_ind <- which(names(cardata) == "bdi")
cvpars <- train(x = cardata[train, -bdi_ind], y = cardata[train, bdi_ind],
               method = 'gbm', distribution = "gaussian", tuneGrid = tuneGrid)
cvpars
```