

CS4221/CS5421

Tutorial 5: Dependencies, entity-relationship modelling and the Chase

Mark Meng Huasong

School of Computing
National University of Singapore


Week 7, 2022 Spring



All the materials within presentation slides are protected by copyrights.
It is forbidden by NUS to upload these materials to the Internet.

Question 1

Consider the entity-relationship diagram of Figure 1.



(a) Without other knowledge than that captured by the entity-relationship diagram, what are the **functional** and **multi-valued** dependencies?

Question 1 (Cont.)

Solution: The entity-relationship diagram tells us the following functional dependencies.

$$\Sigma = \{\{A\} \rightarrow \{B\}, \{D\} \rightarrow \{E, F\}, \{A, D\} \rightarrow \{C\}\}$$

Multi-valued dependencies depend on the translation of this design into tables. The entity-relationship diagram and its translation will only result in “not interesting” multi-valued dependencies, those are trivial or correspond to the table or the functional dependencies.

If we canonically translate this design into three tables, we have $\{A\} \twoheadrightarrow \{B\}$ and $\{C\} \twoheadrightarrow \{A, D\}$ and many more (none of them being useful for normalisation), for instance.

Question 1 (Cont.)

Note that additional knowledge of the application could tell us additional functional and multivalued dependencies not captured by the design.

For instance, we could know that $\{E\} \rightarrow \{F\}$ (which would suggest that the entity-relationship design is probably missing entities and relationships that have been merged too early), which we could use to produce a design in the Boyce-Codd normal by splitting the table $R_3(D, E, F)$ into two tables $R_{3.1} = (\underline{D}, E)$ and $R_{3.2} = (E, \underline{F})$.

For instance, we could know that $\{E\} \twoheadrightarrow \{F\}$, which we could use to produce a design in the fifth normal by splitting the table $R_3(D, E, F)$ into two tables $R_{3.1} = (\underline{D}, E)$ and $R_{3.2} = (\underline{E}, F)$.

Question 2

Consider the relational schema $R = \{A, B, C, D, E\}$ with the following set of functional and multi-valued dependencies.

$$\Sigma = \{\{C\} \rightarrow \{A\}, \{D\} \rightarrow \{D, B\}, \{B\} \rightarrow \{E\}, \{E\} \twoheadrightarrow \{A, D\}, \{A, B, D\} \rightarrow \{A, B, C, D\}, \{B\} \rightarrow \{D\}\}$$

(a) Prove that $\{E\} \rightarrow \{D\}$ using the Armstrong and multi-valued dependencies axioms.

Solution:

1. We know that $\{E\} \twoheadrightarrow \{A, D\}$.
 2. We know that $\{B\} \rightarrow \{D\}$.
 3. We see that $\{D\} \subset \{A, D\}$.
 4. We see that $\{B\} \cap \{A, D\} = \emptyset$
 5. Therefore $\{E\} \rightarrow \{D\}$ by Coalescence of (1), (2), (3) and (4).
- Q.E.D.

Question 3

Consider the relation $R(A, B, C, D, E, G)$ with the following set, F , of functional and multi-valued dependencies.

$$F = \{\{A, B\} \rightarrow \{C\}, \{A, B\} \twoheadrightarrow \{E\}, \{C, D\} \twoheadrightarrow \{A, B\}\}$$

Prove that the decomposition of R into $R_1(A, B, C, D, G)$ and $R_2(C, D, E)$ is lossless using the Chase algorithm (as shown in the lecture).

Solution:

1. Initial table.

A	B	C	D	E	G
a1	b1	c1	d1	e1	g1
a2	b2	c2	d2	e2	g2

2. We want to chase $\{C, D\} \twoheadrightarrow \{E\}$, make C and D values the same.

A	B	C	D	E	G
a1	b1	c1	d1	e1	g1
a2	b2	c1	d1	e2	g2

Question 3 (Cont.)

3. Apply $\{C, D\} \rightarrow \{A, B\}$ by copying two tuples that have the same C and D values but swapping their A and B values.

A	B	C	D	E	G
a1	b1	c1	d1	e1	g1
a2	b2	c1	d1	e2	g2
a2	b2	c1	d1	e1	g1
a1	b1	c1	d1	e2	g2

4. Apply $\{A, B\} \rightarrow \{E\}$ by copying two tuples that have the same A and B values but swapping their A and E values.

A	B	C	D	E	G
a1	b1	c1	d1	e1	g1
a2	b2	c1	d1	e2	g2
a2	b2	c1	d1	e1	g1
a1	b1	c1	d1	e2	g2
a1	b1	c1	d1	e2	g1
a2	b2	c1	d1	e1	g2
a2	b2	c1	d1	e2	g1
a1	b1	c1	d1	e1	g2

Question 3 (Cont.)

- Applying $\{A, B\} \rightarrow \{C\}$ do not change the table.
- Sort the table and proved that $\{C, D\} \rightarrow \{E\}$

A	B	C	D	E	G
a1	b1	c1	d1	e1	g1
a1	b1	c1	d1	e2	g1
a2	b2	c1	d1	e1	g2
a2	b2	c1	d1	e2	g2
a1	b2	c1	d1	e1	g1
a1	b2	c1	d1	e2	g1
a2	b1	c1	d1	e2	g2
a2	b1	c1	d1	e1	g2

Q.E.D

Question 4

Consider the relation $R(A, B, C, D, E, F, G)$ with the following set, Σ , of functional dependencies.

$$\Sigma = \{\{A, B\} \rightarrow \{C\}, \{C\} \rightarrow \{D, E\}, \{E\} \rightarrow \{D\}, \{F\} \rightarrow \{G\}\}$$

Prove that the decomposition of R into $R_1(A, B, C, D, E)$ and $R_2(A, B, F, G)$ is lossless using the Chase algorithm (as shown in the lecture).

Solution:

1. Initial table.

A	B	C	D	E	F	G
a1	b1	c1	d1	e1	f1	g1
a2	b2	c2	d2	e2	f2	g2

2. We want to chase $\{A, B\} \twoheadrightarrow \{C, D, E\}$, make A and B values the same.

A	B	C	D	E	F	G
a1	b1	c1	d1	e1	f1	g1
a1	b1	c2	d2	e2	f2	g2

Question 4 (Cont.)

3. Apply $\{A, B\} \rightarrow \{C\}$, make C with the same A and B values the same.

A	B	C	D	E	F	G
a1	b1	c1	d1	e1	f1	g1
a1	b1	c1	d2	e2	f2	g2

4. Apply $\{C\} \rightarrow \{D, E\}$, make D and E with the same C values the same.

A	B	C	D	E	F	G
a1	b1	c1	d1	e1	f1	g1
a1	b1	c1	d1	e1	f2	g2

5. Applying $\{E\} \rightarrow \{D\}$ does not change the table.

6. Applying $\{F\} \rightarrow \{G\}$ does not change the table.

7. Proved that $\{A, B\} \twoheadrightarrow \{C, D, E\}$.

Q.E.D

Question 5

Consider the relation $R(A, B, C, D, E)$ with the following set, F , of functional dependencies.

$$\Sigma = \{\{A\} \rightarrow \{B, C\}, \{B\} \rightarrow \{A\}, \{C\} \rightarrow \{D\}\}$$

Check whether the decomposition of R into $R_1(A, E)$, $R_2(C, D)$ and $R_3(A, B, C)$ is lossless using the Chase algorithm with the distinguished attributes.

Solution:

1. Initial table.

	A	B	C	D	E
R_1	a				a
R_2			a	a	
R_3	a	a	a		

2. Apply $\{A\} \rightarrow \{B, C\}$.

	A	B	C	D	E
R_1	a	a	a		a
R_2			a	a	
R_3	a	a	a		

Question 5 (Cont.)

3. Applying $\{B\} \rightarrow \{A\}$ does not change the table.
4. Apply $\{C\} \rightarrow \{D\}$.

	A	B	C	D	E
R_1	a	a	a	a	a
R_2			a	a	
R_3	a	a	a		

5. R_1 has distinguished variables in all of the columns, therefore the decomposition is lossless.

Q.E.D

For any further question, please feel free to email me:

huasong.meng@u.nus.edu

Cases in the extra practice are contributed by our students.

Copyright 2022 Mark H. Meng. All rights reserved.