

The bicaption package^{*}

Axel Sommerfeldt

`axel.sommerfeldt@f-m.fm`

2010/09/19

Abstract

This package supports the typesetting of bilingual captions.

Contents

1	The user interface	2
1.1	Loading the package	2
1.2	Setting options	2
1.3	Additional options	3
1.4	The <code>\bicaption</code> commands	4
1.5	An example code	4

^{*}This package has version number v0.9a, last revised 2011/07/13.

1 The user interface

1.1 Loading the package

`\usepackage` This package will be loaded by

```
\usepackage[\langle options \rangle]{bication} .
```

The options for the bication package are the same ones as for the caption package and specify settings which are used for the second language *additionally*. In fact

```
\usepackage[\langle options \rangle]{bication}
```

is identical to

```
\usepackage{bication}  
\captionsetup[bi-second]{\langle options \rangle} .
```

1.2 Setting options

`\captionsetup`

```
\captionsetup[bi]{\langle options \rangle}
```

do setup options which will be used for bilanguage captions *additionally* to the ones which are setup for the specific floating environment.

```
\captionsetup[bi-first]{\langle options \rangle}
```

do setup options which will be used for the *first* heading of the bilanguage captions *additionally* to the ones which are setup for the specific floating environment and the ones which are setup by `\captionsetup[bi]{...}`.

```
\captionsetup[bi-second]{\langle options \rangle}
```

do setup options which will be used for the *second* heading of the bilanguage captions *additionally* to the ones which are setup for the specific floating environment and the ones which are setup by `\captionsetup[bi]{...}`.

Options specified with `\usepackage[...]{bication}` and `\captionsetup[bi...]{...}` will override the ones specified by `\captionsetup{...}` and `\captionsetup[figure]{...}` (same for 'table'). So finally we have the following order how settings for bilingual captions are applied:

1. Global settings (`\usepackage[...]{caption}` and `\captionsetup{...}`)
2. Environmental settings (`\captionsetup[figure -or- table]{...}`)
3. Local settings (`\captionsetup{...}` inside figure or table environment)
4. Custom 'bi' settings (`\captionsetup[bi]{...}`)

5. Custom ‘bi-first’ resp. ‘bi-second’ settings (`\usepackage[...]{bication}` and `\captionsetup[bi-first]{...}` resp. `\captionsetup[bi-second]{...}`)

An example:

```
\usepackage[labelsep=quad,indentation=10pt]{caption}
\usepackage[labelfont=bf]{bication}
\captionsetup[table]{labelfont=it,position=top}
```

causes the second heading of the bilingual caption inside `table` environments to be typeset with the settings

```
labelsep=quad,indentation=10pt,position=top,labelfont=bf.
```

1.3 Additional options

These options are available additional to the ones offered by the `caption` package:

<code>language=</code>	<code>language=</code>	Sets the language of the caption, e.g. <code>\usepackage[english]{bication}</code> will typeset the second caption of bilingual captions in English. (The language will be set with <code>\selectlanguage</code> internally, so the <code>babel</code> package must be loaded for using this option.)
<code>bi-lang=</code>	<code>bi-lang=</code>	Causes a selection of the headings of bilingual captions. <code>\captionsetup{bi-lang=both}</code> will cause that both caption headings are being typeset. (This is the default.) <code>\captionsetup{bi-lang=first}</code> will cause that only the <i>first</i> heading is being typeset, and <code>\captionsetup{bi-lang=second}</code> will cause that only the <i>second</i> heading is being typeset.
<code>bi-singlelinecheck=</code>	<code>bi-slc=</code>	Switches the common single-line-check on or off, i.e. when switched on only a single check will be done for both captions, and the result will affect both captions afterwards. So if only one caption is longer than a single line, both captions will be treated as if they are longer than a single line, even if the second one isn't. (The default is on.)
<code>bi-swap=</code>	<code>bi-swap=</code>	<code>\captionsetup{bi-swap}</code> will swap the primary and secondary language, making the first language the second one and vice versa. (The default is <code>false</code> .)

1.4 The `\bicaption` commands

`\bicaption` Bilingual captions will be typeset by

```
\bicaption[<list entry>]{<heading #1>}{<heading #2>}  
\bicaption*{<heading #1>}{<heading #2>}
```

The `\label` should be placed either after this command, or inside the first heading.

If the `subcaption` package is loaded, these commands are available additionally:

`\bisubcaption` Bilingual sub-captions will be typeset by

```
\bisubcaption[<list entry>]{<heading #1>}{<heading #2>}  
\bisubcaption*{<heading #1>}{<heading #2>}
```

The `\label` should be placed either after this command, or inside the first heading.

`\bisubcaptionbox` Bilingual sub-caption boxes will be typeset by

```
\subcaptionbox[<list entry>]{<heading #1>}{<heading #2>}  
[<width>][<inner-pos>]{<contents>}  
\subcaptionbox*{<heading #1>}{<heading #2>}  
[<width>][<inner-pos>]{<contents>}
```

The `\label` should be placed inside the first heading.

1.5 An example code

```
\documentclass[english,ngerman]{article}  
\usepackage{selinput}  
\SelectInputMappings{adieresis={ä},germandbls={ß}}  
  
\usepackage{babel}  
\usepackage[lang=english,font=it]{bicaption}  
\usepackage[format=hang,list=on]{subcaption}  
  
\begin{document}  
  
\begin{figure}[!htb]  
  \centering  
  \bisubcaptionbox  
    {Teilabbildung A\label{fig:test:A}}  
    {Subfigure A}[0.4\textwidth]{IMAGE}%  
  \quad  
  \bisubcaptionbox  
    {Teilabbildung langer Titel B\label{fig:test:B}}  
    {Subfigure long title B}[0.4\textwidth]{IMAGE}%  
  \bicaption{Deutscher Titel}{English Title}  
  \label{fig:test}  
\end{figure}
```

```

\captionsetup{bi-lang=both}

\begin{figure}[!htb]
  \centering
  \bisubcaptionbox[A]
    {Und eine gaaaanz lange Caption: Teilabbildung A}
    {Subfigure A}[0.4\textwidth]{IMAGE}%
  \qquad
  \bisubcaptionbox[B]
    {Teilabbildung B}
    {Subfigure B}[0.4\textwidth]{IMAGE}%
  \bicaption[Abbildungsverzeichnistitel]
    {Und eine noch viel viel viel
      längere deutsche Beschriftung: Deutscher Titel}
    {Short English heading}
\end{figure}

\captionsetup{bi-slc=0}

\begin{figure}[!htb]
  \centering
  \bisubcaptionbox[A]
    {Und eine gaaaanz lange Caption: Teilabbildung A}
    {Subfigure A}[0.4\textwidth]{IMAGE}%
  \qquad
  \bisubcaptionbox[B]
    {Teilabbildung B}
    {Subfigure B}[0.4\textwidth]{IMAGE}%
  \bicaption[Abbildungsverzeichnistitel]
    {Und eine noch viel viel viel
      längere deutsche Beschriftung: Deutscher Titel}
    {Short English heading}
\end{figure}

\captionsetup{slc=0}

\begin{figure}[!htb]
  \centering
  \bisubcaptionbox[A]
    {Und eine gaaaanz lange Caption: Teilabbildung A}
    {Subfigure A}[0.4\textwidth]{IMAGE}%
  \qquad
  \bisubcaptionbox[B]
    {Teilabbildung B}
    {Subfigure B}[0.4\textwidth]{IMAGE}%
  \bicaption[Abbildungsverzeichnistitel]
    {Und eine noch viel viel viel
      längere deutsche Beschriftung: Deutscher Titel}
    {Short English heading}

```

```
\end{figure}

\end{document}
```

IMAGE	IMAGE
(a) Teilabbildung A	(b) Teilabbildung langer Titel B
(a) <i>Subfigure A</i>	(b) <i>Subfigure long title B</i>

Abbildung 1: Deutscher Titel
Figure 1: English Title

IMAGE	IMAGE
(a) Und eine gaaaanz lange Caption: Teilabbildung A	(b) Teilabbildung B
(a) <i>Subfigure A</i>	(b) <i>Subfigure B</i>

Abbildung 2: Und eine noch viel viel viel längere deutsche Beschriftung: Deutscher Titel
Figure 2: Short English heading

IMAGE	IMAGE
(a) Und eine gaaaanz lange Caption: Teilabbildung A	(b) Teilabbildung B
(a) <i>Subfigure A</i>	(b) <i>Subfigure B</i>

Abbildung 3: Und eine noch viel viel viel längere deutsche Beschriftung: Deutscher Titel
Figure 3: Short English heading

IMAGE	IMAGE
(a) Und eine gaaaanz lange Caption: Teilabbildung A	(b) Teilabbildung B
(a) <i>Subfigure A</i>	(b) <i>Subfigure B</i>

Abbildung 4: Und eine noch viel viel viel längere deutsche Beschriftung: Deutscher Titel
Figure 4: Short English heading