

Gradient Mechanics and Controlled Boundary Geometry

Professional reading edition of the evolving public MKUFT canon

Mark Charles McLaughlin

ORCID: [0009-0005-7736-1511](https://orcid.org/0009-0005-7736-1511)

Scientific affiliation	Independent Researcher
Object status	Research module reading edition — not a standalone Zenodo publication
Public source	Open canonical public source
Source commit	26e06b6fea52e6b052dbdd540e80d1d926b96b07
MKUFT backbone DOI	10.5281/zenodo.17780566

Status boundary. This PDF is a reader-facing rendering of an evolving GitHub research module. It is not a frozen standalone paper and does not receive a separate DOI. The cited Git commit fixes the exact source identity of this edition.

Rights. Copyright © 2026 Mark Charles McLaughlin. All rights reserved. Historical licences remain controlling only for their exact frozen objects.

Abstract

This paper develops a cautious gradient-mechanics bridge in MKUFT. It asks whether defined physical gradients, boundaries, thresholds, geometry, and orientation can alter measurable behaviour beyond simpler matched models.

It does not introduce a new force, explain reported craft, assign unusual motion to object shapes, or grant physical meaning to an undefined substrate variable.

The central falsifiable hypothesis is:

In a system with a defined physical coupling, geometry and orientation may alter threshold onset, stability duration, field distribution, propagation, or energetic cost beyond what stronger ordinary models predict.

1. Position inside MKUFT

The typed architecture is

$$S \rightarrow I \rightarrow P \rightarrow O.$$

The substrate layer is not treated as a visible physical medium with ordinary internal geography. The geometry examined here is **post-boundary geometry**: measurable physical structure arising in an actual P-layer system under a proposed and explicitly defined coupling.

A useful description is **post-boundary constraint geometry under a proposed substrate/information coupling**. The coupling itself remains hypothetical until derived and measured.

2. Gradient mechanics

A gradient is the rate and direction of change of a quantity across a region. Pressure gradients drive flow, temperature gradients drive heat transfer, electric-potential gradients define electric fields, refractive-index gradients bend light, density gradients affect propagation and stability, and velocity gradients produce shear.

Here **gradient mechanics** means the study of how measured changes across a boundary region organise physical behaviour, especially when several declared gradients become coupled.

Candidate classes include density, velocity/shear, refractive or structural, pressure/temperature, and propagation-constant gradients.

A boundary may be a finite region in which one physical state becomes another rather than an infinitely thin edge.

3. LUCY threshold relation

The canonical LUCY sequence is:

LUCY threshold $\rightarrow$ LUCY-1 membrane $\rightarrow$ LUCY-2 sustained local region.

The physical question is whether increasing a declared control parameter produces a reproducible threshold, followed by an interface state and, if sufficiently stable, a sustained finite region with behaviour distinguishable from the baseline.

This language is comparable to phase transitions, bifurcations, ionisation thresholds, surface formation, superconductive transitions, and related threshold phenomena. The comparison supplies mathematical grammar rather than evidence for a new field.

See [LUCY Boundary Threshold Framework](#) and the downstream [LUCY Threshold Geometry and Relational Closure](#).

4. Minimal mathematical scaffold

Let a candidate physical boundary state be represented by a scalar variable $\tau(x, t)$. The symbol does not acquire physical meaning by notation alone; its units and measurement protocol must be specified in each application.

Define

$$\mathbf{G}_\tau(x, t) = -\nabla\tau(x, t).$$

For rotational or circulating structure, introduce a vector variable $\mathbf{A}_\tau(x, t)$ with

$$\mathbf{H}_\tau(x, t) = \nabla \times \mathbf{A}_\tau(x, t).$$

A candidate boundary functional density is

$$\mathcal{F}_{\text{boundary}} = \frac{1}{2}\alpha\|\nabla\tau\|^2 + \frac{1}{2}\beta\|\nabla \times \mathbf{A}_\tau\|^2 + V(\tau, \mathbf{A}_\tau).$$

α , β , and V are effective coefficients or interaction terms. Every term must share compatible dimensions before quantitative use.

Until τ , $\mathbf{A}_\tau$, α , β , and V are physically derived and measured, $\mathcal{F}_{\text{boundary}}$ is an **effective functional density**, not automatically an energy or Lagrangian density.

5. Coherence threshold

Let Y_L be a local yield or threshold index:

$$Y_L(x, t) \geq Y_{\text{crit}}.$$

A generic response model may be written

$$Y_L = F(\|\nabla\tau\|, \|\nabla \times \mathbf{A}_\tau\|, \kappa_O, Q_{\text{env}}, R_{\text{geom}}).$$

The function F and threshold remain placeholders until a specific physical system supplies variables, units or normalisation, and a measurement protocol.

In physical tests, ordinary environmental, material, and geometry variables remain primary unless an observer coupling has independently demonstrated predictive value.

6. Geometry-response term

A geometry term may depend on shape, curvature, aspect ratio, symmetry, orientation, material, and field distribution:

$$R_{\text{geom}} = R(\text{extshape}, \text{curvature}, \text{aspect ratio}, \text{symmetry}, \theta, \text{material}, \text{field distribution}).$$

Geometry already affects resonance, stress, field concentration, waveguiding, breakdown, and threshold behaviour. MKUFT's additional question is whether a common boundary-cost description improves held-out prediction after these ordinary effects are modelled.

No geometry is assigned a preferred angle or motion class without an independent derivation.

7. Orientation as a measured variable

Let $\hat{\mathbf{n}}_P$ be a normalised physical reference axis of the apparatus and $\hat{\mathbf{n}}_G$ the measured direction of the applied gradient. Define

$$\theta = \arccos(\hat{\mathbf{n}}_P \cdot \hat{\mathbf{n}}_G).$$

This measures apparatus orientation relative to the gradient. It does not imply unusual propulsion or a privileged numerical angle.

A generic scalar comparison score may use normalised components:

$$J(\theta) = w_S \tilde{S}_{\text{boundary}}(\theta) - w_E \tilde{E}_{\text{cost}}(\theta) + w_R \tilde{R}_{\text{geom}}(\theta),$$

where the weights are fixed in advance. If unnormalised physical quantities are combined, the weights must carry the units required to make the expression meaningful.

8. Controlled geometry hypothesis

The defensible prediction is comparative:

After matching material, scale, surface area, thermal behaviour, field distribution, vibration, manufacturing tolerance, and sensor placement, some geometries or orientations may exhibit reproducible differences in threshold onset, stability duration, propagation, or energetic cost.

The null is that geometry or orientation adds no predictive value once established physical variables are modelled.

9. Relation to trajectory formalism

Let Γ be an admissible physical trajectory set and $C[\gamma]$ a declared physical-state-space cost. A measured boundary condition may modify either:

$$\begin{aligned}\Gamma &\longrightarrow \Gamma_{\text{boundary}}, \\ C[\gamma] &\longrightarrow C_{\text{boundary}}[\gamma].\end{aligned}$$

The testable question is whether

$$C_{\text{boundary}}[\gamma] \neq C_{\text{standard}}[\gamma]$$

in a way predicted before measurement and unexplained by the ordinary baseline.

A Gibbs-like path weight, where appropriate, requires a dimensionless exponent:

$$P(B \mid A) \propto \sum_{\gamma \in \Gamma(A \rightarrow B)} \exp[-\beta C[\gamma]].$$

A physical apparatus trajectory belongs to a physical state space. It is not automatically an I-layer graph route or S-layer relation.

10. Experimental programme

Candidate systems include plasma boundary layers, dielectric breakdown geometries, acoustic levitation nodes, fluid interfaces, superconducting or high-field boundary systems, and photonic or refractive-index-gradient systems.

Matched tests should control material, characteristic dimensions, surface area and volume, thermal behaviour, applied field distribution, vibration, manufacturing tolerance, and sensor placement.

Primary observables may include threshold onset, orientation dependence, stability duration, field distortion, energetic cost, propagation effects, uncertainty, and repeatability.

Blinded condition labels, calibration injections, preregistered primary outcomes, and held-out replication data are preferred.

11. Falsification conditions

This branch is weakened or rejected if geometry or orientation adds no predictive value after accepted physical variables are modelled; apparent effects disappear under material, thermal, field-distribution, vibration, perspective, or sensor controls; fitted geometry-cost terms fail on held-out or independently replicated data; no measurable coupling can be defined; or the proposed functional cannot be made dimensionally consistent or outperform existing physical models.

It is strengthened only by preregistered, reproducible geometry-dependent effects that survive strong ordinary models and retain the same parameter relationships under independent replication.

12. Public interpretation boundary

This model does not establish fixed-angle behaviour, shape-specific anomalous motion, craft origin, advanced propulsion, or physical travel through extra dimensions.

Appropriate descriptions include **candidate boundary-gradient model**, **effective boundary functional**, **geometry-dependent threshold hypothesis**, **orientation-dependent stability test**, **post-boundary constraint geometry**, and **matched laboratory comparison**.

13. Related public documents

- [LUCY Boundary Threshold Framework](#)
- [LUCY Threshold Geometry and Relational Closure](#)
- [Mathematical Appendix](#)
- [Standalone Formal Addendum](#)
- [Cross-Layer Invariants and Layer Addressing](#)
- [Typed Traversal and Equation Hygiene](#)
- [Experimental Test Programme](#)
- [Falsification Summary](#)

14. Summary

The narrow scientific proposal is:

Geometry and orientation may affect boundary threshold, stability, propagation, or transition cost in controlled physical systems.

The decisive question is whether a preregistered geometry-and-boundary model predicts controlled outcomes better than the strongest ordinary matched explanation. If not, this extension is revised or discarded.