Troubleshoot XCP File Analytics errors

XCP 1.6.2

Ciaran McNamara October 28, 2020

This PDF was generated from https://docs.netapp.com/us-en/xcp/xcp-troubleshoot-xcp-file-analytics-errors.html on October 30, 2020. Always check docs.netapp.com for the latest.



Table of Contents

| Troubleshoot XCP File Analytics errors | | | 1 |
|--|--|--|---|
|--|--|--|---|

Troubleshoot XCP File Analytics errors

| Issue | Solution |
|---|---|
| PostgreSQL installation or service failed | Run configure again and select the installation option. If the previous installation was successful, you can select the repair option. If you are still getting the error, try manual steps as follows: |
| | 1. Run PostgreSQL on the Linux system |
| | <pre>sudo yum -y install postgresql-serversudo systemctl start postgresq</pre> |
| | 2. Create a data directory for the PostgreSQL database: |
| | sudo mkdir /var/lib/postgres/data |
| | 3. Initialize the database: |
| | sudo -i -u postgres initdb -D '/var/lib/pgsql/data |
| | 4. Open the following file using an appropriate Linux file editor: |
| | /var/lib/pgsql/data/pg_hba.conf |
| | 5. Remove the following entry: |
| | `# host all all 127.0.0.1/32 trust |
| | 6. Add the following entry: # host all all 0.0.0.0/0 password |
| | 7. Open the file /var/lib/pgsql/data/postgresql.conf |
| | 8. Add the following entry: |
| | # listen_addresses='*' |
| | 9. Start the PostgreSQL service: |
| | sudo systemctl start postgresql.service |

| Run configure again and select the installation option. If the previous installation was successful, you can select the repair option. If you are still getting the error, try manual steps as follows: |
|--|
| Install HTTPD on the Linux system: sudo yum -y install httpd Open the following configuration file to rewrite the rules: /etc/httpd/conf/httpd.conf Add the following entries to the file: RewriteEngine On RewriteOptions Inherit Directory "/var/www/html/"> |
| 4. Start the HTTPD services: sudo systemctl start httpd |
| |

| Issue | Solution |
|--|---|
| SSL installation failed | Run configure again and select the installation option. If the previous installation was successful, you can select the repair option. If you are still getting the error, try manual steps as follows: |
| | 1. Install mod_ssl: |
| | yum install mod_ssl -y |
| | 2. Generate the Secure Sockets Layer (SSL) certificate: |
| | yum openssl req -x509 -nodes -days 365 -newkey rsa:2048 -keyout /etc/ssl/private/apache-selfsigned.key -out /etc/ssl/certs/apache-selfsigned.crt |
| | 3. Enable the HTTPS services: |
| | yum openssl dhparam -out /etc/ssl/certs/dhparam.pem 2048 |
| | 4. Restart the HTTPD services: |
| | sudo systemctl restart httpd |
| | 5. Copy the SSL certificate to an appropriate location: |
| | <pre>sudo cp -pr /etc/pki/tls/certs/localhost.crt /opt/NetApp/xFiles/xcp/server.crt sudo</pre> |
| Not able to open login page after successful install | Make sure your system is able to ping the Linux machine where XCP File Analytics is installed and HTTPD is running. If the services are not running, run configure and choose the repair option. |
| | Make sure that you are using supported version of browser. See the IMT: https://mysupport.netapp.com/matrix/ |

| Issue | Solution | |
|---------------------------------------|---|--|
| User login failed | Make sure that you are using a supported version of the browser. See the IMT: https://mysupport.netapp.com/matrix/ | |
| | Check the user is "admin" and the password is correct | |
| | • Make sure the XCP service is running by issuing "xcp service status" | |
| | Verify that port 5030 is open on Linux. Open the application at https:// linux ip> :5030/api/xcp, and confirm that the messagereads msg: Missing Authorization Header | |
| | Check whether the xcp.ini file is present in the /opt/NetApp/xFiles/xcp/ location. To reset the xcp.ini file, run the configuration script and select the Repair option. Next, select the menu option to rebuild xcp.ini file | |
| XCP GUI is not showing updated pages. | Clear the cache and try again | |
| XCP service is not starting | To run the xcp service, use the sudo systectl start xcp command. Alternatively, run the configuration script and select the Repair option to start the services that are stopped | |
| Failed to scan file share | File share/volume might not be readable. Check manually whether the file share is accessible/readable by running the xcp show command | |

| Issue | Solution |
|--|---|
| Could not load file servers | Try a page refresh. If the problem persists, manually run the xcp show command on the prompt and check whether you can scan the file server. If successful, raise a ticket with NetApp customer support. If unsuccessful, check manually to see if the file server is active Check whether the xcp.ini file and license files are in the correct location. To reset the xcp.ini file, run the configuration script and select the Repair option. Next, select the menu option to rebuild xcp.ini file. Check the xcpfalogs logs to see if the license needs renewal |
| XCP File Analytics page is not displayed after system reboot | XCP services might be down. Run the configuration script and select the option to Repair . This will restart all the services that are stopped |
| The total space for an exported file system on a given file server might show more space compared to the allocated physical storage. | This can happen when there are qtree level exports inside the volume. For example, if the volume size is 10 GB that is exported as /vol1 and there is a qtree inside the volume /vol1/qtree1, then the xcp show command will show the vol1 size as 10 GB and the qtree1 size as 10 GB. XCP File Analytics sums the space of both exports and gives the total space, in this case, 20 GB. It does not understand that qtree1 is a logical space. |

Copyright Information

Copyright © 2020 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval systemwithout prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.