


```
(defn weapon-query-handler [{:name} params :keys [conn] :as request]
```

```
(defn file-handler [{:keys [query]} {:keys [^File kind]} as-event]
```

(f/insert-file on {*name*(getNamel file): *prosed*(Date.)})

{:jdbc/condition{:condition-unix'jdbc:h2:men:men_only'}}

```
(defn add-weapon-handler [{:keys [params] :as request}]
```

`(timbre/debug(str 'Detected hang to file: ' (getNamel file)))`

```
(let [name & weapons] (map cs/trim (cs/spplit line #', '')))
```


:= jdbc/init { :conn (ig/ref := jdbc/conn) }

`awk/watch { :groups { :paths ['example']`

```
(let [data (map fn [[kv]] { :name kv :weapon v })] params)
```

(defmethod dig/init-key *jd/bc/init* [{:keys [conn]}])

;(tibre/debug'checking for new items in queue.')

(defn queue->dsdb [{:keys [queue-name queue-dsdb]}])

is cheduling/job { *job* #'queue->dsdb

(when-one[task(dq/take!queue-name 10 nil)])


```
{:data{:precisionreit.it.cerion.spec/cerion
```

is_durable/queue { *delete-on-halt?* **true**

is chdule { : in [5 : seconds : every : second }

(tinbre/debug 'Putting data into data script')

:dsdb(ig/ref::data\$ip\$connection)

webserver { host "0.0.0.0"

:con (ig/ref::data input/connetion)

(d//t rand t! dsdb[(line->read@task)])

`(ok(without-str(pp/print request)))`

```
(defn filter-handler [{:keys [sql-con]}])
```

We were able to connect the route here

(ok(w/weapons@acornn(keyparams)))

(cs/ends-with? (.getNamel file) ".csv"))

(ok(f/all-proposed-files ql-con))

(constantly(not-found'Not found'))

(timbre/debug 'Adding data queue.')

['/add_webon' add-weapons-handler'])

:queue(ig/ref::durabte/queue)

(when (and (#*modify* *read*) kind)

sqz-conn(ig/ref:jdb/cnnec tion)

['/weapons'-query-handler]

{conn(i:ig/ref::j:dbc/connec:tion)}

```
["/files"{:agetfiles-handler}] ] )
```

:queue (ig/ref::durablere/queue)

(dq/put! queue:my-queue line))

data/cnript/cnnect_idn **wschema**

(w/everybody's-weapons@acnn))

mind/leware [params/wrap-params]

(with-open [r(io//reader file)])

```
[[['/echo'{:aget_echo_handler}]]
```

[baisic-routes-weapons-routes]

(define sys(create conf))

(defn echo-handler [request])

mind[eware//wrap-format]})

(assoc: *Weapon* weapons)

(doseq[line](line-seq r))]

(define-line->record [line])

hand/zer # *final-e-hand/zer* }

(w/weapons@conn[name])

`:'directory'"/tmp'}`

(d/transact!commanddata)

(dq/complete!task)()

#hand/ler **#'hand/ler}}**)

queque-nammy-queque

(cond=>{:name name})

(def weapons-routes

;Routes--Alldata

(ring/ring-handler

(defbasic-inputs

Handwritten

(f/setup con)

(.exits file)

(.isFile file file)

print 30000

(seq weapons)

(ring/router

def handler

defrouter

(defconfid)

Handzlers

Router

)

i

f

n

a

m

e

route

ctx)

(

o

k

(

d

o

