Index

A

ACEPR (adjacent channel error power ratio), 95
Active subcarriers, 24, 120, 123, 125, 128, 134, 136, 150, 195, 284
Additive white Gaussian noise, *see* AWGN
Adjacent channel error power ratio, *see* ACEPR
Adjacent channel leakage ratio (ACLR), 88, 99
Amplifier, 88, 90–92, 100, 146
Analog array, 217, 222
  architectures, 217, 218
Antenna array, 201–203, 215, 216, 219, 222, 230
  architectures, 215
Antenna effects, 37, 38
Antenna elements, 40, 144, 160, 200, 201, 203–207, 209, 215–219, 227, 229, 230, 235, 236, 245, 247, 249, 250
  dual-polarized, 219, 249
Antenna gains, 8, 38, 201, 239
Antenna patterns, 32, 37, 38, 41, 54, 75
Antenna ports, 100, 223, 224, 227, 229, 231–233, 236, 242
Architectures, hybrid array, 216, 218, 219
Array gain, 199, 202–208, 215, 218
  composite link, 203, 206
Asymmetric digital subscriber line (ADSL), 119, 159
AWGN (additive white Gaussian noise), 189, 190, 193, 194, 253, 280, 284, 286

B

Baseband complexity, 18, 144, 146, 161
Basis functions, 90–92, 97, 100
  local, 89, 93, 96, 97, 281
Beam
  correspondence, 239, 244, 245
  management, 29, 32, 217, 224, 230, 232, 235, 238–244
  wide, 239, 240, 242, 243
Beam-forming, 25, 33, 143, 144, 160, 201–204, 217, 219, 222, 225, 228–230, 235, 238, 239, 243, 245–247, 249, 250
Beam-forming gain, 245–247, 249, 250
  estimated, 245–247
Beam-forming weights, 203, 217, 223, 239
BEC (binary erasure channel), 265, 266, 268
Behavioral models, 34, 87, 109, 111, 115
Binary erasure channel, *see* BEC
Blocklength, 253, 255, 257, 258, 266, 267, 269, 270, 273, 275

C

Carrier-frequency offset, *see* CFO
CDD (cyclic delay diversity), 208
CFO (carrier-frequency offset), 159, 186–188, 191, 279, 280, 282–284, 286, 287, 290, 293
Challenges, 3, 7, 16, 21, 32
Channel bandwidths, 21, 161, 163
Channel capacity, 212, 255
Channel coding, 23
Channel correlation, 204–206
Channel delay, 139, 162, 170, 173
Channel estimation, 28, 29, 149, 223, 225, 226, 229, 231, 279, 280
Channel impulse response, *see* CIR
Channel knowledge, 207
  accurate, 211
  detailed, 204, 224, 226, 229
Channel matrix, 208–210, 212, 227
Channel measured, 50–52, 73
Channel model, 17, 59, 61, 74, 75, 82, 171, 172, 175, 248–250, 273, 277, 279–281
  geometry-based stochastic, 18, 279
  stochastic, 74, 281
Channel modeling, 17, 32, 35
Channel prediction, 193, 195, 197
Channel quality, 224, 229
Channel quality indicator, *see* CQI
Channel responses, 42–44, 50
Channel state information, *see* CSI
Channel time selectivity, 18, 160
  robustness to, 144, 160
Channel transfer functions (CTFs), 189, 193, 283
Channel vectors, 204, 205, 212

CIR (channel impulse response), 189, 190, 284
Codebooks, 209, 225, 227–229, 232, 235–237
Codes, convolutional, 270, 271, 275
Codewords, 182, 254, 255, 259, 262, 269, 270, 272, 273
Coding schemes, 18, 25, 29, 224, 254, 255, 257, 258, 271, 272, 275
Commercial deployments, 1, 6, 14, 16
Common phase error, *see* CPE
Control-plane, 14, 22, 23
CP (cyclic prefix), 24, 123–127, 129, 132, 141, 161–163, 166, 170, 185, 189, 193, 279, 280, 284, 285
CP-OFDM, 24, 123, 126–128, 138, 139, 141, 142, 146–149, 151, 152, 235, 279, 284–287, 290, 293, 294
  waveform, 159, 162
CPE (common phase error), 28, 153, 167–169, 186–188, 282, 291
CQI (channel quality indicator), 29, 224, 226, 235
CSI acquisition, 29, 224, 225, 227, 229–232, 235, 242
CSI (channel state information), 25, 28, 200, 216, 224, 225, 227, 229–232, 234–236
CSI-RS, 28, 29, 224, 231, 232, 235, 238, 241–245
CTFs, *see* Channel transfer functions
Cyclic prefix, *see* CP

D

DAB (digital audio broadcast), 119, 159
Data transmission, 23, 25, 27, 32, 201, 227, 231, 233–235, 237, 238, 240, 241, 253
Demodulation, 28–30, 149, 153, 154, 156, 167, 186, 227, 230, 231, 280, 290
Deployments, 8, 14, 15, 18, 24, 119, 143, 144, 159, 160, 165–167, 170, 172
  large cell, 142–144, 160
DFT Spread OFDM (DFTS-OFDM), 24, 119, 141, 142, 149, 160, 179, 180, 184, 235, 279
Digital array, 216, 217, 229
Digital audio broadcast (DAB), 119, 159
Distortion, 33, 87, 88, 95, 97, 98, 109, 112, 140, 180, 182, 195, 281, 284
Dolph–Chebyshev filter, 284, 286, 290, 291, 293
Dominant channel directions, 232
Doppler effect, 163, 172, 186
Doppler frequencies, 45
Doppler time domains, 48
Downlink, 14, 23, 24, 26–28, 31, 142, 159, 162, 179, 180, 202, 224–226, 238, 243
Downlink beam management, 238–241, 244
Downlink channel, 225, 226, 235
Downlink MIMO transmission, 232, 235
Downlink transmissions, 24, 27, 119, 225, 226
Dynamic TDD, 30, 145, 161

E

Elevation, 41, 46, 50, 51, 59, 70–74, 78, 220, 245, 247, 281
EMBB (Enhanced Mobile Broadband), 8–10, 15, 30, 31, 142, 143, 145, 172, 253, 258
Equalization, 54, 68, 151, 279, 280, 283

F

Fading channels, 18, 197, 205, 253, 271, 273, 274, 293
  time-varying, 149, 293
Fast Fourier transform, *see* FFT
FBMC symbol, 133, 135, 140
FBMC waveforms, 122, 130, 133, 137, 138, 140, 151, 158
FBMC-OQAM, 133–135, 137–139, 146–149, 152, 157, 279, 280, 285–287, 289–291, 293
FBMC-QAM, 135, 137–139, 146, 149, 157, 158, 279, 280, 286, 290, 291, 293, 294
FDD (frequency division duplex), 2, 31, 202, 209, 225–227, 229, 232, 235
FEC (forward error correction), 253
FFT (fast Fourier transform), 125, 127, 130, 185, 220
Filter bank, 284–287, 290
Filtered OFDM, 123, 127
Frame, 6, 26
  structure, 21, 27, 30, 31, 166
Frequencies
  corner, 107
  dependence, 38, 56, 58, 63, 75, 77, 201
  domain, 28, 29, 42, 43, 45, 119, 120, 122, 130, 132, 141, 143, 151, 161, 172, 175, 185, 186, 207, 208
  higher, 6, 7, 30, 33, 54, 58–60, 66, 68, 82, 87, 144, 159
  higher carrier, 18, 28, 119, 142, 143, 167, 170, 172
  increasing, 38, 54, 58, 75, 221
  lower carrier, 143, 144, 159
  random jitter, 291, 293

Frequency division duplex, *see* FDD
Function, nonlinear, 92, 97, 109, 110

G
Generalized memory polynomial, *see* GMP
GMP (generalized memory polynomial), 92, 93, 95–97, 279, 281
GoB (grid-of-beams), 228, 245–249
Grid-of-beams, *see* GoB
Guard interval, 129, 151

H
Half-power beam width (HPBW), 220, 245, 247
Hann filter, 43, 44, 51
Hardware impairments, 16, 18, 21, 32, 87, 109, 115, 117, 145, 159, 167, 279–281
High frequencies, 25, 33, 38, 66, 144, 145, 160, 161, 166, 200, 201, 221, 230, 242

I
IMT (international mobile telecommunications), 5, 8, 78
Information bits, 254, 266–268, 275
Information theory, 253, 255, 264
Input power, low, 287–289
Inter-symbol interference, *see* ISI
Intercarrier interference, 133, 153, 167, 168, 172, 186
Interference, 122, 123, 127, 133, 135, 175, 176, 200, 206, 209, 212–215, 217, 226, 227, 230, 234, 235, 280, 282
  intercell, 213, 214, 231, 234
  measurements, 29, 232, 235
  presubtraction, 212, 213
  suppression, 80, 199, 200, 210–212, 215, 224, 233
International mobile telecommunications, *see* IMT
International telecommunications union, *see* ITU
Internet of things, *see* IoT
Internumerology interference, 173, 175, 176
IoT (internet of things), 1, 9, 15
ISI (inter-symbol interference), 123, 124, 133, 140, 153, 155, 186
ITU (international telecommunications union), 4, 6, 7, 10, 205

K
Kalman filter, 193–195, 197
Key performance indicators, *see* KPIs
Key technology components, 23, 229
KPIs (key performance indicators), 18, 144, 146, 161

L
Large bandwidths, 8, 81, 144, 146, 147, 161, 200, 216
Layers, 22, 23, 26, 28, 71, 208–212, 214, 215, 224, 228, 231–233, 235–238, 247
  higher, 23, 26, 28, 244
  transmitted, 209, 211, 214
LDPC code, 25, 261–263, 271
Linear block codes, 258–261, 264, 269, 270
Link adaptation, 27, 29, 171, 175, 225, 226
Link types, 142, 159–162
Listen-before-talk (LBT), 31, 164, 165
Low latency, 1, 12, 30, 31, 142, 143, 145, 161, 165, 171, 172, 272
LTE (long term evolution), 2–5, 14–16, 21, 23–26, 30, 140, 159–161, 163, 165, 179, 199, 200, 208, 209, 223, 224, 226–231, 233–235
LTE numerology, 165, 166

M
Maximum ratio transmission, *see* MRT
Measurement data, 55, 56, 73, 74, 78, 80, 84, 93, 95, 96
Medium access control (MAC) layer, 22, 23
Millimeter-wave, 3, 6, 7, 25, 30–33, 59, 60, 87, 88, 142, 143, 164, 165, 200, 201, 216, 217, 219–224, 229, 230, 244, 245, 247, 248, 281, 282
MIMO (multiple-input multiple-output), 25, 33, 48, 137, 142, 143, 199, 277
Mini-slots, 26, 30, 31, 164, 165, 172
MMTC (massive Machine Type Communications), 8–10, 23, 142, 143, 145, 172, 253
Mobile communications, 1–3, 5, 6, 12, 24, 35, 66, 74, 82, 84
Model parameters, 52, 62, 64, 95
Modeling error, 93, 189, 190
Models
  baseline, 55, 79–81
  phase-noise, 105, 169, 279
  system, 101, 102
MRC (maximum ratio combining), 204, 206, 207, 215
MRT (maximum ratio transmission), 113, 205–207, 230
Multiantenna techniques, 8, 18, 24, 25, 87, 199, 200, 202, 203, 215, 216, 223, 224, 230

Multicarrier waveforms, 18, 24, 119–121, 140, 141, 146, 148, 149, 160, 167, 186, 282, 284, 287, 291, 293
Multipath channel, 119, 123, 125, 185, 212, 282, 283
Multipath components, 44, 51, 53, 78–80
Multiple antennas, 199, 200, 206, 208, 215, 257
Multiple-input multiple-output, *see* MIMO
Mutual coupling, 88, 89, 100–102

N

Narrowband interference, 120
Narrowband subcarriers, 176–178
New radio, 3
NLoS measurements, 66, 67, 69
NLoS (non-line-of-sight), 33, 48, 53, 58, 59, 61, 67–69, 79, 201, 205, 206, 245, 250
Noise, 48, 52, 60, 73, 104–106, 203, 204, 214, 215, 230, 253
  additive, 168, 189, 190, 284
Non-line-of-sight, *see* NLoS
Non-stand-alone (NSA), 6, 14
Number theory, 268
Numerologies, 24, 26, 126, 163–166, 170–178
  aggressor, 175, 176
  subcarriers of, 176–178

O

OFDM based waveforms, 123, 130, 131, 137
OFDM numerologies, 24, 30, 163, 166, 167, 172
OFDM (orthogonal frequency division multiplexing), 2, 24, 119–121, 131, 132, 134, 135, 137, 140, 141, 146, 147, 149, 151, 157–163, 167, 168, 175, 176, 179, 279, 280
OFDM subcarrier spacing, 29, 163, 167
OFDM symbols, 26, 28–32, 124, 126, 127, 150, 153, 163, 164, 166, 168, 182, 183, 186, 191, 193–195, 197, 272, 273
  core, 126, 127
OFDM systems, 113, 160, 167, 168, 170, 172, 179, 183–188, 191, 208, 216, 224
OFDM waveforms, 122, 124, 125, 127, 140, 141, 179
OOB, *see* Out-of-band
Orthogonal frequency division multiplexing, *see* OFDM
Orthogonality, 110, 112, 287, 291
Oscillator, 29, 104, 105, 107, 282, 287, 291
Oscillator frequencies, 154, 170
Out-of-band (OOB), 24, 127, 145, 146, 179, 180, 195, 281
Overlapping factor, 133–137, 147, 151, 285–287, 289–291, 293

P

PA, *see* Power amplifier
Packet data convergence protocol (PDCP) layer, 22
Panoramic photographs, 67, 68, 73
PAPR (peak-to-average-power-ratio), 119, 141, 144, 148, 149, 160, 181, 182
PAPR reduction, 160, 182
  schemes, 183, 184
Partial transmit sequence (PTS), 182, 183
Peak-to-average-power-ratio, *see* PAPR
Penetration losses, 33, 57, 58, 77, 143
Phase locked loop, *see* PLL
Phase-noise
  oscillator, 18, 28, 88, 279, 280
  power spectral density, 104–106
Phase shifters, 217–219
PHY layer, 23, 28
PHYDYAS prototype filter, 285, 290, 291, 293
Physical broadcast channel (PBCH), 27, 232
Physical channels, 26
Physical downlink control channel (PDCCH), 27, 238, 241, 243, 244
Physical downlink shared channel (PDSCH), 26, 27, 238, 243, 244
Physical random access channel (PRACH), 27, 239
Physical signals, 26, 28
Physical uplink control channel (PUCCH), 27, 242, 245
Physical uplink shared channel (PUSCH), 27, 235, 236, 242
Pilots, scattered, 190, 191, 195, 282, 285
PLL (phase-locked loop), 34, 104, 105, 107, 111, 152, 167, 282, 283
PMI (precoding matrix indicator), 29, 224, 227, 228, 235, 242
Polar codes, 25, 253, 258, 264, 266–269, 271
Polarizations, 38, 41, 203, 207, 216, 219, 220, 228, 232, 233, 247, 249, 264
Power amplifier, 17, 18, 33, 87–91, 93, 97, 100–103, 110, 111, 114, 116, 140, 141, 144, 147, 148, 179, 205, 279–281
  modeling, 89, 93, 97, 100

Power delay profiles, 53, 54, 59, 62, 67–69, 73, 78, 114
Power spectral density, *see* PSDs
PRB (same as Resource Block (RB)), 26, 29, 175, 176, 179
Precoder matrix, 208, 209, 227, 232
Precoders, 29, 205, 210, 212, 213, 227, 228, 231, 233, 236, 237
Precoding, 202, 204–206, 208, 210, 211, 213, 214, 225, 227, 235
Precoding matrix indicator, *see* PMI
Propagation, 35–37, 40, 84, 215, 226
  distance, 59, 69–71, 73, 79, 80
  free-space, 36, 37, 39, 41, 70, 201, 203
  radio wave, 16, 21, 32
Prototype filters, 120–123, 127, 130–134, 136, 147, 284–286, 290, 291, 293
PSDs (power spectral density), 95, 96, 104, 106, 108, 115, 134, 173, 184, 189
PTS (partial transmit sequence), 182, 183

Q

QoS, *see* Quality of service
QuaDRiGa channel model, 149, 191, 197, 293
Quality of service (QoS), 3, 18, 22, 159, 162

R

Radiation patterns, 98, 99, 205
Radio interface technologies, 5
Radio link control (RLC) layer, 22, 23
Radio link failure (RLF), 23, 244
Radiowave propagation, 35, 36, 48
Rank indicator, *see* RI
RB, *see* Resource block
Received signal vector, 207, 208, 214
Receiver side, 126, 132, 274
Reciprocity, 202, 225–227, 229, 231, 232, 235, 237, 239
Reference signal received power (RSRP), 29, 224
Reference signals, 25, 28, 30, 31, 178, 223–225, 227, 229–232, 239, 240, 243–245
  received, 225, 238, 239, 241
Resource block (RB), 26, 128, 175–179, 230, 272–275
Retransmission, 27, 244
RF power amplifiers, 33
RFICs (radio frequency integrated circuits), 219, 220
RI (rank indicator), 29, 224, 235, 242
Robustness, 18, 144, 160, 161, 199, 238, 240–242, 253
  phase-noise, 144, 146, 160, 161

S

Sampling frequency offset (SFO), 187, 188, 191, 193, 195–197
Scattering channel, 199, 204, 206, 207
Self-interferences, 123, 135, 136
Service data adaptation protocol (SDAP) layer, 22
Sidelink, 144, 145, 159–162, 179
Signal
  bandwidth, 128, 147, 160, 163
  processing, 16, 199
Signal-to-interference ratio, 136, 153, 154, 157, 158, 168, 169, 187, 199, 286, 290, 291
  achievable, 153, 154, 157, 158, 168, 169, 187
Simulation, 113, 146, 147, 171, 190, 233, 234, 250, 286, 287, 291
  exercises, 18, 279
Simulator, 279–286
  open-source, 18, 279, 280
Single-carrier waveforms, 119, 140, 141, 146, 159, 186
SIR, *see* Signal-to-interference ratio
Slot, 26–28, 30–32, 140, 163, 164, 166, 170, 172, 231, 272
SNR (signal-to-noise ratio), 49, 120, 190, 199, 203–205, 207–210, 212, 254, 257, 268
Sounding reference signal, *see* SRS
SRS (sounding reference signal), 28, 29, 231, 238, 244, 245
SSB (synchronization signal block), 232, 238–245
Stochastic model, 110, 111, 113, 115
Subarrays, 218, 219, 245, 246
Subcarrier bandwidth, 172, 173, 186
Subcarrier spacing, 24, 26, 137, 160–164, 166–168, 170, 172–174, 176, 190, 191
  function of, 154, 157
  wider, 164, 170, 171, 173
Subcarriers, 26, 28, 29, 119–123, 127–129, 133–138, 149–151, 153–156, 167, 168, 172, 173, 175–179, 182, 186–189, 216, 282–286, 290, 291
  demodulated, 153, 155, 157, 168, 185–187
Subchannels, 208, 209, 268, 285
Subframe, 26, 140, 165, 230
Symbols, pilot, 273–275, 277
Synchronization signal block, *see* SSB

Synthetic channels, 265–268
System
  practical, 191, 193, 209, 210, 213
  simulations, 245, 248, 249

T
Tail-biting (TB), 258, 270, 271, 275
TB, *see* Tail-biting
TDD (time division duplex), 2, 30, 31, 143, 145, 202, 226, 227, 229, 231, 232, 235
Time division duplex, *see* TDD
Time domain, 26, 28, 29, 45, 47, 123, 126, 130, 143, 145, 147, 151, 153, 161, 164, 285
Time-frequency resources, 21, 26–28
Timing offset, 185, 186, 282
TM, *see* Transmission mode
TPMI (transmit precoder matrix indicator), 236
Tracking reference signal (TRS), 29, 244
Transmission loss, 7, 25, 32, 37–39, 48, 49, 55, 56, 59, 75, 83, 84, 119, 201, 211, 281
  free-space basic, 37–39
Transmission mode (TM), 208, 227, 230, 231
Transmission points, 247, 248
Transmission ranks, 209, 224, 233, 235, 236
Transmission schemes, 180, 227, 232, 235
Transmitter, 57, 58, 61, 151, 175, 181, 193, 199, 202–212, 214, 238, 239, 277, 280, 282, 284, 285, 287

U
UF-OFDM, 123, 128, 146, 149, 151, 279, 280, 284–291, 293
  waveform, 128, 129
ULA (uniform linear array), 99, 205, 206, 227, 228
Ultra-reliable low-latency communications, *see* URLLC
Uniform linear array, *see* ULA
Uniform planar array (UPA), 219, 228
Unlicensed spectrum, 30, 31, 142, 164, 165
Uplink, 14, 23, 24, 28–31, 119, 142–144, 159, 161, 162, 179, 202, 209, 225, 226, 235, 239, 245
Uplink and downlink, 23, 24, 26, 180, 225, 226
Uplink and sidelink, 145, 160, 161
Uplink beam management, 29, 238, 244
Uplink measurements, 202, 229, 230
Uplink transmissions, codebook-based, 235, 236
URLLC (ultra-reliable low-latency communications), 8–10, 30, 31, 142, 145, 161, 172, 253, 269, 272, 274, 276, 277
User-plane, 14, 22, 23

V
Vector network analyzer (VNA), 48
Volterra series, 88–90, 92, 281

W
W-OFDM, 123, 125, 127, 130, 146, 149, 151, 175, 176, 279, 280, 284, 286, 287, 290, 291, 293
Waveform design requirements, 119, 161, 162
Wide range of frequencies, 21, 24, 142, 161, 166, 170
Wireless communications, 35, 203

Z
ZF receiver, 214, 215