
# 5G Ultra-Reliable Low Latency Communication (URLLC)

(3) 5ghub.us/5g-ultra-reliable-low-latency-communication-urllc/

January 20, 2020



#### Introduction

5G is rapidly coming close bringing with it the promise of powerful new use cases that will require a flexible technology that can provide ultra-reliable low latency (uRLLC), massive machine-type communications (mMTC), and much huge faster data rates with enhanced Mobile Broadband (eMBB).

So, the expectation in the industry is growing for the Internet of Things (IoT), so requirements for URLLC have been set anticipating integration in industries other than mobile communications, such as automobiles, robots, and sensors.

## **URLLC Use Cases**

URLLC is targeted mainly for services like traffic control or remote control, which require both high reliability and low latency.

Example:

• Control of Autonomous Vehicles and Traffic control, this involves sending warning signals between different vehicles, roadways and even pedestrians to control the traffic efficiency and support movement of emergency vehicles.

- Robot Control and 3D Connection with Drones and other devices, as the
  manufacturing automation using robots, is anticipated and control of this is a use
  case for 5G. It's also expected to control drones and other devices in the air
  remotely.
- Remote Surgery, It can be implemented using optical communications but it's difficult to apply in disaster areas or other dangerous situations. So, it's one of the use cases for 5G.



URLLC Use Cases (Source: Nokia)

All the above use cases need high reliability and low latency and mobility rather than high transmission speed or a large number of connected terminals. So, the question now what are the URLLC requirements?

# **URLLC Requirements**

Ensuring low-latency and ultra-reliable communication for future wireless networks is of capital importance as the main requirements for URLLC.

#### 1. Latency

There's are different definitions of Latency as below:

- 1. End-to-End Latency and this include the over the air transmission delay, queuing delay, processing/computing delay and retransmission.
- 2. User Plan Latency (3GPP), defined as the one-way time it takes to successfully deliver an application layer packet/message from the radio protocol layer ingress point to the radio protocol ingress point of the radio interface, in either uplink or downlink in the network for a given service in unloaded conditions (assuming the user equipment (UE) is in active state).
- 3. Control Plan Latency (3GPP), defined as the transition time from a most "battery efficient" state (e.g., idle state) to the start of continuous data transfer (e.g. active state).

The URLLC requirements from 3GPP RAN TR 38.913 for the latency is as below:

- Control Plane Latency: 10 msec.
- User Plan Latency: 0.5 msec for both UL and DL.

## 2. Reliability

In general, reliability is defined as the probability that a data of size D is successfully transferred within a time period T. However, other definitions can be encountered:

Reliability (3GPP): capability of transmitting a given amount of traffic within a predetermined time duration with high success probability.

The URLLC requirements from 3GPP RAN TR 38.913 for the Reliability is 1-10^-5 for 32 bytes with a user plane latency of 1ms.

## **URLLC Use Cases and Requirements**

As per 3GPP TS 22.261, Table 7.2.21 performance requirements for low latency and high-reliability scenarios.

Scenario	End-to- and latency	Communication service evaluability	Reliability	User experienced data rate	Payload size	Traffic density	Connection density	Service area dimension
Discrete automation - motion control	1 ma	96.3000%	90,0000%	1 Mbps up to 10 Mbps	Small	1 ThouAm <sup>2</sup>	100 000Am²	100 x 100 x 30 m
Discrete automation	10 ms	99,99%	99.39%	10 Mbps	Small to big	1 Thousen	100 000Am <sup>2</sup>	1000 x 1000 x 30 m
Process automation - remote control	50 ms	90.3000%	99,0000%	I Misps up to 100 Misps	Small to big	100 Gbps/km²	1 000 Aust	300 x 300 x 50 m
Process automation - monitoring	50 ma	99,9%	99,9%	1 Mbps	Small	10 Gbpuleni <sup>a</sup>	10-000Am/	300 x 300 x 50
Electricity distribution - medium voltage	25 ms	90,9%	99,9%	10 Mbps	Small to big	10 Göpulumi	1 0000km²	100 km along power line
Electricity distribution - high voltage	5 ma	98,9000%	99,9999%	10 Mbps	Small	100 Gbpulkm <sup>2</sup>	1 000 km²	200 km along power line
Intelligent transport systems - infrastructure backhaul	10 ms	98,3900%	99,9990%	10 Mbps	Simuli to big	10 Göpelen <sup>o</sup>	1 000Am <sup>2</sup>	2 km along a road
Tactile interaction	6.5 ms	[99.90954]	[99.99974]	[Low]	[Small]	[Low]	[Low]	TBC
Remote control	[5-ms]	[99,9995]	[90,999%]	[From low to 10 Mbps]	(Small to High	[Low]	[Low]	TBC

Performance requirements for low-latency and high-reliability scenarios (Source: 3GPP)

## Issues in meeting URLLC Requirements

To meet URLLC requirements for reducing latency requires:

- Reducing radio signal transmission time, the longer the slot length the longer the transmission time, so reducing the slot length is desirable.
- Reducing the time needed for transmission, it's mandatory to reduce the time for the retransmission of the lost packets to achieve both high reliability and low latency.

#### **Conclusion:**

This article has given an overview of URLLC as a 5G use case and the different requirements for best performance from low latency to high reliability. Also, to support future services with flexibility, it's desirable to increase the volumes of data that can be transmitted while satisfying the URLCC requirements.

#### References:

- 3GPP TS 22.261
- Nokia
- NTT DOCOMO.

Dual Connectivity (DC) E-UTRAN supports Dual Connectivity (DC) operation whereby a multiple Rx/Tx UE in RRC\_CONNECTED is configured to utilize radio resources provided by two distinct schedulers, located in two nodes connected via a non-ideal... Read more

Introduction MEC (Mobile Edge Computing) transforms the topology and architecture of mobile networks from pure communication networks for voice and data to an application platform for services. The MEC should be seen as complementing and...

#### Read more

Introduction Mobile operators continue to build more capacity while driving down costs and looking for new service revenue opportunities. As they focus on 5G, they are exploring innovations and new operating models that will help...

#### Read more

5G synchronization is crucial for the development and expansion of the new 5G networks. Especially when it comes to 5G Synchronization in TDD (Time-Division-Duplex) systems, where the resources are shared in the time domain...

#### Read more

5G networks will have to provide extensive coverage and connectivity to support the various demanding 5G services. From an architectural point of view, heterogeneous networks have already been developed for existing networks. Still, due...

### Read more

This decade will be the one where 5G networks will be deployed and developed around the globe. So it seems that 5G is here to stay. However, the reality is that it will take...

## Read more

Introduction The increasing demand for higher data rates and reduced latency continues to drive cellular communication evolution and transmission. 5G promises to take performance to levels never seen before, with mounting pressure to deploy 5G...

### Read more

Introduction 5G builds upon existing telecommunication infrastructure to improve bandwidth and capabilities and reduce network-generated delays. However, 5G also carries over and introduces new risks that must be addressed to ensure its secure and safe...

#### Read more

There is a lot of discussion about the disruption that 5G will bring to many areas of society. At the same time, it is worth noting the network disruptions that have actually taken place...

## Read more

In 5G deployment, there are some similarities and a few differences between LTE and 5G NR protocols. The typical OSI layers and 5G NR Protocols on the air interface are mainly relevant for Stand-alone...

### Read more

GSM and the corresponding 3GPP technologies have become a success story because of the developed ecosystem. There are currently more than 5 billion GSM subscribers worldwide with a rich ecosystem for many industry players...

## Read more

Telecommunications in the last several decades have definitely not only changed the way we communicate, but they have also transformed our lives and altered our perception of society. It has been a steadily increasing...

# Read more