

# Risk Assessment Report

Site: Example Site    Company: The Technology Studio    Risk assessment by: Mark Short

Task:		Example Task										
Report Identifier:		cf09d19d			Page Number:			1/2				
Site:	Example Site (The Technology Studio)		Assessor:	Mark Short			Created Date:			15 May 2013		
Hazard	Who might be harmed	How might they be harmed	Existing Controls	Risk Rating (L * S)			Further Controls/Actions	New Risk Rating				
				L	S	R		L	S	R		
ENV- Gases/Fumes/Vapours	Working Party	Land	<ul style="list-style-type: none"><li>• Medium Risk - Ensure existing controls are maintained and monitored</li><li>• Emission monitoring (e.g. CEMS)</li><li>• Stack height</li><li>• In stack heaters</li><li>• Electrostatic precipitators</li><li>• SO3 injection</li><li>• Ventilation of work area</li><li>• Venting of storage vessels</li><li>• Incineration</li><li>• Absorption</li><li>• Condensers</li><li>• Wet scrubbers</li><li>• Dry scrubbers</li><li>• BAT</li><li>• Flame arresters</li></ul>	5	5	25	<ul style="list-style-type: none"><li>• Emission monitoring (e.g. CEMS)</li><li>• In stack heaters</li><li>• Low nox burners</li><li>• Ventilation of work area</li><li>• Incineration</li><li>• Adsorption</li><li>• Filtration</li><li>• Operating regime</li><li>• Metering to check levels</li></ul>	2	5	10		
Flying Object (ejected)	Working Party	Objects discharged by stored energy	<ul style="list-style-type: none"><li>• Controlled release of stored energy</li><li>• Plant washed down to control the build up of dust and debris</li><li>• PPE - Safety glasses to be worn (Standard BS EN 166, 1F grade)</li><li>• PPE - Safety goggles to be worn (Standard BS EN 166, 1B grade)</li><li>• Routine inspection and maintenance</li></ul>	4	3	12	<ul style="list-style-type: none"><li>• PPE - Safety goggles to be worn (Standard BS EN 166, 1B grade)</li><li>• PPE - Safety visor to be worn (Standard BS EN 166, 1B grade)</li><li>• Robustness of guarding confirmed</li><li>• Routine inspection and maintenance</li><li>• Tolerable Risk - No further controls required</li></ul>	3	3	9		
Chemical	Working Party	Absorption	<ul style="list-style-type: none"><li>• Clean tools after use with COSHH assessed cleaning chemicals</li><li>• PPE - Chemical resistant overalls to be worn (Standard BS EN 465)</li></ul>	4	5	20	<ul style="list-style-type: none"><li>• PPE - Safety glasses to be worn (Standard BS EN 166, 1F grade)</li><li>• PPE - Respiratory protective equipment to be worn</li></ul>	4	2	8		

Task:		Example Task						
Report Identifier:		cf09d19d				Page Number:		2/2
Site:	Example Site (The Technology Studio)		Assessor:	Mark Short			Created Date:	15 May 2013
Hazard	Who might be harmed	How might they be harmed	Existing Controls	Risk Rating (L * S)			Further Controls/Actions	New Risk Rating
				L	S	R		L
Electricity	Working Party	Exposure to damaged electrical apparatus	<ul style="list-style-type: none"><li>Insulation of electrical supply</li><li>PPE - Electrical Gloves (standard EN 60903)</li><li>Use of insulated tools</li></ul>	2	3	6		236
ENV-Oil	Working Party	Water	<ul style="list-style-type: none"><li>Bunding of oil storage areas</li><li>Installation of interceptor pits</li><li>Maintenance of equipment</li><li>Spill kits located locally</li></ul>	4	5	20	<ul style="list-style-type: none"><li>Bunding of oil storage areas</li><li>Maintenance of equipment</li><li>Tolerable Risk - No further controls required</li></ul>	122
Key:	Likelihood 1 = Highly unlikely, 2 = Unlikely, 3 = Possible, 4 = Likely, 5 = Certain			Risk Rating = L X S (Likelihood X Severity)			<div></div> Low = 1 to 4	
	Severity 1 = No injury, 2 = Minor injury, 3 = Medical treatment, 4 = Reportable, 5 = Major injury/Fatal						<div></div> Medium = 5 to 11	
							<div></div> High = 12 to 25	