## Risk Assessment Report

Site: Example Site Company: The Technology Studio Risk assessment by: Mark Short

Example Task	
52ac3369	

Page 1/3

Report Identifier: 52ac3369											
Site:		The Technology udio)	Assessor:	Ma	rk SI	nort	Created Date:		5 M 201	-	
Hazard				Risk Rating (L * S)						Risk ting	
	Who might be harmed	How might they be harmed	Existing Controls	L	S	R	Further Controls/Actions	L	S	R	
ENV- Gases/Fumes/Vapours	Working Party	Land	Medium Risk - Ensure existing controls are maintained and monitored     Emission monitoring (e.g. CEMS)     Stack height     In stack heaters     Electrostatic precipitators     SO3 injection     Ventilation of work area     Venting of storage vessels     Incineration     Absorption     Condensers     Wet scrubbers     Dry scrubbers     BAT     Flame arresters	5	5	25	Emission monitoring (e.g. CEMS) In stack heaters Low nox burners Ventilation of work area Incineration Adsorption Filtration Operating regime Metering to check levels	2	5	10	
Flying Object (ejected)	Working Party	Objects discharged by stored energy	Controlled release of stored energy Plant washed down to control the build up of dust and debris PPE - Safety glasses to be worn (Standard BS EN 166, 1F grade) PPE - Safety goggles to be worn (Standard BS EN 166, 1B grade) Routine inspection and maintenance	4	3	12	PPE - Safety goggles to be worn (Standard BS EN 166, 1B grade) PPE - Safety visor to be worn (Standard BS EN 166, 1B grade) Robustness of guarding confirmed Routine inspection and maintenance Tolerable Risk - No further controls required	3	3	9	
Chemical	Working Party	Absorption	Clean tools after use with COSHH assessed cleaning chemicals     PPE - Chemical resistant overalls to be worn (Standard BS EN 465)	4	5	20	PPE - Safety glasses to be worn (Standard BS EN 166, 1F grade) PPE - Respiratory protective equipment to be worn	4	2	8	

Site: Example Site	Company: The Technology Studio	Risk assessment by: Mark Short							Pa	ge 2/3
Hazard		They be	Existing Controls	Risk Rating (L * S)				200	w Risk Rating	
	Who might be harmed			L	S	R	Further Controls/Actions	L	S	R
ENV-Odour	Lone worker	Land	Use of air fresheners     Tolerable Risk - No further controls required     Process/waste/materials/sewage causing odour monitored	4	4	16	Process/waste/materials/sewage causing odour investigated     Process/waste/materials/sewage causing odour monitored	4	2	8
Electricity	Working Party	Exposure to damaged electrical apparatus	Insulation of electrical supply     PPE - Electrical Gloves (standard EN 60903)     Use of insulated tools	2	3	6		2	3	6
ENV- Gases/Fumes/Vapours	Working Party	Land	Electrostatic precipitators     Flue gas desulphurisation	5	1	5		5	1	5

Site: Example Site	Company: The Technology Studio	Risk assessment by: Mark Short								Pa	ge 3/3
Hazard	Who might be harmed	How might they be harmed	Existing Controls	Risk Rating (L * S)						Risk ing	
				L	S		R	Further Controls/Actions	L	S	R
ENV-Oil	Working Party	Water	Bunding of oil storage areas     Installation of interceptor pits     Maintenance of equipment     Spill kits located locally	4	5		20	Bunding of oil storage areas     Maintenance of equipment     Tolerable Risk - No further controls required	1	2	2
ENV-Fire	Working Party	Water	Site drains covered     Shut off valves	1	2		2		1	2	2
Flying Object (ejected)	Working Party	Ejected objects striking body	Emergency eye wash bottles to be carried     PPE - Safety glasses to be worn (Standard BS EN 166, 1F grade)	1	1		1		1	1	1
Key:	Likelihood 1 = Highly unlikely, 2 = Unlikely, 3 = Possible, 4 = Likely, 5 = Certain  Severity 1 = No injury, 2 = Minor injury, 3 = Medical treatment, 4 = Reportable, 5 = Major injury/Fatal			Risk Rating = L X S (Likelihood X Severity)				Low = 1 to 4			
							XS	Medium = 5 to 11			
					High = 12 to 25			High = 12 to 25			

iRisk Assess ©, www.iriskassess.co.uk