Risk Assessment Report

Site: Example Site Company: The Technology Studio Risk assessment by: Mark Short

Ta	sk:	Example Task 38320937			
Report I	dentifier:				
Site:	Example Site (The Technology	Assessor:			

Report Identifier:		38320937								
Site:		(The Technology Studio)	Assessor:	Mark Short Risk Rating (L*S)		ort	Created Date:		15 May 2013	
Hazard									New Risk Rating	
	Who might be harmed	How might they be harmed		L	S	R	Further Controls/Actions	L	S	R
ENV- Gases/Fumes/Vapours	Working Party	Land	Medium Risk - Ensure existing controls are maintained and monitored Emission monitoring (e.g. CEMS) Stack height In stack heaters Electrostatic precipitators SO3 injection Ventilation of work area Venting of storage vessels Incineration Absorption Condensers Wet scrubbers Dry scrubbers BAT Flame arresters	5	5	25	Emission monitoring (e.g. CEMS) In stack heaters Low nox burners Ventilation of work area Incineration Adsorption Filtration Operating regime Metering to check levels	2	5	10
Flying Object (ejected)	Working Party	Objects discharged by stored energy	Controlled release of stored energy Plant washed down to control the build up of dust and debris PPE - Safety glasses to be worn (Standard BS EN 166, 1F grade) PPE - Safety goggles to be worn (Standard BS EN 166, 1B grade) Routine inspection and maintenance	4	3	12	PPE - Safety goggles to be worn (Standard BS EN 166, 1B grade) PPE - Safety visor to be worn (Standard BS EN 166, 1B grade) Robustness of guarding confirmed Routine inspection and maintenance Tolerable Risk - No further controls required	3	3	9
Chemical	Working Party	Absorption	Clean tools after use with COSHH assessed cleaning chemicals PPE - Chemical resistant overalls to be worn (Standard BS EN 465)	4	5	20	PPE - Safety glasses to be worn (Standard BS EN 166, 1F grade) PPE - Respiratory protective equipment to be worn	4	2	8

Key:	Likelihood 1 = Highly unlikely, 2 = Unlikely, 3 = Possible, 4 = Likely, 5 = Certain Severity 1 = No injury, 2 = Minor injury, 3 = Medical treatment, 4 = Reportable, 5 = Major injury/Fatal			Risk Rating = L X S (Likelihood X Severity)			Low = 1 to 4 Medium = 5 to 11 High = 12 to 25			
ENV-Oil	Working Party	Water	Bunding of oil storage areas Installation of interceptor pits Maintenance of equipment Spill kits located locally	4	5	20	Bunding of oil storage areas Maintenance of equipment Tolerable Risk - No further controls required	1	2	2
Electricity	Working Party	Exposure to damaged electrical apparatus	Insulation of electrical supply PPE - Electrical Gloves (standard EN 60903) Use of insulated tools	2	3	6		2	3	6

iRisk Assess ©, www.iriskassess.co.uk