

Kazalo vsebine

1. Uvod v API	4
1.1 Base URL	4
1.2 Splošne konvencije	4
1.3 HTTP status codes	4
2. Avtentikacija	6
2.1 Prijava (PIN)	6
2.2 Uporaba tokena	6
2.3 Permission levels	6
3. Naročila (Orders)	8
3.1 Seznam naročil	8
3.2 Ustvari naročilo	8
3.3 Posodobi naročilo	9
3.4 Pridobi posamezno naročilo	9
3.5 Prenos mize	9
4. Plačila (Payments)	11
4.1 Ustvari plačilo (gotovina)	11
4.2 Stripe PaymentIntent (kartica)	11
4.3 Stripe webhook	12
4.4 Refund	12
5. FURS (Davčno potrjevanje)	13
5.1 FURS status	13
5.2 Cert status	13

5.3 Upload certifikata (P0-1)	13
5.4 Verify invoice	14
6. Meniji in artikli	15
6.1 Seznam menijev	15
6.2 Seznam artiklov	15
6.3 Ustvari artikel	15
7. Mize in sektorji	17
7.1 Seznam miz	17
7.2 QR batch generacija	17
7.3 Transfer mize	17
8. Dashboard in poročila	18
8.1 Dashboard podatki	18
8.2 Dnevno poročilo	18
8.3 Poročilo po natakarih	18
8.4 Z-Report (zapiranje izmene)	18
9. Zaloge (Inventory)	20
9.1 Seznam zaloga	20
9.2 Restock (dopolnitev)	20
9.3 Adjust (korekcija)	20
10. Uporabniki (Employees)	21
10.1 Seznam uporabnikov	21
10.2 Ustvari uporabnika	21
10.3 Posodobi uporabnika	21

10.4 Reset PIN	21
11. PWA in Push Notifications	22
11.1 Subscribe na push	22
11.2 Pošlji push notification	22
12. Audit Log	23
12.1 Pridobi audit log	23
12.2 Verificiraj chain	23
13. Error handling in konvencije	25
13.1 Error response format	25
13.2 Error kode	25
13.3 Rate limiting	27
13.4 Idempotency	28
14. SDK in primeri uporabe	29
14.1 JavaScript/TypeScript SDK (načrtovan)	29
14.2 cURL primeri	29
14.3 Postman collection	29
14.4 OpenAPI specifikacija	29

1. Uvod v API

RestaurantOS API je RESTful API zgrajen na Next.js API Routes. Vsebuje **229 endpointov** v 102 kategorijah, ki pokrivajo celotno funkcionalnost sistema: avtentikacijo, naročila, plačila, FURS, zaloge, računovodstvo in več. Ta dokumentacija vsebuje ključnih 60+ endpointov, ki so dovolj za večino integracij.

229	102	60+	5
API endpointov	kategorij	dokumentiranih	HTTP metod

1.1 Base URL

```
# Produkcija
https://restaurantos.app/api

# Staging
https://restaurantos-staging.vercel.app/api

# Lokalno (razvoj)
http://localhost:3000/api
```

1.2 Splošne konvencije

- **Format:** JSON (Content-Type: application/json)
- **Avtentikacija:** Bearer token v Authorization header-ju
- **Encoding:** UTF-8
- **Časovni format:** ISO 8601 (2025-09-04T10:30:00Z)
- **Valuta:** EUR (centi za plačila: 4990 = 49.90 EUR)
- **ID format:** CUID (clxyz123abc...)
- **Paginacija:** ?limit=20&offset;=0 (default limit=20, max=100)
- **Rate limiting:** 60 req/min (authenticated), 20 req/min (public)

1.3 HTTP status codes

Code	Status	Pomen
200	OK	Uspešna zahteva (GET, PUT, PATCH)
201	Created	Resource uspešno ustvarjen (POST)
204	No Content	Uspešno izbrisano (DELETE)
400	Bad Request	Neveljavni parametri ali body
401	Unauthorized	Manjka ali neveljaven token
403	Forbidden	Ni dovoljenja za to akcijo

Code	Status	Pomen
404	Not Found	Resource ne obstaja
409	Conflict	Optimistic lock conflict (updatedAt)
413	Payload Too Large	Body prevelik (max 512KB)
429	Too Many Requests	Rate limit presežen
500	Internal Server Error	Napaka na serverju (Sentry alert)
503	Service Unavailable	FURS/Stripe nedosegljiv

Tabela 1.1: HTTP status codes

2. Avtentikacija

RestaurantOS uporablja PIN-based auth z Bearer token. Po uspešni prijavi se generira JWT token, ki velja 8 ur. Token se pošilja v Authorization header-ju za vse zaščitene endpointe.

2.1 Prijava (PIN)

POST	/api/auth	Public
Prijava uporabnika z employee ID in PIN		

Request body

```
{
  "employeeId": "test-admin",
  "pin": "1234"
}
```

Response 200 OK

```
{
  "success": true,
  "employee": {
    "id": "clxyz123abc",
    "name": "Janez Novak",
    "role": "admin",
    "locationId": "clabc456def"
  },
  "token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...",
  "expiresAt": "2025-09-04T18:30:00Z"
}
```

Response 401 Unauthorized

```
{
  "error": "Neveljaven PIN",
  "code": "INVALID_PIN"
}
```

2.2 Uporaba tokena

Vsi zaščiteni endpointi zahtevajo Authorization header:

```
curl -H "Authorization: Bearer eyJhbGciOi..." \
  -H "Content-Type: application/json" \
  https://restaurantos.app/api/orders
```

2.3 Permission levels

Vloga	PIN	Dovoljenja	Primer endpointa
Natakar	0000	take_orders, process_payments	POST /api/orders
Kuhar	2222	view_orders, update_status	PUT /api/orders/[id]/status
Manager	3333	view_reports, manage_staff	GET /api/reports/daily
Admin	1234	all + configuration	PUT /api/settings
Super-admin	5555	all + cross-branch	GET /api/audit-log?locationId=all

Tabela 2.1: Vloge in dovoljenja

3. Naročila (Orders)

API za upravljanje naročil - od ustvarjanja do plačila in FURS potrjevanja.

3.1 Seznam naročil

GET	/api/orders?limit=20&offset;=0&status;=open	take_orders
Pridobi seznam naročil		

Query parametri

Parameter	Tip	Default	Opis
limit	number	20	Št. rezultatov (max 100)
offset	number	0	Offset za paginacijo
status	string	-	Filter: open, paid, cancelled, all
locationId	string	-	Filter po lokaciji (super-admin)
tableId	string	-	Filter po mizi
dateFrom	string	-	ISO datum (od)
dateTo	string	-	ISO datum (do)

Response 200

```
{
  "orders": [
    {
      "id": "clxyz123",
      "number": "2025-001",
      "tableId": "clabc",
      "tableNumber": 5,
      "status": "open",
      "total": 49.90,
      "items": [
        { "id": "clitem1", "name": "Pizza Margherita", "quantity": 1, "price": 12.00, "modifiers": [] },
        { "id": "clitem2", "name": "Pivo Laško", "quantity": 2, "price": 3.50, "modifiers": [] }
      ],
      "employeeId": "clemp1",
      "employeeName": "Janez",
      "locationId": "clloc1",
      "createdAt": "2025-09-04T10:30:00Z",
      "updatedAt": "2025-09-04T10:35:00Z"
    }
  ],
  "total": 145,
  "limit": 20,
  "offset": 0
}
```

3.2 Ustvari naročilo

POST	/api/orders	take_orders
Ustvari novo naročilo		

Request body

```
{
  "tableId": "clabc456",
  "items": [
    {
      "menuItem": "clitem123",
      "quantity": 2,
      "modifiers": ["clsize1", "cltopping1"],
      "notes": "Brez čebule"
    }
  ],
  "locationId": "clloc1",
  "type": "dine_in"
}
```

Response 201 Created

```
{
  "id": "clxyz789",
  "number": "2025-002",
  "status": "open",
  "total": 25.00,
  "items": [...],
  "fursZoi": null,
  "fursEor": null,
  "createdAt": "2025-09-04T11:00:00Z"
}
```

3.3 Posodobi naročilo

PUT	/api/orders/[id]	take_orders
Posodobi naročilo (optimistic lock)		

Request body

```
{
  "items": [...],
  "status": "open",
  "updatedAt": "2025-09-04T10:35:00Z" // za optimistic lock
}
```

Response 409 Conflict (optimistic lock)

```
{
  "error": "Naročilo je bilo posodobljeno s strani drugega uporabnika",
  "code": "OPTIMISTIC_LOCK_CONFLICT",
  "currentUpdatedAt": "2025-09-04T10:36:00Z",
  "yourUpdatedAt": "2025-09-04T10:35:00Z"
}
```

3.4 Pridobi posamezno naročilo

GET	/api/orders/[id]	take_orders
Pridobi naročilo z vsemi podrobnostmi		

3.5 Prenos mize

POST	/api/orders/[id]/transfer	take_orders
------	---------------------------	-------------

Request body

```
{  
  "newTableId": "c1table8"  
}
```

4. Plačila (Payments)

API za upravljanje plačil - gotovina, kartice (Stripe), darilne kartice.

4.1 Ustvari plačilo (gotovina)

POST	/api/payments	take_orders
Ustvari plačilo za naročilo		

Request body (gotovina)

```
{
  "orderId": "clxyz789",
  "method": "cash",
  "amount": 50.00,
  "receivedAmount": 50.00,
  "tip": 0.00
}
```

Response 201 Created

```
{
  "id": "clpay123",
  "orderId": "clxyz789",
  "method": "cash",
  "amount": 50.00,
  "status": "completed",
  "change": 0.10,
  "receiptNumber": "2025-001",
  "fursZoi": "abc123def456...",
  "fursEor": "uuid-1234-5678",
  "createdAt": "2025-09-04T11:05:00Z"
}
```

4.2 Stripe PaymentIntent (kartica)

POST	/api/payments/stripe-intent	take_orders
Ustvari Stripe PaymentIntent		

Request body

```
{
  "amount": 4990,
  "currency": "eur",
  "orderId": "clxyz789",
  "locationId": "clloc1",
  "metadata": {
    "tableNumber": "5",
    "waiterName": "Janez"
  }
}
```

Response 200

```
{
  "clientSecret": "pi_3Pxyz...secret_abc123...",
  "paymentIntentId": "pi_3Pxyz...",
  "amount": 4990,
  "currency": "eur",
}
```

```
"status": "requires_payment_method"
}
```

4.3 Stripe webhook

POST	/api/payment-gateways/webhook	Stripe
Stripe webhook (HMAC verified)		

Webhook prejema Stripe evente. Signature se preverja z HMAC-SHA256. Ni potrebna auth (Stripe signature je auth).

Podprti eventi

Event	Akcija	DB update
payment_intent.succeeded	Payment.status = "completed"	Order.status = "paid"
payment_intent.payment_failed	Payment.status = "failed"	Order ostane "open"
charge.refunded	Payment.status = "refunded"	Refund zapisa n

4.4 Refund

POST	/api/payments/[id]/refund	admin
Refund plačila (delni ali polni)		

Request body

```
{
  "amount": 25.00, // null za polni refund
  "reason": "customer_request"
}
```

5. FURS (Davčno potrjevanje)

API za FURS modul - davčno potrjevanje računov po ZDDV-1.

5.1 FURS status

GET	/api/furs	admin
Preveri FURS povezavo in konfiguracijo		

Response 200

```
{
  "connected": true,
  "environment": "production",
  "configValid": true,
  "certificateLoaded": true,
  "certificateValidUntil": "2030-09-04",
  "lastSuccessfulVerify": "2025-09-04T11:05:00Z"
}
```

5.2 Cert status

GET	/api/furs/cert-status	admin
Status certifikata (veljavnost, renewal)		

Response 200

```
{
  "valid": true,
  "validUntil": "2030-09-04",
  "daysUntilExpiry": 1825,
  "issuer": "FURS CA",
  "environment": "production",
  "warningLevel": "none"
}
```

5.3 Upload certifikata (P0-1)

POST	/api/furs/cert-upload	admin
Upload .p12 certifikata		

Request (multipart/form-data)

POST /api/furs/cert-upload
Content-Type: multipart/form-data

Form fields:

cert: File (.p12, max 100KB)
password: string
locationId: string (optional)
environment: "test" | "production"

Response 200

```
{
  "success": true,
}
```

```
"certPath": "./certs/furs-clloc1-production.p12",
"environment": "production",
"validUntil": "2030-09-04",
"issuer": "FURS CA",
"message": "Certifikat uspešno naložen"
}
```

5.4 Verify invoice

POST	/api/furs	admin
Pošlji račun FURS-u za potrjevanje		

Request body

```
{
  "orderId": "clxyz789",
  "invoiceNumber": "2025-001",
  "issueDateTime": "2025-09-04T11:05:00Z",
  "taxNumber": "SI12345678",
  "premisesId": "PE123",
  "electronicDeviceId": "BLAG1",
  "invoiceAmount": 49.90,
  "paymentAmount": 50.00,
  "taxes": [
    { "rate": 22, "base": 30.00, "tax": 6.60 },
    { "rate": 9.5, "base": 13.30, "tax": 1.26 }
  ]
}
```

Response 200

```
{
  "success": true,
  "zoi": "abc123def456ghi789jk1012mno345...", // 32-znakovni MD5
  "eor": "uuid-1234-5678-9012-345678901234",
  "fursTimestamp": "2025-09-04T11:05:01Z"
}
```

6. Meniji in artikli

API za upravljanje menijev, artiklov, kategorij in modifikatorjev.

6.1 Seznam menijev

GET	/api/menus	view_reports
Pridobi vse menije		

6.2 Seznam artiklov

GET	/api/menu-items?categoryId=clcat1	take_orders
Pridobi artikle (z filter)		

Query parametri

Parameter	Tip	Opis
categoryId	string	Filter po kategoriji
search	string	Iskanje po imenu
active	boolean	Samo aktivni artikli
includeModifiers	boolean	Vključi modifikatorje
locationId	string	Filter po lokaciji

Response 200 (skrajšano)

```
{
  "items": [
    {
      "id": "clitem123",
      "name": "Pizza Margherita",
      "nameEn": "Margherita Pizza",
      "price": 12.00,
      "categoryId": "clcat1",
      "taxRate": 22,
      "allergens": ["gluten", "milk"],
      "imageUrl": "/images/pizza-margherita.jpg",
      "active": true,
      "modifiers": [
        { "id": "clmod1", "name": "Velikost", "options": ["S", "M", "L"] }
      ]
    }
  ],
  "total": 145
}
```

6.3 Ustvari artikel

POST	/api/menu-items	admin
Ustvari nov artikel		

Request body

```
{
  "name": "Pizza Margherita",
  "nameEn": "Margherita Pizza",
  "price": 12.00,
  "categoryId": "clcat1",
  "taxRate": 22,
  "allergens": ["gluten", "milk"],
  "description": "Klasična italijanska pizza",
  "preparationTime": 15,
  "active": true
}
```

7. Mize in sektorji

7.1 Seznam miz

GET	/api/tables?locationId=clloc1	take_orders
Pridobi vse mize		

Response 200

```
{
  "tables": [
    {
      "id": "cltab1",
      "number": 5,
      "capacity": 4,
      "section": "Main Hall",
      "status": "occupied",
      "currentOrderId": "clxyz789",
      "locationId": "clloc1"
    }
  ]
}
```

7.2 QR batch generacija

POST	/api/tables/qr-batch	admin
Generiraj QR kode za mize		

Request body

```
{
  "tableIds": ["cltab1", "cltab2", "cltab3"],
  "format": "png"
}
```

7.3 Transfer mize

POST	/api/tables/transfer	admin
Prenesi mizo na drugo lokacijo		

8. Dashboard in poročila

8.1 Dashboard podatki

GET	/api/dashboard?date=2025-09-04	view_reports
Pridovi dashboard metrike		

Response 200

```
{
  "today": {
    "revenue": 1542.50,
    "orders": 47,
    "avgOrderValue": 32.82,
    "items": 156
  },
  "hourly": [
    { "hour": 9, "revenue": 125.50, "orders": 4 },
    { "hour": 10, "revenue": 234.00, "orders": 7 }
  ],
  "topItems": [
    { "id": "clitem123", "name": "Pizza Margherita", "quantity": 12, "revenue": 144.00 }
  ],
  "paymentMethods": {
    "cash": 542.50,
    "card": 1000.00
  }
}
```

8.2 Dnevno poročilo

GET	/api/reports/daily?date=2025-09-04	view_reports
Dnevno poročilo prodaje		

8.3 Poročilo po natakarih

GET	/api/reports/employees?dateFrom=2025-09-01&dateTo;=2025-09-04	view_reports
Poročilo po natakarih		

8.4 Z-Report (zapiranje izmene)

POST	/api/cash-register/close	admin
Zapri izmeno z Z-Report		

Request body

```
{
  "locationId": "clloc1",
  "closingAmount": 542.50,
  "countedCash": 540.00,
  "notes": "Manjka 2.50 EUR"
```

```
}
```

Response 200

```
{  
  "zReportNumber": "Z-2025-001",  
  "openingAmount": 200.00,  
  "closingAmount": 542.50,  
  "cashSales": 342.50,  
  "cardSales": 1000.00,  
  "totalSales": 1342.50,  
  "discrepancy": -2.50,  
  "closedAt": "2025-09-04T22:00:00Z"  
}
```

9. Zaloge (Inventory)

9.1 Seznam zaloga

GET	/api/inventory?locationId=clloc1	view_reports
Pridobi stanje zalog		

Response 200

```
{
  "items": [
    {
      "id": "clinv1",
      "name": "Paradižnik",
      "quantity": 25.5,
      "unit": "kg",
      "minQuantity": 5.0,
      "cost": 2.50,
      "locationId": "clloc1",
      "supplier": "clsup1"
    }
  ]
}
```

9.2 Restock (dopolnitev)

POST	/api/inventory/restock	admin
Dopolni zalogo		

Request body

```
{
  "itemId": "clinv1",
  "quantity": 10.0,
  "cost": 25.00,
  "supplierId": "clsup1",
  "note": "Tedenska dobava"
}
```

9.3 Adjust (korekcija)

POST	/api/inventory/adjust	admin
Korekcija zaloge (inventura)		

Request body

```
{
  "itemId": "clinv1",
  "newQuantity": 23.0,
  "reason": "inventura",
  "note": "Manjka 2.5 kg (razlitje)"
}
```

10. Uporabniki (Employees)

10.1 Seznam uporabnikov

GET	/api/employees?locationId=clloc1	manage_staff
Pridobi seznam zaposlenih		

10.2 Ustvari uporabnika

POST	/api/employees	admin
Ustvari novega uporabnika		

Request body

```
{
  "name": "Ana Horvat",
  "pin": "4444",
  "role": "waiter",
  "locationId": "clloc1",
  "email": "ana@restaurant.com",
  "phone": "+386 41 234 567"
}
```

10.3 Posodobi uporabnika

PUT	/api/employees/[id]	admin
Posodobi uporabnika		

10.4 Reset PIN

POST	/api/employees/[id]/reset-pin	admin
Reset PIN uporabnika		

Request body

```
{
  "newPin": "5555"
}
```

11. PWA in Push Notifications

11.1 Subscribe na push

POST	/api/push/subscribe	take_orders
Subscribe na Web Push notifications		

Request body

```
{
  "endpoint": "https://fcm.googleapis.com/fcm/send/...",
  "keys": {
    "p256dh": "BNa...",
    "auth": "abc..."
  },
  "expirationTime": null
}
```

11.2 Pošlji push notification

POST	/api/push/send	manage_staff
Pošlji push notification uporabniku		

Request body

```
{
  "employeeId": "clemp1",
  "title": "Novo naročilo",
  "body": "Miza 5 - 2x Pizza",
  "data": {
    "url": "/orders/clxyz789",
    "orderId": "clxyz789"
  }
}
```

Response 200

```
{
  "succeeded": 1,
  "failed": 0,
  "total": 1
}
```

12. Audit Log

Audit log je chain hash (SHA-256), nepopravljiv. Vsi kritični dogodki so loggani.

12.1 Pridobi audit log

GET	/api/audit-log?from=2025-09-01&to;=2025-09-04	admin
Pridobi audit log vnose		

Query parametri

Parameter	Tip	Opis
from	string	ISO datum (od)
to	string	ISO datum (do)
employeeId	string	Filter po uporabniku
action	string	Filter po akciji (furs.verify, payment.create)
locationId	string	Filter po lokaciji (super-admin: all)

Response 200

```
{
  "logs": [
    {
      "id": "cllog1",
      "timestamp": "2025-09-04T11:05:00Z",
      "employeeId": "clemp1",
      "employeeName": "Janez",
      "action": "payment.create",
      "entityId": "clpay123",
      "entityType": "payment",
      "ipAddress": "192.168.1.100",
      "metadata": { "method": "cash", "amount": 50.00 },
      "previousHash": "abc123...",
      "currentHash": "def456..."
    }
  ],
  "total": 1247,
  "chainValid": true
}
```

12.2 Verificiraj chain

GET	/api/audit-log/verify	super_admin
Verificiraj integriteto audit log chain-a		

Response 200

```
{
  "valid": true,
  "totalEntries": 1247,
  "verifiedAt": "2025-09-04T12:00:00Z",
  "firstEntry": "2025-01-01T00:00:00Z",
  "lastEntry": "2025-09-04T11:59:00Z"
}
```

}

13. Error handling in konvencije

Vsi error-ji sledijo standardnemu formatu z error kodo za programsko obravnavo.

13.1 Error response format

```
{
  "error": "Človeku berljivo sporočilo",
  "code": "MACHINE_READABLE_CODE",
  "details": {
    "field": "pin",
    "issue": "must be 4 digits"
  },
  "requestId": "req_abc123"
}
```

13.2 Error kode

Code	HTTP	Pomen	K d aj
INVALID_PIN	401	Neveljaven PIN	P O S T / a p i / a u t h
OPTIMISTIC_LOCK_CONFLICT	409	Konflikt pri posodobitvi	P U T / a p i / o r d e r s/ [id]
INSUFFICIENT_FUNDS	400	Premalo sredstev na kartici	S t r i p e p l a č i l o
FURS_TIMEOUT	503	FURS API ne odgovarja	P O S T / a p i / f u r s

Code	HTTP	Pomen	K d aj
FURS_CERT_INVALID	400	FURS certifikat neveljaven	P O S T /a p i /f u r s/ c e r t - u p l o a d
RATE_LIMIT_EXCEEDED	429	Presežen rate limit	K a t e r i k o l i e n d p o i n t
PERMISSION_DENIED	403	Ni dovoljenja	K a t e r i k o l i z a š č i t e n e n d p o i n t
VALIDATION_ERROR	400	Neveljavni parametri	P O S T /P U T z n e v e l j a v n i m b o d y

Code	HTTP	Pomen	K d aj
NOT_FOUND	404	Resource ne obstaja	G E T/ P U T/ D E L E T E z ne ob st oj eč i m ID
STRIPE_WEBHOOK_INVALID	400	Neveljaven webhook signature	P O S T /a p i /p a y m e n t- g a t e w a y s/ w e b h o o k

Tabela 13.1: Standardne error kode

13.3 Rate limiting

Vsi endpointi so rate-limited. Header-ji v responsu prikazujejo trenutno stanje:

```
# Response headers:
X-RateLimit-Limit: 60
X-RateLimit-Remaining: 45
X-RateLimit-Reset: 1695840000
```

```
# Ko presežen (429):
Retry-After: 60
```

Kategorija	Limit	Okno	Endpointi
Public	20 req	1 min	/api/auth (POST), /api/qr-menu
Authenticated	60 req	1 min	Večina endpointov
FURS	10 req	1 min	/api/furs/*
Auth attempts	5 req	15 min	/api/auth (POST) - zaščita brute force
Public menu	100 req	1 min	/api/menus, /api/menu-items (public)

Tabela 13.2: Rate limit kategorije

13.4 Idempotency

Kritični endpointi (plačila, FURS) podpirajo idempotency prek Idempotency-Key header-ja:

POST /api/payments

Idempotency-Key: random-uuid-12345

Content-Type: application/json

```
{
  "orderId": "clxyz789",
  "method": "cash",
  "amount": 50.00
}
```

Če se request ponovi z istim key-em, se vrne originalni rezultat

(preprečuje duplikate pri network retry)

14. SDK in primeri uporabe

14.1 JavaScript/TypeScript SDK (načrtovan)

```
// Namestitev (načrtovano):
npm install @restaurantos/sdk

// Uporaba:
import { RestaurantOSClient } from '@restaurantos/sdk'

const client = new RestaurantOSClient({
  baseUrl: 'https://restaurantos.app/api',
  token: 'eyJhbGciOi...' // iz /api/auth
})

// Ustvari naročilo:
const order = await client.orders.create({
  tableId: 'cltab1',
  items: [{ menuItemId: 'clitem1', quantity: 2 }]
})

// Plačaj:
const payment = await client.payments.create({
  orderId: order.id,
  method: 'cash',
  amount: order.total,
  receivedAmount: order.total
})
```

14.2 cURL primeri

Prijava

```
curl -X POST https://restaurantos.app/api/auth \
-H "Content-Type: application/json" \
-d '{"employeeId": "test-admin", "pin": "1234"}'
```

Pridobi naročila

```
curl https://restaurantos.app/api/orders?limit=10 \
-H "Authorization: Bearer eyJhbGciOi..."
```

Ustvari naročilo

```
curl -X POST https://restaurantos.app/api/orders \
-H "Authorization: Bearer eyJhbGciOi..." \
-H "Content-Type: application/json" \
-d '{
  "tableId": "cltab1",
  "items": [{"menuItemId": "clitem1", "quantity": 2}]
}'
```

14.3 Postman collection

Postman collection je na voljo v `/docs/postman-collection.json`. Import v Postman za hitro testiranje vseh endpointov.

14.4 OpenAPI specifikacija

OpenAPI 3.1 specifikacija je na voljo v `/docs/openapi.yaml`. Uporabi jo za generacijo SDK-jev v drugih jezikih (Python, Go, Java, itd.) prek `swagger-codegen` ali `openapi-generator`.

API STATUS

API je v stabilni fazi v1.0.0. Breaking changes bodo verzionirani (v2, v3). Backward compatibility je zagotovljena za 12 mesecev po release-u. Za integracijo kontaktiraj api-support@restaurantos.app.