WONDERLAND INTEGRATION

WONDERLAND FORKING DETAILS

WONDERLAND FORKING TESTNET FOR TRILL

CONTRACTS FOLDER:

There are several contracts being provided that are necessary for the fork of wonderland.

Visit remix.ethereum.org and install the contracts in the following manner:

1. ERC20TRILL (deployment)
2. sTrillERC20 (deployment)
3. BondingCalculator(ERC20Trill Contract address) put ERC20 Trill address
4. Treasury(ERC20TrillContract address, MIM ContractAddress address, 0) deployment
5. inside ERC20Trill ----> setVault(Treasury address)
6. Staking(ERC20TrillContract address, sTrillERC20 Contract address, 28800, 0, block.timestamp(ofLaunch) + 28800) deployment
7. Inside sTrillERC20 -----> initialaze(staking Contract address)
8. StakingWarmup(Staking Contract address, sTrill address) deployment
9. StakingDistributor(Treasury Contract address, ERC20Trill contract address, 28800, block.timestamp(ofLaunch) + 28800) deployment
10. StakingDistributor ----> addRecipient(Staking Contract address, 5000);
11. Inside Staking Contract ------> SetContract(0, StakingDistributor Contract address)
12. Inside Staking Contract ------> SetContract(1, StakingWarmup Contract address)
13. StakingHelper(ERC20Trill Contract address, Staking Contract address) deployment

14. ETHBondDepository(ERC20 Trill Contract address, Wavax contract address, Treasury Contract Address, Own Wallet Address, feed address of Avax/USD from chain link) deployment.

    - To Get feed address visit https://docs.chain.link/docs/avalanche-price-feeds/ and there you can find the pairs and their addresses.

    - Inside ETHBondDepository ----> initializeBondTerms (257, 432000, 17000, 1000, 100000000000000000000000, 0)

    - Inside ETHBondDepository ----> setStaking(stakingHelper Contract address, 1)

15. BondDepository we need to deploy it 3 times the same contract (ERC20 Trill Contract Address , MIM contract Address, treasury Contract Address, Own wallet Address , 0x0000000000000000000000000000000000)

    - Inside BondDepository ----> initializeBondTerms (257,17000, 1000,100, 100000000000000000000000, 432000)

    - Inside BondDepository ----> setStaking(stakingHelper Contract address, 1)

16. **2nd Time** BondDepository (ERC20 Trill Contract Address , MIM-TRILL PAIR LP Address, treasury Contract Address, Own wallet Address , Bonding Calulator Contract Address)

    - Inside BondDepository ----> initializeBondTerms (257,17000, 1000,100, 100000000000000000000000, 432000)

    - Inside BondDepository ----> setStaking(stakingHelper Contract address, 1)

17. **3rd Time** BondDepository (ERC20 Trill Contract Address , WAVAX-TRILL PAIR LP Address, treasury Contract Address, Own wallet Address , Bonding Calulator Contract Address)

    - Inside BondDepository ----> initializeBondTerms (257,17000, 1000,100, 100000000000000000000000, 432000)

    - Inside BondDepository ----> setStaking(stakingHelper Contract address, 1)

18. Inside Treasury Smart Contract
    - Queue(0, Own Wallet Address)
    - Queue (2, Own Wallet Address)
    - Queue(3, Own Wallet Address)
    - Queue (4 , Own Wallet Address)
    - Queue (5 , Trill-Wavax LP Pair Address)
    - Queue (8,Own Wallet Address)

    After the Queues now goto toggle and then do this :

    - Toggle (0, OwnwalletAddress , 0x00000000000000)
    - Toggle (2, OwnwalletAddress , 0x00000000000000)
    - Toggle (3, OwnwalletAddress , 0x00000000000000)
    - Toggle (4, OwnwalletAddress , 0x00000000000000)
    - Toggle (5, Trill-Wavax LP Pair Address ,Bonding Calcuator Contract Address)
    - Toggle (4, OwnwalletAddress , 0x00000000000000)

TRILL FRONTEND :

Now goto Trill Front end and change the addresses in this file location :

/src/constants/addresses.ts

In the DAO Address put your own wallet address rest the variables are easy to understand. 😊

```
src > constants > TS addresses.ts > AVAX_MAINNET > TREASURY_ADDRESS
1   import { Networks } from "./blockchain";
2
3   const AVAX_MAINNET = {
4     DAO_ADDRESS: "0xB414f40774f67caF650870be1e3f6ae7F2C9BBdd",
5     MEMO_ADDRESS: "0x01942A4A7Df098eDB0a9AfC8880Fe3DC6006ea40",
6     TIME_ADDRESS: "0x8E0A4daba1b2e3e4d934148Fb13Fd79f343c7E99",
7     MIM_ADDRESS: "0xe72FE0D472E05F425012e0d45Cc4eAA29787830F",
8     STAKING_ADDRESS: "0x8094b4B57631Fb65e41a30C20d5160Be259E9447",
9     STAKING_HELPER_ADDRESS: "0x86e1139dc61d3605a67F345Fa7101FD39b18E18F",
10    TIME_BONDING_CALC_ADDRESS: "0xEd58907Ecb0EFf2Ee53c21d80903E837b1810939",
11    TREASURY_ADDRESS: "0xE5cBad4a24A8D2aCDb24A5E9E7fc53086cA76544",
12    ZAPIN_ADDRESS: "0xBD601fa5D76a13131FD21e78a41985DdfB2Ab08F", //"0xb98007C04f475022bE681a890512518052CE6104",
13    WMEMO_ADDRESS: "0x0c1d958fc190602884F4c0386772e67b7A6cd792",
14  };
15
16  // const AVAX_MAINNET = {
```

Secondly goto /src/helpers/bonds/index.ts

Put the Bond Address of MIM as we did for bonddepository with MIM address

In the reserver address put the contract address of MIM Token .

```
export const mim = new StableBond({
  name: "mim",
  displayName: "MIM",
  bondToken: "MIM",
  bondIconSvg: MimIcon,
  bondContractABI: StableBondContract,
  reserveContractAbi: StableReserveContract,
  networkAddrs: {
    [Networks.AVAX]: {
      bondAddress: "0x43A09E5E398F9148aEc1e587fef271987429a55b",
      reserveAddress: "0xe72FE0D472E05F425012e0d45Cc4eAA29787830F",
    },
  },
  tokensInStrategy: "605000000000000000000000",
});

export const wavax = new CustomBond({
  name: "wavax",
  displayName: "wAVAX",
  bondToken: "AVAX",
```

Now in the second one where its says name : wavax put the Ethbond Depository contract Address in the bond address and in the reserver address put wavax contract address

```
export const wavax = new CustomBond({
  name: "wavax",
  displayName: "wAVAX",
  bondToken: "AVAX",
  bondIconSvg: AvaxIcon,
  bondContractABI: WavaxBondContract,
  reserveContractAbi: StableReserveContract,
  networkAddrs: {
    [Networks.AVAX]: {
      bondAddress: "0xd2dA4B8aa98376B7FaF9F260b819152aa6DfeCe3",
      reserveAddress: "0xd00ae08403b9bbb9124bb305c09058e32c39a48c",
    },
  },
  tokensInStrategy: "756916000000000000000000",
});
```

Now in the third where it says mim-time LP put the bond depository Contract address where we have put mim-trill lp pair as address . and in the reserve address put the mim-trill lp pair address

```
export const mimTime = new LPBond({
  name: "mim_time_lp",
  displayName: "TRILL-MIM LP",
  bondToken: "MIM",
  bondIconSvg: MimTimeIcon,
  bondContractABI: LpBondContract,
  reserveContractAbi: LpReserveContract,
  networkAddrs: {
    [Networks.AVAX]: {
      bondAddress: "0x078c2e25a85F4028a7173CD5c2Bb0d41cEE42f3c",
      reserveAddress: "0x5333722f458abd825ce2d25a4de38a70454337de",
    },
  },
  lpUrl:
    "https://www.traderjoexyz.com/#/pool/0x130966628846BFd36ff31a822705796e8cb8C18D/0xb54f16fB19478766A268F172C9480f8da1a7c9C3",
});
```

Now in the fourth one where it says avax-time lp put the bond depository contract address where we have put the address of avax-trill in the principle address constructor. And in the reserver address put the avax-trill lp pair address

```
export const mimTime = new LPBond({
  name: "mim_time_lp",
  displayName: "TRILL-MIM LP",
  bondToken: "MIM",
  bondIconSvg: MimTimeIcon,
  bondContractABI: LpBondContract,
  reserveContractAbi: LpReserveContract,
  networkAddrs: {
    [Networks.AVAX]: {
      bondAddress: "0x078c2e25a85F4028a7173CD5c2Bb0d41cEE42f3c",
      reserveAddress: "0x5333722f458abd825ce2d25a4de38a70454337de",
    },
  },
  lpUrl:
    "https://www.traderjoexyz.com/#/pool/0x130966628846BFd36ff31a822705796e8cb8C18D/0xb54f16fB19478766A268F172C9480f8da1a7c9C3",
});
```

NOTE :

- Don’t Forget to do Zapin contract it will ask you for the DAO address that will be your own wallet address
- And also in the Wmemo contract it will ask you for sTrill contract address in the constructor .

After doing the changes run it with NPM start 😊