

Product	Product Code	Description	Visible Light Transmitted	Solar Energy Reflected	Solar Energy Absorbed	Single Pane						Dual Pane				Inboard/Outboard		Low E				Triple Pane				Laminated	Product	
						Clear Anodized		Tinted Tempered	Tinted Anodized		Clear Anodized		Outdoor Tinted		Inboard Tinted	Temperd	Standard		Plus or E2		Plus Plus or E3		Clean/Clear/Clean	Clean/Clear/Low E	Tinted/Clear/Clean	Tinted/Clear/Low E		Clear or Tinted
						180°-194° Mono 1.76 sq ft @ 1.30 sq ft @	180°-194° Mono 1.98-2.34 sq ft @ 2.34-2.69 sq ft @	HIS Tempered 1.98-2.34 sq ft @ 2.34-2.69 sq ft @	180°-194° Mono 1.76 sq ft @ 1.30 sq ft @	180°-194° Mono 1.98-2.34 sq ft @ 2.34-2.69 sq ft @	180°-194° IG 1.76 sq ft @ 1.30 sq ft @	180°-194° IG 1.98-2.34 sq ft @ 2.34-2.69 sq ft @	180°-194° IG 1.76 sq ft @ 1.30 sq ft @	180°-194° IG 1.98-2.34 sq ft @ 2.34-2.69 sq ft @	180°-194° IG 1.76 sq ft @ 1.30 sq ft @	180°-194° IG 1.98-2.34 sq ft @ 2.34-2.69 sq ft @	180°-194° IG 1.76 sq ft @ 1.30 sq ft @	180°-194° IG 1.98-2.34 sq ft @ 2.34-2.69 sq ft @	180°-194° IG 1.76 sq ft @ 1.30 sq ft @	180°-194° IG 1.98-2.34 sq ft @ 2.34-2.69 sq ft @	180°-194° IG 1.76 sq ft @ 1.30 sq ft @	180°-194° IG 1.98-2.34 sq ft @ 2.34-2.69 sq ft @	180°-194° IG 1.76 sq ft @ 1.30 sq ft @	180°-194° IG 1.98-2.34 sq ft @ 2.34-2.69 sq ft @	180°-194° IG 1.76 sq ft @ 1.30 sq ft @	180°-194° IG 1.98-2.34 sq ft @ 2.34-2.69 sq ft @		Any Size
Silver																								Silver				
Silver 15	Silver 15 DAP(S) SR	Silver	15%	48%	41%																					Silver 15		
Silver 35	Silver 35 DAP(S) SR	Silver	36%	40%	36%																				Silver 35			
Silver 60	Silver 60 DAP(S) SR	Silver	58%	12%	43%																				Silver 60			
Solar Bronze																									Solar Bronze			
Solar Bronze 20	Solar Bronze 20 DA SR	Bronze	18%	42%	46%																				Solar Bronze 20			
Solar Bronze 35	Solar Bronze 35 DA SR	Bronze	37%	31%	46%																				Solar Bronze 35			
Signature																									Signature			
Signature 20	Signature 20 DA (PS) SR	Gray	18%	22%	61%																				Signature 20			
Signature 35	Signature 35 DA (PS) SR	Gray	33%	15%	57%																				Signature 35			
Signature 60	Signature 60 PS SR	Gray	60%	8%	39%																				Signature 60			
Dual Reflective																									Dual Reflective			
Ovation® S	Ovation S 5A (PS) SR	Night Neutral	8%	53%	37%																				Ovation® S			
Ovation® LS	Ovation LS 5A (PS) SR	Night Neutral	14%	47%	39%																				Ovation® LS			
Ovation® JS	Ovation JS 5A (PS) SR	Night Neutral	27%	29%	44%																							