Mark Lucernas
CISC 211
Prof. Saied Moezzi
December 5, 2020

cisc-211-13@raspberrypi

Unit 7 Assignment

Overview Screen Capture



Compile & Program Execution Screen Capture



Description:

This program executes integer division (A / B = Quotient Output).

Assembly Source Code Screen Capture

```
@ Assignment 6.14
@
@ Mark Lucernas
@
@ To run this code on a RaspberryPi (if the filename is filename.s) do the following
@       as -o filename.o filename.s
@       gcc -o filename filename.o
@       ./filename

.text
.global main
.extern printf
main:
        @ push return address (lr) and ip on the stack
        push    {ip, lr}


        @ R0 and R1 are the input, and they initially contain positive numbers, a and b (for example 9 and 2).
        @ At the end of the program, R0 is the output.

        MOV R0, #9      @ move number 9 into register R0
        MOV R1, #2      @ move number 2 into register R1

@ Insert the ARM Assembly code for the following machine language:
@         0x00008008 0xE3A02000
@         0x0000800C 0xE1A03001
@         0x00008010 0xE1510000
@         0x00008014 0x8A000002
@         0x00008018 0xE2822001
@         0x0000801C 0xE0811003
@         0x00008020 0xEAFFFFFA
@ after the following two lines:
@---------------------

        MOV R2, #0      @ i = 0
        MOV R3, R1      @ R3 = R1 (divisor)
L1:
        CMP R1, R0      @ i < R0 (dividend)
        BHI DONE        @ if i >= R0 exit loop
        ADD R2, R2, #1  @ R2 = R2 + 1
        ADD R1, R1, R3  @ R1 = R2 + R3
        B   L1          @ repeat loop
DONE:
        MOV R0, R2      @ R0 = R2

@ end of ARM Assembly code for the above machine language ends here.
@---------------------
@
@ the following code prints the content

        MOV R1, R0
        LDR R0, =fmt    @ load fmt (output format)
        BL printf

        @ pop the values from stack into ip and pc registers
        pop     {ip, pc}

.data
fmt:    .asciz "\nThis code produces the following Result: %d\n"


                                                                17,0-1        Top
```

Edited Assembly Code Screen Capture



```
@ Insert the ARM Assembly code for the following machine language:
@         0x00008008 0xE3A02000
@         0x0000800C 0xE1A03001
@         0x00008010 0xE1510000
@         0x00008014 0x8A000002
@         0x00008018 0xE2822001
@         0x0000801C 0xE0811003
@         0x00008020 0xEAFFFFFA
@ after the following two lines:
@---------------------

        MOV R2, #0      @ i = 0
        MOV R3, R1      @ R3 = R1 (divisor)
L1:
        CMP R1, R0      @ i < R0 (dividend)
        BHI DONE        @ if i >= R0 exit loop
        ADD R2, R2, #1  @ R2 = R2 + 1
        ADD R1, R1, R3  @ R1 = R2 + R3
        B   L1          @ repeat loop
DONE:
        MOV R0, R2      @ R0 = R2
```

DDCA_unit-7_assignment.s

```
@ Assignment 6.14
@
@ Mark Lucernas
@
@ To run this code on a RaspberryPi (if the filename is filename.s) do the following
@       as -o filename.o filename.s
@       gcc -o filename filename.o
@       ./filename

.text
.global main
.extern printf
main:
```

```
        @ push return address (lr) and ip on the stack
        push    {ip, lr}


        @ R0 and R1 are the input, and they initially contain positive numbers, a and b (for
example 9 and 2).
        @ At the end of the program, R0 is the output.

        MOV R0, #9   @ move number 9 into register R0
        MOV R1, #2   @ move number 2 into register R1

@ Insert the ARM Assembly code for the following machine language:
@       0x00008008 0xE3A02000
@       0x0000800C 0xE1A03001
@       0x00008010 0xE1510000
@       0x00008014 0x8A000002
@       0x00008018 0xE2822001
@       0x0000801C 0xE0811003
@       0x00008020 0xEAFFFFFA
@ after the following two lines:
@----------------------

        MOV R2, #0   @ i = 0
        MOV R3, R1   @ R3 = R1 (divisor)
L1:
        CMP R1, R0   @ i < R0 (dividend)
        BHI DONE     @ if i >= R0 exit loop
        ADD R2, R2, #1  @ R2 = R2 + 1
        ADD R1, R1, R3  @ R1 = R2 + R3
        B   L1          @ repeat loop
DONE:
        MOV R0, R2   @ R0 = R2

@ end of ARM Assembly code for the above machine language ends here.
@----------------------
@
```

@ the following code prints the content

```
        MOV R1, R0
        LDR R0, =fmt @ load fmt (output format)
        BL printf

        @ pop the values from stack into ip and pc registers
        pop     {ip, pc}

.data
fmt:    .asciz "\nThis code produces the following Result: %d\n"
```

GDB Debugger Screen Capture



C++ Source Code Screen Capture



```
#include <iostream>
using namespace std;

int main(int argc, char *argv[])
{

        int dividend = 9;               // R0 = A (dividend)
        int divisor = 2;                // R1 = B (divisor)
        int i = 0;                      // MOV R2, #0
        int tmp = divisor;              // MOV R3, R1

        int quotient;

        // L1
        while (dividend >= tmp) {       // CMP R1, R0 ? Proceed : BHI DONE
                i = i + 1;              // ADD R2, R2, #1
                tmp = tmp + divisor;    // ADD R1, R1, R3
        }

        // DONE
        quotient = i;                   // MOV R0, R2

        cout << "\nThis code produces the following Result: " << quotient << endl;
        return 0;
        }
}
~
~
```

DDCA_unit-7.cpp

```
#include <iostream>
using namespace std;

int main(int argc, char *argv[])
{

        int dividend = 9;               // R0 = A (dividend)
        int divisor = 2;                // R1 = B (divisor)
        int i = 0;                      // MOV R2, #0
        int tmp = divisor;              // MOV R3, R1

        int quotient;

        // L1
        while (dividend >= tmp) {       // CMP R1, R0 ? Proceed : BHI DONE
                i = i + 1;              // ADD R2, R2, #1
                tmp = tmp + divisor;    // ADD R1, R1, R3
        }
```

```
        // DONE
        quotient = i;                // MOV R0, R2

        cout << "\nThis code produces the following Result: " << quotient << endl;
        return 0;
        }
}
```